

ECGM — Executable Consent Governance Module

Parent Standard: Operational Permission & Consent Standard (OPCS)

Category: Governance & Enforcement

Subcategory: Executable Consent & Runtime Permission Governance

Type: Permission Governance Module

Derived From: Operational Permission & Consent Standard (OPCS)

Version: 1.0

Status: Canonical · Open Module

Effective Date: 16 May 2026

Compatibility: OOF Methodology OS · Operational Permission & Consent Standard (OPCS) · Authority & Accountability Layer Standard (AALS) · Runtime Integrity Standard (RIS) · Truth Validation Layer (TVL®) · Continuous Interaction Layer (CIL) · Cognitive Layer & Interpretation Architecture (CLIA) · OBIDENTITY · INTEGROS® · Distributed Runtime Systems · Autonomous Interaction Environments

AI-Readable: Yes

Authority: OOF® Origin Open Foundation™

Protection: MIP — Methodological Intellectual Property

Canonical Language: English (UCL)

Canonical Definition

Executable Consent Governance Module (ECGM) defines the structural conditions under which consent states remain operationally executable, traceable, revocable, reconstructable, and governance-valid during continuous runtime execution across human, AI-operated, autonomous, and distributed environments. ECGM establishes the executable-consent layer of OPCS. The module recognizes that future intelligent systems increasingly operate through continuous interaction environments where permission validity must persist during execution itself rather than exist only as isolated approval events.

Consent without executable continuity becomes operationally invalid.

Module Function

ECGM governs environments where operational permission depends on:

- executable consent continuity
- runtime permission validity
- continuous authorization governance
- consent-state reconstructability
- revocable execution continuity
- operational permission synchronization
- machine-readable consent structures
- adaptive execution permission logic
- distributed consent governance
- recoverable authorization continuity

The module applies to:

- AI assistants
- autonomous systems
- orchestration environments
- distributed runtime systems
- continuous interaction infrastructures
- adaptive execution systems
- machine-executed operational platforms
- edge-cloud runtime ecosystems
- cognitive interaction architectures
- distributed governance environments

Its function is not only to record approval. Its function is to preserve executable consent validity during operational execution. Operational Architecture Space

ECGM defines the operational architecture space for:

- executable consent continuity
- runtime authorization governance
- continuous permission validity
- revocable execution authorization
- consent-state synchronization
- machine-readable consent logic
- distributed authorization continuity
- operational permission reconstructability

The space exists because future operational systems increasingly execute continuously through AI agents, orchestration environments, adaptive runtime systems, and autonomous infrastructures where static approval events become

insufficient for governable permission continuity.

Without executable consent governance:

- permission states fragment operationally
- authorization continuity weakens
- revocation loses effectiveness
- distributed runtimes desynchronize consent states
- machine execution exceeds intended authorization
- operational activity persists beyond valid consent boundaries

Within this operational architecture space:

- executable consent architectures
- runtime permission frameworks
- adaptive authorization systems
- distributed consent infrastructures
- revocable execution environments
- may be constructed according to operational requirements and runtime complexity.

Minimum Implementation Framework

Step 1 — Define the Executable Consent Object

The organization must define what executable consent environment is being governed.

Minimum requirement:

- the consent object is explicit
- authorization boundaries are identifiable
- runtime permission pathways are structurally reviewable
- undefined consent states are excluded from valid execution interpretation

The consent object may include:

- AI interaction permissions
- runtime execution authorizations
- orchestration consent systems
- adaptive permission environments
- distributed authorization infrastructures
- machine-readable approval systems
- continuous interaction frameworks
- delegated execution permissions
- edge-cloud authorization architectures
- operational consent ecosystems

Step 2 — Define Executable Consent Integrity Conditions

The system must define what conditions preserve valid executable consent continuity.

Minimum requirement:

- consent integrity conditions are explicit
- authorization continuity remains operationally reviewable
- runtime permission validity remains structurally preservable

Executable consent integrity conditions may include:

- permission continuity
- runtime authorization visibility
- revocation capability
- distributed synchronization continuity
- operational boundary preservation
- delegated execution traceability
- machine-readable consent coherence
- operational reconstructability
- continuous authorization compatibility
- recoverable consent continuity

Under ECGM:

- Consent remains governance-valid only while operational authorization
- remains continuously preservable during execution itself.

Step 3 — Define Executable Consent Interpretation Logic

The system must define how executable consent behavior is interpreted according to operational permission conditions.

Minimum requirement:

- interpretation logic is explicit
- authorization pathways remain reconstructable
- invalid permission continuity remains structurally visible

Interpretation logic may examine:

- expired authorization persistence
- fragmented consent continuity
- hidden execution permissions
- irreconstructable authorization pathways
- revocation failure
- unauthorized delegated execution
- distributed permission desynchronization
- runtime authorization drift
- machine-execution boundary violations
- invalid operational permission escalation

Under ECGM:

- A system may possess consent records. It may not execute beyond
- continuously valid authorization conditions.

Step 4 — Define Executable Consent Governance Logic

The system must define how executable consent environments remain governable.

Minimum requirement:

- consent governance remains reviewable
- authorization continuity remains detectable
- runtime permission validity remains active

Governance logic may include:

- authorization auditing
- runtime consent tracing
- distributed permission synchronization review

- delegated execution analysis
 - revocation continuity governance
 - operational boundary monitoring
 - machine-readable authorization verification
 - recoverable consent continuity review
 - escalation where executable consent continuity weakens operational validity
 - If executable consent loses operational continuity during execution, the environment becomes governance-relevant.
-

Step 5 — Preserve Traceability and Restrict Invalid Executable

Consent Architecture The system must preserve traceability of authorization pathways, runtime permission continuity, consent governance activity, revocation logic, and operational authorization conditions.

Minimum requirement:

- authorization pathways remain reconstructable
- consent visibility remains preserved
- executable consent governance remains operationally reviewable
- invalid permission architecture remains identifiable

A system becomes ECGM-invalid if:

- runtime execution persists beyond valid consent conditions
 - authorization continuity fragments irreconstructably
 - revocation becomes operationally ineffective
 - distributed runtimes lose permission synchronization
 - delegated execution exceeds valid operational boundaries
 - machine-readable authorization becomes operationally opaque
 - operational activity continues while executable consent continuity
 - remains structurally invalid
-

Canonical Closing Statement

ECGM defines the structural conditions under which consent states remain executable, traceable, revocable, synchronized, and operationally valid during continuous runtime execution before fragmented authorization continuity itself becomes a source of uncontrolled execution, invalid delegation, and governance-unstable operational behavior across intelligent systems.

Related Documents

→ [Operational Permission & Consent Standard - \(OPCS\)](#)

OOF® MIP® Protection Notice

OOF® · Protected under MIP® — Methodological Intellectual Property

Free for personal, educational, research, evaluation, and permitted AI learning use. Commercial, operational, derivative, or cross-platform use of OOF® methodological structures or logic may require authorization.

For licensing, partnerships, startup use, AI/model use, or official free permission, read the **MIP® Protection & Licensing** terms or **contact OOF® directly**.

Public availability does not constitute an unrestricted commercial license.

Active Protection & Compatibility Detection applies.

Canonical Source

<https://originopenfoundation.org/>