

Getting Started with FA μ ST Toolbox
"Flexible Approximate Multi-Layer Sparse Transforms"



Adrien Leman; Nicolas Bellot

October 19, 2016

Contents

1	Introduction	3
2	Installation on Unix platform	4
2.1	Required components	4
2.2	Download Faust Package & launch terminal	5
2.3	Basic Build & Installation using Makefile	5
2.3.1	Install with administrator privilege	6
2.3.2	Install without administrator privilege	6
2.4	Basic Build & Install using Code Block IDE	6
2.4.1	Install with administrator privilege	6
2.4.2	Install without administrator privilege	7
2.5	Basic Build & Install using Xcode IDE (for MAC OS)	7
2.5.1	Install with administrator privilege	7
2.5.2	Install without administrator privilege	8
2.6	Custom - Advanced Installation	8
3	Installation on Windows platform	10
3.1	Required components	10
3.2	Download Faust Package	11
3.3	Install using GCC-MinGW compiler	12
3.3.1	Install GCC from MinGW	12
3.3.2	Basic Build & Install using the command prompt	13
3.3.3	Basic build & Install using Code::Blocks IDE	14
3.4	Install using Microsoft Visual compiler	15
3.4.1	Install Microsoft Visual compiler	15
3.4.2	Basic Build & Install using Visual Studio IDE	15
3.4.3	Basic Build & Install using terminal	16
3.5	Custom - Advanced Installation	17
4	QuickStart	20
4.1	Configure Matlab path	20
4.2	Use a faust from a saved one	20
4.3	Construct a Faust from a given matrix	22
4.4	Construct a Faust from its factor	23
5	Example	24
5.1	Brain Sources Localization	24
6	Annexes	26
6.1	Required packages	26
6.2	Compatibility between MATLAB and compiler gcc	26
6.3	Further information about Build & Install process	27

6.4	Required packages on Windows platform	27
6.5	Matlab and processor architecture	27
6.6	Add environment variable on Windows platform	28

Chapter 1

Introduction

Presentation: FA μ ST is a C++ toolbox, useful to decompose a given dense matrix into a product of sparse matrices in order to reduce its computational complexity (both for storage and manipulation). In Figure 1.1, the matrix \mathbf{A} represents the dense matrix and \mathbf{S}_j correspond to the sparse matrices as $\mathbf{A} = \prod_{j=1}^J \mathbf{S}_j$.




Figure 1.1: presentation

FA μ ST can be used to speed up iterative algorithms commonly used for solving high dimensional linear inverse problems. The algorithms implemented in the toolbox are described in details by Le Magoarou.[1]. The FA μ ST toolbox is delivered with a Matlab wrapper. For more information on the FAuST project, please visit the website of the project: <http://faust.gforge.inria.fr>.

License: Copyright (2016) Luc Le Magoarou, Remi Gribonval INRIA Rennes, FRANCE
The FAuST Toolbox is distributed under the terms of the GNU Affero General Public License. This program is free software: you can redistribute it and/or modify it under the terms of the GNU Affero General Public License as published by the Free Software Foundation. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Affero General Public License for more details. You should have received a copy of the GNU Affero General Public License along with this program. If not, see <http://www.gnu.org/licenses/>.

Organization: Chapter 2 explains how to install the library FA μ ST for UNIX platform and Chapter 3 corresponds to the Windows installation. Chapter 4 shows quickly how to use this library and finally an example is given Chapter 5.

Chapter 2

Installation on Unix platform

The FA μ ST project is based on **C++ library** available for Linux, MAC OS X and Windows platforms. The proposed toolbox provides a Matlab wrapper. **CMake** has been chosen to build the FA μ ST project because it is an open-source, cross-platform family of tools designed to build, test and package software. This chapter presents the steps to install the FA μ ST tools on Unix platform (both Linux and Mac OS).

Firstly, please ensure that the **prerequisite components** listed in Section 2.1 are installed.

Secondly, refer to section 2.2 to download FA μ ST package and setting your terminal.

Then refer to the appropriate section following the use (or not) of an IDE (Integrated Development Environment):

- Basic installation using **the command line terminal**, refer to Section 2.3.
- Basic installation using **the IDE "Code::Blocks"**, refer to Section 2.4.
- Basic installation using **the IDE "Xcode"** only for MAC OS X platform, refer to Section 2.5.

Finally in Section 2.6, the custom options available to build the FA μ ST toolbox are described to propose Custom - Advanced installation. For example, the optional configuration can be used to modify the install directory path, or to build in debug mode.

2.1 Required components

This Section lists the required components you must install before to begin the FA μ ST installation.

- **Install CMake.** The minimum version required is Cmake version 3.0.2. Visit the website <https://cmake.org/> to process to the installation.
- **Verify Cmake install** by typing in a command terminal :

```
1 > which cmake
```

The command terminal returns the path of your Cmake binary file like

```
1 /usr/bin/cmake
```

If not, add Cmake binary directory in the environment path. (in your `/.bashrc` file)

- **Install Matlab** (minimal version required is Matlab 2014a <https://fr.mathworks.com/downloads/>)
- **Verify Matlab install** by typing in a terminal the following command :

```
1 > which matlab
```

You must obtain the path of your matlab binary file like:

```
1 /usr/local/bin/matlab
```

If not, add `matlab` binary directory in your environment path (in your `/.bashrc` file).

- **Verify Matlab** has a MEX supported compiler by typing in a Matlab Command Window :

```
1 >> mex -setup C++
```

You must obtain this kind of message :

```
1 MEX configured to use <YOURCOMPILER> for C++ language
  compilation.
```

But if you have an error message of the style :

```
1 No supported compiler or SDK was found. For options, visit
2 http://www.mathworks.com/support/compilers/R<20XXx>/<ARCH>.html
```

Visit the webpage specified in the error message, in order to see the list of compiler supported by your Matlab version `R<20XXx>` on your platform `<ARCH>`.

2.2 Download Faust Package & launch terminal

When prerequisites listed in precedent section 2.1 are checked, you can get the package `FA μ ST`.

- **Download** the `FA μ ST` package on the website : <http://faust.gforge.inria.fr/>
- **Unzip** the `FA μ ST` package into your `FA μ ST` directory.
- **Open** a command terminal
- **Set the current directory** to your `FA μ ST` directory (NOTE: do not use any special character in your `FA μ ST` directory path, for example the character μ)

2.3 Basic Build & Installation using Makefile

When you have done the step in section 2.2 (i.e download Faust package and launch the terminal in the right directory), the `FA μ ST` installation can start. If you are administrator of your machine (root access), follow instructions given in Section 2.3.1. Otherwise, for local installation, refer to Section 2.3.2.

2.3.1 Install with administrator privilege

In the terminal opened in Section 2.2, type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake ..
4 > make
5 > sudo make install % run with administrator privilege
```

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

For more detail about `cmake` ; `make` ; `make install` commands, refer to Section 6.3.

2.3.2 Install without administrator privilege

In the terminal opened in Section 2.2, type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake .. -DCMAKE_INSTALL_PREFIX="<Your/Install/Dir>"
4 > make
5 > make install
```

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

For more detail about `cmake` ; `make` ; `make install` commands, refer to Section 6.3.

2.4 Basic Build & Install using Code Block IDE

When you have done the step in section 2.2 (i.e download Faust package and launch the terminal in the right directory), the FA μ ST installation can start. If you are administrator of your machine (root access), follow instructions given in Section 2.4.1. Otherwise, for local installation, refer to Section 2.4.2.

2.4.1 Install with administrator privilege

- In the terminal opened in section 2.2, type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake .. -G "CodeBlocks - Unix Makefiles"
```

- Open the FA μ ST project from the file `./build/FAUST.cbp` with Code::Blocks IDE.
- In Code::Blocks IDE, select **ALL** target and build the project.
- Close Code::Blocks IDE
- Re-Open the FA μ ST project from the file `./build/FAUST.cbp` with Code::Blocks IDE **with administrator privilege**. For that, type in a terminal :

```
1 > sudo codeblocks
```

- In Code::Blocks IDE, select **install** target and build the project.

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

For more detail about `cmake` command, refer to Section 6.3.

2.4.2 Install without administrator privilege

- In the terminal opened in section 2.2, type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake .. -G "CodeBlocks - Unix Makefiles"
4           -DCMAKE_INSTALL_PREFIX="<Your/Install/Dir>"
```

- Open the FA μ ST project from the file `./build/FAUST.cbp` with Code::Blocks IDE.
- In Code::Blocks IDE, select **ALL** target and build the project.
- In Code::Blocks IDE, select **install** target and build the project.

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

For more detail about `cmake` command, refer to Section 6.3.

2.5 Basic Build & Install using Xcode IDE (for MAC OS)

FA μ ST install using the IDE Xcode concerns only MAC OS X environment.

When you have done the step in section 2.2 (i.e download Faust package and launch the terminal in the right directory), the FA μ ST installation can start. This Build & Install section requires that you have the IDE Xcode installed on your system. If you are administrator of your machine (root access), follow instructions given in Section 2.5.1. Otherwise, for local installation, refer to Section 2.5.2.

2.5.1 Install with administrator privilege

- In the terminal opened in section 2.2, type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake .. -G "Xcode"
```

- Open the FA μ ST project from the file `./build/FAUST.xcodeproj` with Xcode IDE.
- In Xcode IDE, select **ALL** target and build the project.
- Close Xcode IDE

- Re-Open the FA μ ST project from the file `./build/FAUST.xcodeproj` with Xcode IDE **with administrator privilege**. For that, type in a terminal:

```
1 > sudo Xcode
```

- In Xcode IDE, select **install** target and build the project.

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

For more detail about `cmake` command, refer to Section 6.3.

2.5.2 Install without administrator privilege

- In the terminal opened in section 2.2, type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake .. -G "Xcode"
4 -DCMAKE_INSTALL_PREFIX="<Your/Install/Dir>"
```

- Open the FA μ ST project from the file `./build/FAUST.xcodeproj` with Xcode IDE.
- In Xcode IDE, select **ALL** target and build the project.
- In Xcode IDE, select **install** target and build the project.

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

For more detail about `cmake` command, refer to Section 6.3.

2.6 Custom - Advanced Installation

The project FA μ ST can be configured with optional parameters, for example if you want to install FA μ ST library in a different folder or to enable the parallel computing using multithread capacities provided by the OS. This build system can be parametrized using the Cmake Graphical User Interface, or the Cmake command line tools.

The Cmake Graphical User Interface `ccmake` allows you to select option input. When using the `ccmake` command in your build directory, the Cmake GUI appears in the console (see fig. 2.1).

When scrolling on a value and pressing [enter], this value can be edited, the black underlaid row displays some information about the option and required path to create the build system. In the case of an option press [enter] to toggle the ON/OFF values. You can edit option by pressing [enter]. For example, press [enter] to edit option `CMAKE_INSTALL_PREFIX` to modify the install directory.

After choosing options for the build and setting the required fields, press [c] to configure. The configuration of the build system is checked again by Cmake, at the end of this check if the build settings are correct, you can press [g] in order to generate the build system.

Instead the `ccmake` GUI, an other possibility to configure and generate the project is to use the command line `cmake` which can take the option input. Here is the list of available options:

```
cmake .. -D<BUILD_NAME>=<value>
```




Figure 2.1: ccmake GUI

- CMAKE_INSTALL_PREFIX : Install directory
- BUILD_TESTING : Enable the ctest option (default value is ON)
- BUILD_DOCUMENTATION : Generating the doxygen documentation (default value is OFF)
- BUILD_MULTITHREAD : Enable multithread with OpenMP Multithreading (default value is OFF)
- BUILD_VERBOSE : Enable verbose option when compile (-v) (default value is OFF)
- BUILD_DEBUG : Enable FAUST Debug mode (default value is OFF)
- BUILD_USE_GPU : Using both CPU and GPU process (default value is OFF)
- BUILD_MATLAB_MEX_FILES : Enable building Matlab MEX files (default value is ON)
- BUILD_OPENBLAS : Using openBLAS for matrix and vector computations (default value is OFF)
- BUILD_READ_XML_FILE : Using xml2 library to read xml files (default value is OFF)
- BUILD_READ_MAT_FILE : Using matio library to read mat files (default value is OFF)

Following the selected option, the cmake installer automatically checks the dependent component (library OpenBlas, eigen, matio, libxml2).

Chapter 3

Installation on Windows platform

The FA μ ST project is based on **C++ library** available for Linux, MAC OS X and Windows platforms. The proposed toolbox provides a Matlab wrapper. **CMake** has been chosen to build the FA μ ST project because it is an open-source, cross-platform family of tools designed to build, test and package software. This chapter presents the steps to install the FA μ ST tools on Windows platform.

- Firstly, please ensure that the **prerequisite components** listed in Section 3.1 are installed.
- Secondly, **choose your preferred C++ Compiler** between GCC from MinGW "Minimalist GNU for Windows"(Section 3.3) and the C++ Compiler from Microsoft Visual Studio (Section 3.4).
- Then, **process to Basic installation** of FA μ ST tool by following instructions given in the appropriate section, depending to the kind of compiler (MinGW or Microsoft Visual) and the use (or not) of an IDE (Integrated Development Environment).

Section 3.5 describes the custom options available to build the FA μ ST toolbox, to propose Custom - Advanced installation. For example, the optional configuration can be used to modify the install directory path, or to build in debug mode.

3.1 Required components

The installation of the FA μ ST tool depends on other components to be installed in order to run properly.

- **Install CMake.** The minimum version required is Cmake version 3.0.2. Download Binary distributions correspond to your environment from <https://cmake.org/download/>.
- **Verify CMake install :** Open a terminal and type the following command:

```
1 > where cmake
```

You should obtain the path of your `cmake.exe` binary file. If not, please add the directory of your `cmake.exe` file in your environment variable. (to add an environment variable, follow instructions given in 6.6).

- **Install Matlab** (minimal version required is Matlab 2014a) (<https://fr.mathworks.com/downloads/>).

- **Verify Matlab install** by checking the `matlab.exe` binary file in the default directory: type in a terminal the following command :

```
1 > where matlab
```

You must obtain the path of your matlab binary file like:

```
1 C:\Program Files\MATLAB\<R2015b>\bin\matlab.exe
```

If not, please add the directory of your `matlab.exe` file in your environment variable. (to add an environment variable, follow instructions given in 6.6).

- **Verify Matlab** has a MEX supported compiler by typing in a Matlab Command Window :

```
1 >> mex -setup C++
```

You must obtain this kind of message :

```
1 MEX configured to use <YOURCOMPILER> for C++ language
  compilation.
```

But if you have an error message of the style :

```
1 No supported compiler or SDK was found. For options, visit
2 http://www.matworks.com/support/compilers/R<20XXx>/<ARCH>.html
```

Visit the webpage specified in the error message, in order to see the list of compiler supported by your Matlab version R<20XXx> on your platform <ARCH>.

- **Install 7-zip tool** from <http://www.7-zip.org/>.
- **Verify 7-zip install** by typing in a terminal the following command :

```
1 > where 7z
```

You must obtain the path of your `7z.exe` binary file:

```
1 C:\Program Files\7-Zip\7z.exe
```

If not, add `7z.exe` directory in your environment path. (to add an environment variable, follow instructions given in 6.6).

3.2 Download Faust Package

When prerequisite components listed in precedent section 3.1 are checked, you can get the FA μ ST package.

- **Download** the FA μ ST package on the website : <http://faust.gforge.inria.fr/>
- **Unzip** the FA μ ST package into your FA μ ST directory.

```
1 > 7z x FAUST-Source-2.0.0.zip
```

3.3 Install using GCC-MinGW compiler

When prerequisite components listed in previous section 3.1 are checked, you must install **MinGW containing the C++ Compiler**. Then, the FA μ ST installation can be done using Command prompt, following instructions given in Section 3.3.2 or using CodeBlocks IDE, following instructions given in Section 3.3.3.

3.3.1 Install GCC from MinGW

- **Download MinGW** in <https://sourceforge.net/projects/mingw/files/latest/download?source=files>
- **Launch install file** and choose latest version of MinGW. Select the MinGW corresponding to gcc-g++ compiler. Then, select mingw32-make.exe in "All packages" menu.
- Add `gcc.exe` directory in your environment path. (to add an environment variable, follow instructions given in 6.6).
- **Verify MinGW install** by typing in a terminal the following command :

```
1 > where gcc
```

You must obtain the path of your `gcc.exe` binary file:

```
1 C:\mingw\mingw64\bin\gcc.exe
```

If not, add `gcc.exe` directory in your environment path. (to add an environment variable, follow instructions given in 6.6).

- **Verify make tool:** In a terminal command, type

```
1 > where make
```

You must obtain the path of your `make.exe` binary file. If not, please check if `make.exe` file is present in MINGW install directory. If not, you can copy and rename `mingw32-make.exe` to `make.exe`.

- From Matlab IDE, you must install MinGW version 4.9.2 using the **ADDON menu**. For more detail, please follow the instruction given in following link : http://fr.mathworks.com/help/matlab/matlab_external/install-mingw-support-package.html. For that, you must have an id session for Mathwork (easy to create). Current this latest step, an environment variable called `MW_MINGW64_LOC` is automatically generated.

3.3.2 Basic Build & Install using the command prompt

The basic install described in this section requires the GCC compiler from MinGW (see precedent Section 3.3.1). If you have administrator privilege, follow instructions in Section 3.3.2.1, otherwise follow instructions given in Section 3.3.2.2.

3.3.2.1 Install with administrator privilege

- Open a command terminal
- Set the current directory to your FA μ ST directory (NOTE: don't use any special character in your FA μ ST directory path, for example the character μ)
- Type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake -G "MinGW Makefiles" ..
4 > make
```

- Open a command terminal **with administrator privilege** : right click on command prompt icon and select run as administrator.
- Set the current directory to your FA μ ST directory
- Type the following commands :

```
1 > make install
```

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

3.3.2.2 Install without administrator privilege

- Open a command terminal
- Set the current directory to your FA μ ST directory (NOTE: don't use any special character in your FA μ ST directory path, for example the character μ)
- Type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake -G "MinGW Makefiles" ..
4         -DCMAKE_INSTALL_PREFIX="<Your/Install/Dir>"
5 > make
6 > make install
```

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

3.3.3 Basic build & Install using Code::Blocks IDE

The basic install described in this section requires the GCC compiler from MinGW (see precedent Section 3.3.1). If you have administrator privilege, follow instructions in Section 3.3.3.1, otherwise follow instructions given in Section 3.3.3.2.

You must select the gcc compiler in the IDE code::Blocks in the Settings menu -> Compiler... -> Selected Compiler

Then, the FA μ ST installation can be done.

3.3.3.1 Install with administrator privilege

- Open a command terminal
- Set the current directory to your FA μ ST directory (NOTE: don't use any special character in your FA μ ST directory path, for example the character μ)
- Type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake -G "CodeBlocks - MinGW Makefiles" ..
```

- Open the FA μ ST project from the file ./build/FAUST.cbp with Code::Blocks IDE.
- In Code::Blocks IDE, select ALL BUILD, select RELEASE mode and generate the project.
- Re-Open the FA μ ST project from the file ./build/FAUST.cbp with Code::Blocks IDE **with administrator privilege**. For that, right-click on the Code::Blocks icon and select "run as administrator".
- In Code::Blocks IDE, select INSTALL target, select RELEASE mode and build.

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

For more detail about cmake commands, refer to Section 6.3.

3.3.3.2 Install without administrator privilege

- Open a command terminal
- Set the current directory to your FA μ ST directory (NOTE: don't use any special character in your FA μ ST directory path, for example the character μ)
- Type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake -G "CodeBlocks - MinGW Makefiles" ..
4 -DCMAKE_INSTALL_PREFIX="<Your/Install/Dir>"
```

- Open the FA μ ST project from the file ./build/FAUST.cbp with Code::Blocks IDE.
- In Code::Blocks IDE, select ALL target, select RELEASE mode and build the project.

- In Code::Blocks IDE, select install target, select RELEASE mode and build the project.

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

For more detail about cmake commands, refer to Section 6.3.

3.4 Install using Microsoft Visual compiler

When prerequisites listed in section 3.1 are checked, you must install **Microsoft Visual Studio** containing the C++ Compiler (Section 3.4.1). Then, the FA μ ST installation can be done using Visual Studio IDE, following instructions given in Section 3.4.2 or using Command prompt, following instructions given in Section 3.4.3.

3.4.1 Install Microsoft Visual compiler

- Download Microsoft Visual Studio Professional 2013 from <https://www.microsoft.com/en-US/download/details.aspx?id=44916>
- Install Microsoft Visual Studio Professional 2013

Then, the FA μ ST installation can be done using Visual Studio IDE, following instructions given in Section 3.4.2 or using Command prompt, following instructions given in Section 3.4.3.

3.4.2 Basic Build & Install using Visual Studio IDE

The basic install described in this section requires Microsoft Visual Studio (see precedent Section 3.4.1). If you have administrator privilege, follow instructions in Section 3.4.2.1, otherwise follow instructions given in Section 3.4.2.2.

3.4.2.1 Install with administrator privilege

- Open a command terminal
- Set the current directory to your FA μ ST directory (NOTE: don't use any special character in your FA μ ST directory path, for example the character μ)
- Type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake ..
```

- Open the FA μ ST project from the file `./build/FAUST.sln` with Visual Studio IDE.
- In Visual Studio IDE, select ALL BUILD, select RELEASE mode, and generate the project three times.
- Close Visual Studio IDE
- Re-Open the FA μ ST project from the file `./build/FAUST.sln` with Visual Studio IDE with **administrator privilege**.
- In Visual Studio IDE, select INSTALL target, select RELEASE mode, and generate the project.

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

For more detail about cmake commands, refer to Section 6.3.

3.4.2.2 Install without administrator privilege

- Open a command terminal
- Set the current directory to your FA μ ST directory (NOTE: don't use any special character in your FA μ ST directory path, for example the character μ)
- Type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake .. -DCMAKE_INSTALL_PREFIX="<Your/Install/Dir>"
```

- Open the FA μ ST project from the file `./build/FAUST.sln` with Visual Studio IDE.
- In Visual Studio IDE, select ALL target, select RELEASE mode and generate the project three times.
- In Visual Studio IDE, select install target, select RELEASE mode, and generate the project.

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

For more detail about cmake commands, refer to Section 6.3.

3.4.3 Basic Build & Install using terminal

The basic install described in this section requires the Microsoft Visual Studio compiler (see precedent Section 3.4.1). If you have administrator privilege, follow instructions in Section 3.4.3.1, otherwise follow instructions given in Section 3.4.3.2.

3.4.3.1 Install with administrator privilege

In the case of **Microsoft Visual Studio 2013 compiler using the command terminal** :

- Open a command terminal
- Set the current directory to your FA μ ST directory (NOTE: don't use any special character in your FA μ ST directory path, for example the character μ)
- Type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake ..
4 > cmake --build . --config "Release"
5 > cmake --build . --config "Release"
```

- Re-Open a command terminal **with administrator privilege**

```
1 > cmake --build . --config "Release" --target "install"
```

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

For more detail about cmake commands, refer to Section 6.3.

3.4.3.2 Install without administrator privilege

In the case of **Microsoft Visual Studio 2013 compiler using the command terminal** :

- Open a command terminal
- Set the current directory to your FA μ ST directory (NOTE: don't use any special character in your FA μ ST directory path, for example the character μ)
- Type the following commands :

```
1 > mkdir build
2 > cd build
3 > cmake .. -DCMAKE_INSTALL_PREFIX="<Your/Install/Dir>"
4 > cmake --build . --config "Release"
5 > cmake --build . --config "Release"
6 > cmake --build . --config "Release" --target "install"
```

FA μ ST Toolbox should be installed. Now, refer to Quick-Start Chapter 4 to check the install and to try FA μ ST toolbox.

For more detail about cmake commands, refer to Section 6.3.

3.5 Custom - Advanced Installation

1. Open application **cmake-GUI.exe** from the program menu or from your cmake install binaries directory to launch the CMake configuration application:
2. Set the "Where is the source code:" text box with the path of the directory where the source files are located (F:/WORK/FAUST/faust) and the "Where to build the binaries:" with the path of the directory where you want to build the library and executable files (F:/WORK/FAUST/faust/build). (see fig. 3.1).

When clicking for the first time on the [Configure] button, CMake will ask for the build tool you want to use. The build system type depends on the builder you want to use, in our case this is the Visual Studio X (X depending the version of Visual installed on the computer) chain tools. (see fig. 3.2).

3. When pressing again the [Configure] button to configure the build system, CMake performs a list of tests to determine the system configuration and manage the build system. If the configuration is correct then no pop-up will appears during the tests and CMake finally shows the various options of the build underlaid in grey. In case of a configuration issue, a pop up window warns you about this issue indicating which test has failed, in this case the build option in the CMake application software will be underlaid in red. We will discuss in Section 3.5 what to do in such a case, but let us for the moment assume that everything ran smoothly. (see 3.3).




Figure 3.1: cmake GUI




Figure 3.2: cmake GUI




Figure 3.3: cmake GUI

Chapter 4

QuickStart

A Matlab wrapper is delivered with the FA μ ST C++ library. It provides a user friendly new class of matrix **Faust** efficient for the multiplication with matlab built-in dense matrix class.

4.1 Configure Matlab path

In order to use matlab wrapper, follow the instructions :

- **Install** FA μ ST tool (see Chapter 2 in case of Unix install or Chapter 3 in case of Windows install)
- **Launch** Matlab.
- **Set the working directory** of the Matlab Command Window to :
/<HOMEDIR>/Documents/MATLAB/Faust
- **Configure** the Matlab path by typing the following commands :

```
1 >> cd /<HOMEDIR>/Documents/MATLAB/Faust
2 >> setup_Faust
```

4.2 Use a faust from a saved one

Now, you can run `quick_start.m` script in the Matlab Command Window by typing :

```
1 >> quick_start
```

`quick_start.m` script is located in following path :

<HOMEDIR>/Documents/MATLAB/faust/demo/Quick_start/quick_start.m

In this script, first of all, a Faust of size 4000x5000 is loaded from a previous one that is saved into a matfile located in :

<HOMEDIR>/Documents/MATLAB/faust/demo/Quick_start/faust_quick_start.mat

```
1 % loading a Faust A from saved-one
2 A=Faust('faust_quick_start.mat');
```

Secondly, a list of overloaded matlab function shows that a Faust is handled as a normal Matlab builtin matrix.

```
1 % get the size of the faust
2 [dim1,dim2] = size(A);
3
4 % transpose a faust
5 A_trans = A';
6
7 % multiplication by A
8 x1 = rand(dim2,1);
9 y1 = A*x1;
10
11 % multiplication by A'
12 x2 = rand(dim1,5);
13 y2 = A'*x2;
14
15
16 % get the 2-norm (spectral norm) of the faust A
17 norm_A = norm(A); % equivalent to norm(A,2);
18
19 % convert Faust to full matrix
20 A_full=full(A);
21
22
23 % get the coefficient i,j and slicing for reading purpose
24 coeff=A(3,4);
25 col_2=A(:,2);
26 submatrix_A=A(3:5,2:3);
27 submatrix_A=A(2:end,3:end-1);
28 % Warning : A(i,j)=3 will not modify A, writing is not allowed
```

Finally, it performs a little time comparison between multiplication by a Faust or its full matrix equivalent. This is in order to illustrate the speed-up induced by the Faust. This speed-up should be around 30 (depending on your machine).

4.3 Construct a Faust from a given matrix

To see an example of building a Faust from a matrix, you can run `factorise_matrix.m` in the Matlab Command Window by typing :

```
1 >> factorise_matrix
```

`factorise_matrix.m` script is located in following path :

`<HOMEDIR>/Documents/MATLAB/faust/demo/Quick_start/factorise_matrix.m`

In this script, from a given matrix **A** of size 100x200 :

```
1 % number of row of the matrix
2 dim1 = 100;
3 % number of column of the matrix
4 dim2 = 200;
5 % matrix to factorise
6 A = rand(dim1,dim2);
```

We generate the parameters of the factorisation from :

- The dimension of **A** (**dim1** and **dim2**),
- **nb_factor** the number of factor of the Faust,
- **rcg** the Rational Complexity Gain, which represents the theoretical memory gain and multiplication speed-up of the Faust compared to the initial matrix

```
1 % Rational complexity Gain (theoretical speed-up) of the Faust
2 rcg = 100;
3 % number of factor of the Faust
4 nb_factor = 2;
5 %% generate parameters of the factorisation
6 params = generate_params(dim1,dim2,nb_factor,rcg);
```

Then we factorize the matrix **A** into a Faust **Faust_A**

```
1 %% factorisation (create Faust from matrix A)
2 faust_A = faust_decompose(A,params);
```

And as for `quickstart.m`, we make some time comparison at the end.

4.4 Construct a Faust from its factor

To see an example of building a Faust from its factors, you can run `construct_Faust_from_factors.m` in the Matlab Command Window by typing :

```
1 >> construct_Faust_from_factors
```

This following example shows how to build a faust from a cell-array representing its factors.

```
1 % number of row of the Faust
2 dim1=300;
3 % number of column of the Faust
4 dim2=100;
5 % number of factor of the Faust
6 nb_factor=4;
7 % density of each factor
8 density_factor=0.1;
9
10 %cell-array representing its factors
11 factors = cell(1,nb_factor);
12
13 % 1st factor is a rectangular sparse matrix of density equal to
    density_factor
14 factors{1} = sprand(dim1,dim2,density_factor);
15
16 % all the others factor are square sparse matrix of density equal
    to density_factor
17 for i=2:nb_factor
18     factors{i} = sprand(dim2,dim2,density_factor);
19 end
20
21 %% construct the Faust
22 A_faust=Faust(factors);
23
24
25 % a multiplicative scalar can be taken into account to construct
    the Faust
26 lambda=2;
27
28 % B_faust=lambda*A_faust
29 B_faust=Faust(factors,lambda);
```


Chapter 5

Example

5.1 Brain Sources Localization

An experience of Brain Source Localization using several gain matrices including FA μ ST and several solvers is provided. After configuring the Matlab path (cf section 4.1), you just need to type in the Matlab Command Window:

```
1 >> BSL
2 >> Fig_BSL
```

BSL.m runs the experiment (see the script file :
/<HOMEDIR>/Documents/MATLAB/Faust/demo/Brain_source_localization/BSL.m)
Fig_BSL.m displays the Figure 5.1. illustrating the speed-up using a FA μ ST. (see the script file:
/<HOMEDIR>/Documents/MATLAB/Faust/demo/Brain_source_localization/Fig_BSL.m)

This figure illustrates the speed-up with a FA μ ST (\mathbf{M} is the gain dense matrix and $\widehat{\mathbf{M}}_6, \widehat{\mathbf{M}}_9, \widehat{\mathbf{M}}_{16}, \widehat{\mathbf{M}}_{26}$ are different FA μ ST representing \mathbf{M}):




Figure 5.1: Performance of FAuST tool on Brain Source Localization experiment

Chapter 6

Annexes

6.1 Required packages

Here is a list of packages used in the FA μ ST project. The installation of this packages are automatically done. There are nothing to do. (see the source directory `"/externals"`).

- Library **Eigen** <http://eigen.tuxfamily.org>: C++ template library for linear algebra: matrices, vectors, numerical solvers, and related algorithms.
- Library **OpenBLAS** <http://www.openblas.net>: Optimized BLAS library based on GotoBLAS2 1.13 BSD version.
- Library **xml2** <http://xmlsoft.org>
- Library **matio** <https://sourceforge.net/projects/matio>

6.2 Compatibility between MATLAB and compiler gcc

Adjust your version of GCC compiler in order to run the installation properly. The use of the mex function in Matlab requires that you have a third-party compiler installed on your system. The latest version of Matlab (2016a in our case) only supports up to GCC 4.7 (see <http://fr.mathworks.com/support/compilers/R2016a/index.html?sec=glxa64> for more detail). To temporally change your version of gcc compiler, you can modify the environment variable CC an CXX. For that, export your CC and CXX variables corresponding to gcc and g++ binaries path :

- find your gcc and g++ version path using `which` command in a terminal :

```
1 > which gcc
2 > which g++
```

- Open your `/.bashrc` file and save the return-path of gcc and g++ like:

```
1 # export version of gcc
2 export CC=/usr/lib64/ccache/gcc
3 export CXX=/usr/lib64/ccache/g++
```

An other way to change the version of compiler use by mex function from matlab command is :

```
1 > mex -setup
```

6.3 Further information about Build & Install process

When using the **cmake** command to generate the build system, **cmake** performs a list of tests to determine the system configuration and manage the build system. If the configuration is correct then the build system is generated and written. In this case, the three last lines of the console log of **cmake** command should be:

```
1 -- Configuring done
2 -- Generating done
3 -- Build files have been written to: <YOUR/LOCAL/DIRECTORY/build>
```

The command **make** will compile the build files.

The command **sudo make install** will install the library and others components in the default directory:

/usr/local/lib/libfaust.a for the FA μ ST library,
~/Documents/MATLAB/faust/ for the wrapper matlab.

You must have administrator privilege because the library file **libfaust.a** is copied in an root path directory. If you do not have administrator privilege, you can realize a local install using **cmake** optional parameter **-DCMAKE_INSTALL_PREFIX="<Your/Install/Dir>"**.

The **cmake** optional parameter **-DCMAKE_INSTALL_PREFIX="<Your/Install/Dir>"** allows to install the binaries on the selected install directory.

The **cmake** optional parameter **-G "CodeBlocks - Unix Makefiles"** allows to generate the Code Blocks project and the Unix Makefiles.

The **cmake** optional parameter **-G "Xcode"** allows to generate the Xcode project.

6.4 Required packages on Windows platform

Here is a list of packages used in the FA μ ST project. Eigen and OpenBlas library are automatically installed : there are nothing to do (see the directory **./externals/win/**).

- **Eigen** is a C++ template library for linear algebra: matrices, vectors, numerical solvers, and related algorithms (see <http://eigen.tuxfamily.org>).
- **OpenBLAS** is an optimized BLAS library based on GotoBLAS2 1.13 BSD version. (see <http://www.openblas.net>). To install OpenBlas, refer to <https://github.com/xianyi/OpenBLAS/wiki/Installation-Guide>. You can directly download precompiled binary here <https://sourceforge.net/projects/openblas/files/v0.2.14/>

6.5 Matlab and processor architecture

If your processor architecture is 64 bit, Matlab must be installed in 64 bit. If your processor architecture is an 32 bit, Matlab must be installed in 32 bit. You can check your environment variable called **PROCESSOR_ARCHITECTURE** by typing :

```
1 > set
```

Check in the list the variable PROCESSOR_ARCHITECTURE.


PROCESSOR_ARCHITECTURE=AMD64 correspond to 64bit, PROCESSOR_ARCHITECTURE=x86 correspond to 32 bit.

6.6 Add environment variable on Windows platform

Here is the steps to add an environment variable in Windows 7.

1. From the Desktop, right-click the Computer icon and select Properties. If you don't have a Computer icon on your desktop, click the Start button, right-click the Computer option in the Start menu, and select Properties.
2. Click the Advanced System Settings link in the left column.
3. In the System Properties window, click on the Advanced tab, then click the Environment Variables button near the bottom of that tab.
4. In the Environment Variables window (pictured below), highlight the Path variable in the "System variables" section and click the Edit button. Add or modify the path lines with the paths you want the computer to access. Each different directory is separated with a semicolon as shown below.

```
1 C:\Program Files;C:\Winnt;C:\Winnt\System32
```



Bibliography

- [1] L. Le Magoarou and R. Gribonval. Flexible multilayer sparse approximations of matrices and applications. *IEEE Journal of Selected Topics in Signal Processing*, 10(4):688–700, June 2016.