

This is extra-credit homework to get more practice with programming, small steps at a time. Odd-numbered problems have answers on the next page, while you get credit for any even-numbered answers turned in. Practice doing both even and odd problems, using the answers as a guide afterward.

First, create a basic C++ program:

```
#include <iostream>
#include <string>
using namespace std;

int main()
{
    return 0;
}
```

For the turn-in problems (even numbered), you can have one right after another in the same program. Use a comment to specify which part of the code belongs to which problem. Example:

```
#include <iostream>
#include <string>
using namespace std;

int main()
{
    // Question 1.
    int number;

    // Question 2.
    char letter;

    return 0;
}
```

Submit the .cpp (C++ Source) file once you are done.

Questions: Variables

Points possible: 4

1.	Declare a variable whose name is amountOfCats , and whose data type is an integer. Assign it a value of 20
2.	Declare a variable whose name is pricePerCat , and whose data type is a float. Assign it a value of 49.99
3.	Declare a variable whose name is nameOfCat , and whose data type is a string. Assign it a value of PumpkinSparkles
4.	Declare a variable whose name is catLocation and whose data type is a string. Assign it a value of Kansas City
5.	Declare a variable whose name is grade and whose data type is a character. Assign it a value of A
6.	Declare a variable whose name is rating and whose data type is a character. Assign it a value of +
7.	Declare a variable whose name is success and whose data type is a boolean. Assign it a value of true
8.	Declare a variable whose name is done and whose data type is a boolean. Assign it a value of false

Answers: Variables

1.	<pre>int amountOfCats = 20;</pre> <p>int is the data type (integer), amountOfCats is the name of the variable, and we are assigning it a value of 20 with the assignment operator =.</p>
3.	<pre>string nameOfCat = "PumpkinSparkles";</pre> <p>the value of a string variable must be contained within double-quotes.</p>
5.	<pre>char grade = 'A';</pre> <p>the value of a char variable must be contained within single-quotes. Chars can only hold a single character – numbers, letters, symbols, etc.</p>
7.	<pre>bool success = true;</pre> <p>booleans can be set to true or false.</p>

Questions: Output

Points possible: 5

9.	Output the text Hello World to the screen.
10.	Output the text How are you? To the screen.
11.	Output the text I have , then output the value of the amountOfCats variable, then output the text cats . <u>Example output:</u> I have 20 cats.
12.	Output the text The price of a cat is , then output the value of pricePerCat . <u>Example output:</u> The price of a cat is 49.99
13.	Output a single new line with no text.
14.	Output two new lines with one cout statement.
15.	Output the text Cat Name: , then output the value of nameOfCat . Then output a new line. Then, output the text Cat Location: , then output the value of catLocation . <u>Example output:</u> Cat Name: PumpkinSparkles Cat Location: Kansas City
16.	Output the text Grade: , then output the value of grade . Then output a new line. Then, output the text Success: , then output the value of success . (Note: success will show up as either a 1 or a 0, not true or false) <u>Example output:</u> Grade: A Success: 1
17.	With one cout statement, output the text Rating: With a second cout statement, output the value of rating on the same line.
18.	With one cout statement, output the text Grade: With a second cout statement, output the value of grade on the same line.

Answers: Output

9.	<pre>cout << "Hello World";</pre> <p>the cout command stands for console-out. Use the stream operator <<. Strings must be contained within two double-quotes.</p>
11.	<pre>int amountOfCats = 20; // Problem 1 cout << "I have " << amountOfCats << " cats.";</pre> <p>You can combine string literals (within “ ”) and variables. Any time you switch, you must put the stream operator << between them.</p>
13.	<pre>cout << endl;</pre> <p>The endl command stands for end-line.</p>
15.	<pre>cout << "Cat Name: " << nameOfCat << endl; cout << "Cat Location: " << catLocation << endl;</pre> <p>It looks nice when the program runs to end each cout line with an endl if you don't need the next cout statement to appear on the same line.</p>
17.	<pre>cout << "Rating: "; cout << rating;</pre> <p>If there is no endl at the end of a cout, any future cout statements will appear at the end of the first one.</p>

Questions: Input

Points possible: 3

19.	Declare a variable named age whose data type is an integer. Output the text Enter your age: Then get the input from the user and store it in the age variable.
20.	Declare a variable named balance whose data type is a float. Output the text How much money do you have: Then get the input from the user and store it in the balance variable.
21.	Declare two variables of type float. Name them number1 and number2 . Output the text Enter two numbers: Get the input for two numbers and store them in number1 and number2 . Then, output the text Sum: And output the result of number1 + number2 .
22.	Declare two variables of type float. Name them x and y . Output the text Enter two numbers: Get the input for two numbers and store them in x and y . Then, output the text Product: And output the result of number1 * number2 .
23.	Declare a character variable and name it userChoice Output the text Do you want to quit? Y or N: Get the input and store it in the variable userChoice Output the text You selected: Output the value of userChoice .
24.	Declare a character variable and name it input Output the text Which direction? N, E, S, or W: Get the input and store it in the variable input Output the text You selected: Output the value of input .

Answers: Input

19.	<pre>int age; cout << "Enter your age: "; cin >> age;</pre> <p>The cin command stands for console-in. The stream operator >> points away from the cin and towards the variable you are storing data in.</p>
21.	<pre>int number1, number2; cout << "Enter two numbers: "; cin >> number1 >> number2; cout << "Sum: " << number1 + number2;</pre> <p>You can declare multiple variables of the same type on one line, with the variable names separated by a comma. You can also get the input for two variables at once, by linking them together with the stream operator >>.</p>
23.	<pre>char userChoice; cout << "Do you want to quit? Y or N: "; cin >> userChoice; cout << "You selected: " << userChoice;</pre> <p>Use a generic name for variables. The user is inputting their choice. Later on, we will worry about whether they chose Y or N, by using if statements. Don't name the variable yes or no.</p>