

P5 Archive Overview

A native macOS application for querying and managing Archiware P5 Archive server data with secure credential storage and historical tracking.

Requirements

- macOS 14.0 or later
- Archiware P5 server with REST API enabled
- jq command-line tool (optional, for CSV export during queries)

```
brew install jq
```

Quick Start

1. Add a Server

- Click Manage Servers in the sidebar, then choose Add
- Enter server alias, IP address, port (default: 8000), username, and password
- Click "Add"

2. Run a Query

- Select a server from the sidebar
- Click "Run Query"
- View results in the table (top) and progress in the log (bottom)
- If the selected server is unavailable, click **Cancel Query** or press Esc, then select another server

3. View History

- Toggle from "Current" to "History" in the toolbar
- Filter by server using the dropdown
- Export to CSV using the export button (↑)

File Locations

File Type	Location
Query Output (CSV/JSON)	~/Documents/P5ArchiveOverview/[ServerAlias]_[timestamp]/
SQLite Database	~/Library/Application Support/P5ArchiveOverview/P5ArchiveHistory.sqlite
History CSV Export	~/Documents/P5ArchiveOverview/ArchiveHistory_[Server]_[timestamp].csv

Server List Import & Export

Share server configurations with other P5 Archive apps using a common JSON file.

Discovery and review at launch - place `P5Servers.json` in either location and the app offers new server configurations for review on next launch:

- `/Users/Shared/P5Servers.json` - shared across all users
- `~/Documents/P5Servers.json` - current user only

Import Servers JSON and **Export Servers JSON** are available in the **Manage Servers** sheet. Export saves the current list (passwords excluded) as `P5Servers.json`.

Duplicate handling:

- **Launch discovery** never changes the saved server list until you confirm **Add New Servers**.
- Existing connections are matched by IP address, port, and username; changing an alias does not make a server new.
- **Not Now** defers the prompt, while **Ignore This File Version** remembers the file's SHA-256 fingerprint.
- **Manual import** warns if duplicates are found, then lets you import only the new servers or cancel.

After importing, edit each new server once to enter its password (stored in Keychain).

See `README-servers-feature.md` for the full JSON format reference and cross-app workflow.

Features

- **Secure Credentials:** Passwords stored in macOS Keychain
- **No ATS Issues:** Uses `curl` to bypass App Transport Security restrictions
- **Path-First Results:** The Directories column receives the flexible table space by default, and manual column widths persist across launches
- **Bounded and Cancellable Queries:** Offline connections time out after eight seconds; active queries can be cancelled while the server list remains available
- **Automatic Deduplication:** Historical records are deduplicated by server, pool, start time, finish time, and client
- **CSV Export:** Export both current query results and historical data

Keyboard Shortcuts

Action	Shortcut
Add Server	Manage Servers -> Add
Run Query	Click "Run Query"
Cancel Query	Esc or click "Cancel Query" while running
Cancel Dialog	Esc
Save/Confirm	Return

Troubleshooting

- **"No password found"**: Edit the server and re-enter the password
- **Offline server**: Connection attempts stop after eight seconds. Use **Cancel Query** or Esc to stop sooner and select another server
- **Query times out after connecting**: Large connected queries have a five-minute ceiling; verify P5 responsiveness and try again
- **Query fails**: Check server IP, port, and credentials; ensure P5 REST API is enabled
- **CSV not created**: Install jq with `brew install jq`

License

Apache 2.0 License