SERVICE BULLETIN

SUBJECT: Introduction of the revised service schedule requirements and revised Service and Warranty Book. (Revision A)

GROUP: 00 - General Information	**ISSUE DATE:** 20-06-2008	**ISSUE NO:** 00-2007-011-A
MODEL: All	**DISTRIBUTION:** Australia	
DOCUMENT ISSUE DATES: First Issue: 27-07-2007 Revision A: 20-06-2008	**D. R. BUDDEN** **NATIONAL SERVICE MANAGER** 	
	This Bulletin consists of 5 Pages	

This revision **00-2007-011-A** replaces **00-2007-011.**

Changes in this revision are highlighted in italics with the revision symbol. A

This Service Bulletin informs you of the introduction of the revised service requirements for applicable 07 M/Y and 08 M/Y vehicles and a revised Service and Warranty Book Part No. **MR936234**. This book will be introduced as a running change, effective from August 2007.

Attachments

ITEM	ATTACHMENT
Regular service schedule chart	**1**
Fuel injector supply pipe service schedule and record	**2**
Approximate regular service times (Hours)	**3**

Note: *Additions / changes on attachments are highlighted.*

Changes

1. Revised valve clearance check / adjustment schedules for DI-Diesel engines (common rail - ML Triton and NS Pajero).
2. Revised valve clearance check / adjustment schedules for 4A9 and 4B1 engines (including Colt Cabriolet engine 135950).
3. Revised valve clearance check / adjustment schedules for 6B3 and 6G7 MIVEC engines.
4. Revised schedule for automatic transmission fluid replacement for CVT (excluding F1C1A) and W6AJA transmissions.
5. Revised schedules for manual transmission oil replacement for F5MBB, F5MGA, F5MGB and W5MBB transmissions.
6. Revised schedule for transfer case oil replacement for ZG Outlander.
7. Added common rail DI-Diesel engine fuel injector pipe removal record.

NOTE: Details contained in this Service Bulletin and Attachments are current at the time of publication.
MMAL however, reserves the right to make changes at any time without prior notice or obligation.
Copyright © Mitsubishi Motors Australia Limited. Reproduction in whole or part prohibited without written approval.

8. The requirement for a 7,500km initial engine oil change on NS Pajero DI-Diesel engines (with common rail fuel system) has been deleted. However, the initial engine oil change at 7,500kms is still required for ML Triton DI-Diesel engines (with common rail fuel system).
9. The approximate regular service times on page 16 of the Service and Warranty Book, Part No. **MR936234** will change to reflect the revised schedules.

Notes:

- Please ensure that all Dealer staff involved in Service Administration are aware of these revisions.
- ~~An addendum will be made available for Dealers wanting to update current Service and Warranty Books (Part No. MR936026) already supplied with applicable 07 M/Y and 08 M/Y vehicles (details will be advised separately).~~

  An addendum has been made available for Service and Warranty Book (Part No. MR936026) and can be ordered by Dealers on LAMP. (Reference No. for addendum is 00/2007/011)
  Please affix addendum to page 15 of the Service and Warranty Book.
- **Refer to attachments 1, 2 and 3 for full details of additions / changes.**
- To assist Dealer staff with these changes and customer enquiries regarding scheduled service requirements, MMAL will provide itemised service schedules/approximate regular service times for each vehicle in the near future.

Applicable Publication

Service and Warranty Book Part No. **MR936234** replaces MR936026.

Applicable Vehicles

These changes will apply to all applicable 07 M/Y vehicles retrospectively and 08 M/Y vehicles.

Attachment 1

REGULAR SERVICE SCHEDULE CHART

R = Replace
A = Check and adjust as necessary
I = Inspect and report to customer
L = Lubricate
AU = Audible check for excess clearance
C = Inspect and correct or replace as necessary

Special Requirements (additional items, refer page 17)
@ = Replace every 45,000km under severe conditions
= Replace every 30,000km under severe conditions
¥ = Replace every 7,500km under severe conditions
^ = Inspect every 6 months
† = Replace more frequently under severe conditions
‡ = Replace every 3,750km under severe conditions
+ = Replace every 2,500km under severe conditions
Ø = Replace every 5,000km under severe conditions
‡‡ = Replace every 90,000km under severe conditions

Service Interval (use odometer reading or months, whichever occurs first)		x1,000km	15	30	45	60	75	90	105	120	135	150	165	180	195	210	Vehicle	
		Months	12	24	36	48	60	72	84	96	108	120	132	144	156	168	Passen-ger	Com-mercial
LUBRICATION																		
Automatic transmission fluid	FWD (incl. F1C1A CVT)	@	C	C	C	C	C	C	R	C	C	C	C	C	C	R	0	-
	2WD	@	C	C	C	C	C	R	C	C	C	C	C	R	C	C	-	0
	CVT (excl. F1C1A) & W6AJA	@	C	C	C	C	C	R	C	C	C	C	C	R	C	C	0	-
	4WD		C	C	R	C	C	R	C	C	R	C	C	R	C	C	0	0
Manual transmission oil	FWD	#	C	C	C	C	C	C	R	C	C	C	C	C	C	R	0	-
	2WD	#	C	C	C	C	R	C	C	C	C	R	C	C	C	C	-	0
	AWD/4WD	#	C	C	R	C	C	R	C	C	R	C	C	R	C	C	0	0
	F5MBB, F5MGA, F5MGB & W5MBB only	‡‡	C	C	C	C	C	C	C	C	C	C	C	C	R	C	0	-
Transfer case	AWD/4WD	#	C	C	R	C	C	R	C	C	R	C	C	R	C	C	0	0
	4WD (Outlander only)	@	C	C	C	C	R	C	C	C	C	R	C	C	C	C	0	-
Front/rear axle oil	2WD		C	C	C	C	C	R	C	C	C	C	C	R	C	C	-	0
	AWD/4WD		C	C	R	C	C	R	C	C	R	C	C	R	C	C	0	0
	4WD (W1CJA & W6AJA)	@	C	C	C	C	C	R	C	C	C	C	C	R	C	C	0	-
UNDER HOOD OPERATIONS (Continued)																		
Valve clearance (if applicable - excludes engines listed separately below)			I	I	I	I	I	I	I	I	I	I	I	I	I	I	0	0
Valve clearance (4A9 and 4B1 engines)			AU	AU	AU	AU	AU	I	AU	AU	AU	AU	AU	I	AU	AU	0	0
Valve clearance (DI-Diesel engines)			AU	A	AU	A	AU	A	AU	A	AU	A	AU	A	AU	A	-	0
Valve clearance (6G7 MIVEC and 6B3 MIVEC engines)			AU	AU	A	AU	AU	A	AU	AU	A	AU	AU	A	AU	AU	0	0
UNDER VEHICLE OPERATIONS																		
Drive train components for leaks			I	I	I	I	I	I	I	I	I	I	I	I	I	I	0	0

=additions / changes

Attachment 2

FUEL INJECTOR SUPPLY PIPE SERVICE SCHEDULE AND RECORD (COMMON RAIL DIESEL ENGINES ONLY)

Service Interval (use odometer reading or months, whichever occurs first)	x1,000km	15	30	45	60	75	90	105	120	135	150	165	180	195	210	Vehicle	
	Months	12	24	36	48	60	72	84	96	108	120	132	144	156	168	Pas-senger	Com-mercial
NORMAL REMOVAL, INSTALLATION AND REPLACEMENT SCHEDULE																	
Fuel injector supply pipe removal, refitment and replacement schedule - (normal process for valve clearance check and adjustment)		-	A	-	A	-	A	-	A	-	A	-	R	-	A	-	0
RECORD THE ACTUAL NUMBER OF TIMES FUEL INJECTOR SUPPLY PIPES HAVE BEEN REMOVED, REFITTED AND REPLACED																	
Fuel injector supply pipe removal and refitment record. (Record a “1” each time fuel injector supply pipes are removed and refitted, after pipes have been removed and refitted 5 times, replace pipes on the 6th time pipes are removed, record replacement with “R”)																-	0

=additions / changes

Attachment 3

APPROXIMATE REGULAR SERVICE TIMES (HOURS)

NOTE: 1. Engine timing belt(s) must be replaced at 100,000 km or 60 months.
2. Iridium, platinum and surface discharge spark plugs must be replaced at 100,000 kms.
3. Brake fluid and engine coolant must be replaced every 24 months, irrespective of kms.

Service interval (use odometer reading or months, whichever comes first)	x1,000km	15	30	45	60	75	90	105	120	135	150	165	180	195	210
	Months	12	24	36	48	60	72	84	96	108	120	132	144	156	168
FWD		1.0	0.7	1.4	0.7	1.0	1.5	1.3	0.7	1.4	0.7	1.0	1.5	1.0	1.3
		1.0	1.3	0.8	1.3	3.5	1.5	1.3	1.3	0.8	3.8	1.0	1.5	1.0	1.9
AWD		1.3	1.4	2.3	1.5	1.5	2.4	1.9	1.5	2.3	1.5	1.3	2.4	1.3	2.0
		1.3	2.0	1.7	2.1	4.8	2.4	1.9	2.1	1.7	4.4	1.3	2.4	1.3	2.6
RWD Petrol (4x2)		1.1	1.1	2.3	1.1	1.2	2.4	1.4	1.1	2.3	1.2	1.1	2.4	1.1	1.4
		1.1	1.7	1.7	1.7	3.5	2.4	1.4	1.7	1.7	4.1	1.1	2.4	1.1	2.0
4WD Petrol		1.3	1.4	2.7	1.5	1.5	2.8	1.5	1.5	2.7	1.5	1.3	2.9	1.3	1.6
		1.3	2.0	2.1	2.1	3.8	2.8	1.5	2.1	2.1	4.4	1.3	2.9	1.3	2.2
RWD Diesel (4x2)		1.4	1.8	2.2	1.8	1.5	2.7	1.7	1.8	2.2	1.9	1.4	2.7	1.4	2.1
		1.4	2.4	1.6	2.4	1.5	2.7	1.7	2.4	1.6	2.5	1.4	2.7	1.4	2.7
4WD Diesel		1.6	2.1	2.6	2.3	1.8	3.1	1.8	2.3	2.6	2.2	1.6	3.1	1.6	2.3
		1.6	2.7	2.0	2.9	1.8	3.1	1.8	2.9	2.0	2.8	1.6	3.1	1.6	2.9
Additions/deductions (refer below)		BEQ	BEFQ	BCEGLMOQ	BEFQ	BEKQ	ABCEFGHLOQ	BDEINQ	BEFQ	BCEGLMOQ	BEFKQ	BEQ	ABCEFGHLOQ	BEPQ	BDE-FINQ

A=Add 1.4hr - check valve clearance (4B1 and 4A9 engines)
B= Add 0.2hr - vehicle with pollen filter
C= Add 2.3hr - adjust valve clearance (6G7 MIVEC engines)
D= Add 0.4hr - vehicles with in-tank fuel filter
C= Add 2.2hr - adjust valve clearance (6B3 MIVEC engines)
E= Add 0.2hr - vehicles with common rail diesel
F= Add 1.5hr - adjust valve clearance (DI-Diesel engines)
G= Add 0.2hr - vehicles with rear drum brakes
H= Add 0.2hr - vehicles with F1CJA, W1CJA & W6AJA transmissions only
I= Deduct 0.2hr - vehicles with F1CJA transmission only
J= Deduct 0.2hr - vehicles with W1CJA & W6AJA transmissions only
K= Add 0.1hr - Transfer case oil (Outlander only)
L= Deduct 0.1hr - Transfer case oil (Outlander only)
M= Deduct 0.1hr - Rear axle oil (Outlander only)
N= Deduct 0.1hr - FWD manual trans. oil (F5MBB, F5MGA & F5MGB only)
O= Deduct 0.1hr - 4WD manual trans. oil (W5MBB only)
P= Add 0.1hr - FWD manual trans. oil (F5MBB, F5MGA & F5MGB only) and 4WD manual trans. oil (W5MBB only)
Q= Add 0.3hr - check valve clearance (excludes DI-Diesel, 4B1, 4A9, 6G7 MIVEC & 6B3 MIVEC engines)

=additions / changes