MITSUBISHI MOTORS

SERVICE BULLETIN

AFTERSALES SERVICE OFFICE, MITSUBISHI MOTORS AUSTRALIA LTD

PURPOSE: INFORMATION	ISSUE: 00-2014-009	DATE: 02-06-2014
SUBJECT: 2015 M/Y NEW MODEL INTRODUCTION		<MODEL> ASX / <MY> 15
GROUP: 00 - GENERAL		

This Service Bulletin advises you of the introduction of the 2015 M/Y XB ASX model range.

Please note that the warranty on the 15MY ASX has been revised to 5 years/ 100,000km (whichever occurs first) Please refer to page 9 of this bulletin for further details

Model Codes

Model	Type	MMAL Model Code	Model Code	Engine		Transmission
				Type	Fuel	Type
LS	2WD	XB1L45	GA2WXNSHR8	2.0L D4 MIVEC	Petrol	5 M/T
		XB2L45	GA2WXTSHR8			CVT
	4WD	XB4H45	GA8WXLSFZR8	2.2L D4 I/C,T/C, DID	Diesel	6 A/T
XLS	4WD	XB4P45	GA8WXLSFZR8			
XLS	2WD	XB2P45	GA2WXTSHR8	2.0L D4 MIVEC	Petrol	CVT

Note:

- Vehicle information plate is located on the underside of the engine hood.
- Data label is located on the passenger side A-pillar.
- Compliance label is located on the driver side A-pillar.
- Chassis number is stamped on the bulk head in the engine bay.

Summary of changes

The 2015 M/Y ASX is based on the 2014 M/Y ASX with the following changes

- Revised design 17” Alloy Wheels
- Day time running lamps
- Emergency stop signal function (ESS)
- Improved NVH
- Improved steering feeling, handling stability and ride comfort
- Revision to Continuously Variable Transmission (CVT models only)
  - Sensation of acceleration is enhanced
  - Improved performance (faster standing start acceleration and passing)
  - Fuel economy improvement (from 7.7L to 7.4L)

NOTE: Details contained in this Service Bulletin and Attachments are current at the time of publication.
MMAL however, reserves the right to make changes at any time without prior notice or obligation.
Copyright © Mitsubishi Motors Australia Limited. Reproduction in whole or part prohibited without written approval

Summary of changes (continued)

ASX LS

- Chrome exhaust tip
- Chrome belt line moulding
- Privacy glass
- Black roof rails

OPTIONS

No options are available on 15MY ASX

Specifications

Engine

- 4B11: 2.0L MPI MIVEC petrol engine: 4 cylinder, DOHC 16 valve (D4).
- 4N14: 2.2L DID diesel engine: 4 cylinder, DOHC 16 valve (D4)

ITEM	4B11 (PETROL)	4N14 (DIESEL)
Total displacement (cc)	1,998	2,268
Cylinder arrangement	4 inline vertical	
Bore x Stroke (mm)	86.0 x 86.0	86.0 x 97.6
Compression Ratio	10.0:1	14.9:1
MIVEC	Intake and exhaust (Variable Valve Timing)	n/a
Auto Lash Adjuster	Not Equipped	
Maximum output	110 kW @ 6,000 rpm	110 kW @ 3,500 rpm
Maximum Torque	197 Nm @ 4,250 rpm	360 Nm @ 1,500 ~3,000 rpm
Emission Standard	Euro 4	Euro 5
Catalytic Converter	Equipped (2 oxygen sensors)	Equipped *
Fuel tank capacity (L)	2WD - 63 4WD - 60	60

Note: * The forced DPF regeneration procedure for XB ASX is different to NS Pajero.
For information on DPF forced regeneration refer to **Technical Service Bulletin 17-2010-003 and the applicable workshop manual**

Fuel Requirements

Petrol-powered vehicles

- Unleaded fuel: Unleaded fuel with an octane number of 90 or higher
- Ethanol: A mixture of up to 10% ethanol (grain alcohol) and 90% unleaded petrol may be used provided the octane rating is at least as high as that recommended for unleaded petrol

CAUTION: Do not use more than 10% concentration of ethanol by volume. Use of more than 10% concentration may lead to damage of vehicle fuel system, engine, engine sensors and exhaust system

Diesel-powered vehicles

- Diesel fuel: Diesel fuel with a Cetane number of 45 or higher
- Bio-diesel: Diesel fuel mixed with Fatty Acid Methyl Ester (FAME) may be used provided the quality of FAME conforms to the European Standard EN14214 and the amount of FAME must be below 5% concentration by volume. (Refer to General Letter GL-06-008)

Liquid Petroleum Gas (LPG) compatibility

The diesel 2.2L 4 cylinder 4N14 and the petrol 2.0L 4 cylinder 4B11 engines and ARE NOT LPG compatible

Transmission

- M/T: F5MBB 5 Speed
- CVT: F/W1CJA INVECS III Continuously Variable Transmission (CVT) with Sports mode (6 speed)
- A/T: W6AJA Electronic control 4WD, INVECS-II 6A/T with sport mode

Item		F5MBB	F1CJA		W6AJA
		5 M/T	CVT	Sports mode	6 A/T
Transmission type		5-speed forward, 1-speed reverse	Forward: continuously variable (with steel belt), reverse: 1 gear		Electronically controlled 6-speed full-automatic. 3-element torque converter with damper clutch
Transmission gear ratio	1st	3.538	2.349-0.394	2.349	4.199
	2nd	1.913		1.397	2.405
	3rd	1.333		1.074	1.583
	4th	1.028		0.832	1.161
	5th	0.820		0.631	0.855
	6th	N/A		0.518	0.685
	Reverse	3.583	1.750		3.457
Final reduction ratio			6.466		3.360

- Electronic Controlled 4WD system. Incorporates an Electronic Controlled Coupling (ECC) in front of the rear differential which is activated via the drive mode switch. Drive mode (2WD, 4WD, LOCK) can be changed at any time while the ignition switch is on. Standard on 4WD models
- **Refer to Group 27C of the Workshop and Technical Information Manuals for further information**
- For M/T the clutch slave cylinder is a concentric type mounted inside the clutch housing
- Paddle shift levers mounted behind the steering wheel on XLS CVT & Automatic models

Brakes

- Brake override system. (Smart Brake) is a system that prevents accidental engagement of both the throttle and brake pedal by the driver which can occur in emergency braking situations. In this circumstance, throttle input is overridden allowing maximum braking action to proceed
- Brake Assist system. Refer brake section of the Workshop Manual section 35 – Brakes Info ID M351-00-011-60300-01)
- Anti-Skid Brake System (ABS) with Electronic Brake-Force Distribution (EBD)
- Hill Start Control (HSC) system
- Active Stability Control (ASC) system incorporating Traction Control (TCL)
- Front ventilated discs and rear solid discs with single piston floating calipers
- Overall disc diameter / thickness (mm)
- Front: 241/26. Rear: 259.8/10

Steering and Suspension

- Rack and pinion with electric power assist steering
- Front suspension is McPherson Strut with coil spring and stabiliser bar
- Rear suspension is trailing arm with multi-link with coil spring and stabiliser bar

Body

- Reinforced Impact Safety Evolution (RISE) body structure which is designed to reduce the force of impact that is transferred to the passenger compartment.
- High-tensile steel panels of 590MPa and 980MPa grade have been used for some panels to improve collision safety and reduce weight.
- Plastic front guard used to reduce repair cost during low speed impact

Wheels and Tyres

Wheel		**ROAD WHEEL**	**SPARE WHEEL**
		ALL MODELS	
Wheel	Type	Alloy	Steel
	Size	17 x 6.5 JJ	16 x 4.0T
	Amount wheel rim offset	46	40
	PCD mm	114.3	
Tyre	Size	215/60R17 96H	T125/70D16 96M*[1] T155/70D16 96M*[2]
	Inflation Pressure		

Note:

- PCD indicates pitch circle diameter of the wheel installation holes
  - *1 indicates 2WD spare
  - *2 indicates 4WD Spare

Vehicle Ride Height

ITEM	**MEASUREMENT** (for all models)
Front (mm)	441 (± 20)
Rear (mm)	439 (± 20)

Note: Vertical measurement from wheel centre to top of wheel arch opening at unladen mass.

Electrical

- **Keyless Operation System (KOS):**
  A system that integrates the door entry, engine starting, keyless entry and immobilizer functions. This system is also referred to as “Smart Key”. The system varies from previous models. The push button on the front exterior door handles locks and unlocks the doors as there is no longer a sensor in the handle. KOS is Standard on XLS models

  Note: The transponder for the immobiliser function is located in the KOS key. Should the KOS key battery be flat place the KOS key in the glove box to start the vehicle. Refer to Group 42B of the Workshop and Technical Information Manuals for further information

- **Emergency Stop signal System (ESS)** reduces the possibility of rear end collisions during sudden braking by the rapid and automatic blinking of the hazard warning lamps to alert vehicles approaching from behind.

- **One-Touch Start System (OSS)**
  A system that utilises a push button control instead of a key to switch between OFF-ACC-ON-START. It is integrated with the KOS system. OSS is Standard on XLS models
  Refer to Group 42B of the Workshop Manual for further information

- **Wireless Control Module (WCM):**
  A system that integrates the keyless entry and immobilizer functions. Standard on ALL models except XLS.
  Refer to Group 42C of the Workshop Manual for further information

- **Electronic Total Automobile Control System (ETACS):**
  The ETACS system is integrated into the Junction Box. Functions include body electrical control function,gateway function, variant coding function and customisation function

  Note: Vehicle customisation can be performed through MUT III or MMCS if equipped (refer to page 162 of the MMCS Owner’s manual)
  Refer to Group 54A of the Workshop Manual for further information

- **Engine, SRS and ETACS ECU:**
  These ECUs contain variant coding files

  Note: The Engine ECU, SRS ECU and ETACS ECU are programmed with variant coding files. *Should one of these ECU’s require replacement follow the variant coding procedure found in TSB: 00-2007-014*

Overview of interior and exterior features and standard equipment

OVERVIEW				
ITEM	**MODEL**			
	2WD	**4WD**	**XLS 2WD**	**XLS 4WD**
Interior				
Dual stage deployment driver and passenger front SRS air bags	S	S	S	S
Side and curtain SRS air bags	S	S	S	S
Driver's knee air bag	S	S	S	S
Driver's seat - slide, recline, and height adjuster	S	S	Powered	Powered
Passenger seat - slide and recline adjuster	S	S	S	S
Driver and passenger seat heater	-	-	S	S
Front and rear seat material	Cloth	Cloth	Leather	
Front seat belts: 3 point Emergency Locking Retractor (ELR) with pretensioner and force limiter and adjustable shoulder anchors	S	S	S	S
Rear seats: 60:40 split fold type with adjustable head rests	S	S	S	S
Rear seat belts: Outer, 3 point ELR and Automatic Locking Retractor	S	S	S	S
(ALR). Centre, 3 point ELR	S	S	S	S
3 Child restraint anchor positions	S	S	S	S
Keyless Operating System (KOS)	-	-	S	S
One-Touch Start System (OSS)	-	-	S	S
Keyless entry system - Wireless control module (WCM)	S	S	-	-
Immobiliser / Central door locking / Theft alarm	S	S	S	S
Electric tailgate opener	S	S	S	S
Door trim	Cloth	Cloth	Leather look	
Inside door handles, air oulet knobs,	Chrome			
Telescopic and tilt adjustable steering column	S	S	S	S
Cruise control (controls on steering wheel)	S	S	S	S
Remote Audio Controls mounted on steering wheel	S	S	S	S
Handsfree phone controls mounted on steering wheel	S	S	S	S
High contrast combination meter cluster	S	S	S	S
Leather wrapped steering wheel and shift lever	S	S	S	S
Automatic air conditioning with air pollen filter and 2nd row ducts	S	S	S	S
Paddle shifters mounted behind steering wheel (CVT & Auto only)	-	-	S	S
Front and rear door power windows	S	S	S	S
Auto up/ down on driver's window	S	S	S	S
12V / 120W accessory socket in console and instrument panel	S	S	S	S
Electrochromic mirror	-	-	S	S

OVERVIEW (cont)				
ITEM	**MODEL**			
	2WD	**4WD**	**XLS 2WD**	**XLS 4WD**
MMCS Navigation system with SD card mapping	-	-	S	S
Exterior				
Fog lamps	-	-	S	S
Halogen headlights	S	S	S	S
Welcome light and come home light	S	S	S	S
Dusk sensing headlamps	-	-	S	S
Windshield wipers with vehicle speed sensitive intermittent control	S	S	-	-
Windshield wipers with automatic ON/OFF function (Rain sensor) type	-	-	S	S
Rear window intermittent wiper and washer	S	S	S	S
Privacy glass	S	-	S	S
Rear spoiler with high-mount stop lamp	S	S	S	S
Colour coded electric fold door mirrors, front and rear bumpers, side air dam	S	S	S	S
Belt line moulding	Chrome			
Fog lamp bezel, radiator grille,	Black		Chrome	
Radiator grille	Chrome	Chrome	Chrome	Chrome
Rear Park Assist	-	-	S	S
Rear camera	S	S	S	S
Panoramic glass roof	-	-	S	S
Rear mud guards	S	S	S	S
Chrome muffler tip	S	S	S	S
Space Saver spare	S	S	S	S

Note: S: Standard

Paint Codes

Vehicle Colour	Code (MMC)	Paint Repair Codes				
		PPG	Glasurit	Dupont Standox	Protec	AKZO Nobel
White(S)	W37	MIT W37	MIT W37		B02908	MIT4021
Starlight (P)	W13	MIT W13	MIT W13		B03048	MIT9154
Cool Silver (M)	A31	MIT A31	MIT A31	P9452	B02919	MIT9938
Black Mica (P)	X42	MIT X42	MIT X42	X2235	B02572	MIT9403
Red (M)	P26	MIT.P26	MIT.P26	X2235	MIT9571	MIT9571
Lightning Blue (M)	D06	MIT D06	D06	X5252		HT / D06
Titanium (M)	U17	MIT U17	CMU10017	X8421		MITU17

Reverse sensor colours

Vehicle colour	Code (MMC)	Reversing sensor colour
White (S)	W37	White (P)
Starlight (P)	W13	White (P)
Cool Silver (M)	A31	Silver
Black (P)	X42	Black
Red (M)	P26	Red (M)
Lightning Blue (M)	D06	Blue
Titanium (M)	U17	Grey (M)

Note:
(M) Metallic paint and (P) Pearlescent paint

Service Publications

PUBLICATION	PART NO
2015 M/Y XA ASX Workshop Manual including Body Repair Manual	AU900418
Customer information booklet Service and Warranty	AU900447
Mitsubishi PDI Manual	MR936475
Mitsubishi Vehicle Hand over Report (available on the MMAL Asset database - Diamond Advantage Section).	PAM 441
Vehicle Customisation Guide	XA-7-2010
Technicians Data Guide	XB-09-2012

Audio System and Mitsubishi Multi Communication System (MMCS)

LS MODEL

- MELCO, AM/FM radio/CD/MP3 with 4 speakers system MP3 and auxiliary socket, steering wheel controls, USB

STANDARD ON XLS ONLY:

- MMCS: MELCO AM/FM radio/single CD/MP3 reverse camera, with auxiliary socket and Satellite Navigation with Rockford Fosgate Premium Audio 9 speaker system.USB

Note: When the MMCS is installed the voice command function will operate only with the mobile phone not the satellite navigation system

Mobile Phone Handsfree System/ Bluetooth Compatibility

ALL MODELS

- Factory fitted mobile phone handsfree system with bluetooth connectivity, voice recognition and controls mounted on the steering wheel

Audio and MMCS manual and warranty procedures

Audio Instructions are contained within the Owner's Manuals and MMCS instructions are contained within the MMCS Owner's Manual. Should either the Audio unit or MMCS unit require repairs during the warranty period, then the existing Audio change over system is to be utilised. (Refer to Service Procedure Manual - Section 4.7)

Mitsubishi Factory Warranties and Roadside Assistance

The vehicle is covered by a 5 year/100,000 km warranty. Please refer to the applicable Service and Warranty book that is provided with the vehicle

5 year / 100,000 km Roadside Assistance subject to servicing requirements is standard on all models.

Capped price servicing applies to the ASX model range. Refer to the Capped Price Servicing Dealer Operations manual for information

Service Information

- The 2015 M/Y XB ASX Workshop Manual was issued to Dealers in April 2014

Pre Delivery and Vehicle delivery

The vehicle must be prepared in accordance with the Mitsubishi PDI Manual and the vehicle hand over to the customer is to be in accordance with the Mitsubishi Vehicle Hand over Report.

Additionally:

- Ensure the Ignition Off Draw (IOD) fuse located in the engine bay relay box is pushed down.
- Ensure the Steering Wheel Sensor is initialized.
- Enable the Service Reminder function and check Service Schedule. (Disabled for shipment).
- For Service information refer to WorkShop Manual, 54A Chassis Electrical / Combination Meter / On Vehicle Service / Setting Service Reminder Function or the "Service Reminder" section of the Owner's manual.

Major Service Items

ITEM		REGULAR SERVICE SCHEDULES	ADDITIONAL SERVICE SCHEDULES
Engine oil	4B11, or 4N14	15,000 km or 12 months	7,500 km or 6 months
Engine oil filter			
Valve clearances	4B11.	90,000 km or 72 months (with an audible check every 15,000 km)	
Valve clearances	4N14	45,000 km or 36 months (with an audible check every 15000 km)	
Coolant		Change every 96 months (maximum 120,000 km) then every 60 months (maximum 75,000km)	
Timing chain		As required	
Brake fluid		Change every 24 months (maximum 30,000 km)	
Air cleaner element		45,000 km or 36 months	Inspect every 7,500 km
CVT/ Auto transmission fluid		90,000 km or 72 months	Refer to *1
Manual Transmission oil		195,000 km or 156 months	
Transfer Box oil (4WD vehicles only)		75,000 km or 60 months	
Differential (4WD vehicles only)		90,000 km or 72 months	45,000 km
A/C Air Pollen Filter		15,000km	
Fuel filter (in tank)	4B11.	150,000km	As required
Fuel Filter	4N14	24 months or 30,000 km	
Spark plugs	4B11	90,000 km	

*Note: *1 Severe use for CVT fluid is determined by referring to MUT III data list item **CVT oil degradation level** (from System Select menu select AT/CVT/A-MT/TC-SST / Special Function / CVT oil degradation level). The fluid must be replaced when the count reaches 210,000. After replacing the CVT fluid use MUT III to reset the CVT oil* degradation *level count from the same screen.*

Refer to Workshop Manual Group 23A - CVT / Troubleshooting / Symptom procedures / The fluid temperature warning lamp illuminates too frequently (Inspection Procedure 7).

Lubrication

ITEM		CAPACITY	LUBRICATION	MITSUBISHI MOTORS GENUINE OIL PART NUMBERS
Engine Petrol (with filter)	4B11	4.0 litres 4.3 litres	A.P.I classification “SG or higher” with the correct S.A.E. viscosity grade for the expected temperature range.*1	AW349163 / 5L AW350293 / 20L AW349162 / 205L
Engine Diesel (with filter)	4N14	5.5 litres 5.8 litres	ACEA: For service C1,C2,C3 or C4 JASO: For service DL-1” *2	8967401 / 20L
Manual transmission (F5MBB) **Genuine Mitsubishi fluids only**		2.5 litres	MTF Manual transmission fluid GL-3 SAE 75W-80	MR935272 / 20L
Automatic transmission **Genuine Mitsubishi fluids only**	CVT	7.1 litres	CVTF-J4 Automatic transmission fluid	MZ320261 / 1L MZ320262 / 4L
	Auto	8.2 litres	ATF-J3 Automatic trans fluid	4031610 / 4L
Transfer case	All	0.5 litres	A.P.I. classification GL-5 with a S.A.E. 80 viscosity grade	AW329392 / 1L
Rear differential		0.5 litres	A.P.I. classification GL-5 with a S.A.E. 80 viscosity grade	AW329392 / 1L
Engine coolant	4B11	8.0 litres	Mitsubishi Genuine Coolant Blue (SLLCP)	MZ101075EX / 2L
	4N14	8.5 litres		
Brakes and clutch		As required	Dot 3 or Dot 4 brake fluid	MR936863 / 0.5L
Air conditioning		500 ± 200g	Refrigerant R-134a	N/A

Note:

- *1 Conforming to the requirements of the API or ACEA classification with the correct SAE viscosity grade number for the expected ambient temperature range
- *2 Low SAP conforming to the requirements of the ACEA or JASO classification with the correct SAE
- viscosity grade number for the expected ambient temperature range.
- *3 Premix coolant is 50% concentration.

Special Tools

The following special tools have been deemed as mandatory for ASX and have been issued to Dealers.

PART NUMBER	PART NAME
MB992211	Wrench, crowfoot
MB992281	Socket, hexagon
MB992282	Bar, sealing
MB992283	Holder, retainer
MB992284	Installer, valve stem seal
MB992285	Adaptor, compression pressure test
MB992286	Guide, connecting rod
5021-MITS	Gauge, valve and adapter kit
MB992287	Installer, circlip
MB992288	Installer, drive belt
MB992289	Remover, injector
MB992290	Installer, oil seal
MB992333	Remover, injector nozzle gasket

For the “Essential Special Service Tool list for Mitsubishi Dealers” please refer to the Dealer Portal \ My Work \ Service \ Quick References \ QR-18.

MUT III data

- To access the vehicle diagnostic systems using the MUT-III tester the current software upgrade version PRA14031 or later is required.
- The MUT III vehicle diagnostic connector is located under the dash to the right of the drivers SRS knee air bag module.

Production date

All models commenced April 2014.