

Translation Protégé Knowledge for Executing Clinical Guidelines

Jeong Ah Kim,
BinGu Shim, SunTae Kim·JaeHoon Lee, InSook Cho, Yoon Kim

Agenda

1. Motivation

2. How to translate

3. Implementation and Case study

4. Conclusion

Motivation

❖ Definition of CDSS

- any piece of software that takes as input information about a clinical situation and that produces as output inferences that can assist practitioners in their decision making and that would be judged.

❖ CDSS can

- give specific reminders at particular clinical situations
 - give exact information to support drug choosing, dosing, preventing adverse drug effects
 - support the health care management at the hospital level
 - be used as educational systems for medical students or young doctors
-

Motivation

❖ In CDSS, core component is guidelines.

- Computer-interpretable guidelines (CIG) have been developed for decision support during clinical process
- evidence based guideline practice promises to improve health care quality.

❖ Several approaches for modeling the clinical guideline

- Arden syntax, EON, PRODIGY, GUIDE, GLIF,
 - SAGE (Standard-based Sharable Active Guideline Environment)
-


Motivation

❖ SAGE

- uses standardized components that allow interoperability of guideline execution elements
 - Integrate guideline-based decision support with the workflow of care process
 - synthesizes prior guideline modeling work for encoding guideline knowledge
 - *A Suite of Models and Services to Support Guideline Modeling and Execution*
 - *Deployment-Driven Knowledge-Base Development Process*
 - there is not publically available execution engine yet
-

Motivation

❖ EHR Knowledge Engine




Motivation

❖ Knowledge Model of u-BRAIN

- Ontology-based
 - Domain Ontology defines the concepts and criterion value in each domain
 - Interface ontology define the required information from outside(ex: patient information stored in CIS)
 - Rule is defined to make the decisions with concepts in domain ontology and values in interface ontology
 - Each rule has identifier


- Structured workflow based



How to translate

❖ Our approach

- Analyze the SAGE representation formalism
- Use protégé KnowledgeBase interface to get the SAGE object model
- Apply “Export” plug-in development method to integrate SAGE model and u-BRAIN converter and u-BRAIN execution engine
 - SAGE object(Knowledge base) -> uEngine Object mapping -> serialize -> Plug-in Export -> XPD & XML for u-BRAIN representation




How to Translate

❖ Object model of SAGE and mapping to uBRAIN object

SAGE model	Meaning	features
Guideline	Collection of associated Recommendation Set	Process
Recommendation Set	Decision Map or set of activity graph	Sub-Process
Context	where the recommendations associated with the Context node is applicable.	Rule
Expression	expression language that can be used with any object-oriented model.	Rule
Concept	Constant atomic term	Rule
Variable	Meaningful result from executing the internal logic	Rule
Evidence Statement	represents a relationship between clinical conditions and interventions and additional contextual information and supporting references	Rule/Process
Activity graph	inter-related activities.	Process
Action	flow-of-control information	Process
Decision	representation of decision knowledge required to recommend a choice among alternatives	Rule/Process


How to Translate

❖ New Architecture of u-BRAIN



How to translate

❖ Workflow at runtime



How to translate

❖ **SAGE Workflow to u-BRAIN activity**

- Each action node is mapped to one activity node
- Decision node is mapped to also u-BRAIN activity to invoke rule engine to do decision-making using rule
- Complex action node is mapped one decision making node and decision structure of activity

❖ **SAGE decision to u-BRAIN rule**

- Each expression is mapped to rule expression (if then else)
 - Generate the interface model to access the EMR (external data resource)
-

How to Translate

❖ 2 Kinds Expression in translation perspectives

- EMR database access is not required during rule execution
 - N-ary criterion, variable_comparison_criterion, VKB_Query
- EMR Database access is required during rule execution
 - Prsence_criterion, adverse_reaction_prsence_criterion, observation_presence_criterion, medication_presence_criterion, comparison_criterion, VMR_query

How to translate

❖ **N-ary criterion**

- Expression of BOOLEAN combination (AND, OR, or NOT) of simpler criterion expression
- Each expression is mapped to one rule expression and connected with logical operator
- Connected expression is another rule expression

❖ **Variable_Comparison_Criterion**

- compares the value of a variable to some other value.
 - Rule expression compare the value to element of interface XML
 - The value of 'References As' slot is translated into the element of interface XML
 - Interface XML is already made at the invocation time of CDSS service
-

How to translate

❖ **Presence_Criterion**


- checks for presence or absence of coded concept in instances of a VMR class within the valid time
- Translate the rule to check the value availability in interface XML
- interfaceXML contains the data queried from EMR by ExecuteVMRQuery()

❖ **Comparison_Criterion**

- Check for equality of data stored in EMR and variable or value
 - Translate the rule to compare the value in interface XML with defined operator
-

How to Translate


❖ N-ary criterion



RuleExpr	
Comment	diastolic BP for Stage I with DM
RuleExprObjec...	SAGE
RuleName	HTMgtV1_3_evaluation_Instance_72
RuleText	Boolean HTMgtV1_3_evaluation_Instance_72() {IF(FIRE("HTMgtV1_3_evaluation_Instance_73") and FIRE("HTMgtV1_3_evaluation_Instance_79")) THEN(true) ELSE(false) RESULTINFO(BOTH:"") }

How to Translate

❖ Variable_Comparison_Criterion,



RuleExpr	
Comment	Current sub-max dose BB order exists
RuleExprObjec...	SAGE
RuleName	HTMgtV1_3_evaluation_Instance_198
RuleText	Boolean HTMgtV1_3_evaluation_Instance_198() {IF((input.element(label="Daily dose of current BB").value != "" and input.element(label="max dose of BB medication").value != "") and (input.element(label="Daily dose of current BB").value < input.element(label="max dose of BB medication").value)) THEN(true) ELSE(false) RESULTINFO(BOTH:"") }


How to translate

❖ Workflow to translate


- Verify the guideline in SAGE according to SWM
 - Identify the logical error
 - Translate into u-BRAIN representation model
 - Viewing the translated representation model
 - Simulating the guideline
-

Implementation and Case study

❖ Pulgin Module





❖ Several Options





Implementation and Case study

❖ Verification Report




Implementation and Case study

❖ Translated Guideline



Implementation and Case study

❖ Translated Results



Implementation and Case study

❖ Translated Results

Criterion 2

Today BP state is controlled without DM (instance of N_ary_C...

Label
Today BP state is controlled without DM

Criteria

- diastolic BP for Controlled state without DM
- systolic BP for Controlled state without DM

Boolean Connective
AND

Converted to

RuleExpr	
Comment	Today BP state is controlled without DM
RuleExprObjec...	SAGE
RuleName	HTMgtV1_3_evaluation_Instance_128
RuleText	Boolean HTMgtV1_3_evaluation_Instance_1280 {IF(FIRE("HTMgtV1_3_evaluation_Instance_129") and FIRE("HTMgtV1_3_evaluation_Instance_135")) THEN(true) ELSE(false) RESULTINFO(BOTH:"")}

Rule

diastolic BP for Controlled state without DM (instance of Com...

Label
diastolic BP for Controlled state without DM

Vmr Class
Observation

Aggregation Operator
most_recent

Code
Diastolic blood pressure

Valid Window
Today (midnight to midnight)

Operator
<

Assume
no_assumption

Value
90

Converted to

RuleExpr	
Comment	diastolic BP for Controlled state without DM
RuleExprObjec...	SAGE
RuleName	HTMgtV1_3_evaluation_Instance_129
RuleText	Boolean HTMgtV1_3_evaluation_Instance_1290 {IF(ExecuteVMRQuery_CC("HTMgtV1_3_evaluation_Instance_129","Observation","most_recent","EHR005 2","EHR Concept","TimeInterval/low_label/Start of today variable/high_label/End of today variable/","TimeInterval/low_label/Start of today variable/high_label/End of today variable/","no_assumption") < 90.0) THEN(true) ELSE(false) RESULTINFO(BOTH:"") }

Comparison_Criterion_Query	
query_id	HTMgtV1_3_evaluation_Instance_129
evmr_class	Patient
agg_operator	most_recent
Abc Text	Select EMR_PATIENT.DBP , EMR_PATIENT.VS_DATE from EMR_PATIENT where EMR_PATIENT.ID=input.pid

Rule

DIA
Query

Implementation and Case study

❖ Evaluation in Lab alerting CDSS

- 10 kinds lab test

Env	Server	Test Server
	CPU	1.86GHz
	Memory	1.5GB
	OS	windows2003 SP1

Performance

Unit: ms

# of cases	Turnaround Time of DI	Turnaround Time of KE
323,445	346.16	51.90

Correctness

item	# of cases	Error ratio
DIA	323,445	0%
Knowledge engine	323,445	0%

Conclusion

❖ **SAGE Guideline execution environment is available**

❖ **In the future**

- Several case studies is going now.
- Verification environment will be added
 - So far, debugging utility verify the SAGE model corresponding structured workflow model
 - We have a plan to develop verification tool based on test case
- develop knowledge repository management tools
 - Access control
 - Version control
 - Change control
 - Configuration management
 - Reuse

Thank You !

Executable Guideline
