

Lesson 13 Strings

Trịnh Thành Trung


trungtt@soict.hust.edu.vn

Strings

- An array of characters
- Used to store text
- Another way to initialize:

```
char str[] = "Text";
```

The terminator



The Terminator

- Strings terminate with NULL character, signed by '\0' (ascii code 0)
- This is a convention used to know where the string ends
- It means that in order to hold a string of N characters we need an array of length $N + 1$
- So the previous initialization is equivalent to

```
char str[] = {'b', 'l', 'a', 'b', 'l', 'a', '\0'};
```

String library

- Like in the case of `stdio.h` and `math.h`, we have a special library for handling strings
- We should have

```
#include <string.h>
```

String library

- Functions:
 - `strlen(const char s[])`
returns the length of s
 - `strcmp(const char s1[],
 const char s2[])`
compares s1 with s2
 - `strcpy(char s1[],
 const char s2[])`
copies to contents of s2 to s1
 - ...

Example

```
#include <stdio.h>
#include <string.h>
int main()
{
    char s1[ 20 ] = "Happy ";
    char s2[] = "New Year ";
    char s3[ 40 ] = "";
    printf( "s1 = %s\ns2 = %s\n", s1, s2 );
    printf("strcat( s1, s2 ) = %s\n",
           strcat( s1, s2 ));
    printf("strncat( s3, s1, 6 ) = %s\n",
           strncat( s3, s1, 6 ));
    printf("strcat( s3, s1 ) = %s\n",
           strcat( s3, s1 ));
    return 0;
}
```

```
s1 = Happy
s2 = New Year
strcat( s1, s2 ) = Happy New Year
strncat( s3, s1, 6 ) = Happy
strcat( s3, s1 ) = Happy Happy New Year
```

String Conversion Functions

- Conversion functions
 - In **<stdlib.h>** (general utilities library)
- Convert strings of digits to integer and floating-point values

Prototype	Description
<code>double atof(const char *nPtr)</code>	Converts the string nPtr to double .
<code>int atoi(const char *nPtr)</code>	Converts the string nPtr to int .
<code>long atol(const char *nPtr)</code>	Converts the string nPtr to long int .

Character Analysis and Conversion

Functions (ctype.h)	Description
isalpha	Check if the argument is a letter
isdigit	Check if the argument is one of the ten digits
isspace	Check if argument is a space, newline or tab.
tolower	Converts the lowercase letters in the argument to upper case letters.

String conversion function

Prototype	Description
<code>double atof(const char *nPtr)</code>	Converts the string nPtr to double .
<code>int atoi(const char *nPtr)</code>	Converts the string nPtr to int .
<code>long atol(const char *nPtr)</code>	Converts the string nPtr to long int .

Arrays of Strings

- An array of strings is a two-dimensional array of characters in which each row is one string.
 - `char names[People][Length];`
 - `char month[5][10] = {"January",
"February", "March", "April", "May"};`

Exercise 13.1

- Write a program that inputs a line of text, counts the number of blanks by using a function, and displays the number of blanks.

Exercise 13.2

- write a function that:
 - gets a string and two chars
 - the function scans the string and replaces every occurrence of the first char with the second one.
- write a program to test the above function
 - the program should read a string from the user (no spaces) and two characters, then call the function with the input, and print the result.
- example
 - input: "papa", 'p', 'm'
 - output: "mama"

Exercise 13.3

- Write a program that tests a customer number to determine whether it is in the proper format(LLLNNNN with LLL are letters and NNNN are numbers).

Exercise 13.4

- Write a program asks the user to enter his or her first and last names, separated by a space. Then print out the first name.
- The program should use a function which cuts off the last name off the string in parameter.

Exercise 13.5

- Write the function `strend(s,t)`, which returns 1 if the string `t` occurs at the end of the string `s`, and zero otherwise.

Exercise 13.6: Using strstr

- A list of product number and description of shop is:
 "TV127 31 inch Television",
 "CD057 CD Player",
 "TA877 Answering Machine",
 "CS409 Car Stereo",
 "PC655 Personal Computer"
- Store this list in an array of string and write a program allowing user to lookup a product description by entering all or part of its product number.

Exercise 13.7

- Write a program that accepts a string from the user and replaces all punctuation signs (, . ; : ! ?) with spaces