

# Lesson 12 Pointers and arrays

Trịnh Thành Trung

[trungtt@soict.hust.edu.vn](mailto:trungtt@soict.hust.edu.vn)

# Pointers and arrays

- Recall that an array `S` holds the address of its first element `S[0]`
  - `S` is actually a pointer to `S[0]`

```
int s[10];  
int *iptr;  
iptr=s; /* From now iptr is equivalent to s */
```
- Both `iptr` and `s` now point to `s[0]`

# Pointer-array equivalence

- Arrays are actually a kind of pointers!
- When an array is defined, a fixed amount of memory (the size of the array) is allocated.
  - The array variable is set to point to the beginning of that memory segment
- When a pointer is declared, it is uninitialized (like a regular variable)
- Unlike pointers, the value of an array variable cannot be changed

# Pointer arithmetic

- Pointers can be incremented and decremented
- If **p** is a pointer to a particular type, **p+1** yields the correct address of the next variable of the same type
- **p++**, **p+i**, and **p += i** also make sense

# Pointer arithmetic

- If **p** and **q** point to elements in an array, **q-p** yields the number of elements between **p** and **q**.
- However, there is a difference between pointer arithmetic and “regular” arithmetic.

# Pointer arithmetic - example

```
int main(void)
{
    int a[3] = {17,289,4913}, *p, *q;

    p = a;    /* p points to the beginning of a, that is &a[0] */
    q = p+2;  /* q points to a[2]. Equivalent to q = &a[2] */

    printf("a is %p\n", a);
    printf("p is %p, q is %p\n", p, q);
    printf("p points to %d and q points to %d\n", *p, *q);
    printf("The pointer distance between p and q is %d\n", q-p);
    printf("The integer distance between p and q is %d\n",
           (int)q-(int)p);
    return 0;
}
```

```
a is 0012FECC
p is 0012FECC, q is 0012FED4
p points to 17 and q points to 4913
The pointer distance between p and q is 2
The integer distance between p and q is 8
```

# Passing arrays to function

- Another way to pass arrays to function is using pointer
- In fact, we pass just the array's address, or more precisely a pointer to the array.
- The function calculate the sum of all array elements.

```
#include <stdio.h>
int addNumbers(int *fiveNumber)
{
    int i,sum=0;
    for(i=0; i<5; i++, fiveNumbers++)
        sum+= *fiveNumbers;
    return sum;
}
```

# Exercise 12.1

- Write a function `countEven(int*, int)` which receives an integer array and its size, and returns the number of even numbers in the array.



## Exercise 12.2

- Write a function that returns a pointer to the maximum value of an array of double's. If the array is empty, return NULL.

```
double* maximum(double* a, int size);
```

## Exercise 12.3

- Write a function `getSale` uses a pointer to accept the address of an array. It asks the user to enter the sales figures and stores those figures in the array.
- Write a function `totalSale` return the total of the element in the array.
- Use these two functions in a program to input the sales figure from different quarters and display the total. Using pointers instead of array in function's parameters.

## Exercise 12.4

- Write a program to list all the sub array of an given array. For example the array 1 3 4 2 has the following sub array:

```
1
1 3
1 3 4
1 3 4 2
3
3 4
3 4 2
4
4 2
2
```

# Exercise 12.5

- Write a program to reverse an array in two different ways: using indexes and using pointers.