

Hulle_Madeline_Individual_Assignment_05

Madeline Hulle

2026-05-01

Set Up

Packages

```
# general use and cleaning

library(tidyverse)
library(here)
library(janitor)
library(snakecase)

# wrap axis labels
library(scales)

# reading in .xlsx files
library(readxl)

# visualize missing data
library(naniar)

# arrange plots
library(patchwork)
```

Data

```

# taxonomic information
taxon_list <- read_csv(here("data", "taxon_list.csv"))

#survey data (reading different sheets in as seperate data frames)

aq_ins <- read_xlsx(
  here("data", "Aquatic Sampling Data-2026-03-10.xlsx"),
  sheet = "Aquatic Insects")

# site information

sites <- read_xlsx(
  here("data", "Aquatic Sampling Data-2026-03-10.xlsx"),
  sheet = "sites"
)

# water quaity

water_quality <- read_xlsx(
  here("data", "Aquatic Sampling Data-2026-03-10.xlsx"),
  sheet = "Water Quality",
  # values in df that are actually indicating missing values, making it seem as a chr when :
  # different ways missing values show up in data set
  na = c("over", "", "n/a", "N/A", "173+")
)

```

Class Code

2. Cleaning

sites object

```

# creating new object from sites
ncos_sites <- sites |>
  # filtering to only include NCOS quarterly sites
  filter(sector == "NCOS" &
    sampling_frequency == "Quarterly")

```

clean taxon_list

```
# creating new object from taxon_list
taxon_list_clean <- taxon_list |>
  # converted taxon names to snake case
  mutate(verbatim_name = to_any_case(verbatim_name,
                                     case = "snake"))
```

clean water_quality

```
# creatign new object from water_quality
water_quality_clean <- water_quality |>
  # cleaning column name
  clean_names() |>
  # a filtering join, only keep the rows in wq clean in which the site matches up with the s
  semi_join(ncos_sites, by = "site") |>
  # creating new column to join with later data frames
  unite("date_site", date, site, remove = TRUE) |>
  # grouping by date/site
  group_by(date_site) |>
  # calculating the medians
  summarize(med_pH = median(p_h, na.rm = TRUE),
            med_sal = median(salinity_ppt, na.rm = TRUE),
            med_do = median(dissolved_oxygen_mg_l, na.rm = TRUE)) |>
  # ungrouping df
  ungroup() |>
  # filtering out outliers
  filter(date_site != "2022-08-12_NVBR")
```

clean aq_ins

```
# create a new object
aq_ins_clean <- aq_ins |>
  # clean column names
  clean_names() |>
  # filtering join only include quarterly ncos surveys
  semi_join(ncos_sites, by = "site") |>
  # renaming date_on_vial column to date
```

```

rename(date = date_on_vial) |>
# selecting columns of interest
# keeping information about each survey and the 9 most abundant taxa
select(date, sample_type, site,
        ostracod,
        copepod,
        hemiptera_corixidae_boatman,
        cladocera,
        nematode,
        diptera_ceratopogonidae,
        annelida_oligochaete,
        diptera_chironomid,
        annelida_polychaete) |>
# filtered to only include filterer beaker samples (better sampling technique)
filter(sample_type %in% c("FB 250", "FB250")) |>
# converting to long format, making df longer
pivot_longer(
  # name the columns to make longer
  cols = ostracod:annelida_polychaete,
  # new column for old column names
  # column names are all in new column called taxon
  names_to = "taxon",
  # new column for the values in each of the old columns
  # counts now under a column called abundance
  values_to = "abundance"
) |>
# group by date site and taxon
group_by(date, site, taxon) |>
# calculated average count per liter (total abundance/7.7)
summarise(ave_lit = sum(abundance, na.rm = TRUE)/7.5) |>
# ungrouping data frame
ungroup() |>
# new column to join data frames, didnt remove them
unite("date_site", date, site, remove = FALSE) |>
# joined with water quality clean
left_join(water_quality_clean, by = "date_site") |>
# joined with taxonomic information
left_join(taxon_list_clean, by = c("taxon" = "verbatim_name")) |>
# fill in full site names
mutate(site_full = case_when(
  site == "NVBR" ~ "North of Venoco Bridge",
  site == "NEC" ~ "East Channel",

```

```

    site == "NMC" ~ "Main Channel",
    site == "NPB" ~ "South of Phelps Bridge",
    site == "NPB1" ~ "North of Phelps Bridge",
    site == "NPB2" ~ "Phelps Road",
    site == "NWP" ~ "West Pond",
    site == "NDC" ~ "Devereux Creek"
  )) |>
  # set factor levels for full site name by median salinity
  mutate(site_full = fct_reorder(site_full,
                                med_sal,
                                .fun = "median",
                                .na_rm = TRUE),
         # reversing the order
         site_full = fct_rev(site_full))

```