


Table Creation and Management

CS 630 Database Management Systems

Professor Nardi

Normalized JustLee Books Database...



Database Table...

- A Database Object...
- Stores Data for the Database...
- Consists of Columns and Rows...
- Created and Modified Through Data Definition Language (DDL) Commands...

Table Design – Table and Column Names...

- Can Contain a Maximum 30 Characters...
- NO Blank Spaces...
- Must Begin With a Letter...
- Can Contain Numbers, Underscore (_), and Number Sign (#)...
- Must Be Unique Within a Table...
- No Reserved Words Are Allowed...

Table Design – Field Types : VARCHAR2(n)...

- Variable Length CHARACTER Data...
- “n” Represents the Maximum Number of Characters Allowed..
- STANDARD Maximum Number of Characters CANNOT Exceed 4000 Characters...
- EXTENDED Maximum Number of Characters Cannot Exceed 32767 Characters...
- Minimum Number of Characters is 1...
- There is NO Default Size...
- For Example, VARCHAR2(5)
 - Can Hold Up to FIVE Letters, Numbers, or Symbols...
 - The Word “Joe” Will Only Use 3 of the Allotted 5 Characters...It Does Not Pad...
 - The Word “Nicholas” Will Generate an Error Because the Value Exceeds 5 Characters...

Table Design – Field Types : CHAR(n)...

- Fixed Length CHARACTER Data...
- “n” Represents the Length of the Field...
- Maximum Number of Characters CANNOT Exceed 2000 Characters...
- Default Size is ONE Character...
- For Example, CHAR(5)
 - Will ALWAYS Store FIVE Letters, Numbers, or Symbols...
 - The Word “Joe” Will Store the 3 Characters Given (i.e., J – O – E) and PAD the Field with TWO Spaces...
 - The Word “Nicholas” Will Generate an Error Because the Value Exceeds 5 Characters...

Table Design – Field Types : NUMBER (p,s)...

- Stores NUMERIC Data...
- “p” is the PRECISION of the Number...That Is, the Total Number of Numbers to the Left AND the Right of the Decimal Place...
- Maximum Number of Precision Cannot Exceed 38 Digits...
- “s” is the SCALE or the Number of Digits to the RIGHT of the Decimal...
- Numbers Defined With a Scale of 0 Are Considered to Be Integers...

Table Design – Field Types : NUMBER (p,s)...

- For Example, NUMBER(7,2)
 - Can Store a Numeric Value Up to 99999.99...
 - If You Could the Number of Digits, There are 7 in Total and 2 to the Right of the Decimal...
 - If No Precision or Scale is Specified, the Column Defaults to 38 Digits...
- For Example, NUMBER(5) or NUMBER(5,0)
 - Can Store an INTEGER Up to the Value 99999...

Table Design – Field Types : DATE...

- Stores Data and Time Between January 1, 4712 BC and December 31, 9999 AD...
- Uses 7 Bytes to Store the Century, the Year, the Month, the Day, the Hour, the Minute, and the Second...
- Standard Data Format for Both Input and Output is DD-MON-YY...
- You Can Use Other Formats (i.e., YYYY-MM-DD) By Changing the NLS_DATE_FORMAT...
- MUCH More on Dates Later...

Table Design – Field Types : Unicode Formats...

- Is a Character Encoding Format That Can Support Over One Million Characters (vs. ASCII Which Supports 128 or 256)...
- Allows You to Store Characters in Any Other Non-ASCII Language Sets...
- Used “Under the Covers” By Major Manufacturers Whether You Utilize It or Not...
- Oracle Supports Unicode Via NCHAR and NVARCHAR...

Create a Table...


- Column Definition List Must Be Enclosed in Parentheses...
- Datatype Must Be Specified For Each Column...
- Maximum of 1,000 Columns...

```
CREATE TABLE [ schema. ] tablename  
    ( columnname datatype [ DEFAULT value ]  
    [ , columnname datatype [ DEFAULT value ] ] );
```

Sample CREATE TABLE...

- Notice the “Virtual Column”...
- Virtual Columns Are Defined Using Create But Their Values Are NOT Stored in the Table...
- Values Are Derived at the Time They Are Accessed...

```
CREATE TABLE ACCTMANAGER
(
  AM_ID      CHAR(4),
  AM_NME_FST VARCHAR2(12),
  AM_NME_LST VARCHAR2(12),
  AM_ENT_DTE DATE DEFAULT SYSDATE,
  AM_SAL     NUMBER(8,2),
  AM_COM_RTE NUMBER(7,2) DEFAULT 0,
  AM_TOT_COM AS (AM_SAL + AM_COM_RTE),
  AM_REG     CHAR(2)
);
```



Virtual Column

CREATE TABLE succeeded.

Success Message

Viewing Tables in Your Database...

- Data Dictionary is a Typical Component of a DBMS That Maintains Information About Database Objects...
- Query the Data Dictionary to Verify the Tables That Exist in the Schema...
- USER_TABLES Data Dictionary Object Maintains Information On All the Tables in the Schema...
- DESCRIBE Displays the Structure of a Specified Table...

Example of Viewing Tables in Your Database...

Enter SQL Statement:

```
DESCRIBE ACCTMANAGER
```

Results Script Output Explain Autotrace DBMS Output OWA Output

DESC acctmanager

DESCRIBE ACCTMANAGER	type
AMID	CHAR(4)
AMFIRST	VARCHAR2(12)
AMLAST	VARCHAR2(12)
AMEDATE	DATE
AMSAL	NUMBER(8,2)
AMCOMM	NUMBER(7,2)
AMEARN	NUMBER
REGION	CHAR(2)

8 rows selected

Invisible Columns...

- Columns Defined as Invisible Are NOT Available to Be Used in SQL...
- Used Typically to Provide Flexibility of Testing the Impacts of Adding New Fields to a Database...
- Used to Store Data That Is Not Generally Available to All Users...
- Can Be Changed to Visible (and Vice Versa) at Any Time...





Table Creation Through Subqueries...

- Use Subqueries to Retrieve Data From an Existing Table...
- Requires Use of AS Keyword...
- New Column Names Can Be Assigned...
- More On This Later...



Modifying Existing Tables...

- Accomplished Through the ALTER TABLE Command...
- Use an ADD Clause to Add a Column...
- Use a MODIFY Clause to Change a Column...
- Use a DROP COLUMN to Drop a Column...
- Always Use DESC After an Alter to Validate the Change Was Made Correctly...

```
ALTER TABLE tablename  
ADD|MODIFY|DROP COLUMN| columnname [definition];
```

ALTER TABLE : ADD and MODIFY...

Enter SQL Statement:

```
ALTER TABLE publisher
ADD (ext NUMBER(4));

DESC publisher
```

Results Script Output Explain Autotrace DBMS Output OWA Output

ALTER TABLE publisher succeeded.

DESC publisher

Name	Null	Type
PUBID	NOT NULL	NUMBER(2)
NAME		VARCHAR2(23)
CONTACT		VARCHAR2(15)
PHONE		VARCHAR2(12)
EXT		NUMBER(4)

5 rows selected

Enter SQL Statement:


```
ALTER TABLE acctmanager
MODIFY (amlast VARCHAR2(18));
```

Results Script Output Explain Autotrace DBMS Output OWA Output

ALTER TABLE acctmanager succeeded.

Important Note On MODIFY...

- DBMS Will Not Allow a MODIFY Condition That Jeopardizes the Integrity of the Data...
- Column Must Be As Wide As the Data Already in the Table...
- Adding or Changing Default Data Does NOT Affect Existing Data...




Enter SQL Statement:

```
ALTER TABLE books  
MODIFY (title VARCHAR2(10));
```

Results Script Output Explain Autotrace DBMS Output OWA Output

Error starting at line 1 in command:
ALTER TABLE books
MODIFY (title VARCHAR2(10))
Error report:
SQL Error: ORA-01441: cannot decrease column length because some value is too big
01441. 00000 - "cannot decrease column length because some value is too big"
*Cause:
*Action:

A red arrow points to the error message.



Enter SQL Statement:

```
ALTER TABLE books  
MODIFY (retail NUMBER(5,1));
```


Results Script Output Explain Autotrace DBMS Output OWA Output

Error starting at line 1 in command:
ALTER TABLE books
MODIFY (retail NUMBER(5,1))
Error report:
SQL Error: ORA-01440: column to be modified must be empty to decrease precision or scale
01440. 00000 - "column to be modified must be empty to decrease precision or scale"
*Cause:
*Action:

A red arrow points to the error message.

ALTER TABLE : DROP COLUMN...

- Can Only Reference One Column Per Execution...
- Deletion Is PERMANENT...
- Cannot Delete Last Remaining Column in a Table...
- Think About Using INVISIBLE First...Test Results...Then DROP...



ALTER TABLE : SET UNUSED...

- Process of Dropping a Column From a Large Table Can Be Time and Resource Consuming...
- Typically, Drop the Column Logically First Using SET UNUSED...During Off-Peak Hours Drop the Unused Column Physically...

```
ALTER TABLE tablename  
SET UNUSED (columnname);  
OR  
ALTER TABLE tablename  
SET UNUSED COLUMN columnname;
```

```
ALTER TABLE tablename  
DROP UNUSED COLUMNS;
```

Renaming a Table...

- Use RENAME...TO When Renaming a Table...
- Old Name is No Longer Valid...YOU CANNOT ROLLBACK A RENAME STATEMENT...
- When Renaming a Table, Oracle Automatically Transfers Indexes, Constraints, and Grants on the Old Table to the New One...
- It Also Invalidates All Objects That Depend on the Renamed Table (i.e., Views, Stored Procedures, Function, Synonyms)...

Enter SQL Statement:

```
RENAME cust_mkt TO cust_mkt_092009;
```

Truncating and Deleting a Table...

- TRUNCATE : Rows Are Deleted...Structure Remains...
- Use DROP to Delete the Table Structure AND the Contents...
- Using DROP With the PURGE Clause Drops the Table and Reclaims the Space...
- Using DROP Without the PURGE Clause Allows You to Roll Back or Recover the Table From the Recycle Bin...
- Can Also Use DELETE to Remove Small Tables With Few Rows...

Enter SQL Statement:

```
TRUNCATE TABLE cust_mkt_092009;
```

Enter SQL Statement:

```
DROP TABLE cust_mkt_092009;
```

```
DROP TABLE cust_mktg_092009 PURGE;
```

Recovering a Table...

- Dropped Tables in the Recycle Bin Are Given a Different Name...
- Find the New Name of the Table...Use FLASHBACK to Restore the Table...

1

```
Enter SQL Statement:
```

```
TRUNCATE TABLE cust_mkt_092009;
```

2

```
Enter SQL Statement:
```

```
DROP TABLE cust_mkt_092009;
```

3

```
Enter SQL Statement:
```

```
SELECT object_name, original_name
FROM recyclebin;
```

Results:

	OBJECT_NAME	ORIGINAL_NAME
1	BIN\$XBQID3hTTA/M+u+n6mhqhQ==\$	CUST_MKT_092009

4

```
Enter SQL Statement:
```

```
FLASHBACK TABLE cust_mkt_092009
TO BEFORE DROP;
```

KING GRADUATE MONROE

Questions...