Status	Finished
Started	Monday, 26 October 2026, 2:40 PM
Completed	Monday, 26 October 2026, 3:07 PM
Duration	26 mins 47 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What will be printed when the following code executes?

```
a = ("Python Programming")
```

```
print type(a)
```

a. <class 'tuple'>

b. str

c. <class 'str'> ✓

d. <class 'int'>

Question **2**

Correct

Mark 1.00 out of 1.00

What will the below Python code do?

```
set1={2,3}

set2={3,2}

set3={2,1}

if(set1==set2):

    print("yes")

else:

    print("no")

if(set1==set3):

    print("yes")

else:

    print("no")
```

a. "==" is not supported for set in Python

b. Yes, Yes

c. No, No

d. Yes, No ✓

Question **3**

Correct

Mark 1.00 out of 1.00

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

a. (16,17,18)

b. Error

c. (16,17,18,19) ✓

d. (25,19,18,17)

Question **4**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

a. {1,3,4}

b. {4} ✓

c. {1,3,2}

d. {2}

Question **5**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. {40, 10, '10', 50, 20, 60, 30} ✓

b. {40, 10, 50, 20, 60, 30}

c. SynatxError: Different types cannot be used with sets

d. {40, '10', 50, 20, 60, 30}

Question **6**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (1,2,3,(4,5))
t2 = (3,2,1,(4,5))
print(t1>t2)
```

a. True

b. False ✓

c. Error

d. Error

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

my_t1 = (1, 2, 3, 4)

my_t1.append((5, 6, 7))

print(len(my_t1))

a. Error ✓

b. 1

c. 2

d. 5

Question **8**

Correct

Mark 1.00 out of 1.00

Select all the correct options to remove “ECE” from the set.

```
sampleSet = {"ECE", "R&A", "MCT"}
```

a. del.sampleSet("ECE")

b. remove.sampleSet("ECE")

c. sampleSet.delete("ECE")

d. sampleSet.discard("ECE") ✓

Question **9**

Correct

Mark 1.00 out of 1.00

What will be the output of below Python code?

```
tupl=("python","programming","Computer")
print(tupl[-3:0])
```

a. Error

b. Computer

c. () ✓

d. (Computer)

Question **10**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

t1 = (55, 44, 33, 22, 11)

x = [t1[i] for i in range(0, len(t1), 2)]

print(x)

a. [55, 33, 11] ✓

b. [(55,33,11)]

c. (55,33,11)

d. ([55,33,11])

Question **11**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. True ✓

b. False

Question **12**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

- a. 12
- b. (12)
- c. Error ✓
- d. (55,78,64,25)

Question **13**

Correct

Mark 1.00 out of 1.00

Which of the following options will not result in an error when performed on tuples in Python where tupl=(5,2,7,0,3)?

- a. tupl.append(2)
- b. tupl.sort()
- c. tupl1=tupl+tupl ✓
- d. tupl[1]=2

Question **14**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

- a. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓
- b. Name Error
- c. TypeError: update() doesn't allow list as a argument.
- d. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

Question **15**

Correct

Mark 1.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

a. ['2', '3', '30', '8']

b. ['30', '8', '3', '2']

c. ['8', '30', '3', '2'] ✓

d. ['2', '3', '8', '30']