

Ex. No.: 2

Name: MADHAN KUMAR

231901028

Date:6/9/24

CRACK THE HASHES


Aim:

To install and crack the hashed passwords using John-the-Ripper tool in Kali Linux.

Algorithm:

1. Install John-the-Ripper on your system using `sudo apt install john`
2. Prepare the hash file `hashes.txt` that is to be cracked.
3. Run John-the-Ripper specifying the path to the `wordlist.txt` and `hashes.txt`
4. Monitor the cracking process using `status` option in another terminal

Output:

A screenshot of a terminal window titled 'root@ip-10-10-88-66: ~'. The terminal shows the command 'sudo apt-get install john' being executed. The output indicates that several packages were automatically installed and are no longer required, including docutils-common, gir1.2-goa-1.0, gir1.2-snapd-1, libpkcs11-helper1, linux-headers-4.15.0-115, linux-headers-4.15.0-115-generic, linux-image-4.15.0-115-generic, linux-modules-4.15.0-115-generic, linux-modules-extra-4.15.0-115-generic, python-bs4, python-chardet, python-dicttoxml, python-dnspython, python-html5lib, python-jsonrpclib, python-lxml, python-mechanize, python-olefile, python-pypdf2, python-slowaes, python-webencodings, python-xlsxwriter, python3-boto, python3-botocore, python3-docutils, python3-jmespath, python3-pygments, python3-roman, python3-rsa, and python3-s3transfer. It also shows that 'john-data' will be installed along with 'john'. The terminal concludes with the message 'Need to get 4,466 kB of archives.' and 'After this operation, 7,875 kB of additional disk space will be used.'

```
root@ip-10-10-233-209: ~
File Edit View Search Terminal Help
root@ip-10-10-233-209:~# echo -n joshua1993 | md5sum | awk '{print $1}' > hashes.
txt
root@ip-10-10-233-209:~# cat hashes.txt
046df2d40bc0a99fd11a1cc0a8e67434
root@ip-10-10-233-209:~# john --format=raw-md5 --wordlist=/usr/share/wordlists/
rockyou.txt hashes.txt
Using default input encoding: UTF-8
Loaded 1 password hash (Raw-MD5 [MD5 256/256 AVX2 8x3])
Warning: no OpenMP support for this hash type, consider --fork=2
Press 'q' or Ctrl-C to abort, almost any other key for status
joshua1993      (?)
1g 0:00:00:00 DONE (2024-06-19 07:30) 33.33g/s 6668Kp/s 6668Kc/s 6668KC/s kensle
y..joseph85
Use the "--show --format=Raw-MD5" options to display all of the cracked password
s reliably
Session completed.
root@ip-10-10-233-209:~#
```

```
root@ip-10-10-233-209: ~
File Edit View Search Terminal Help
0g 0:00:00:01 0g/s 0p/s 0c/s 0C/s
root@ip-10-10-233-209:~# john --status
0g 0:00:00:01 3/3 0g/s 71632p/s 71632c/s 143264C/s
```

Result: Thus, successfully installed John-the-Ripper tool and cracked the password hashes.

