

EXP NO: 09

DATE:

DEVELOP THE BACK-END OF A COMPILER THAT TAKES THREE-ADDRESS CODE (TAC) AS INPUT AND GENERATES CORRESPONDING 8086 ASSEMBLY LANGUAGE CODE AS OUTPUT.

AIM:

To design and implement the back-end of a compiler that takes three-address code (TAC) as input and produces 8086 assembly language code as output. The three-address code is an intermediate representation used by compilers to break down expressions and operations, while the 8086 assembly code is a machine-level representation of the program that can be executed by a processor.

ALGORITHM:

1. Parse the Three-Address Code (TAC):

Input: Three-Address Code, which is an intermediate representation. For example:

```
t0 = b + c
t1 = t0 * d
a = t1
```

Output: 8086 assembly language code. For example:

```
MOV AX, [b]      ; Load b into AX
ADD AX, [c]      ; Add c to AX
MOV [t0], AX     ; Store result in t0
```

2. Process Each TAC Instruction:

1. **Initialize Registers:**

- Set up the registers in 8086 assembly (e.g., AX, BX, CX, etc.) for storing intermediate results and final outputs.
- Maintain a temporary register counter for naming temporary variables in TAC (e.g., t0, t1).

2. **For each TAC instruction**, based on its operation:

- Identify the components: operands and operator.
 - Choose an appropriate register (AX, BX, etc.) for storing intermediate results.
 - If the operation involves multiple operands or temporary variables, map them to registers.
-

3. Translating TAC to 8086 Assembly:

- **Addition/Subtraction (e.g., $t0 = b + c$):**
 - Load operands into registers and perform the operation:

```
MOV AX, [b]    ; Load b into AX
ADD AX, [c]    ; Add c to AX
MOV [t0], AX   ; Store result in t0
```

- **Multiplication (e.g., $t1 = t0 * d$):**

- Load operands into registers and perform the operation:

```
MOV AX, [t0]   ; Load t0 into AX
MOV BX, [d]    ; Load d into BX
MUL BX         ; Multiply AX by BX (result in AX)
MOV [t1], AX   ; Store result in t1
```

- **Assignment (e.g., $a = t1$):**

- Move the value from a temporary variable to the target variable:

```
MOV [a], [t1]  ; Move value of t1 into a
```

- **Division (e.g., $t2 = b / c$):**

- Division is a bit more complex due to the 8086's limitations with the DIV instruction. For example, the result might need to be stored in AX or DX:AX (if it's a 32-bit result):

```
MOV AX, [b]    ; Load b into AX
MOV DX, 0      ; Clear DX (important for division)
MOV BX, [c]    ; Load c into BX
DIV BX         ; AX = AX / BX (quotient in AX, remainder in DX)
MOV [t2], AX   ; Store quotient in t2
```

4. Manage Memory and Registers:

- **Variables:** Variables like a, b, c are stored in memory, so you will use memory addressing modes such as [variable_name] to access them.
- **Temporary Variables:** Temporary variables like t0, t1, t2, etc., are stored in registers (AX, BX, etc.) or memory if there are more variables than registers available.

5. Handle Control Flow (Optional):

If the TAC contains control structures (such as loops, if-else statements, or function calls), you will need to generate labels and jump instructions in 8086 assembly.

- **If Statements:** For example, if $(x > 0)$ { $y = 1$; } could generate:

```
MOV AX, [x]
CMP AX, 0
JG positive_case ; Jump if greater
JMP end_if
```

PROGRAM:

```

#include <stdio.h>
#include <string.h>

#define MAX_LINES 100
#define MAX_LEN 100

int main() {
    char tac[MAX_LINES][MAX_LEN];
    int count = 0;

    printf("Enter TAC instructions (Ctrl+Z to stop):\n");

    // Read all input first
    while (fgets(tac[count], sizeof(tac[count]), stdin)) {
        tac[count][strcspn(tac[count], "\n")] = '\0'; // Remove newline
        count++;
    }

    printf("\n--- 8086 Assembly Output ---\n");

    // Process each line after input is complete
    for (int i = 0; i < count; i++) {
        char lhs[20], op1[20], op2[20], op;
        if (sscanf(tac[i], "%s = %s %c %s", lhs, op1, &op, op2) == 4) {
            if (op == '+') {
                printf("MOV AX, [%s]\n", op1);
                printf("ADD AX, [%s]\n", op2);
                printf("MOV [%s], AX\n\n", lhs);
            } else if (op == '-') {
                printf("MOV AX, [%s]\n", op1);
                printf("SUB AX, [%s]\n", op2);
                printf("MOV [%s], AX\n\n", lhs);
            } else if (op == '*') {
                printf("MOV AX, [%s]\n", op1);
                printf("MOV BX, [%s]\n", op2);
                printf("MUL BX\n");
                printf("MOV [%s], AX\n\n", lhs);
            } else if (op == '/') {
                printf("MOV AX, [%s]\n", op1);
                printf("MOV DX, 0\n");
                printf("MOV BX, [%s]\n", op2);
                printf("DIV BX\n");
                printf("MOV [%s], AX\n\n", lhs);
            }
        } else if (sscanf(tac[i], "%s = %s", lhs, op1) == 2) {
            printf("MOV AX, [%s]\n", op1);

```

```

    printf("MOV [%s], AX\n\n", lhs);
} else {
    printf("; Unsupported TAC format: %s\n\n", tac[i]);
}
}
return 0;
}

```

OUTPUT :

```

MOV AX, [b]
ADD AX, [c]
MOV [t0], AX

MOV AX, [t0]
MOV BX, [d]
MUL BX
MOV [t1], AX

MOV AX, [t1]
MOV [a], AX

```

Implementation	
Output/Signature	

RESULT:

Thus the above example provides a foundational approach to converting TAC to 8086 assembly using C. For a complete compiler back-end, you would need to handle additional aspects such as register allocation, memory management, and more complex control flow constructs.