# Safety Data Sheet

# ULTRABOND ECO 571 2K comp. B

Safety Data Sheet dated: 28/05/2021 - version 1

Date of first edition: 28/05/2021



#### 1. Identification

### **GHS Product Identifier**

Mixture identification:

Trade name: ULTRABOND ECO 571 2K comp. B

Trade code: 902325

### Recommended use of the chemical and restrictions on use

Recommended use: Polyurethane catalyst Uses advised against: Data not available.

Supplier's details

Company: MAPEI CONSTRUCTION CHEMICALS L.L.C

P.O. BOX 73869 DUBAI - United Arab Emirates

Office: 00971 4 8156666 Factory: 00971 4 8858428 Responsable: info@mapei.ae **Emergency phone number** Office: 00971 4 8156666

#### 2. Hazard identification

#### Classification of the substance or mixture

Acute Tox. 4 Harmful if inhaled.

Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2A Causes serious eye irritation.

Resp. Sens. 1 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 May cause an allergic skin reaction.

Carc. 2 Suspected of causing cancer.

STOT SE 3 May cause respiratory irritation.

STOT RE 2 May cause damage to organs through prolonged or repeated exposure.

Adverse physicochemical, human health and environmental effects:

No other hazards

## GHS label elements, including precautionary statements

### Hazard pictograms and Signal Word



## Hazard statements

H315	Causes skin	irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

## **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist/vapours/spray. P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

Print date 29/11/2023 Production Name ULTRABOND ECO 571 2K comp. B Page n. 1 of 7

P284 [In case of inadequate ventilation] wear respiratory protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P33 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice.
P312 Call a POISON CENTER if you feel unwell.
P314 Get medical advice/attention. if you feel unwell.

P321 Specific treatment (see supplementary instructions on this label)
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

#### Other hazards which do not result in a classification

No other hazards

### 3. Composition/information on ingredients

### **Substances**

N.A.

#### **Mixtures**

## Hazardous components within the meaning of GHS and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥75 - <100 %	O diphenylmethanediisocyanate isomers and homologues	EC:618-498-9	Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Resp. Sens. 1, H334; Skin Sens. 1, H317; STOT RE 2, H373; Carc. 2, H351	

## 4. First-aid measures

### Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

## Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

## Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

## 5. Fire-fighting measures

# **Extinguishing media**

## Suitable extinguishing media:

Print date 29/11/2023 Production Name ULTRABOND ECO 571 2K comp. B Page n. 2 of 7

Water.

Carbon dioxide (CO2).

#### Unsuitable extinguishing media:

None in particular.

## Special hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: N.A.

Explosive properties: N.A. Oxidizing properties: N.A.

## Special protective actions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

### **Environmental precautions**

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

#### Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

## 7. Handling and storage

### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

## Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

## 8. Exposure controls/personal protection

## **Control parameters**

No data available

Appropriate engineering controls: N.A.

## Individual protection measures, such as personal protective equipment (PPE)

Eye protection:

Eye glasses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Print date 29/11/2023 Production Name ULTRABOND ECO 571 2K comp. B Page n. 3 of 7

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

CR (polychloroprene, chloroprene rubber). FKM (fluoro rubber). NBR (nitrile rubber)

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

## Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

In case of insufficient ventilation use mask with ABEKP filters (EN 14387).

Use adequate protective respiratory equipment.

## 9. Physical and chemical properties

Physical state Liquid Color: light brown Appearance: liquid Odour: Characteristic Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: 230 °C (446 °F)

Flash point: 200 °C (392 °F) Evaporation rate: N.A. Solid/gas flammability: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour pressure: N.A. Vapour density: N.A.

Relative density: 1.23 g/cm3 Solubility in water: Insoluble

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Viscosity: 180.00 cPs

## 10. Stability and reactivity

### Reactivity

Stable under normal conditions

## Chemical stability

Data not available.

## Possibility of hazardous reactions

None.

## Conditions to avoid

Stable under normal conditions.

## **Incompatible materials**

None in particular.

### **Hazardous decomposition products**

## 11. Toxicological information

### Information on toxicological effects

## **Toxicological Information of the Preparation**

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

### Toxicological information on main components of the mixture:

diphenylmethanediisocya a) acute toxicity

LD50 Oral Rat > 10000 mg/kg

nate isomers and homologues

LD50 Skin Rabbit > 9400 mg/kg

LC50 Inhalation Dust Rat = 0.31 mg/l 4h

LD50 Skin Rabbit > 9.4 g/kg

LC50 Inhalation Rat = 490 mg/m3 4h

Print date 29/11/2023 **Production Name** ULTRABOND ECO 571 2K comp. B Page n. 4 of 7 g) reproductive toxicity

NOAEL Inhalation Rat = 12 mg/m3

## If not differently specified, the information required in the regulation and listed below must be considered as N.A.

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure

Toxicological kinetics, metabolism and distribution information

- i) STOT-repeated exposure
- j) aspiration hazard

## 12. Ecological information

#### **Toxicity**

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

## List of Eco-Toxicological properties of the components

Component	Ident. Numb.	<b>Ecotox Data</b>

diphenylmethanediisocyanate isomers and homologues

- EINECS: 618-

CAS: 9016-87-9 a) Aquatic acute toxicity: LC50 Fish > 1000 mg/L 96

498-9 - INDEX: 615-005-00-9

a) Aquatic acute toxicity: EC50 Daphnia > 1000 mg/L 24

b) Aquatic chronic toxicity: NOEC Daphnia > 10 mg/L - 21 d

a) Aquatic acute toxicity: EC50 Algae > 1640 mg/L 72

c) Bacteria toxicity: EC50 > 100 mg/L 3

d) Terrestrial toxicity: NOEC > 1000 mg/kg - 14 d e) Plant toxicity: NOEC > 1000 mg/kg - 14 d

## Persistence and degradability

N.A.

## **Bioaccumulative potential**

N.A.

## Mobility in soil

N.A.

## Other adverse effects

No Data found about other evironmental hazard properties.

### 13. Disposal considerations

# **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

## Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

## Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Print date 29/11/2023 Production Name ULTRABOND ECO 571 2K comp. B 5 of 7 Page n.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

#### Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

## 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

### **UN** number

N.A.

## **UN proper shipping name**

N.A.

## Transport hazard class(es)

N.A.

### Packing group, if applicable

Road and Rail (ADR-RID):

NA

Air (IATA):

N.A.

Sea (IMDG):

N.A.

#### **Environmental hazards**

Marine pollutant: No

Environmental Pollutant: N.A.

#### Special precautions for user

N.A

## Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

N.A.

## 15. Regulatory information

## Safety, health and environmental regulations specific for the product in question

This Safety Data Sheet has been prepared according to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS), Fifth revised edition.

SCAQMD Rule 1113 : N.A. SCAQMD Rule 1168: N.A.

### 16. Other information

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

Insert here further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no quarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

Print date 29/11/2023 Production Name ULTRABOND ECO 571 2K comp. B Page n. 6 of 7

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

 Print date
 29/11/2023
 Production Name
 ULTRABOND ECO 571 2K comp. B
 Page n.
 7 of 7