

WOOD BOND

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name WOOD BOND

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified usesTwo component epoxy based adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Delta Adhesives Itd

39-40 Claycliffe Business Park

Barugh Green, Barnsley

South Yorkshire S75 1JU, UK

Tel: +44 (0)1226 381571 Fax: +44 (0)1226 381722

Web www.delta-adhesives.co.uk

Contact person info@delta-adhesives.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0)1226 381571 (Mon - Fri 08:00 - 17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 3 - H412

Human health May cause skin sensitisation or allergic reactions in sensitive individuals.

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.



Precautionary statements P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P501 Dispose of contents/ container in accordance with national regulations.

Contains EPOXY RESIN (Number average MW <= 700), POLY[OXY(METHYL-1,2-ETHANEDIYL)], A-

HYDRO-ω-HYDROXY-, ETHER WITH 2,2-BIS(HYDROXYMETHYL)-1,3-PROPANEDIOL

(4:1), 2-HYDROXY-3-MERCAPTOPROPYL ETHER

Supplementary precautionary

statements

P264 Wash contaminated skin thoroughly after handling.

P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

TALC 20-50%

CAS number: 14807-96-6 EC number: 238-877-9 REACH registration number: 01-

2120140278-58

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

AMORPHOUS SODA LIME GLASS 20-50%

CAS number: 65997-17-3 EC number: 266-046-0 REACH registration number: 01-

2119990048-30

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

EPOXY RESIN (Number average MW <= 700) 20-50%

CAS number: 25068-38-6 EC number: 500-033-5 REACH registration number: 01-

2119456619-26

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411



POLY[OXY(METHYL-1,2-ETHANEDIYL)], A-HYDRO- ω -HYDROXY-, ETHER WITH 2,2-BIS(HYDROXYMETHYL)-

1,3-PROPANEDIOL (4:1), 2-HYDROXY-3-

MERCAPTOPROPYL ETHER

CAS number: 72244-98-5 EC number: 615-735-8 REACH registration number: 01-

2120118957-46

Classification

Skin Sens. 1B - H317 Aquatic Chronic 3 - H412

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

1-5%

10-20%

CAS number: 90-72-2 EC number: 202-013-9 REACH registration number: 01-

2119560597-27

Classification

Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Remove affected person from source of contamination. Get medical attention if any discomfort

continues.

Ingestion DO NOT induce vomiting. Get medical attention immediately.

Skin contact Wash skin thoroughly with soap and water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after

washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation No specific symptoms known.

Ingestion May cause discomfort.

Skin contactCauses skin irritation. May cause sensitisation or allergic reactions in sensitive individuals.

Eye contact Irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Water spray, foam, dry powder or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Specific hazards No unusual fire or explosion hazards noted.



Hazardous combustion

products

Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during

firefighting

No specific firefighting precautions known.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. Collect and dispose of spillage as indicated in Section

13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions No special storage precautions required.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

TALC

Long-term exposure limit (8-hour TWA): WEL 1 mg/m³ respirable dust

AMORPHOUS SODA LIME GLASS

Long-term exposure limit (8-hour TWA): 5 mg/m³ dust

WEL = Workplace Exposure Limit

EPOXY RESIN (Number average MW <= 700) (CAS: 25068-38-6)

DNEL Industry - Inhalation; Long term systemic effects: 12.25 mg/m³

Industry - Inhalation; Short term systemic effects: 12.25 mg/m³ Industry - Dermal; Long term systemic effects: 8.33 mg/kg/day Industry - Dermal; Short term systemic effects: 8.33 mg/kg/day

REACH dossier information



PNEC - Fresh water; 0.006 mg/l

Marine water; 0.0006 mg/lIntermittent release; 0.018 mg/l

- STP; 10 mg/l

Sediment (Freshwater); 0.996 mg/kgSediment (Marinewater); 0.0996 mg/kg

- Soil; 0.196 mg/kg

REACH dossier information

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL (CAS: 90-72-2)

DNEL Industry - Inhalation; Long term systemic effects: 0.31 mg/m³

Industry - Dermal; Long term systemic effects: 0.2 mg/kg/day

PNEC - Intermittent release; 0.84 mg/l

Marine water; 0.0084 mg/lFresh water; 0.084 mg/l

- STP; 0.2 mg/l

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

No specific ventilation requirements.

Eye/face protection Wear eye protection.

Hand protection Wear protective gloves.

Hygiene measures Wash promptly if skin becomes contaminated. Wash at the end of each work shift and before

eating, smoking and using the toilet.

Respiratory protection No specific recommendations.

Environmental exposure

controls

Residues and empty containers should be taken care of as hazardous waste according to

local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Solid. Coloured paste.

Colour Beige. White.

Odour Characteristic. Sulphur.

Odour threshold Not determined.

pH Not applicable.

Melting point Not applicable.

Initial boiling point and range >35°C @ 760 mm Hg

Flash point >100°C

Evaporation rate Not applicable.

Evaporation factor Not applicable.



Flammability (solid, gas)

Not determined.

Upper/lower flammability or

explosive limits

Not determined.

Vapour pressure <500 Pa @ 20°C

Vapour density Not applicable.

Relative density ~ 0.9

Bulk density Not applicable.

Solubility(ies) Insoluble in water

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity Not applicable.

Explosive properties Not applicable.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid contact with the following materials: Acids.

10.5. Incompatible materials

Materials to avoid Acids. Amines.

10.6. Hazardous decomposition products

Hazardous decomposition (

Oxides of carbon. Oxides of nitrogen.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 29,585.8

Skin sensitisation

Skin sensitisation Sensitising.

Ingestion May cause discomfort.

Skin contact Irritating to skin. May cause sensitisation by skin contact.

Eye contact Irritation of eyes and mucous membranes.

Route of exposure Skin and/or eye contact.



Toxicological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

11,400.0

Species

Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 1,200.0

Rat

mg/kg)

Species

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

Acute toxicity - oral

Acute toxicity oral (LD₅o

mg/kg)

2.169.0

Rat

Species

500.0 ATE oral (mg/kg)

Acute toxicity - dermal

Acute toxicity dermal (LD50 1.0

mg/kg)

Species Rat

SECTION 12: Ecological Information

12.1. Toxicity

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: 2 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 1.8 mg/l, Daphnia magna

Acute toxicity - aquatic

EC₅₀, 72 hours: 11 mg/l, Freshwater algae

plants

EC₅₀, 96 hours: 220 mg/l, Scenedesmus subspicatus

Chronic aquatic toxicity

Chronic toxicity - aquatic

invertebrates

NOEC, 21 days: 0.3 mg/l, Daphnia magna

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

Acute aquatic toxicity

LC50, 96 hours: 180 - 240 mg/l, Oncorhynchus mykiss (Rainbow trout) Acute toxicity - fish

LC50, 96 hours: 175 mg/l, Cyprinus carpio (Common carp)

12.2. Persistence and degradability



Persistence and degradability The product is not biodegradable.

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Biodegradation - 12% Degradation (%): 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Bioaccumulative potential May accumulate in soil and water systems. BCF: 100 - 3000,

Partition coefficient log Pow: 3.242 Estimated Value

12.4. Mobility in soil

Mobility The product is insoluble in water and will spread on the water surface. The product is non-

volatile. Semi-mobile.

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Mobility Semi-mobile.

Adsorption/desorption

coefficient

Water - Koc: 1800 - 4400 @ 25°C Estimated Value

Henry's law constant 4.93E-05 Pa m3/mol @ 25°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

Ecological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste via a licensed waste disposal contractor.

Waste class

The waste code classification is to be carried out according to the European Waste Catalogue

(EWC).

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).



14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation (EU) No 2015/830

Guidance Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 15/05/2018

Version number 1.002

Supersedes date 12/02/2018

SDS number 20655

Hazard statements in full H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

Delta Adhesives Limited, Units 39-40 Claycliffe Business Park, Cannon Way, Barugh Green, Barnsley, South Yorkshire, S75 1JU, Tel: +44 (0) 1226 381 571 email: sales@delta-adhesives.co.uk

