

Sanir Kittur Sir's



APTTECH

Campus Recruitment Training



accenture

Pseudo Code..



By: Rehan Chougale

Software Engineer

(Technical Trainer At Apt-Tech)



Level: P-01 Beginner



Int a,b,c

Set b=10;

For (each a from 1 to 4)

b=b+a;

End for

c=b/5;

Print c;

a. 5

b.4

c. 10

d. None



Int a,b,c

Set b=10;

For (each a from 1 to 4)

b=b+a;

End for

c=b/5;

Print c;

a. 5

★ **b. 4**

c. 10

d. None



What will be the output of following pseudocode for input a = 2 and b = 4 ?

```
int fun(int a, int b)
{
    int n = 0
        if(b < 1)
            return n
    else
        return fun(a + b + 2, b - 2)
}
```

a. 0
b. 22
c. 58
d. 9



What will be the output of following pseudocode for input a = 2 and b = 4 ?

```
int fun(int a, int b)
{
    int n = 0
    if(b < 1)
        return n
    else
        return fun(a + b + 2, b - 2)
}
```

- a. 0
- ☒ b. 22
- c. 58
- d. 9

What will be the output of following pseudocode?

integer a , b , c , d;

Set a = 14, b = 15, c = 16;

if(a > 6)

 b = c - a

 if(a > c)

 d = b + c

 Else

 d = b - c

Else

 d = a + b + c - 3

Print d

A:42 B:14 C:Compile error D:-14

What will be the output of following pseudocode?

integer a , b , c , d;

Set a = 14, b = 15, c = 16;

if(a > 6)

 b= c - a

 if(a > c)

 d= b + c

 Else

 d= b - c

Else

 d = a + b + c - 3

Print d

A:42 B:14 C:Compile error D:-14★

What will be the value of t ?if a = 56, b = 876?

Read a , b

Function mul (a, b)

t = 0

while (b != 0)

t= t + a

b=b-1

End While

return t;

End Function

A:490563

B:490056

C:490561

D:49056



What will be the value of t ?if a = 56, b = 876?

Read a , b

Function mul (a, b)

 t = 0

 while (b != 0)

 t= t + a

 b=b-1

 End While

 return t;

End Function

A:490563

B:490056

C:490561

D:49056



If m=9, n=6
m=m+1;
n= n-1;
m= m+n;
If(m>n)
 print m;
Else
 print n;

Answer:..... —

If m=9, n=6
m=m+1;
n= n-1;
m= m+n;
If(m>n)
 print m;
Else
 print n;

15

Answer:.....—.....



What is Output for below Code?

```
Integer n
Set n = 11
Integer arr [4] = {10, 11, 1, 12}
arr[1]= arr [1]- arr [3]
arr[2] = arr [2] + arr [2]
arr[3] = 1 + arr[3]
n = arr [3]
if (n > arr [2])
    n=n-1
Else
    n=n-1
End if
Print n;
```

- 1. 7
- 2. 18
- 3. 22
- 4. 12



What is Output for below Code?

```
Integer n
Set n = 11
Integer arr [4] = {10, 11, 1, 12}
arr[1]= arr [1]- arr [3]
arr[2] = arr [2] + arr [2]
arr[3] = 1 + arr[3]
n = arr [3]
if (n > arr [2])
    n=n-1
Else
    n=n-1
End if
Print n;
```

- 1. 7
- 2. 18
- 3. 22
- 4. 12A





What is the Out Put for Following Code:?

Integer x, y, z

Set x = 9, y = 2, z = 1

if (x + y > 8)

 if (7 > x + z)

 z = 7

End if

 if (9 > x - z)

 z = 9

End if

 y = y + z + 1

End if

Print x + y + z

A.31

B.42

C.30

D.11

What is the Out Put for Following Code:?

Integer x, y, z

Set x = 9, y = 2, z = 1

if (x + y > 8)

if (7 > x + z)

z = 7

End if

if (9 > x - z)

z = 9

End if

y = y + z + 1

End if

Print x + y + z

A.31

B.42

C.30
★

D.11



Level: P-02



Input p = 9, W = 6,

p=p+1;

w=w-1:

p=p+ W

if (p > w)

print p

else

print w

a.6 b.5 c.10 d.15



Input p = 9, W = 6,

p=p+1;

w=w-1:

p=p+ W

if (p > w)

print p

else

print w

a.6 b.5 c.10  d.15

3. What will be the output of following pseudocode?

```
char[] text = "TESTSTRING"
```

```
Integer a,c;  
char ch = 'T'  
c= 0  
for(each a from 0 to length of text)  
    if(text[a] == ch)  
        c=c+1  
    end if  
end for  
if( c > 0)  
    print c  
else  
    print "0"
```

A:10 B:3 C:1 D:6



3. What will be the output of following pseudocode?

```
char[] text = "TESTSTRING"
```

```
Integer a , c;
```

```
char ch = 'T'
```

```
c= 0
```

```
for(each a from 0 to length of text)
```

```
    if(text[a] == ch)
```

```
        c=c+1
```

```
    end if
```

```
end for
```

```
if( c > 0)
```

```
    print c
```

```
else
```

```
    print "0"
```

A:10 B:3 C:1 D:6





Input $t = 6$, $h = 9$ and set $x = 0$

Integer c

if ($h > t$)

for ($c = t$; $c < h$; $c = c + 1$)

$X = x + C$

End for loop

print X

print error message print x

a. 9 b.21 c.15 d.6



Input t = 6, h = 9 and set x = 0

Integer c

if (h > t)

for (c = t; c < h; c = c + 1)

X = x + C

End for loop

print X

print error message print x

a. 9  b.21 c.15 d.6



```
do  
integer i  
set i= 3  
print i+3  
i=i-1  
while( i not equals 0)  
end while
```

- a)6 5 6
- b)6 5 4
- c)5 5 5
- d)6 6 6



```
do  
integer i  
set i= 3  
print i+3  
i=i-1  
while( i not equals 0)  
end while
```

- a)6 5 6 ★
- b)6 5 4
- c)5 5 5
- d)6 6 6



for input $a = 30$, $b = 60$, $C = 90$?

Integer a,b,c, Sum

Read a, b,

Set $sum = a + b + c$

if ((sum EQUALS 180) and (a NOT EQUALS 0) and
(b NOT EQUALS 0) and (E NOT EQUALS 0))

Print " Success"

Otherwise

Print " Fail"

End if

a. Compiler Error

b. Fail

c. Success

d. None of M entioned



for input $a = 30, b = 60, C = 90$?

Integer a,b,c, Sum

Read a, b,

Set $sum = a + b + c$

if ((sum EQUALS 180) and (a NOT EQUALS 0) and
(b NOT EQUALS 0) and (C NOT EQUALS 0))

Print " Success"

Otherwise

Print " Fail"

End if

a. Compiler Error

b. Fail

★ c. Success

d. None of Mentioned



What will be the output of the following pseudocode for $a = 2$, $b = 6$?

```
Integer fun(Integer a, Integer b)
if(a > 0)
    if(b > 0)
        return a + b + fun(a + 1, 0) + fun(a + 2, 0) + fun(a + 3, 0)
    End if
End if
return a + b
End function fun()
```

a.17 b.21 c.20 d.8



What will be the output of the following pseudocode for $a = 2$, $b = 6$?

Integer fun(Integer a, Integer b)

if($a > 0$)

 return $a + b + \text{fun}(a + 1, 0) + \text{fun}(a + 2, 0) + \text{fun}(a + 3, 0)$

End if

End if

 return $a + b$

End function fun()

a.17 b.21 c.20 d.8



Integer count

for (each count from 0 to 9)

print " #"

if (count >= 6)

CONTINUE

print count

End for

a. #0#1#2#3#4#5#

b. 0#1#2#3#4#5#6##

c. #0#1#2#3#4#5#6###

d. 0#1#2#3#4#5#6#7#8#9#10



Integer count

for (each count from 0 to 9)

print " #"

if (count > = 6)

CONTINUE

print count

End for

a. #0#1#2#3#4#5#

b. 0#1#2#3#4#5#6##

c. #0#1#2#3#4#5#6### ★

d. 0#1#2#3#4#5#6#7#8#9#10



Level: P-03



Set p=3 q=4 r=5

p=p+p

p=(9+10)+p

r=r+2

if((p-q) < (q+p))

q=10^r

End if

Print q+p+r

a.13 b.35 c. 45 d. 11



Set $p=3$ $q=4$ $r=5$

$p=p+p$

$p=(9+10)+p$

$r=r+2$

if($(p-q) < (q+p)$)

$q=10^r$

Hint:(Because this is XOR operation: diff=1
same =0)

End if

Print $q+p+r$

a.13 b.35 c. 45[★] d. 11



a=8 b=8 c=5

if ((a^ 4)<4 & & (9& b) < c)

c=4+b

Print a+b+c

a. 12

b. -21

c. 21

d. -12



a=8 b=8 c=5

if ((a^4)<4 && (9&b) < c)

c=4+b

Print a+b+c

**Hint: Here && is logical operator
Where expect 0 all will true**

a. 12

b. -21

c. 21 ★

d. -12



```
Int x , y , z;  
Set x=,y=8, z=2;  
If(x^y && x^y && x^y^z)  
    x=1;  
End if  
Print x + y + z;
```

- a. 12
- b. 11
- c. 16
- d. 9



```
Int x , y , z;  
Set x=,y=8, z=2;  
If(x^y && x^y && x^y^z)  
    x=1;  
End if  
Print x + y + z;
```

- a. 12
- ☒ b. 11
- c. 16
- d. 9

(Hint: (9 && 9 && 11) -> here all number are nonzero hence prediction will true)



String str1=" pP" str2=" Q qQ " Print

(countC on so(lower (str1+low er (str2)+low er (str1))))

- a.-7
- b.14
- c.7
- d.8



String str1=" pP" str2=" Q qQ " Print

(countC on so(lower (str1+low er (str2)+low er (str1))))

- a.-7
- b.14
- c.7 ★
- d.8



Int a=6 b=7 c=5

if((b+c-a) > (a+b))

b=a+a

c=b&b

if((b-a+c) < (c+b))

b=(b+7+b)

Print a+b+c

a.23

b.21

c.32

d.None Above



Int a=6 b=7 c=5

if((b+c-a) > (a+b))

b=a+a

c=b&b

if((b-a+c) < (c+b))

b=(b+7+b)

Print a+b+c

a.23

b.21

c.32 ★

d.None Above



Int p=3 q=2 r=7

r=(6+7)+q

p=(p+q) +r

if((p& q)<r || q<r)

p=7+q

Print p+r

a. 9

b.5

c. 24

d. 15



Int p=3 q=2 r=7

r=(6+7)+q

p=(p+q) +r

if((p& q)<r || q<r)

p=7+q

Print p+r

a. 9

b.5

c. 24 ★

d. 15



p=1 q=4 r=8
if(r>q || (p+q) > (q-p))
p=(8 &1) & q

p=p^p

Print p+q+r

a. 12

b.9

c. 13

d. 0



p=1 q=4 r=8

if(r>q || (p+q) > (q-p))

p=(8&1) & q

p=p^p

Print p+q+r

a. 12 ★

b. 9

c. 13

d. 0



String str1=" optimum"

str2=" efficiency"

Print

countconsonent(str1) + countVowel(str2)

ANS:



String str1=" optimum"

str2=" efficiency"

Print

countconsonent(str1) + countVowel(str2)

ANS: **8**



Set $p=7$ $q=3$ $r=5$

$q=(2+1)+r$

$r=(r \& q) \wedge q$

if($(5 \& p) < (q \wedge 5) \parallel 2 > q$)

$r=p+q$

Print $p+q+r$

a. 30

b. 15

c. 10

d. All the Above



Set $p=7$ $q=3$ $r=5$

$q=(2+1)+r$

$r=(r \& q) \wedge q$ **hint: $(x \wedge 0 = x)$**

if($(5 \& p) < (q \wedge 5) \parallel 2 > q$)

$r=p+q$

Print $p+q+r$

- a. 30 ★
- b. 15
- c. 10
- d. All the Above



```
Int p=0 q=6 r=5
if(p& q& r) < (q^ r^ p)
    r=(r+5)+r
    q=(9+2)^ q
Print p+q+r
```

ANS:



Int p=0 q=6 r=5

if(p& q& r) < (q^ r^ p) (hint: 0& anything =0)

here 0& p& r=0)

r=(r+5)+r

q=(9+2)^ q

Print p+q+r

ANS:28.....



Points To Remember :

$X \wedge 0 = X$

$\&$ = Except 0 All true

$\wedge$ = Diff=1; Same=0



Thank You..



By: Rehan Chougale

Software Engineer

(Technical Trainer At Apt-Tech)