

## Gaussian Graphical Models.

### Summary:

Can learn Attractive and Walk-Summable GGMS

with  $O(d^2 \log p / \kappa^6)$  samples and quadratic

run-time.

$d$  - degree (max)



$p$  - total number of parameters

Open: Can any sparse GGMM be learnt with



$O\left(\frac{d \log p}{\kappa^2}\right)$  samples and a fixed polynomial

run-time?


$$\kappa(\Theta) = \min_{i,j:\Theta_{ij}\neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}$$



# Learning Gaussian Graphical Models w/o condition number bounds



# GGMs



# Motivation

# Algorithm

While  $|S| < t$  :  
Add  $\arg \min_j \text{Var}(X_i | X_{S \cup j})$ .

# Special Models

# Analysis




# Attractive. SDD

# Gaussian Graphical Models (GGMs)

$X \sim N(0, \Sigma)$ .  $\Sigma \in R^{p \times p}$  covariance matrix.


$p$  = number of features.



$$Pr[X = x] = \frac{1}{\sqrt{(2\pi)^p \det(\Sigma)}} \exp(-x^T \Sigma^{-1} x / 2)$$

# Gaussian Graphical Models (GGMs)

$X \sim N(0, \Sigma)$ .  $\Sigma \in R^{p \times p}$  covariance matrix.




Today's Focus: Precision Matrix  $\Theta = \Sigma^{-1}$ .

$$\text{Cov}(x)_{ij} = E[x_i, x_j]$$

# Gaussian Graphical Models (GGMs)

$X \sim N(0, \Sigma)$ .  $\Sigma \in R^{p \times p}$  covariance matrix.



Today's Focus: Precision Matrix  $\Theta = \Sigma^{-1}$ .

**Dempster 72: Encodes conditional independence structure**

# Gaussian Graphical Models (GGMs)

$X \sim N(0, \Sigma)$ .  $\Sigma \in R^{p \times p}$  covariance matrix.

**Precision Matrix  $\Theta = \Sigma^{-1}$ .**

# Gaussian Graphical Models (GGMs)

$X \sim N(0, \Sigma)$ .  $\Sigma \in R^{p \times p}$  covariance matrix.

**Precision Matrix  $\Theta = \Sigma^{-1}$ .**

**Dependency graph  $G = \text{Supp}(\Theta)$ .**




# Gaussian Graphical Models (GGMs)

$X \sim N(0, \Sigma)$ .  $\Sigma \in R^{p \times p}$  covariance matrix.

**Precision Matrix  $\Theta = \Sigma^{-1}$ .**

**Dependency graph  $G = \text{Supp}(\Theta)$ .**




# Gaussian Graphical Models (GGMs)

$X \sim N(0, \Sigma)$ .  $\Sigma \in R^{p \times p}$  covariance matrix.

Precision Matrix  $\Theta = \Sigma^{-1}$ .

Dependency graph  $G = \text{Supp}(\Theta)$ .




**Markov property:**  $\Theta_{ij} = 0 \Rightarrow X_i, X_j$  are independent conditioned on neighbors of  $i$ .

# Gaussian Graphical Models (GGMs)

$X \sim N(0, \Sigma)$ .  $\Sigma \in R^{p \times p}$  covariance matrix.

Precision Matrix  $\Theta = \Sigma^{-1}$ .

Dependency graph  $G = \text{Supp}(\Theta)$ .



**Example:**  $(X_1 | X_2, X_5)$  independent  
of  $(X_3 | X_2, X_5)$

**Markov property:**  $\Theta_{ij} = 0 \Rightarrow X_i, X_j$  are independent  
conditioned on neighbors of  $i$ .

# Gaussian Graphical Models (GGMs)

$X \sim N(0, \Sigma)$ .  $\Sigma \in R^{p \times p}$  covariance matrix.

Precision Matrix  $\Theta = \Sigma^{-1}$ .

Dependency graph  $G = \text{Supp}(\Theta)$ .

**Complexity of GGMs:** max-degree of G  $d \ll p$ .

# Gaussian Graphical Models (GGMs)

$X \sim N(0, \Sigma)$ .  $\Sigma \in R^{p \times p}$  covariance matrix.


Precision Matrix  $\Theta = \Sigma^{-1}$ .

Dependency graph  $G = \text{Supp}(\Theta)$ .


**Complexity of GGMs:** max-degree of  $G$   $d \ll p$ .

The assumption that makes the formalism non-trivial  
and useful ...


**Why?**



# Fundamental model for modeling statistical relations between variables



# Fundamental model for modeling statistical relations between variables



**Many applications in machine learning, sciences:**

**Gene-regulatory networks**

**Brain connection networks from fMRI**

...



# Bigger Picture

**Can we learn sparse dependency graphs from few samples?**

**(aka learning Markov random fields, undirected graphical models)**

# Bigger Picture

**Can we learn sparse dependency graphs from few samples?**

(aka learning Markov random fields, undirected graphical models)

$$X \sim \{1, -1\}^p.$$

**Dependency graph of  $X$ :**  $i \not\sim j \Rightarrow X_i, X_j$  are independent conditioned on neighbors of  $i$ .

# Example: “Random Walk” Model

$$X_i = X_{i-1} + Z_i, \text{ where } Z_1, \dots, Z_p \text{ i.i.d } N(0,1)$$

1	1	1	1	1	1	1	1	1	1
1	2	2	2	2	2	2	2	2	2
1	2	3	3	3	3	3	3	3	3
1	2	3	4	4	4	4	4	4	4
1	2	3	4	5	5	5	5	5	5
1	2	3	4	5	6	6	6	6	6
1	2	3	4	5	6	7	7	7	7
1	2	3	4	5	6	7	8	8	8
1	2	3	4	5	6	7	8	9	9
1	2	3	4	5	6	7	8	9	10

$$E[x_1, x_2] = 1$$

$$E[x_2, x_3] = 2$$

$\Sigma$  : Covariance Matrix

$$x_1 = z_1 \quad x_2 = z_1 + z_2 \quad x_3 = z_1 + z_2 + z_3$$

# Example: “Random Walk” Model

$$X_i = X_{i-1} + Z_i, \text{ where } Z_1, \dots, Z_p \text{ i.i.d } N(0,1)$$

1	1	1	1	1	1	1	1	1	1
1	2	2	2	2	2	2	2	2	2
1	2	3	3	3	3	3	3	3	3
1	2	3	4	4	4	4	4	4	4
1	2	3	4	5	5	5	5	5	5
1	2	3	4	5	6	6	6	6	6
1	2	3	4	5	6	7	7	7	7
1	2	3	4	5	6	7	8	8	8
1	2	3	4	5	6	7	8	9	9
1	2	3	4	5	6	7	8	9	10

$\Sigma$  : Covariance Matrix

2	-1	0	0	0	0	0	0	0	0
-1	2	-1	0	0	0	0	0	0	0
0	-1	2	-1	0	0	0	0	0	0
0	0	-1	2	-1	0	0	0	0	0
0	0	0	-1	2	-1	0	0	0	0
0	0	0	0	-1	2	-1	0	0	0
0	0	0	0	0	-1	2	-1	0	0
0	0	0	0	0	0	-1	2	-1	0
0	0	0	0	0	0	0	-1	2	-1
0	0	0	0	0	0	0	0	-1	2

$\Theta$  : Precision Matrix

# Example: “Random Walk” Model

$$X_i = X_{i-1} + Z_i, \text{ where } Z_1, \dots, Z_p \text{ i.i.d } N(0,1)$$

1	1	1	1	1	1	1	1	1	1
1	2	2	2	2	2	2	2	2	2
1	2	3	3	3	3	3	3	3	3
1	2	3	4	4	4	4	4	4	4
1	2	3	4	5	5	5	5	5	5
1	2	3	4	5	6	6	6	6	6
1	2	3	4	5	6	7	7	7	7
1	2	3	4	5	6	7	8	8	8
1	2	3	4	5	6	7	8	9	9
1	2	3	4	5	6	7	8	9	10

$\Sigma$  : Covariance Matrix



Dependency  
graph

2	-1	0	0	0	0	0	0	0	0
-1	2	-1	0	0	0	0	0	0	0
0	-1	2	-1	0	0	0	0	0	0
0	0	-1	2	-1	0	0	0	0	0
0	0	0	-1	2	-1	0	0	0	0
0	0	0	0	-1	2	-1	0	0	0
0	0	0	0	0	-1	2	-1	0	0
0	0	0	0	0	0	-1	2	-1	0
0	0	0	0	0	0	0	-1	2	-1
0	0	0	0	0	0	0	0	-1	2


$\Theta$  : Precision Matrix

# Learning Sparse GGMs

- **Structure learning - learn dependency graph.**
- **Parameter learning - learn the matrix.**

# Structure Learning for GGMs


- Structure learning - learn dependency graph.



**Input: Given samples  $X^1, X^2, \dots, X^n$  from a GGM**  
**Output: Dependency graph of the GGM.**

# Structure Learning for GGMs

- Structure learning - learn dependency graph.




**Input: Given samples  $X^1, X^2, \dots, X^n$  from a GGM**  
**Output: Dependency graph of the GGM.**



# Structure Learning for GGMs

- Structure learning - learn dependency graph.




**Input:** Given samples  $X^1, X^2, \dots, X^n$  from a GGM  
**Output:** Dependency graph of the GGM.

**Challenge:** Often  $n \ll p$ .

# Structure Learning for GGMs

- Structure learning - learn dependency graph.



**Assumption: Unknown dependency graph is sparse - each vertex has at most **d** edges.**

**Challenge: Often  $n \ll p$ .**

# Structure Learning for GGMs

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

(Think:  $n = O_d(\log p)$ .)

# Structure Learning for GGMs

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ , can we efficiently find the dependency graph with  $n \ll p$ ?

(Think:  $n = O_d(\log p)$ .)

Core of problem. Can learn parameters easily afterward.

# Structure Learning for GGMs

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

(Think:  $n = O_d(\log p)$ .)

**Ideal: Practical algorithms with provable guarantees.**

# Example: Unknown order Random Walk

$$X_{\pi(i)} = X_{\pi(i-1)} + Z_i, \text{ where } Z_1, \dots, Z_p \text{ i.i.d } N(0,1)$$

7	1	5	6	7	4	3	7	2	7
1	1	1	1	1	1	1	1	1	1
5	1	5	5	5	4	3	5	2	5
6	1	5	6	6	4	3	6	2	6
7	1	5	6	8	4	3	8	2	8
4	1	4	4	4	4	3	4	2	4
3	1	3	3	3	3	3	3	2	3
7	1	5	6	8	4	3	9	2	9
2	1	2	2	2	2	2	2	2	2
7	1	5	6	8	4	3	9	2	10

$\Sigma$  : Covariance Matrix

# Example: Unknown order Random Walk

$$X_{\pi(i)} = X_{\pi(i-1)} + Z_i, \text{ where } Z_1, \dots, Z_p \text{ i.i.d } N(0,1)$$

7	1	5	6	7	4	3	7	2	7
1	1	1	1	1	1	1	1	1	1
5	1	5	5	5	4	3	5	2	5
6	1	5	6	6	4	3	6	2	6
7	1	5	6	8	4	3	8	2	8
4	1	4	4	4	4	3	4	2	4
3	1	3	3	3	3	3	3	2	3
7	1	5	6	8	4	3	9	2	9
2	1	2	2	2	2	2	2	2	2
7	1	5	6	8	4	3	9	2	10

$\Sigma$  : Covariance Matrix



Dependency graph?

2	0	0	-1	-1	0	0	0	0	0
0	2	0	0	0	0	0	0	-1	0
0	0	2	-1	0	-1	0	0	0	0
-1	0	-1	2	0	0	0	0	0	0
-1	0	0	0	2	0	0	-1	0	0
0	0	-1	0	0	2	-1	0	0	0
0	0	0	0	0	-1	2	0	-1	0
0	0	0	0	-1	0	0	2	0	-1
0	-1	0	0	0	0	-1	0	2	0
0	0	0	0	0	0	0	-1	0	1


$\Theta$  : Precision Matrix

# Example: Unknown order Random Walk

$$X_{\pi(i)} = X_{\pi(i-1)} + Z_i, \text{ where } Z_1, \dots, Z_p \text{ i.i.d } N(0,1)$$

7	1	5	6	7	4	3	7	2	7
1	1	1	1	1	1	1	1	1	1
5	1	5	5	5	4	3	5	2	5
6	1	5	6	6	4	3	6	2	6
7	1	5	6	8	4	3	8	2	8
4	1	4	4	4	4	3	4	2	4
3	1	3	3	3	3	3	3	2	3
7	1	5	6	8	4	3	9	2	9
2	1	2	2	2	2	2	2	2	2
7	1	5	6	8	4	3	9	2	10

$\Sigma$  : Covariance Matrix



Dependency graph?

2	0	0	-1	-1	0	0	0	0	0
0	2	0	0	0	0	0	0	-1	0
0	0	2	-1	0	-1	0	0	0	0
-1	0	-1	2	0	0	0	0	0	0
-1	0	0	0	2	0	0	-1	0	0
0	0	-1	0	0	2	-1	0	0	0
0	0	0	0	0	-1	2	0	-1	0
0	0	0	0	-1	0	0	2	0	-1
0	-1	0	0	0	0	-1	0	2	0
0	0	0	0	0	0	0	-1	0	1

$\Theta$  : Precision Matrix

**How many samples of  $X$  to find the hidden permutation?**



# Previous Work

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

Well studied with several popular software packages:  
GLASSO, CLIME, ACLIME

# Previous Work

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

# Previous Work

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ , can we efficiently find the dependency graph with  $n \ll p$ ?

- **GLASSO: Friedman, Hastie, Tibshirani 08**

Can learn with  $O(d^2 \log p)$  samples if precision matrix is incoherent.

# Previous Work

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ , can we efficiently find the dependency graph with  $n \ll p$ ?

Strong assumption: Violated by random walk ...

- **GLASSO: Friedman, Hastie, Tibshirani 08**

Can learn with  $O(d^2 \log p)$  samples if precision matrix is incoherent.

# Previous Work

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

- **GLASSO: Friedman, Hastie, Tibshirani 08**

Can learn with  $O(d^2 \log p)$  samples if precision matrix is incoherent.

- **CLIME: Cai, Liu, Luo 2011**

Can learn with  $O(M^4 \log p)$  samples where  $M \sim$  maximum ratio of entries in  $\Sigma, \Theta$ .

# Previous Work

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

- **GLASSO: Friedman, Hastie, Tibshirani 08**

Can learn with  $O(d^2 \log p)$  samples if precision

Strong assumption: Violated by random walk ...

- **CLIME: Cai, Liu, Luo 2011**

Can learn with  $O(M^4 \log p)$  samples where

$M \sim$  maximum ratio of entries in  $\Sigma, \Theta$ .

# Previous Work

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

- **GLASSO: Friedman, Hastie, Tibshirani 08**

Can learn with  $O(d^2 \log p)$  samples if precision matrix is incoherent.

- **CLIME: Cai, Liu, Luo 2011**

Can learn with  $O(M^4 \log p)$  samples where  $M \sim$  maximum ratio of entries in  $\Sigma, \Theta$ .

# Previous Work

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

Summary: GLASSO, CLIME, ACLIME need 'well-conditioned'  
precision matrix.



# Previous Work

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ , can we efficiently find the dependency graph with  $n \ll p$ ?

Summary: GLASSO, CLIME, ACLIME need 'well-conditioned' precision matrix.

- Violated by simple models
- Not scale invariant
- Not just analysis ... **fail empirically**

# Previous Work

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

What is possible information theoretically?

# Previous Work: MVL18

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

$$\kappa(\Theta) = \min_{i,j:\Theta_{ij} \neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}$$


$\Theta_{ii}$		$\Theta_{ij}$		
$\Theta_{ij}$		$\Theta_{jj}$		

$\Theta$  : Precision Matrix

# Previous Work: MVL18

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

$$\kappa(\Theta) = \min_{i,j:\Theta_{ij} \neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}$$



$\Theta_{ii}$		$\Theta_{ij}$		
$\Theta_{ij}$		$\Theta_{jj}$		

Measures **signal** in 2x2  
submatrices ...  
not whole matrix.

$\Theta$  : Precision Matrix

# Previous Work: MVL18

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

$$\text{MVL18: } \kappa(\Theta) = \min_{i,j:\Theta_{ij}\neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}$$

Dependency graph identifiable with  $n = O(d \log p / \kappa^2)$  samples!

# Previous Work: MVL18

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ , can we efficiently find the dependency graph with  $n \ll p$ ?

$$\text{MVL18: } \kappa(\Theta) = \min_{i,j:\Theta_{ij}\neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}$$

Dependency graph identifiable with  $n = O(d \log p / \kappa^2)$  samples!

Example: Random walk model -  $\kappa = 1/2$ .

# Information-Theoretic Limits: MVL18

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ , can we efficiently find the dependency graph with  $n \ll p$ ?

$$\text{MVL18: } \kappa(\Theta) = \min_{i,j:\Theta_{ij}\neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}$$

Dependency graph identifiable with  $n = O(d \log p / \kappa^2)$  samples!

Wang, Wainwright, Ramachandran 10: Need  $n = \Omega(\log p / \kappa^2)$ .

# Information-Theoretic Limits: MVL18

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ ,  
can we efficiently find the dependency graph with  $n \ll p$ ?

$$\text{MVL18: } \kappa(\Theta) = \min_{i,j:\Theta_{ij}\neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}$$

Dependency graph identifiable with  $n = O(d \log p / \kappa^2)$  samples!

Run-time of algorithm:  $p^{O(d)}$ .



# Information-Theoretic Limits: MVL18

Given samples  $X^1, X^2, \dots, X^n$  from a GGM of degree  $d \ll p$ , can we efficiently find the dependency graph with  $n \ll p$ ?

$$\text{MVL18: } \kappa(\Theta) = \min_{i,j:\Theta_{ij}\neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}$$

Dependency graph identifiable with  $n = O(d \log p / \kappa^2)$  samples!

**Run-time of algorithm:**  $p^{O(d)}$ .

Problematic for even moderate sized instances  
... Can we do better?

# GGMS: Main Learning Challenge

Given  $n$  samples from a GGM of degree  $d \ll p$ ,  
can we find the dependency graph with  $n \approx d \log p / \kappa^2$ , and  
run-time fixed polynomial in  $p$ ? (Or even  $p^{o(d)}$ .)

# GGMS: Main Learning Challenge

Given  $n$  samples from a GGM of degree  $d \ll p$ ,  
can we find the dependency graph with  $n \approx d \log p / \kappa^2$ , and  
run-time fixed polynomial in  $p$ ? (Or even  $p^{o(d)}$ .)

This work — YES for a large class of models:  
Attractive, SDD, ... more generally, Walk-Summable


# GGMS: Main Learning Challenge

Given  $n$  samples from a GGM of degree  $d \ll p$ ,  
can we find the dependency graph with  $n \approx d \log p / \kappa^2$ , and  
run-time fixed polynomial in  $p$ ? (Or even  $p^{o(d)}$ .)

This work — YES for a large class of models:  
Attractive, SDD, ... more generally, Walk-Summable

Main: A simple greedy algorithm solves above ill-conditioned cases  
(and recovers guarantees of GLASSO, CLIME, ...)

# GGMs



# Motivation

# Algorithm

While  $|S| < t$  :  
Add  $\arg \min_j \text{Var}(X_i | X_{S \cup j})$ .


# Special Models

# Analysis



Attractive. SDD.

# GGMs



# Motivation

# Algorithm

While  $|S| < t$  :  
Add  $\arg \min_j \text{Var}(X_i | X_{S \cup j})$ .

# Special Models

# Analysis




# Attractive. SDD.

# Attractive GGMs

**GGM is attractive if all covariances are non-negative.**

**(Equivalently,  $\Theta$  has non-positive off-diagonals.)**




$\Theta$  : Precision Matrix

# Attractive GGMs

**GGM is attractive if all covariances are non-negative.**

(Equivalently,  $\Theta$  has non-positive off-diagonals.)



$\Theta$  : Precision Matrix

## Ex: Gaussian Free Fields

- Many applications via Gaussian processes



# Attractive GGMs

**GGM is attractive if all covariances are non-negative.**

(Equivalently,  $\Theta$  has non-positive off-diagonals.)

2	-1	0	0	0	0	0	0	0	0
-1	2	-1	0	0	0	0	0	0	0
0	-1	2	-1	0	0	0	0	0	0
0	0	-1	2	-1	0	0	0	0	0
0	0	0	-1	2	-1	0	0	0	0
0	0	0	0	-1	2	-1	0	0	0
0	0	0	0	0	-1	2	-1	0	0
0	0	0	0	0	0	-1	2	-1	0
0	0	0	0	0	0	0	-1	2	-1
0	0	0	0	0	0	0	0	-1	2

$\Theta$  : Precision Matrix

## Ex: Gaussian Free Fields

- Many applications via Gaussian processes
- Ex: Random walk model

# Attractive GGMs

**GGM is attractive if all covariances are non-negative.**

(Equivalently,  $\Theta$  has non-positive off-diagonals.)

2	-1	0	0	0	0	0	0	0	0
-1	2	-1	0	0	0	0	0	0	0
0	-1	2	-1	0	0	0	0	0	0
0	0	-1	2	-1	0	0	0	0	0
0	0	0	-1	2	-1	0	0	0	0
0	0	0	0	-1	2	-1	0	0	0
0	0	0	0	0	-1	2	-1	0	0
0	0	0	0	0	0	-1	2	-1	0
0	0	0	0	0	0	0	-1	2	-1
0	0	0	0	0	0	0	0	-1	2

$\Theta$  : Precision Matrix

## Ex: Gaussian Free Fields

- Many applications via Gaussian processes
- Ex: Random walk model
- Ill-conditioned if 'long paths'

# Attractive GGMs

**GGM is attractive if all covariances are non-negative.**

**Previous: No efficient algorithms with  $O_d(\log p)$  sample complexity known.**

# Attractive GGMs


GGM is attractive if all covariances are non-negative.

KKMM: **GreedyPrune** learns attractive models with  $\tilde{O}(d \log p / \kappa^2)$  samples and quadratic run-time.

Previous: No efficient algorithms with  $O_d(\log p)$  sample complexity known.

# Walk-Summable GGMs


**GGM walk-summable if making off-diagonals of precision matrix negative preserves positive semi-definiteness.**



$\Theta$  : Precision Matrix

# Walk-Summable GGMs


GGM walk-summable if making off-diagonals of precision matrix negative preserves positive semi-definiteness.



$\Theta$  : Precision Matrix

all eigenvalues  $> 0$

→




Offdiagonals negative  $\succeq 0$

# Walk-Summable GGMs

**GGM walk-summable if making off-diagonals of precision matrix negative preserves positive semi-definiteness.**

- Introduced by Maliutov, Johnson, Willsky 2006
- Generalize many classes
  - Attractive
  - Pairwise normalizable
  - Non-frustrated
  - Symmetric diagonally-dominant



Offdiagonals negative  $\geq 0$

# Walk-Summable GGMs

**GGM walk-summable if making off-diagonals of precision matrix negative preserves positive semi-definiteness.**

**Previous: ATHW12, MVL18 -  $p^{O(d)}$  run-time algorithm with logarithmic samples.**



# Walk-Summable GGMs

GGM walk-summable if making off-diagonals of precision matrix negative preserves positive semi-definiteness.

KKMM: **GreedyPrune** learns walk-summable models with  $O(d^2 \log p / \kappa^6)$  samples and quadratic run-time.

Previous: ATHW12, MVL18 -  $p^{O(d)}$  run-time algorithm with logarithmic samples.

# Walk-Summable GGMs

GGM walk-summable if making off-diagonals of precision matrix negative preserves positive semi-definiteness.

KKMM: **Hybrid** (Greedy+Lasso) learns walk-summable models with  $O(d \log p / \kappa^4)$  samples.

Previous: ATHW12, MVL18 -  $p^{O(d)}$  run-time algorithm with logarithmic samples.

# Learning GGMs Greedily

**Input: Samples from a sparse GGM  $\sim X$ .**

**Output: Dependency graph of  $X$ .**

**Similar greedy approaches for discrete GMs: [Bresler10],  
[HKM17], [BKM19]**

# Learning GGMs Greedily

**Input: Samples from a sparse GGM  $\sim X$ .**

**Output: Dependency graph of  $X$ .**

## **GREEDYPRUNE**

- 1. Recover neighborhood of each vertex in parallel.**
- 2. Grow a candidate neighborhood.**
- 3. Prune out some vertices.**

**Similar greedy approaches for discrete GMs: [Bresler10], [HKM17], [BKM19]**

# Phase 1: Growing a neighborhood

**Input: Samples from a sparse GGM  $\sim X$ .**

**Goal: Neighborhood of vertex 1.**

# Phase 1: Growing a neighborhood

**Input: Samples from a sparse GGM  $\sim X$ .**

**Goal: Neighborhood of vertex 1.**

## **GREEDY-GROWING**

**1. Set  $S \leftarrow \emptyset$**

**2. While  $S$  is small enough:**

**1. Find  $j$  to minimize estimate of**

**$Var(X_1 | X_{S \cup j})$ .**

$\hookrightarrow$  For each  $var(X_1 | X_{S \cup j})$  we need  $1/\epsilon^2$  samples

**2.  $S \leftarrow S \cup \{j\}$ .**

to get  $(1-\epsilon)$  accuracy.

**Intuition: Add vertex that gives maximum decrease in conditional variance.**

# Phase 2: Pruning a neighborhood

**Input: Samples from a sparse GGM  $\sim X$ .**

**Goal: Neighborhood of vertex 1.**

# Phase 2: Pruning a neighborhood

**Input: Samples from a sparse GGM  $\sim X$ .**

**Goal: Neighborhood of vertex 1.**

## **GREEDY-PRUNING**


**1. For each  $j$  in  $S$ :**

**1. If  $\text{Var}(X_1 | X_{S \setminus \{j\}}) < (1 + \tau) \text{Var}(X_1 | X_S)$ ,  
drop  $j$  from  $S$ .**

**Intuition: If dropping a vertex, does not hurt too much, drop it.**





# Experiments: A Simple Challenge




**Precision: Path + Cliques**  
**Max-degree = 3**  
**Ill-conditioned**

# Experiments: A Simple Challenge




**Precision: Path + Cliques**  
**Max-degree = 3**  
**Ill-conditioned**


True precision matrix.




True precision matrix.




clime: 50




glasso: 50




greedy: 50




True precision matrix.




clime: 50






glasso: 50




greedy: 50






**Final  
Outputs**




# A Simple Challenge: Path + Clique



**GreedyPrune has best error**


# A Simple Challenge: Path + Clique



**GreedyPrune has best error**




# A Simple Challenge: Path + Clique



**GreedyPrune has best error**

# A Simple Challenge: Path + Clique


Sample Complexity for Edge Recovery



Intensity = 0.95

**GreedyPrune needs very few samples.  
CLIME grows nearly linearly ...**


# A Simple Challenge: Path + Clique



**GreedyPrune needs very few samples.  
GLASSO grows nearly linearly ...**

# A Simple Challenge: Random walk

Sample Complexity for Edge Recovery



**GreedyPrune needs very few samples.  
MB grows nearly linearly ...**

# GreedyPrune Summary

KKMM: **GreedyPrune** learns attractive models with  $\tilde{O}(d \log p / \kappa^2)$  samples and quadratic run-time.

KKMM: **GreedyPrune** learns walk-sumnable models with  $O(d^2 \log p / \kappa^6)$  samples and quadratic run-time.

# GreedyPrune Summary


KKMM: **GreedyPrune** learns attractive models with  $\tilde{O}(d \log p / \kappa^2)$  samples and quadratic run-time.

KKMM: **GreedyPrune** learns walk-summable models with  $O(d^2 \log p / \kappa^6)$  samples and quadratic run-time.

**Also ...**

- Recovers guarantees of GLASSO, CLIME
- Empirically better
- Non-Gaussian distributions: Can learn precision matrices if good tail behaviour

# GGMs



# Motivation

# Algorithm

While  $|S| < t$  :  
Add  $\arg \min_j \text{Var}(X_i | X_{S \cup j})$ .


# Special Models

# Analysis



# Attractive. SDD

# GGMs



# Motivation

# Algorithm

While  $|S| < t$  :  
Add  $\arg \min_j \text{Var}(X_i | X_{S \cup j})$ .

# Special Models

# Analysis



# Attractive. SDD



# Summary

**Main Challenge: Can we recover structure of GGM of degree  $d$ , pairwise-correlation  $\kappa$  with run-time  $p^{o(d)}$  and sample complexity  $n \approx O_{d,\kappa}(\text{poly}(\log p))$ ?**

**Very well-studied, practically important!**

# Summary

**Main Challenge: Can we recover structure of GGM of degree  $d$ , pairwise-correlation  $\kappa$  with run-time  $p^{o(d)}$  and sample complexity  $n \approx O_{d,\kappa}(\text{poly}(\log p))$ ?**

**Very well-studied, practically important!**

**Today: A simple greedy algorithm solves interesting special classes**

# Many Questions for GGMs ...

- **What other classes can we solve efficiently without condition number assumptions?**
- **Testing if a model is correct?**
- **Hidden variables?**
- **Computational hardness?**

# Many Questions for GGMs ...

- What other classes can we solve efficiently without condition number assumptions?
- Testing if a model is correct?
- Hidden variables?
- Computational hardness?

**Conjecture:** No  $p^{o(d)}$  algorithm to recover structure of general GGMs with  $\text{poly}(d, 1/\kappa, \log p)$  samples.

# Bigger Picture

**Can we learn sparse dependency graphs from few samples?**

**(aka learning Markov random fields, undirected graphical models)**


# Bigger Picture

**Can we learn sparse dependency graphs from few samples?**

**(aka learning Markov random fields, undirected graphical models)**

**Lots of work ... [Bresler10], [KM17], [HKM17], ...**

# GGMs



# Motivation

# Algorithm

While  $|S| < t$  :  
Add  $\arg \min_j \text{Var}(X_i | X_{S \cup j})$ .


# Special Models

# Analysis



# Attractive. SDD

# GGMs



# Motivation

# Algorithm

While  $|S| < t$  :  
Add  $\arg \min_j \text{Var}(X_i | X_{S \cup j})$ .

# Special Models

# Analysis



# Attractive. SDD



# Learning GGMs Greedily

**Input: Samples from a sparse GGM  $\sim X$ .**

**Output: Dependency graph of  $X$ .**

(d: max-degree; p: dimension;

n: num. samples;  $\kappa$ : pairwise correlation)

# Learning GGMs Greedily

**Input: Samples from a sparse GGM  $\sim X$ .**

**Output: Dependency graph of  $X$ .**

( $d$ : max-degree;  $p$ : dimension;

$n$ : num. samples;  $\kappa$ : pairwise correlation)

**Thm 1: GreedyPrune** learns attractive models with  $\tilde{O}(d \log p / \kappa^2)$  samples and quadratic run-time.

# Learning GGMs Greedily

**Input: Samples from a sparse GGM  $\sim X$ .**

**Output: Dependency graph of  $X$ .**

( $d$ : max-degree;  $p$ : dimension;

$n$ : num. samples;  $\kappa$ : pairwise correlation)

**Thm 1: GreedyPrune** learns attractive models with  $\tilde{O}(d \log p / \kappa^2)$  samples and quadratic run-time.

**Thm 2: GreedyPrune** learns walk-summable models with  $O(d^2 \log p / \kappa^6)$  samples and quadratic run-time.

# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define

$$f(S) = \text{Var}(X_1 | X_S).$$

# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 \mid X_S)$ .

**Claim [MJW06, MS12]:**  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

Claim [MJW06, MS12]:  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

Supermodular:  $S \subset T$ ,  
 $f(S) - f(S \cup \{j\}) \geq f(T) - f(T \cup \{j\})$ .

# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

Claim [MS, MJW]:  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

## Why useful?

- Optimizing supermodularity very well understood
- Greedy algorithm finds minimizer

# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

**Claim [MS, MJW]:**  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

Are we done?



# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

Claim [MS, MJW]:  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

Are we done?

**Almost ...**

- Only have estimates for  $f$
- Crucial: missing a vertex means noticeably away from optimum

# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

**Claim [MS, MJW]:**  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

**Claim [MS, MJW]:**  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

**Proof: ...**

# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

**Claim [MS, MJW]:**  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

**Proof: ...**

- Assume  $\Theta_{ii} = 1$ .

# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

**Claim [MS, MJW]:**  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

**Proof: ...**

- Assume  $\Theta_{ii} = 1$ .
- Linear algebra:

$$\text{Var}(X_1 | X_S) = \sum_{i_1, i_2, \dots, i_k \notin S} (-\Theta_{ii_1})(-\Theta_{i_1 i_2}) \cdots (-\Theta_{i_k i})$$

# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

**Claim [MS, MJW]:**  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

**Proof:** ...

- Product over cycles not touching  $S$  ...

$$\text{Var}(X_1 | X_S) = \sum_{i_1, i_2, \dots, i_k \notin S} (-\Theta_{ii_1})(-\Theta_{i_1i_2}) \cdots (-\Theta_{i_ki})$$

# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

**Claim [MS, MJW]:**  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

**Proof: ...**

- Product over cycles not touching  $S$  ...

$$\text{Var}(X_1 | X_S) = \sum_{i_1, i_2, \dots, i_k \notin S} (-\Theta_{ii_1})(-\Theta_{i_1i_2}) \cdots (-\Theta_{i_ki})$$

- Thus:  $f(S) - f(S \cup \{j\})$  is sum on cycles that touch  $j$  but don't touch  $S$ .

# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

**Claim [MS, MJW]:**  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

Supermodular:  $S \subset T$ ,  
 $f(S) - f(S \cup \{j\}) \geq f(T) - f(T \cup \{j\})$ .

$$\text{Var}(X_1 | X_S) = \sum_{i_1, i_2, \dots, i_k \notin S} (-\Theta_{ii_1})(-\Theta_{i_1 i_2}) \cdots (-\Theta_{i_k i})$$

- **Thus:**  $f(S) - f(S \cup \{j\})$  is sum on cycles that touch  $j$  but don't touch  $S$ .



# Analysis for Attractive: Supermodularity

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

**Claim [MS, MJW]:**  $X$  is attractive GGM. Then,  $f(\cdot)$  is monotonically decreasing and a **supermodular** function.

Supermodular:  $S \subset T$ ,  
 $f(S) - f(S \cup \{j\}) \geq f(T) - f(T \cup \{j\})$ .

$$\text{Var}(X_1 | X_S) = \sum_{i_1, i_2, \dots, i_k \notin S} (-\Theta_{ii_1})(-\Theta_{i_1 i_2}) \cdots (-\Theta_{i_k i})$$

- **Thus:**  $f(S) - f(S \cup \{j\})$  is sum on cycles that touch  $j$  but don't touch  $S$ .
- Is decreasing with  $S$ , so  $f$  is supermodular.

# Analysis for Walk-Summable

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define

$$f(S) = \text{Var}(X_1 \mid X_S).$$

**No longer supermodular!**  
**(Not even weakly-supermodular ...)**

# Analysis for Walk-Summable

Fix vertex 1. For  $S \subseteq \{2, \dots, n\}$ , define  
 $f(S) = \text{Var}(X_1 | X_S)$ .

**No longer supermodular!**  
(Not even weakly-supermodular ...)

- **Walk-summable = Symmetric Diagonally Dominant (SDD)**
- **SDD implies neighbors have noticeable effect**

# Analysis for Walk-Summable

Def:  $\Theta$  is SDD if for all  $i$

$$|\Theta_{ii}| \geq \sum_{j \neq i} |\Theta_{ij}|$$

- **Walk-summable = Symmetric Diagonally Dominant (SDD)**
- **SDD implies neighbors have noticeable effect**

# Analysis for Walk-Summable

Def:  $\Theta$  is SDD if for all  $i$

$$|\Theta_{ii}| \geq \sum_{j \neq i} |\Theta_{ij}|$$

Claim [RTT09]:  $\Theta$  walk-summable iff a diagonal  $D \geq 0$ ,  
 $D\Theta D$  is SDD.

- Walk-summable = Symmetric Diagonally Dominant (SDD)
- SDD implies neighbors have noticeable effect

# Analysis for Walk-Summable

Def:  $\Theta$  is SDD if for all  $i$

$$|\Theta_{ii}| \geq \sum_{j \neq i} |\Theta_{ij}|$$

Claim [RTT09]:  $\Theta$  walk-summable iff a diagonal  $D \geq 0$ ,  
 $D\Theta D$  is SDD.

**Suffices to show greedy works for SDD!**

- **Walk-summable = Symmetric Diagonally Dominant (SDD)**
- **SDD implies neighbors have noticeable effect**

# Analysis: Bounded Conditional Variances

**Lemma:** If  $\Theta$  is SDD, then for any vertex  $i$ , there exists a neighbor  $j$  such that  $\text{Var}(X_i | X_j) \leq 4\text{Var}(X_i | X_{-i})/\kappa^2$ .

# Analysis: Bounded Conditional Variances

There exists a neighbor, that is comparable to the entire neighborhood in conditioning ...

**Lemma:** If  $\Theta$  is SDD, then for any vertex  $i$ , there exists a neighbor  $j$  such that  $\text{Var}(X_i | X_j) \leq 4\text{Var}(X_i | X_{-i})/\kappa^2$ .



# Analysis: Bounded Conditional Variances

## Why useful ...

- $\text{Var}(X_i)$  can be very large!
- But conditioning on one neighbor brings the variance down.
- We can detect it with few samples.

**Lemma:** If  $\Theta$  is SDD, then for any vertex  $i$ , there exists a neighbor  $j$  such that  $\text{Var}(X_i | X_j) \leq 4\text{Var}(X_i | X_{-i})/\kappa^2$ .

# Analysis: Bounded Conditional Variances

## Proof ...

- Triangle inequality of **effective resistance** metric on graphs
- Properties of conditional variance ...

**Lemma:** If  $\Theta$  is SDD, then for any vertex  $i$ , there exists a neighbor  $j$  such that  $\text{Var}(X_i | X_j) \leq 4\text{Var}(X_i | X_{-i})/\kappa^2$ .

# Analysis: Bounded Conditional Variances

For intuition: Assume  $\Theta_{ii} = 1, \forall i$ .

$$\text{Recall: } \kappa(\Theta) = \min_{i,j:\Theta_{ij}\neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}.$$

$$\text{So } i \sim j \Rightarrow |\Theta_{ij}| \geq \kappa.$$

# Analysis: Bounded Conditional Variances

For intuition: Assume  $\Theta_{ii} = 1, \forall i$ .

$$\text{Recall: } \kappa(\Theta) = \min_{i,j:\Theta_{ij}\neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}.$$

$$\text{So } i \sim j \Rightarrow |\Theta_{ij}| \geq \kappa.$$

**Lemma 1:** If  $\Theta$  is SDD, then conditional variances are bounded —  $i \sim j \Rightarrow \text{Var}(X_i | X_j) \leq 1/\kappa$ .

# Analysis: Bounded Conditional Variances

For intuition: Assume  $\Theta_{ii} = 1, \forall i$ .

$$\text{Recall: } \kappa(\Theta) = \min_{i,j:\Theta_{ij}\neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}.$$

So  $i \sim j \Rightarrow |\Theta_{ij}| \geq \kappa$ .

**Lemma 1:** If  $\Theta$  is SDD, then conditional variances are bounded —  $i \sim j \Rightarrow \text{Var}(X_i | X_j) \leq 1/\kappa$ .

# Analysis: Bounded Conditional Variances

For intuition: Assume  $\Theta_{ii} = 1, \forall i$ .

$$\text{Recall: } \kappa(\Theta) = \min_{i,j:\Theta_{ij}\neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}.$$

So  $i \sim j \Rightarrow |\Theta_{ij}| \geq \kappa$ .

**Lemma 1:** If  $\Theta$  is SDD, then conditional variances are bounded —  $i \sim j \Rightarrow \text{Var}(X_i | X_j) \leq 1/\kappa$ .

**Example:** In random walk model

$$\text{Var}(X_{i+1} | X_i) = 1; \quad \text{Var}(X_{i+1}) = i + 1!$$

# Analysis: Bounded Conditional Variances

For intuition: Assume  $\Theta_{ii} = 1, \forall i$ .

Recall:  $\kappa(\Theta) = \min_{i,j:\Theta_{ij}\neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}.$

So  $i \sim j \Rightarrow |\Theta_{ij}| \geq \kappa.$

**Lemma 1:** If  $\Theta$  is SDD, then conditional variances are bounded —  $i \sim j \Rightarrow \text{Var}(X_i | X_j) \leq 1/\kappa.$

Not true for general sparse precision matrices ...

# Analysis: Bounded Conditional Variances

For intuition: Assume  $\Theta_{ii} = 1, \forall i$ .

$$\text{Recall: } \kappa(\Theta) = \min_{i,j:\Theta_{ij}\neq 0} \frac{|\Theta_{ij}|}{\sqrt{\Theta_{ii}\Theta_{jj}}}.$$

So  $i \sim j \Rightarrow |\Theta_{ij}| \geq \kappa$ .

**Lemma 1:** If  $\Theta$  is SDD, then conditional variances are bounded —  $i \sim j \Rightarrow \text{Var}(X_i | X_j) \leq 1/\kappa$ .


**“Proof ...”:**

- If Laplacian ...

$$\text{Var}(X_i | X_j) = \frac{1}{2} R_{\text{eff}}(i, j) \leq \frac{1}{|\Theta_{ij}|} \leq 1/\kappa.$$



# GGMs



# Motivation

# Algorithm

While  $|S| < t$  :  
Add  $\arg \min_j Var(X_i | X_{S \cup j})$ .

# Special Models

# Analysis



# Attractive. SDD