

```

cat <<'EOF' > /tmp/setup-subagents.sh
#!/usr/bin/env bash
set -euo pipefail
cd ~/.openclaw/workspace

# ===== EDIT THESE NAMES/IDS TO MATCH YOUR SUBAGENTS =====
# You can add more blocks for additional agents (finance, support, etc.).
declare -A AGENTS=(
# [status_slug]="agent_id|friendly_name|command_prefix"
[pikachu]="sales_agent|Pikachu|sales"
[charmander]="marketing_agent|Charmander|marketing"
)

# ===== 1) Shared status directories =====
for slug in "${!AGENTS[@]}"; do
mkdir -p "~/openclaw/shared/agents/${slug}"
done

# ===== 2) Subagent SOP skill (skills/subagent-ops/SKILL.md) =====
mkdir -p skills/subagent-ops
cat <<'MD' > skills/subagent-ops/SKILL.md
---
name: subagent-ops
description: Coordinate communication between the supervisor and each sub-agent (task
routing, status refreshes, shared tooling).
---
## Command prefixes
# (Filled dynamically at the bottom of this file)

## Shared status files
# ~/.openclaw/shared/agents/<slug>/STATUS.md

## Status workflow
1. When the user types "status <prefix>", do NOT wake the sub-agent via the chat route.
2. Instead, run the child agent directly (openclaw agent --agent <id> --message "Give me your
current identity/tools/priorities").
3. Write the response to ~/.openclaw/shared/agents/<slug>/STATUS.md with a timestamp, then
share a short snippet back in the main chat.

## Task workflow
1. Strip the prefix (e.g., "sales:") and relay the payload to the matching agent with an envelope
like "Delegated request from <user>: ...".
2. Wait for the child agent's answer and echo it back with a tag "[Sales]" or similar.
3. Log any blockers or tool gaps in the STATUS file so it's easy to spot later.

```

Tooling / env

- Keep API keys in secrets/*.env and load them via scripts/export_env.sh before running mcporter or custom curl helpers.
- Document blockers + active priorities inside each STATUS.md so the supervisor can read them without waking the agent.

MD

Append dynamic table of prefixes to the skill file

```
{
echo
echo "### Command table"
echo "| Prefix | Friendly name | Agent ID | Status file |"
echo "| ----- | ----- | ----- | ----- |"
for slug in "${!AGENTS[@]}"; do
IFS='|' read -r agentId friendly prefix <<<"${AGENTS[$slug]}"
echo "| \`${prefix}\` | \`${friendly}\` | \`${agentId}\` |"
echo "\`~/openclaw/shared/agents/${slug}/STATUS.md\` |"
done
} >> skills/subagent-ops/SKILL.md
```

===== 3) Human-facing cheat sheet (DELEGATION.md) =====

cat <<'MD' > DELEGATION.md

Subagent Command Cheatsheet

Use the prefixes below in this chat to reach each specialist:

MD

```
{
for slug in "${!AGENTS[@]}"; do
IFS='|' read -r agentId friendly prefix <<<"${AGENTS[$slug]}"
echo "- \`${prefix}\`: <task> → forwards to \`${friendly}\` (agent ID: \`${agentId}\`)"
done
echo "- \`${status}\` <prefix> → refreshes \`${prefix}\` and replies with a summary."
echo
echo "Behind the scenes the delegation-router skill runs the child agent and relays the answer here."
} >> DELEGATION.md
EOF
```

bash /tmp/setup-subagents.sh && rm /tmp/setup-subagents.sh