

# Cloud Connected Security Node

```
#include <WiFi.h>
```

```
#define TRIG_PIN 5
```

```
#define ECHO_PIN 18
```

```
const char* ssid = "Wokwi-GUEST";
```

```
const char* password = "";
```

```
void setup() {
```

```
    Serial.begin(115200);
```

```
    pinMode(TRIG_PIN, OUTPUT);
```

```
    pinMode(ECHO_PIN, INPUT);
```

```
    WiFi.begin(ssid, password);
```

```
    while (WiFi.status() != WL_CONNECTED) {
```

```
        delay(500);
```

```
        Serial.print(".");
```

```
    }
```

```
Serial.println();  
Serial.println("WiFi Connected");  
}  
  
void loop() {  
  
    digitalWrite(TRIG_PIN, LOW);  
    delayMicroseconds(2);  
  
    digitalWrite(TRIG_PIN, HIGH);  
    delayMicroseconds(10);  
  
    digitalWrite(TRIG_PIN, LOW);  
  
    long duration = pulseIn(ECHO_PIN, HIGH);  
  
    float distance = (duration / 2.0) * 0.0343;  
  
    Serial.print("Distance: ");  
    Serial.print(distance);  
    Serial.println(" cm");  
  
    if(distance < 50)  
        Serial.println("INTRUDER DETECTED");  
  
    else if(distance < 100)
```

```
    Serial.println("WARNING");

else

    Serial.println("SAFE");

Serial.println("-----");

delay(2000);
}
```

## Wokwi Link

<https://wokwi.com/projects/466998401932463105>