Activities Terminal Apr 7 14:40

madhumitha@localhost:~

```
[madhumitha@localhost ~]$ ls
 ABC                            emp.txt    opendir.c   REC
 abc.sh                         exec.c     os_lab      riya
 ab.h                           fork.c     os_lab1.c   riyaa.sh
 algo                           kee        os_lab.c    roundrobin.c
 a.out                          mad        Pictures    sample.c
'banks alg0'$'\n''mkdir banks'  mad3       pid.c       sample.txt
 bestfit                        madd       pidoutput   sjf.c
 bestfit.c                      madhu      priority    sujjee
 Desktop                        madhu.sh   Public      Templates
 dir.c                          maith      rahuk.sh    Videos
 Documents                      mn         rahul       vms
 Downloads                      Music      rahul.sh    XYZ
[madhumitha@localhost ~]$ vi besttfit.c
[madhumitha@localhost ~]$ gcc besttfit.c -o besttfit
[madhumitha@localhost ~]$ ./besttfit.c
bash: ./besttfit.c: Permission denied
[madhumitha@localhost ~]$ gcc besttfit.c -o besttfit
[madhumitha@localhost ~]$ ./a.out
Enter number of memory blocks:
4
Enter size of each block:
12 13 14 15
Enter number of processes:
4
Enter size of each process:
23 24 25 26

Process No.     Process Size    Block No.
1               23              Not Allocated
2               24              Not Allocated
3               25              Not Allocated
4               26              Not Allocated
[madhumitha@localhost ~]$
```

Activities Terminal Apr 7 14:41

madhumitha@localhost:~ — /usr/bin/vim besttfit.c

```c
#include <stdio.h>

int main() {
    int m, n;
    printf("Enter number of memory blocks:\n");
    scanf("%d", &m);

    int blockSize[m], remaining[m];

    printf("Enter size of each block:\n");
    for (int i = 0; i < m; i++) {
        scanf("%d", &blockSize[i]);
        remaining[i] = blockSize[i];
    }

    printf("Enter number of processes:\n");
    scanf("%d", &n);

    int processSize[n], allocation[n];

    printf("Enter size of each process:\n");
    for (int i = 0; i < n; i++) {
        scanf("%d", &processSize[i]);
        allocation[i] = -1;
    }


    for (int i = 0; i < n; i++) {
        int bestIndex = -1;

        for (int j = 0; j < m; j++) {
            if (remaining[j] >= processSize[i]) {
                if (bestIndex == -1 || remaining[j] < remaining[bestIndex]) {
```

1,1 Top

Activities Terminal Apr 7 14:41

madhumitha@localhost:~ — /usr/bin/vim besttfit.c

```
    allocation[i] = -1;
}


for (int i = 0; i < n; i++) {
    int bestIndex = -1;

    for (int j = 0; j < m; j++) {
        if (remaining[j] >= processSize[i]) {
            if (bestIndex == -1 || remaining[j] < remaining[bestIndex]) {
                bestIndex = j;
            }
        }
    }

    if (bestIndex != -1) {
        allocation[i] = bestIndex;
        remaining[bestIndex] -= processSize[i];
    }
}


printf("\nProcess No.\tProcess Size\tBlock No.\n");
for (int i = 0; i < n; i++) {
    printf("%d\t\t%d\t\t", i + 1, processSize[i]);
    if (allocation[i] != -1)
        printf("%d\n", allocation[i] + 1);
    else
        printf("Not Allocated\n");
}

return 0;
```

56,1 Bot