madhumitha@localhost:~

```
Downloads                       Music       rahul.sh    XYZ
emp.txt                         opendir.c   REC
exec.c                          os_lab      riya
[madhumitha@localhost ~]$ vi bestfit.c
[madhumitha@localhost ~]$ gcc bestfit.c
[madhumitha@localhost ~]$ gcc bestfit.c -o bestfit
[madhumitha@localhost ~]$ ./bestfir
bash: ./bestfir: No such file or directory
[madhumitha@localhost ~]$ ./bestfit
Enter number of memory blocks:
5
Enter size of each block:
100 200 300 400 500
Enter number of processes:
4
Enter size of each process:
123 124 125 126

Process No.     Process Size    Block No.
1               123             2
2               124             3
3               125             3
4               126             4
[madhumitha@localhost ~]$
```

Activities Terminal Apr 7 14:11

madhumitha@localhost:~ — /usr/bin/vim bestfit.c

```c
#include <stdio.h>

int main() {
    int m, n;

    // Input number of memory blocks
    printf("Enter number of memory blocks:\n");
    scanf("%d", &m);

    int blockSize[m], remainingSize[m];

    // Input block sizes
    printf("Enter size of each block:\n");
    for (int i = 0; i < m; i++) {
        scanf("%d", &blockSize[i]);
        remainingSize[i] = blockSize[i];
    }

    // Input number of processes
    printf("Enter number of processes:\n");
    scanf("%d", &n);

    int processSize[n], allocation[n];
```

1,1 Top

Activities Terminal Apr 7 14:12

madhumitha@localhost:~ — /usr/bin/vim bestfit.c

```c
#include <stdio.h>

int main() {
    int m, n;

    // Input number of memory blocks
    printf("Enter number of memory blocks:\n");
    scanf("%d", &m);

    int blockSize[m], remainingSize[m];

    // Input block sizes
    printf("Enter size of each block:\n");
    for (int i = 0; i < m; i++) {
        scanf("%d", &blockSize[i]);
        remainingSize[i] = blockSize[i];
    }

    // Input number of processes
    printf("Enter number of processes:\n");
    scanf("%d", &n);

    int processSize[n], allocation[n];

    // Input process sizes
    printf("Enter size of each process:\n");
    for (int i = 0; i < n; i++) {
        scanf("%d", &processSize[i]);
        allocation[i] = -1; // Not allocated initially
    }

    // First Fit Allocation
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < m; j++) {
            if (remainingSize[j] >= processSize[i]) {
                allocation[i] = j;
                remainingSize[j] -= processSize[i];
                break;
            }
        }
    }
```

1,1 Top

Activities Terminal Apr 7 14:13

madhumitha@localhost:~ — /usr/bin/vim bestfit.c

```c
    for (int i = 0; i < m; i++) {
        scanf("%d", &blockSize[i]);
        remainingSize[i] = blockSize[i];
    }

    // Input number of processes
    printf("Enter number of processes:\n");
    scanf("%d", &n);

    int processSize[n], allocation[n];

    // Input process sizes
    printf("Enter size of each process:\n");
    for (int i = 0; i < n; i++) {
        scanf("%d", &processSize[i]);
        allocation[i] = -1; // Not allocated initially
    }

    // First Fit Allocation
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < m; j++) {
            if (remainingSize[j] >= processSize[i]) {
                allocation[i] = j;
                remainingSize[j] -= processSize[i];
                break;
            }
        }
    }

    // Output allocation
    printf("\nProcess No.\tProcess Size\tBlock No.\n");
    for (int i = 0; i < n; i++) {
        printf("%d\t\t%d\t\t", i + 1, processSize[i]);
        if (allocation[i] != -1)
            printf("%d\n", allocation[i] + 1);
        else
            printf("Not Allocated\n");
    }

    return 0;
}
```