

EXPERIMENT 5

Implement programs to check stationary of a time series data

AIM:

The aim of this program is to analyze the stationarity of a given time series dataset using **Augmented Dickey-Fuller (ADF) Test** and **Kwiatkowski-Phillips-Schmidt-Shin (KPSS) Test**. These statistical tests help determine whether the time series data has a unit root (i.e., is non-stationary) or remains stable over time.

PROCEDURE:

Step 1: Import Necessary Libraries

- Import essential Python libraries such as `numpy`, `pandas`, `matplotlib`, and `statsmodels`.
- `statsmodels.tsa.stattools` is used for stationarity tests (ADF & KPSS).
- `google.colab.files` is used to handle file uploads.

Step 2: Upload the CSV File

- Use `files.upload()` to manually upload the dataset in Google Colab.
- Retrieve the file name dynamically.

Step 3: Load the Dataset

- Read the CSV file using `pd.read_csv()`.
- Display the first few rows using `df.head()` to inspect the dataset.
- Identify a suitable **numerical column** for time series analysis (e.g., `"rainfall"`, `"temperature"`, `"yield"`).

Step 4: Select and Visualize the Time Series Data

- Extract the selected column for analysis.
- Plot the time series using `matplotlib.pyplot` to observe trends.

Step 5: Perform Augmented Dickey-Fuller (ADF) Test

- Apply the **ADF test** using `adfuller()` from `statsmodels.tsa.stattools`.
- Extract the **test statistic**, **p-value**, and **critical values**.
- **Interpretation:**
 - If **p-value < 0.05**, the data is **stationary** (reject null hypothesis).
 - If **p-value > 0.05**, the data is **non-stationary** (fail to reject null hypothesis).

Step 6: Perform Kwiatkowski-Phillips-Schmidt-Shin (KPSS) Test

- Apply the **KPSS test** using `kpss()` from `statsmodels.tsa.stattools`.
- Extract the **test statistic**, **p-value**, and **critical values**.
- **Interpretation:**
 - If **p-value < 0.05**, the data is **non-stationary** (reject null hypothesis).
 - If **p-value > 0.05**, the data is **stationary** (fail to reject null hypothesis).

Step 7: Display Results and Interpret Findings

- Compare ADF and KPSS test results to determine whether the time series is stationary.
- If the series is **non-stationary**, consider transformations such as **differencing** or **detrending** for further analysis.

CODE:

```

import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import statsmodels.api as sm
from statsmodels.tsa.stattools import adfuller, kpss
from google.colab import files

# Step 1: Upload the file manually
uploaded = files.upload()

# Get the file name dynamically
file_name = list(uploaded.keys())[0]

# Step 2: Load the CSV file
df = pd.read_csv(file_name)

# Display the first few rows to check column names
print("First few rows of the dataset:")
print(df.head())

# Step 3: Choose a column for time series analysis (Modify as needed)
column_name = "rainfall" # Change this if needed
if column_name not in df.columns:
    raise ValueError(f"Column '{column_name}' not found in dataset. Check column names: {df.columns}")

# Convert the column into a time series
time_series = df[column_name]

# Step 4: Plot the time series
plt.figure(figsize=(10, 4))
plt.plot(time_series, label=column_name, color='b')
plt.title(f"Time Series Plot of {column_name}")
plt.xlabel("Index")
plt.ylabel("Value")
plt.legend()
plt.show()

# Step 5: Define ADF Test

```

```
def adf_test(series):
    result = adfuller(series.dropna(), autolag='AIC')
    print("\nADF Test Results:")
    print(f"Test Statistic: {result[0]}")
    print(f"P-value: {result[1]}")
    print(f"Critical Values: {result[4]}")
    if result[1] < 0.05:
        print("Conclusion: The series is likely STATIONARY (Reject H0).")
    else:
        print("Conclusion: The series is NON-STATIONARY (Fail to reject H0).")
```

Step 6: Define KPSS Test

```
def kpss_test(series):
    result = kpss(series.dropna(), regression='c', nlags="auto")
    print("\nKPSS Test Results:")
    print(f"Test Statistic: {result[0]}")
    print(f"P-value: {result[1]}")
    print(f"Critical Values: {result[3]}")
    if result[1] < 0.05:
        print("Conclusion: The series is likely NON-STATIONARY (Reject H0).")
    else:
        print("Conclusion: The series is STATIONARY (Fail to reject H0).")
```


Step 7: Perform stationarity tests

```
adf_test(time_series)
kpss_test(time_series)
```

OUTPUT:

First few rows of the dataset:

	N	P	K	temperature	humidity	ph	rainfall	label
0	90	42	43	20.879744	82.002744	6.502985	202.935536	rice
1	85	58	41	21.770462	80.319644	7.038096	226.655537	rice
2	60	55	44	23.004459	82.320763	7.840207	263.964248	rice
3	74	35	40	26.491096	80.158363	6.980401	242.864034	rice
4	78	42	42	20.130175	81.604873	7.628473	262.717340	rice



ADF Test Results:

Test Statistic: -3.38953014162007

P-value: 0.011321008714268511

Critical Values: {'1%': np.float64(-3.4333629045681398), '5%': np.float64(-2.8628709972102797), '10%': np.float64(-2.567478556227762)}

Conclusion: The series is likely STATIONARY (Reject H0).

KPSS Test Results:

Test Statistic: 0.9597635757263195

P-value: 0.01

Critical Values: {'10%': 0.347, '5%': 0.463, '2.5%': 0.574, '1%': 0.739}

Conclusion: The series is likely NON-STATIONARY (Reject H0).

<ipython-input-1-c11a9fd6baa9>:52: InterpolationWarning: The test statistic is outside of the range of p-values available in the look-up table. The actual p-value is smaller than the p-value returned.

```
result = kpss(series.dropna(), regression='c', nlags="auto")
```

RESULT:

Thus the python code implementation for this experiment is executed successfully