

Corporate Codes API Contract

1. Purpose

Allow clients to send PCC + airline + corporateCode mapping in search request to fetch corporate/negotiated fares from supported suppliers.

2. Request Contract

Relevant part of search request:

```
{
  "searchQuery": {
    "cabinClass": "ECONOMY",
    "preferredAirline": [],
    "searchModifiers": {
      "pfts": ["REGULAR"],
      "isDirectFlight": false,
      "isConnectingFlight": false
    },
    "routeInfos": [
      {
        "fromCityOrAirport": { "code": "DEL" },
        "toCityOrAirport": { "code": "DXB" },
        "travelDate": "2026-04-20"
      }
    ],
    "paxInfo": {
      "ADULT": 1,
      "CHILD": 0,
      "INFANT": 0
    },
    "corporateCodes": [
      {
        "pcc": "517Z",
        "airlineKeys": [
          {
            "airline": "AI",
            "corporateCode": "SME"
          }
        ]
      }
    ]
  }
}
```

3. Field Definitions

corporateCodes (Optional): List of PCC mappings used to fetch corporate fares.

Fields:

- pcc (String, Mandatory): Pseudo City Code
- airlineKeys (Array, Mandatory): Airline-specific mappings

airlineKeys:

- airline (String, Mandatory): Airline code (e.g. AI, EK)
- corporateCode (String, Mandatory): Corporate fare code

4. Processing Logic

Step 1: Validation

- Ignore entry if pcc is invalid, airline not supported, or corporateCode is empty.

Step 2: Mapping Creation

(PCC, Airline) → CorporateCode

5. Response Behavior

- If corporate fares found → return along with regular fares
- If not → fallback to regular fares
- No hard failure due to invalid corporate mapping

6. Business Rules

- Multiple PCCs supported
- Multiple airlines per PCC supported
- Corporate codes are airline-specific
- Duplicate mappings are deduplicated internally
- No guarantee corporate fare will be returned

7. Edge Handling

- Invalid PCC → Ignored
- Unsupported airline → Skipped
- Invalid corporate code → Ignored
- No corporate fares → Return regular fares