

SIMATS ENGINEERING ASSESSMENT TOOL 1

COURSE NAME: COMPUTER NETWORKS
COURSE CODE: CSA07

COURSE OUTCOME COVERED

CO2: Configure IP addressing schemes, subnetting, and basic routing techniques using simulation tool, for efficient network design and topology. (BL3)

Assessment Tool Weightage: 40%

Annexure A

ANALYTICAL PROBLEM SOLVING

Code of Conduct:

I Madhulika (192472188) (Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.

I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the student: M. Madhulika

Annexure A

ANALYTICAL PROBLEM SOLVING

1. A university network is assigned the IP address block 192.168.20.0/24 for its internal communication. The network administrator has decided to divide this network into subnets for three different labs using fixed subnet masks. Lab A is assigned a /26 subnet, Lab B is assigned a /27 subnet, and Lab C is assigned a /28 subnet. Based on the given subnet masks, apply subnetting concepts to determine the network address of each lab. Further, identify the valid range of host IP addresses and the broadcast address for each subnet. Finally, calculate the total number of usable host IP addresses available in each lab's subnet.

2. A network administrator has configured two systems with the following details: System 1 has IP address 192.168.1.130 with subnet mask 255.255.255.192, and System 2 has IP address 192.168.1.190 with subnet mask 255.255.255.192. Using the given configuration, apply subnetting techniques to determine the subnet range, network address, and broadcast address for each system. Identify the valid host IP range for both subnets based on the given subnet mask. Calculate whether each IP address falls within its respective subnet range. Also, determine the number of usable host addresses available in each subnet.

3. An organization has been allocated the IP block 172.16.0.0/16 for its internal network. The network administrator has already decided the subnet masks for each department as follows: HR → /25, Sales → /26, IT → /27, and Admin → /28. Using the given subnet masks, apply subnetting techniques to assign suitable subnet addresses for each department. Determine the network address, valid host IP range, and broadcast address for each subnet. Based on the allocation, calculate the number of usable host addresses in each department. Finally, identify the remaining unused IP address range within the given network block.

4. A company uses the IP address 172.16.10.0/24 and has implemented subnetting using a /27 subnet mask for its internal departments. Using the given subnet

mask, apply subnetting techniques to calculate the total number of subnets created and the number of usable hosts per subnet. Determine the subnet to which the IP address **172.16.10.78** belongs. Identify the network address and broadcast address for that subnet. Also, determine whether the IP address **172.16.10.95** falls within the same subnet range based on the given configuration.

5. A network uses the Internet Protocol version 6 address **2001:0db8:0000:0000:ff00:0042:8329**. Apply IPv6 addressing rules to compress the given address into its shortest form and then expand the compressed address back to its full notation. Using a prefix length of **/64**, determine the network prefix of the given address. Also, calculate the total number of possible host addresses available within this network based on the given prefix length.

RUBRICS FOR CALCULATION

Criteria	Weightage	Level 4 (Exemplary)	Level 3 (Proficient)	Level 2 (Developing)	Level 1 (Beginning)
Problem Understanding	20%	Clearly interprets problem, identifies all parameters and requirements accurately	Understands problem with minor gaps	Partial understanding ; misses key elements	Misinterprets or unable to understand problem
Method Selection	20%	Selects most appropriate method/formula with strong justification	Selects correct method with minor errors	Inappropriate or partially correct method	Unable to select method
Solution Process	25%	Logical, systematic steps with correct approach throughout	Mostly correct steps with minor mistakes	Disorganized steps; multiple errors	No clear process
Accuracy of Calculation	20%	All calculations accurate; correct final answer	Minor calculation errors	Frequent errors; incorrect final answer	No valid calculations

University Network : 192.168.20.0/24

Given

Network : 192.168.20.0/24

Lab A $\rightarrow$ /26

Lab B $\rightarrow$ /27

Lab C $\rightarrow$ /28

Step 1: Allocate subnets

Lab A (/26)

- Subnet Mask = 255.255.255.192
- Block size = 64

Network Address : 192.168.20.0

Host Range :

- First Host : 192.168.20.1
- Last Host : 192.168.20.62

Broadcast Address : 192.168.20.63

usable Hosts : $2^6 - 2 = 64 - 2 = 62$

Lab B (/27)

Next available subnet starts at 192.168.20.64

- Subnet Mask : 255.255.255.224
- Block size : 32

Network address : 192.168.20.64

Host Range :

- First Host : 192.168.20.65
- Last Host : 192.168.20.94

Broadcast Address : 192.168.20.95

usable Hosts : $2^5 - 2 = 32 - 2 = 30$

Lab c (/28)

Next available subnet starts at 192.168.20.96

• Subnet Mask = 255.255.255.240

• Block size = 16

Network Address : 192.168.20.96

Host Range : First Host : 192.168.20.97

Last Host : 192.168.20.110

Broadcast Address : 192.168.20.111

usable Hosts : $2^4 - 2 = 16 - 2 = 14$

Summary.

Lab	Subnet	Network Address	Host Range	Broad cast	usable Hosts
A	/26	192.168.20.0	192.168.20.1 - 192.168.20.62	192.168.20.23	62
B	/27	192.168.20.64	192.168.20.65 - 192.168.20.94	192.168.20.95	30
C	/28	192.168.20.96	192.168.20.97 - 192.168.20.110	192.168.20.111	14

systems with /26 Mask.

Subnet Mask = 255.255.255.192 (126)
Block size = 64.

Subnets:

- 192.168.1.0-63
- 192.168.1.64-127
- 192.168.1.128-191
- 192.168.1.192-255

System 1

IP : 192.168.1.130 Falls in subnet 128-191

Network Address : 192.168.1.128

Host Range : 192.168.1.129 - 192.168.1.190

Broadcast : 192.168.1.191

IP valid? : Yes.

System 2

IP : 192.168.1.190

Also falls in 128-191

Network Address : 192.168.1.128

Host Range : 192.168.1.129 - 192.168.1.190

Broadcast : 192.168.1.191

IP valid : Yes

Summary

System	IP Address	Network	Host Range	Broad cast
1	192.168.9.130	192.168.1.128	192.168.1.129 - 192.168.1.190	192.168.1.191
2	192.168.1.190	192.168.1.128	192.168.1.129 - 192.168.1.190	192.168.1.191

Usable Hosts Per subnet = 62

3) organization Network : 172.16.0.0/16

Given

- HR → 125
- Sales → 126
- IT → 127
- Admin → 128

Assign sequentially

HR (125)

Network : 172.16.0.0

Host Range : 172.16.0.1
- 172.16.0.126

Broadcast : 172.16.0.127

Hosts :- 126

Sales (126)

Next subnet

Network : 172.16.0.128

Host Range :

172.16.0.129 - 172.16.0.190

Broadcast : 172.16.0.191

Host :- 62

(2.2)

Network : 172.16.0.192

Host Range

: 172.16.0.193 - 172.16.0.222

Broadcast

: 172.16.0.223

Host : 30

Admin (123)

Network : 172.16.0.224

Host Range : 172.16.0.225

- 172.16.0.238

Broadcast

: 172.16.0.239

Hosts: 14

Remaining IP Range.

172.16.0.240 - 172.16.0.255

4) company Network 172.16.0.0/24.

Given

subnet - 127

Number of ~~127~~ subnets

Borrowed bits

$$2.7.24 = 3$$

Number of subnets

$$2^3 = 8$$

Hosts per subnet.

Host bits = 5

$$2^5 - 2 = 30$$

IP : 172.16.0.78.

Falls in 64-95

Network

: 172.16.10.64

Broadcast

: 172.16.10.95

Host Range

: 172.16.10.65 - 172.16.10.94

Summary.

Items	Answer
Total subnets	8
Hosts / Subnet	30
IP 172.16.10.78 subnet	172.16.10.64/24
Network Address	172.16.10.64
Broadcast	172.16.10.95
172.16.10.95 same subnet	Yes, but is the broadcast address not a usable host.

5) IPv6 Address.

Given

2001:0db8:0000:0000:0000:f000:0042:8329

a) compress the address

- Remove leading zeros.

- Replace longest sequence of consecutive 0000 group with "::".

compressed Address: 2001:db8::f000:42:8329

b) Expand Again.

Expanded Address 2001:0db8:0000:0000:0000:

f000:0042:8329

c) Network prefix

first 64 bits 2001:0db8:0000:0000::/64

d) Total Host addresses

Host bits $128 - 64 = 64$

Total possible host addresses

$$2^{64} = 18,446,744,073,709,551,616$$