

Pushdown Automata

Pushdown Automata is a finite automata with extra memory called stack which helps Pushdown automata to recognize Context Free Languages.

Basic Structure of PDA

A pushdown automaton is a way to implement a context-free grammar in a similar way we design DFA for a regular grammar. A DFA can remember a finite amount of information, but a PDA can remember an infinite amount of information.

Basically a pushdown automaton is –

"Finite state machine" + "a stack"

A pushdown automaton has three components –


- an input tape,
- a control unit, and
- a stack with infinite size.

The stack head scans the top symbol of the stack.

A stack does two operations –

- **Push** – a new symbol is added at the top.
- **Pop** – the top symbol is read and removed.

A PDA may or may not read an input symbol, but it has to read the top of the stack in every transition.




A Pushdown Automata (PDA) can be defined as :

- Q is the set of states
- Σ is the set of input symbols
- Γ is the set of pushdown symbols (which can be pushed and popped from stack)
- q_0 is the initial state

- Z is the initial pushdown symbol (which is initially present in stack)
- F is the set of final states
- δ is a transition function which maps $Q \times \{\Sigma \cup \epsilon\} \times \Gamma$ into $Q \times \Gamma^*$. In a given state, PDA will read input symbol and stack symbol (top of the stack) and move to a new state and change the symbol of stack.

The following diagram shows a transition in a PDA from a state q_1 to state q_2 , labeled as $a, b \rightarrow c$ –



This means at state q_1 , if we encounter an input string ‘a’ and top symbol of the stack is ‘b’, then we pop ‘b’, push ‘c’ on top of the stack and move to state q_2 .

Deterministic PDAs

In general terms, a *deterministic* PDA is one in which there is at most one possible transition from any state based on the current input.

Formally, a deterministic PDA is a PDA where:

- for every state P , input symbol a and stack symbol t , there is at most one transition of the form $(P, a, t) \mapsto (Q, u)$ for any state Q and stack symbol u .

Any context-free language that can be converted to a deterministic PDA is called a *deterministic CFL*.

Non-Deterministic PDAs

A nondeterministic pushdown automaton (NPDA) is a 7-tuple

$M = (Q, \Sigma, \Gamma, q_0, \delta, z, F)$, where

Q is a finite set of states

Σ is the input alphabet (a finite set)

Γ is the stack alphabet (a finite set)

$\delta : Q \times (\Sigma \cup \{\lambda\}) \times \Gamma \rightarrow (\text{finite subsets of } Q \times \Gamma^*)$

is the transition function

$q_0 \in Q$ is the start state

$z \in \Gamma$ is the initial stack symbol

$F \subseteq Q$ is the set of accepting states

Nondeterminism

- Execution: If the machine is in state i and the input letter is b and C is on top of the stack, then pop the stack and enter state j .
- Nondeterminism can occur in two ways, as in the following examples.

