```
mysql> USE college;
Database changed
mysql> SELECT c.CourseName, COUNT(r.SID) AS Total_Students
    -> FROM course c
    -> JOIN registration r
    -> ON c.CourseID = r.CourseID
    -> GROUP BY c.CourseID, c.CourseName;
+------------------+----------------+
| CourseName       | Total_Students |
+------------------+----------------+
| DBMS             |              3 |
| Python           |              3 |
| Electronics      |              1 |
| Mechanics        |              1 |
| Engineering Maths |             2 |
+------------------+----------------+
5 rows in set (0.00 sec)

mysql> SELECT SID, COUNT(CourseID) AS Total_Courses
    -> FROM registration
    -> GROUP BY SID;
+------+---------------+
| SID  | Total_Courses |
+------+---------------+
|  101 |             2 |
|  102 |             2 |
|  103 |             2 |
|  104 |             2 |
|  105 |             2 |
+------+---------------+
5 rows in set (0.00 sec)
```

```
mysql> USE college;
Database changed
mysql> SELECT c.CourseName, COUNT(r.SID) AS Total_Students
    -> FROM course c
    -> JOIN registration r
    -> ON c.CourseID = r.CourseID
    -> GROUP BY c.CourseID, c.CourseName;
+------------------+----------------+
| CourseName       | Total_Students |
+------------------+----------------+
| DBMS             |              3 |
| Python           |              3 |
| Electronics      |              1 |
| Mechanics        |              1 |
| Engineering Maths |             2 |
+------------------+----------------+
5 rows in set (0.00 sec)

mysql> SELECT SID, COUNT(CourseID) AS Total_Courses
    -> FROM registration
    -> GROUP BY SID;
+------+---------------+
| SID  | Total_Courses |
+------+---------------+
|  101 |             2 |
|  102 |             2 |
|  103 |             2 |
|  104 |             2 |
|  105 |             2 |
+------+---------------+
5 rows in set (0.00 sec)
```

MySQL 8.0 Command Line Cli

```
mysql> SELECT Name, Gender, SID
    -> FROM student
    -> ORDER BY SID ASC;
+-------+--------+-----+
| Name  | Gender | SID |
+-------+--------+-----+
| Rahul | NULL   | 101 |
| Rahul | NULL   | 102 |
| Rahul | NULL   | 103 |
| Rahul | NULL   | 104 |
| Rahul | NULL   | 105 |
+-------+--------+-----+
5 rows in set (0.01 sec)

mysql> DESC faculty;
+-------------+-------------+------+-----+---------+-------+
| Field       | Type        | Null | Key | Default | Extra |
+-------------+-------------+------+-----+---------+-------+
| FacultyID   | int         | NO   | PRI | NULL    |       |
| FacultyName | varchar(50) | YES  |     | NULL    |       |
| DeptID      | int         | YES  | MUL | NULL    |       |
| Age         | int         | YES  |     | NULL    |       |
| JoiningDate | date        | YES  |     | NULL    |       |
+-------------+-------------+------+-----+---------+-------+
5 rows in set (0.00 sec)

mysql> SELECT FacultyName, Age
    -> FROM faculty
    -> ORDER BY Age DESC;
+-------------+------+
| FacultyName | Age  |
+-------------+------+
| Mohan       |   59 |
| Priya       | NULL |
| Arun        | NULL |
| Kavitha     | NULL |
+-------------+------+
4 rows in set (0.01 sec)

mysql>
```