

ROSE Tutorial:
A Tool for Building
Source-to-Source Translators
Draft Tutorial
(version 0.9.4a)

Daniel Quinlan, Markus Schordan, Richard Vuduc, Qing Yi
Thomas Panas, Chunhua Liao, and Jeremiah J. Willcock

Lawrence Livermore National Laboratory

Livermore, CA 94550

925-423-2668 (office)

925-422-6278 (fax)

{dquinlan,panas2,liao6}@llnl.gov

markus@complang.tuwien.ac.at

qingyi@cs.utsa.edu

richie@cc.gatech.edu

jewillco@osl.iu.edu

Project Web Page: www.rosecompiler.org

UCRL Number for ROSE User Manual: UCRL-SM-210137-DRAFT

UCRL Number for ROSE Tutorial: UCRL-SM-210032-DRAFT

UCRL Number for ROSE Source Code: UCRL-CODE-155962

ROSE User Manual (pdf)

ROSE Tutorial (pdf)

ROSE HTML Reference (html only)

November 1, 2009

November 1, 2009

Contents

1	Introduction	1
1.1	Why you should be interested in ROSE	1
1.2	Problems that ROSE can address	1
1.3	Examples in this ROSE Tutorial	2
1.4	ROSE Documentation and Where To Find It	9
1.5	Using the Tutorial	9
1.6	Required Makefile for Tutorial Examples	10
I	Working with the ROSE AST	13
2	Identity Translator	15
3	Scopes of Declarations	17
3.1	Input For Examples Showing Scope Information	17
3.2	Generating the code representing any IR node	18
4	AST Graph Generator	21
5	AST Whole Graph Generator	25
6	General AST Graph Generation	29
6.1	Whole Graph Generation	30
7	AST PDF Generator	33
8	Introduction to AST Traversals	37
8.1	Input For Example Traversals	37
8.2	Traversals of the AST Structure	38
8.2.1	Classic Object-Oriented Visitor Pattern for the AST (Not Yet Implemented)	39
8.2.2	Simple Traversal (no attributes)	40
8.2.3	Simple Pre- and Postorder Traversal	40
8.2.4	Inherited Attributes	40
8.2.5	Synthesized Attributes	46
8.2.6	Accumulator Attributes	48

8.2.7	Inherited and Synthesized Attributes	49
8.2.8	Persistent Attributes	52
8.2.9	Nested Traversals	55
8.2.10	Combining all Attributes and Using Primitive Types	57
8.2.11	Combined Traversals	58
8.2.12	Short-Circuiting Traversals	64
8.3	Memory Pool Traversals	67
8.3.1	ROSE Memory Pool Visit Traversal	67
8.3.2	Classic Object-Oriented Visitor Pattern for Memory Pool	69
8.3.3	ROSE IR Type Traversal (uses Memory Pools)	71
9	AST Query	75
9.1	Simple Queries on the AST	75
9.2	Nested Query	75
10	AST File I/O	81
10.1	Source Code for File I/O	81
10.2	Input to Demonstrate File I/O	81
10.3	Output from File I/O	81
10.4	Final Code After Passing Through File I/O	81
11	Debugging Techniques	85
11.1	Input For Examples Showing Debugging Techniques	85
11.2	Generating the code from any IR node	86
11.3	Displaying the source code position of any IR node	86
II	Complex Types	89
12	Type and Declaration Modifiers	91
12.1	Input For Example Showing use of <i>Volatile</i> type modifier	91
12.2	Generating the code representing the seeded bug	92
13	Function Parameter Types	95
14	Resolving Overloaded Functions	99
15	Template Parameter Extraction	103
16	Template Support	105
16.1	Example Template Code #1	105
16.2	Example Template Code #2	105
III	Program Analyses	107
17	Recognizing Loops	109

18 Virtual CFG	113
18.1 Important functions	113
18.1.1 Node methods	113
18.1.2 Edge methods	114
18.2 Drawing a graph of the CFG	115
18.3 Index values	117
18.4 Robustness to AST changes	117
18.5 Limitations	117
18.5.1 Fortran support	117
18.5.2 Exception handling	117
18.5.3 Interprocedural control flow analysis	117
18.6 Node filtering	117
18.6.1 “Interesting” node filter	117
18.6.2 Arbitrary filtering	117
19 Generating Control Flow Graphs	119
20 Dataflow Analysis	123
20.1 Def-Use Analysis	123
20.1.1 Def-use Example implementation	123
20.1.2 Accessing the Def-Use Results	124
21 Generating the Call Graph (CG)	127
22 Generating the Class Hierarchy Graph	131
23 Database Support	133
23.1 ROSE DB Support for Persistent Analysis	133
23.2 Call Graph for Multi-file Application	133
23.3 Class Hierarchy Graph	133
24 Building Custom Graphs	139
 IV Program Transformations and Optimizations	 143
25 Generating Unique Names for Declarations	145
25.1 Example Code Showing Generation of Unique Names	146
25.2 Input For Examples Showing Unique Name Generation for Variables	146
25.3 Example Output Showing Unique Variable Names	147
25.4 Input For Examples Showing Unique Name Generation for Functions	147
25.5 Example Output Showing Unique Function Names	147
26 Command-line Processing Within Translators	153
26.1 Commandline Selection of Files	153

27 Tailoring The Code Generation Format	157
27.1 Source Code for Example that Tailors the Code Generation	157
27.2 Input to Demonstrate Tailoring the Code Generation	157
27.3 Final Code After Tailoring the Code Generation	157
28 AST Construction	161
28.1 Variable Declarations	161
28.2 Expressions	165
28.3 Assignment Statements	167
28.4 Functions	169
28.5 Function Calls	174
28.6 Creating a 'struct' for Global Variables	174
29 Handling Comments, Preprocessor Directives, And Adding Arbitrary Text to Generated Code	187
29.1 How to Access Comments and Preprocessor Directives	187
29.1.1 Source Code Showing How to Access Comments and Preprocessor Directives	188
29.1.2 Input to example showing how to access comments and CPP directives .	188
29.1.3 Comments and CPP Directives collected from source file (skipping headers)	188
29.1.4 Comments and CPP Directives collected from source file and all header files	188
29.2 Collecting #define C Preprocessor Directives	188
29.2.1 Source Code Showing How to Collect #define Directives	188
29.2.2 Input to example showing how to access comments and CPP directives .	190
29.2.3 Comments and CPP Directives collected from source file and all header files	190
29.3 Automated Generation of Comments	190
29.3.1 Source Code Showing Automated Comment Generation	191
29.3.2 Input to Automated Addition of Comments	191
29.3.3 Final Code After Automatically Adding Comments	191
29.4 Addition of Arbitrary Text to Unparsed Code Generation	191
29.4.1 Source Code Showing Automated Arbitrary Text Generation	191
29.4.2 Input to Automated Addition of Arbitrary Text	192
29.4.3 Final Code After Automatically Adding Arbitrary Text	192
30 Partial Redundancy Elimination (PRE)	201
30.1 Source Code for example using PRE	201
30.2 Input to Example Demonstrating PRE	202
30.3 Final Code After PRE Transformation	203
31 Calling the Inliner	205
31.1 Source Code for Inliner	205
31.2 Input to Demonstrate Function Inlining	205
31.3 Final Code After Function Inlining	205

32 Using the AST Outliner	209
32.1 An Outlining Example	209
32.2 Limitations of the Outliner	210
32.3 User-Directed Outlining <i>via</i> Pragmas	212
32.4 Outlining via Abstract Handles	212
32.5 Calling Outliner Directly on AST Nodes	214
32.5.1 Selecting the <i>outlineable</i> if statements	215
32.5.2 Properly ordering statements for in-place outlining	217
32.6 Outliner's Preprocessing Phase	218
33 Loop Optimization	225
33.1 Example Loop Optimizer	225
33.2 Matrix Multiply Example	228
33.3 Loop Fusion Example	230
33.4 Example Loop Processor (LoopProcessor.C)	230
33.5 Matrix Multiplication Example (mm.C)	233
33.6 Matrix Multiplication Example Using Linearized Matrices (dgemm.C)	235
33.7 LU Factorization Example (lufac.C)	237
33.8 Loop Fusion Example (tridvpk.C)	239
34 Parameterized Code Translation	241
34.1 Loop Unrolling	241
34.2 Loop Interchange	245
34.3 Loop Tiling	246
V Correctness Checking	247
35 Code Coverage	249
36 Bug Seeding	257
36.1 Input For Examples Showing Bug Seeding	257
36.2 Generating the code representing the seeded bug	258
VI Binary Support	261
37 Instruction Semantics	263
37.1 The FindConstantsPolicy Class	263
37.2 Sample Output	265
37.3 Building on Instruction Semantics	269
38 Binary Analysis	271
38.1 Loading binaries	271
38.1.1 ROSE Disassembler	271
38.1.2 IdaPro-mysql	272
38.2 The AST	272

38.3 The ControlFlowGraph	272
38.4 DataFlow Analysis	273
38.4.1 Def-Use Analysis	273
38.4.2 Variable Analysis	273
38.5 Dynamic Analysis	273
39 Binary Construction	279
39.1 Constructors	279
39.2 Read-Only Data Members	279
39.3 Constructing the Executable File Container	280
39.4 Constructing the ELF File Header	280
39.5 Constructing the ELF Segment Table	281
39.6 Constructing the .text Section	281
39.7 Constructing a LOAD Segment	283
39.8 Constructing a PAX Segment	284
39.9 Constructing a String Table	284
39.10 Constructing an ELF Section Table	284
39.11 Allocating Space	285
39.12 Produce a Debugging Dump	285
39.13 Produce the Executable File	285
40 Dwarf Debug Support	287
40.1 ROSE AST of Dwarf IR nodes	288
40.2 Source Position to Instruction Address Mapping	288
VII Interacting with Other Tools	293
41 Abstract Handles to Language Constructs	295
41.1 Use Case	296
41.2 Syntax	296
41.3 Examples	297
41.4 Reference Implementation	298
41.4.1 Connecting to ROSE	298
41.4.2 Connecting to External Tools	303
41.5 Summary	306
42 ROSE-HPCToolKit Interface	307
42.1 An HPCToolkit Example Run	307
42.2 Attaching HPCToolkit Data to the ROSE AST	314
42.2.1 Calling ROSE-HPCT	314
42.2.2 Retrieving the attribute values	314
42.2.3 Metric propagation	314
42.3 Working with GNU gprof	315
42.4 Command-line options	316

43	<i>TAU</i> Instrumentation	321
43.1	Input For Examples Showing Information using Tau	321
43.2	Generating the code representing any IR node	321
44	The Haskell Interface	325
44.1	Traversals	326
44.2	Further Reading	326
VIII	Parallelism	329
45	Shared-Memory Parallel Traversals	331
46	Distributed-Memory Parallel Traversals	335
47	Parallel Checker	339
47.1	Different Implementations	339
47.2	Running through PSUB	339
48	Reduction Recognition	341
IX	Tutorial Summary	343
49	Tutorial Wrap-up	345
Appendix		347
49.1	Location of To Do List	347
49.2	Abstract Grammar	347
Glossary		355

List of Figures

1.1	Example <code>Makefile</code> showing how to use an installed version of ROSE (generated by <code>make install</code>).	11
2.1	Source code for translator to read an input program and generate an object code (with no translation).	15
2.2	Example source code used as input to identity translator.	16
2.3	Generated code, from ROSE identity translator, sent to the backend (vendor) compiler.	16
3.1	Example source code used as input to program in codes used in this chapter.	18
3.2	Example source code showing how to get scope information for each IR node.	19
3.3	Output of input code using <code>scopeInformation.C</code>	20
4.1	Example source code to read an input program and generate an AST graph.	21
4.2	Example source code used as input to generate the AST graph.	22
4.3	AST representing the source code file: <code>inputCode_ASTGraphGenerator.C</code> .	23
5.1	Example source code to read an input program and generate a <i>whole</i> AST graph.	25
5.2	Example tiny source code used as input to generate the small AST graph with attributes.	26
5.3	AST representing the tiny source code file: <code>inputCode_wholeAST_1.C</code> .	27
5.4	Example source code used as input to generate a larger AST graph with attributes.	27
5.5	AST representing the small source code file: <code>inputCode_wholeAST_2.C</code> .	28
6.1	Example source code to read an input program and generate an AST graph.	31
6.2	Example source code used as input to generate the AST graph.	32
6.3	AST representing the source code file: <code>inputCode_wholeGraphAST.C</code> .	32
7.1	Example source code to read an input program and generate a PDF file to represent the AST.	33
7.2	Example source code used as input to generate the PDF file of the AST.	34
7.3	Example output from translator which outputs PDF representation of AST.	35
8.1	Example source code used as input to program in traversals shown in this chapter.	38
8.2	Example source showing simple visitor pattern.	39

8.3	Output of input file to the visitor pattern traversal over the memory pools. . . .	41
8.4	Example source showing simple visitor pattern.	42
8.5	Output of input file to the visitor traversal.	42
8.6	Example source showing simple pre- and postorder pattern.	43
8.7	Output of input file to the pre- and postorder traversal.	43
8.8	Example source code showing use of inherited attributes (passing context information down the AST).	44
8.9	Output of input file to the inherited attribute traversal.	45
8.10	Example source code showing use of synthesized attributed (passing analysis information up the AST).	46
8.11	Output of input file to the synthesized attribute traversal.	47
8.12	Example source code showing use of accumulator attributes (typically to count things in the AST).	48
8.13	Output of input file to the accumulator attribute traversal.	49
8.14	Example source code showing use of both inherited and synthesized attributes working together (part 1).	50
8.15	Output of input file to the inherited and synthesized attribute traversal.	51
8.16	Example source code showing use of persistent attributes used to pass information across multiple passes over the AST.	53
8.17	Output of input file to the persistent attribute traversal showing the passing of information from one AST traversal to a second AST traversal.	54
8.18	Example source code showing use nested traversals.	55
8.19	Output of input file to the nested traversal example.	56
8.20	Input code with nested loops for nesting info processing	57
8.21	Example source code showing use of inherited, synthesized, accumulator, and persistent attributes (part 1).	59
8.22	Example source code showing use of inherited, synthesized, accumulator, and persistent attributes (part 2).	60
8.23	Output code showing the result of using inherited, synthesized, and accumulator attributes.	61
8.24	Example source showing the combination of traversals.	62
8.25	Output of input file to the combined traversals. Note that the order of outputs changes as execution of several analyzers is interleaved.	63
8.26	Input code with used to demonstrate the traversal short-circuit mechanism. . . .	64
8.27	Example source code showing use of short-circuit mechanism to avoid traversal of full AST.	65
8.28	Output code showing the result of short-circuiting the traversal.	66
8.29	Example source showing simple visit traversal over the memory pools.	68
8.30	Output of input file to the visitor traversal over the memory pool.	68
8.31	Example source showing simple visitor pattern.	69
8.32	Output of input file to the visitor pattern traversal over the memory pools. . . .	70
8.33	Example source showing simple visit traversal over each type of IR node (one only) in the memory pools.	72
8.34	Output of input file to the IR Type traversal over the memory pool.	73
8.35	Example of output using -rose:verbose 2 (memory use report for AST).	73

9.1	Example source code for translator to read an input program and generate a list of functions in the AST (queryLibraryExample.C).	76
9.2	Example source code used as input to program in figure 9.1 (queryLibraryExample.C).	77
9.3	Output of input file to the AST query processor (queryLibraryExample.C). . . .	78
9.4	Example source code for translator to read an input program and generate a list of access functions in the AST (nestedQueryExample.C).	79
9.5	Example source code used as input to program in figure 9.4 (nestedQueryExample.C).	80
9.6	Output of input file to the AST query processor (nestedQueryExample.C). . . .	80
10.1	Example source code showing how to use the AST file I/O support.	82
10.2	Example source code used as input to demonstrate the AST file I/O support. . .	83
10.3	Output of input code after inlining transformations.	83
10.4	Output of input code after file I/O.	84
11.1	Example source code used as input to program in codes showing debugging techniques shown in this section.	85
11.2	Example source code showing the output of the string from an IR node. The string represents the code associated with the subtree of the target IR node. . . .	87
11.3	Output of input code using debuggingIRnodeToString.C	87
11.4	Example source code showing the output of the string from an IR node. The string represents the code associated with the subtree of the target IR node. . . .	88
11.5	Output of input code using debuggingSourceCodePositionInformation.C	88
12.1	Example source code used as input to program in codes used in this chapter. . .	91
12.2	Example source code showing how to detect <i>volatile</i> modifier.	92
12.3	Output of input code using volatileTypeModifier.C	93
13.1	Example source code showing how to get type information from function parameters. .	96
13.2	Example source code used as input to typeInfoFromFunctionParameters.C. . . .	97
13.3	Output of input to typeInfoFromFunctionParameters.C.	98
14.1	Example source code showing mapping of function calls to overloaded function declarations.	100
14.2	Example source code used as input to resolveOverloadedFunction.C.	101
14.3	Output of input to resolveOverloadedFunction.C.	101
15.1	Example source code used to extract template parameter information.	103
15.2	Example source code used as input to templateParameter.C.	104
15.3	Output of input to templateParameter.C.	104
16.1	Example source code showing use of a C++ template.	105
16.2	Example source code after processing using identityTranslator (shown in figure 2.1).106	
16.3	Example source code showing use of a C++ template.	106
16.4	Example source code after processing using identityTranslator (shown in figure 2.1).106	

17.1	Example source code showing loop recognition (part 1).	110
17.2	Example source code showing loop recognition (part 2).	111
17.3	Example source code used as input to loop recognition processor.	111
17.4	Output of input to loop recognition processor.	112
19.1	Example source code showing visualization of control flow graph.	120
19.2	Example source code used as input to build control flow graph.	121
19.3	Control flow graph for function in input code file: inputCode_1.C.	122
20.1	Example input code.	123
20.2	Def-Use graph for example program.	125
21.1	Example source code showing visualization of call graph.	128
21.2	Example source code used as input to build call graph.	129
21.3	Call graph for function in input code file: inputCode_BuildCG.C.	130
22.1	Example source code showing visualization of class hierarchy graph.	131
22.2	Example source code used as input to build class hierarchy graph.	132
22.3	Class hierarchy graph in input code file: inputCode_ClassHierarchyGraph.C.	132
23.1	Example translator (part 1) using database connection to store function names.	134
23.2	Example translator (part 2) using database connection to store function names.	135
23.3	Example source code used as input to database example.	136
23.4	Output from processing input code through database example dataBaseTranslator23.1.	137
24.1	Graph of top level of ROSE directory tree.	139
24.2	Example source code to read an input program and generate an AST graph.	140
24.3	Graph of top level of ROSE directory tree with filtering of subtree.	141
25.1	Example source code showing the output of mangled name. The string represents the code associated with the subtree of the target IR node.	148
25.2	Example source code used as input to program in codes showing debugging techniques shown in this section.	149
25.3	Output of input code using generatingUniqueNamesFromDeclaration.C	150
25.4	Example source code used as input to program in codes showing debugging techniques shown in this section.	151
25.5	Output of input code using generatingUniqueNamesFromDeclaration.C	152
26.1	Example source code showing simple command-line processing within ROSE translator.	154
26.2	Output of input code using cmdlineProcessing.C	154
26.3	Example source code showing simple command-line processing within ROSE translator.	155
26.4	Output of input code using cmdlineProcessing.C	155
27.1	Example source code showing how to tailor the code generation format.	158

27.2	Example source code used as input to program to the tailor the code generation.	159
27.3	Output of input code after changing the format of the generated code.	160
28.1	AST construction and insertion for a variable using the high level interfaces . . .	162
28.2	Example source code to read an input program and add a new variable declaration at the top of each block.	163
28.3	Example source code used as input to the translators adding new variable. . . .	164
28.4	Output of input to the translators adding new variable.	164
28.5	Example translator to add expressions	165
28.6	Example source code used as input	166
28.7	Output of the input	166
28.8	Example source code to add an assignment statement	167
28.9	Example source code used as input	167
28.10	Output of the input	168
28.11	Addition of function to global scope using high level interfaces	169
28.12	Addition of function to global scope using high level interfaces and a scope stack	170
28.13	Example source code shows addition of function to global scope (part 1). . . .	171
28.14	Example source code shows addition of function to global scope (part 2). . . .	172
28.15	Example source code used as input to translator adding new function.	173
28.16	Output of input to translator adding new function.	173
28.17	Example source code to instrument any input program.	175
28.18	Example source code using the high level interfaces	176
28.19	Example source code used as input to instrumenting translator.	177
28.20	Output of input to instrumenting translator.	177
28.21	Example source code instrumenting end of functions	178
28.22	Example input code of the instrumenting translator for end of functions.	178
28.23	Output of instrumenting translator for end of functions.	179
28.24	Example source code shows repackaging of global variables to a struct (part 1). .	180
28.25	Example source code shows repackaging of global variables to a struct (part 2). .	181
28.26	Example source code shows repackaging of global variables to a struct (part 3). .	182
28.27	Example source code shows repackaging of global variables to a struct (part 4). .	183
28.28	Example source code shows repackaging of global variables to a struct (part 5). .	184
28.29	Example source code used as input to translator adding new function.	185
28.30	Output of input to translator adding new function.	185
29.1	Example source code showing how to access comments.	189
29.2	Example source code used as input to collection of comments and CPP directives.	190
29.3	Output from collection of comments and CPP directives on the input source file only.	193
29.4	Output from collection of comments and CPP directives on the input source file and all header files.	194
29.5	Example source code showing how to access comments.	195
29.6	Example source code used as input to collection of comments and CPP directives.	196
29.7	Output from collection of comments and CPP directives on the input source file and all header files.	196
29.8	Example source code showing how automate comments.	197

29.9	Example source code used as input to automate generation of comments.	198
29.10	Output of input code after automating generation of comments.	198
29.11	Example source code showing how automate the introduction of arbitrary text.	199
29.12	Example source code used as input to automate generation of arbitrary text.	199
29.13	Output of input code after automating generation of arbitrary text.	200
30.1	Example source code showing how use Partial Redundancy Elimination (PRE).	201
30.2	Example source code used as input to program to the Partial Redundancy Elimination (PRE) transformation.	202
30.3	Output of input code after Partial Redundancy Elimination (PRE) transformation.	204
31.1	Example source code showing how to instrument using Tau.	206
31.2	Example source code used as input to program to the inlining transformation.	207
31.3	Output of input code after inlining transformations.	208
32.1	inputCode.OutlineLoop.cc: Sample input program. The <code>#pragma</code> directive marks the nested for loop for outlining.	210
32.2	rose_outlined-inputCode.OutlineLoop.cc: The nested for loop of Figure 32.1 has been outlined.	211
32.3	outline.cc: A basic outlining translator, which generates Figure 32.2 from Figure 32.1. This outliner relies on the high-level driver, <code>Outliner::outlineAll()</code> , which scans the AST for outlining pragma directives (<code>#pragma rose_outline</code>) that mark outline targets.	213
32.4	inputCode.OutlineLoop2.c: Sample input program without pragmas.	213
32.5	rose_inputCode.OutlineLoop2.c: The loop at line 12 of Figure 32.12 has been outlined.	214
32.6	rose_inputCode.OutlineLoop2b.c: The 2nd loop within a function named <code>initialize</code> from Figure 32.12 has been outlined.	215
32.7	outlineIfs.cc: A lower-level outlining translator, which calls <code>Outliner::outline()</code> directly on <code>SgStatement</code> nodes. This particular translator outlines all <code>SgIfStmt</code> nodes.	216
32.8	inputCode.Ifcs.cc: Sample input program, without explicit outline targets specified using <code>#pragma rose_outline</code> , as in Figures 32.1 and 32.12.	217
32.9	rose_inputCode.Ifcs.cc: Figure 32.8, after outlining using the translator in Figure 32.7.	219
32.10	outlinePreproc.cc: The basic translator of Figure 32.3, modified to execute the Outliner's preprocessing phase only. In particular, the original call to <code>Outliner::outlineAll()</code> has been replaced by a call to <code>Outliner::preprocessAll()</code>	220
32.11	rose_outlined_pp-inputCode.OutlineLoop.cc: Figure 32.1 after outline preprocessing only, <i>i.e.</i> , specifying <code>-rose:outline:preproc-only</code> as an option to the translator of Figure 32.3.	221
32.12	inputCode.OutlineNonLocalJumps.cc: Sample input program, with an outlining target that contains two non-local jumps (here, <code>break</code> statements).	222

32.13	rose_outlined_pp-inputCode_OutlineNonLocalJumps.cc: The non-local jump example of Figure 32.12 after outliner preprocessing, but before the actual outlining. The non-local jump is handled by an additional flag, <code>EXIT-TAKEN_</code> , which indicates what non-local jump is to be taken.	223
32.14	rose_outlined-inputCode_OutlineNonLocalJumps.cc: Figure 32.12 after outlining.	224
33.1	Example source code showing use of loop optimization mechanisms.	227
33.2	Example source code used as input to loop optimization processor.	228
33.3	Output of loop optimization processor showing matrix multiply optimization (using options: <code>-bk1 -fs0</code>).	229
33.4	Example source code used as input to loop optimization processor.	230
33.5	Output of loop optimization processor showing loop fusion (using options: <code>-fs2</code>).	230
33.6	Detailed example source code showing use of loop optimization mechanisms (loopProcessor.C part 1).	231
33.7	loopProcessor.C source code (Part 2).	232
33.8	Example source code used as input to loopProcessor, show in figure 33.6.	233
33.9	Output of loopProcessor using input from figure 33.8 (using options: <code>-bk1 -fs0</code>).	234
33.10	Example source code used as input to loopProcessor, show in figure 33.6.	235
33.11	Output of loopProcessor using input from figure 33.10 (using options: <code>-bk1 -unroll nvar 16</code>).	236
33.12	Example source code used as input to loopProcessor, show in figure 33.6.	237
33.13	Output of loopProcessor using input from figure 33.12 (using options: <code>-bk1 -fs0 -splitloop -annotation</code>).	238
33.14	Example source code used as input to loopProcessor, show in figure 33.6.	239
33.15	Output of loopProcessor input from figure 33.14 (using options: <code>-fs2 -ic1 -opt 1</code>).	240
34.1	Example source code used as input to loopUnrolling	242
34.2	Output for a unrolling factor which can divide the iteration space evenly	243
34.3	Output for the case when divisibility is unknown at compile-time	244
34.4	Example source code used as input to loopInterchange	245
34.5	Output for loop interchange	245
34.6	Example source code used as input to loopTiling	246
34.7	Output for loop tiling	246
35.1	Example source code shows instrumentation to call a test function from the top of each function body in the application (part 1).	252
35.2	Example source code shows instrumentation to call a test function from the top of each function body in the application (part 2).	253
35.3	Example source code shows instrumentation to call a test function from the top of each function body in the application (part 3).	254
35.4	Example source code used as input to translator adding new function.	255
35.5	Output of input to translator adding new function.	256
36.1	Example source code used as input to program in codes used in this chapter.	257
36.2	Example source code showing how to seed bugs.	259

36.3	Output of input code using <code>seedBugsExample_arrayIndexing.C</code>	260
38.1	Example source code.	271
38.2	Assembly code.	275
38.3	Controlflow graph for example program.	276
38.4	Dataflowflow graph for example program.	277
40.1	Example source code used to generate Dwarf AST for analysis.	287
40.2	Dwarf AST (subset of ROSE binary AST).	289
40.3	Example source code (typical for reading in a binary or source file).	290
40.4	Example source code (typical for reading in a binary or source file).	291
41.1	Example 1: Generated handles for loops: using constructors with or without a specified handle type.	299
41.2	Example 1: Example source code with some loops, used as input.	300
41.3	Example 1: Abstract handles generated for loops.	300
41.4	Example 2: Generated handles from strings representing handle items.	301
41.5	Example 2: Source code with some language constructs.	302
41.6	Example 2: Handles generated from string and their language constructs.	302
41.7	Example 3: A simple data structure used to represent a loop in an arbitrary tool.	303
41.8	Example 3: A test program for simple loops' abstract handles.	304
41.9	Example 3: Output of the test program for simple loops' abstract handles (as strings).	305
42.1	<code>profiled.c</code> (part 1 of 2): Sample input program, profiled using the HPCToolkit.	309
42.2	<code>profiled.c</code> (part 2 of 2): Sample input program, profiled using the HPCToolkit.	310
42.3	XML schema for HPCToolkit data files: This schema, prepended to each of the HPCToolkit-generated XML files, describes the format of the profiling data. This particular schema was generated by HPCToolkit 1.0.4.	311
42.4	<code>PAPI_TOT_CYC.xml</code> : Sample cycle counts observed during profiling, generated from running the HPCToolkit on <code>profiled.c</code> (Figures 42.1–42.2.) These lines would appear after the schema shown in Figure 42.3.	312
42.5	<code>PAPI_FP_OPS.xml</code> : Sample flop counts observed during profiling, generated from running the HPCToolkit on <code>profiled.c</code> (Figures 42.1–42.2.) These lines would appear after the schema shown in Figure 42.3.	313
42.6	<code>attachMetrics.cc</code> : Sample translator to attach HPCToolkit metrics to the AST.	318
42.7	Sample output, when running <code>attachMetrics.cc</code> (Figure 42.6) with the XML inputs in Figures 42.4–42.5. Here, we only show the output sent to standard output (<i>i.e.</i> , <code>cout</code> and not <code>cerr</code>).	319
42.8	Sample PDF showing attributes.	319
43.1	Example source code used as input to program in codes used in this chapter.	322
43.2	Example source code showing how to instrument using <code>Tau</code>	323
43.3	Output of input code using <code>tauInstrumenter.C</code>	324
44.1	Haskell version of identity translator.	325
44.2	Haskell version of constant folding transformation.	327

45.1	Example source showing the shared-memory parallel execution of traversals. . . .	332
45.2	Output of input file to the shared-memory parallel traversals. Output may be garbled depending on the multi-threaded behavior of the underlying I/O libraries.	333
46.1	Example source demonstrating the use of the distributed-memory parallel analysis framework.	337
46.2	Example output of a distributed-memory analysis running on four processors. . .	338
48.1	Example source code showing reduction recognition.	341
48.2	Example source code used as input to loop reduction recognition processor. . . .	342
48.3	Output of input to reduction recognition processor.	342

Chapter 1

Introduction

1.1 Why you should be interested in ROSE

ROSE is a tool for building source-to-source translators. You should be interested in ROSE if you want to understand or improve any aspect of your software. ROSE makes it easy to build tools that read and operate on source code from large scale applications (millions of lines). Whole projects may be analyzed and even optimized using tools built using ROSE.

To get started immediately consult the ROSE User Manual, chapter *Getting Started* for details).

1.2 Problems that ROSE can address

ROSE is a mechanism to build source-to-source analysis or optimization tools that operate directly on the source code of large scale applications. Example tools that *have* been built include:

- Array class abstraction optimizer,
- Source-to-source instrumenter,
- Loop analyzer,
- Symbolic complexity analyzer,
- Code coverage tools,
- Inliner and outliner,
- OpenMP translator,
- and many more.

Example tools that *can* be built include:

- Custom optimization tools,

- Custom documentation generators,
- Custom analysis tools,
- Code pattern recognition tools,
- Security analysis tools,
- and many more.

1.3 Examples in this ROSE Tutorial

This tutorial lays out a set of progressively complex example programs (located in `<ROSE_SOURCE>/tutorial/*`) that serve as a tutorial for the use of ROSE. Translators built using ROSE can either just analyze (and output results) or compile the input programs just like a compiler (generating object files or executables). Many of the examples in this tutorial just do simple analysis of the input source code, and a few show the full compilation of the input source code. Where the translators generate either object files or executables, the vendor's compiler is used to compile the final ROSE-generated code. Within ROSE, the call to generate source code from the AST and call the vendor's compiler is referred to as the *backend processing*. The specification of the vendor's compiler as a backend is done within the configuration step within ROSE (see options for **configure** in the ROSE User Manual).

Within the example programs below, the user can provide alternative input programs for more complex evaluation of the tutorial examples and ROSE. The end of the chapter, section 1.6, shows the makefiles required to compile the tutorial programs using an installed version of ROSE (compiled using **make install**). This **example_makefile** is run as part of the testing using the **make installcheck** rule.

Chapters are organized in topics including simple ROSE AST visualization, dealing with complex data types, program analysis, program transformation and optimization, correctness checking, binary support, interacting with other tools, and parallelism. We hope readers can easily find the information they want.

Specific chapters in this tutorial include:

- Introduction
 1. Introduction (*this chapter*)
 2. Problems that ROSE can address
 3. Getting Started

This chapter covers where to find ROSE documentation and how to install ROSE.
 4. Example Makefiles demonstrating the command lines to compile and link the example translators in this tutorial are found in `<ROSE_Compile_Tree>/tutorial/exampleMakefile`.
- Working with the ROSE AST:
 1. Identity Translator

This example translator reads a C or C++ application, builds the AST internally, generates source code from the AST (unparsing), and calls the backend vendor compiler

We should constantly
update this

to compile the generated C or C++ application code. Thus the translator acts like and can be used to replace any compiler since it takes in source code and outputs an object code (or executable). This example also shows that the output generated from and ROSE translator is a close reproduction of the input; preserving all comments, preprocessor control structure, and most formatting.

2. Scopes of Declarations (scopeInformation.C)

This example shows the scopes represented by different IR nodes in the AST.

3. AST Graph Generator

This translator reads a C or C++ application code and builds the AST, internally. The translator does not regenerate code from the AST and so does not call the backend vendor's compiler. This shows how simple it could be to build source code analysis tools; the code calls an internal ROSE function to generate a dot graph of the AST, the makefile has the details of converting the dot graph into a postscript file (also shown).

4. AST PDF Generator

This translator reads an C or C++ application code builds the AST internally. The translator does not regenerate code from the AST and so does not call the backend vendor's compiler. This shows how simple it could be to build source code analysis tools, the code calls an internal ROSE function to generate a pdf file with bookmarks representing the AST. The pdf file show as output is in this case a previously generated figure of a screen shot obtained by viewing the output pdf file using **acroread**.

5. Introduction to AST Traversals and Attributes

This collection of examples show the use of the simple visitor pattern for the traversal of the AST within ROSE. The simple visitor pattern permits operations to be programmed which will be invoked on different nodes within the AST. To handle communication of context information down into the AST and permit communication of analysis information up the AST, we have provided inherited and synthesized attributes (respectively). Note that an AST is most often represented as a tree with extra edges and with shared IR nodes that make the full graph (representing all edges) not a tree. We present two styles of traversal, one over the tree representing the AST (which excludes some types of IR nodes) and one over the full AST with all extra nodes and shared nodes. Extra nodes are nodes such as SgType and SgSymbol IR nodes.

(a) AST traversals

These traversals visit each node of the tree embedded within the AST (excluding shared SgType and SgSymbol IR nodes). These traversals visit the IR nodes in an order dependent upon the structure of the AST (the source code from which the AST is built).

i. Classic Object-Oriented Visitor Patterns

This example, `classicObjectOrientedVisitorPatternMemoryPoolTraversal.C`, show the use of a classic visitor patterns. At the moment this example uses the AST's memory pools as a basis but it is identical to a future traversal. The ROSE visitor Pattern (below) is generally more useful. The classic visitor pattern traversals are provided for completeness.

- ii. Visitor Traversal (`visitorTraversal.C`)
Conventional visitor patterns without no attributes. This pattern can explicitly access global variables to provide the effect of accumulator attributes (using static data members we later show the handling of accumulator attributes).
 - iii. Inherited Attributes (`inheritedAttributeTraversal.C`)
Inherited attributes are used to communicate the context of any location within the AST in terms of other parent AST nodes.
 - iv. Synthesized Attributes (`synthesizedAttributeTraversal.C`)
Synthesized attributes are used to pass analysis results from the leaves of the AST to the parents (all the way to the root of the AST if required).
 - v. Accumulator Attributes (`accumulatorAttributeTraversal.C`)
Accumulator attributes permit the interaction of data within inherited attributes with data in synthesized attributes. In our example program we will show the use of accumulator attributes implemented as static data members. Accumulator attributes are a fancy name for what is essentially global variables (or equivalently a data structure passed by reference to all the IR nodes in the AST).
 - vi. Inherited and Synthesized Attributes (`inheritedAndSynthesizedAttributeTraversal.C`)
The combination of using inherited and synthesized attributes permits more complex analysis and is often required to compute analysis results on the AST within a specific context (e.g. number of loop nests of specific depth).
 - vii. Persistent Attributes (`persistantAttributes.C`)
Persistent attributes may be added the AST for access to stored results for later traversals of the AST. The user controls the lifetime of these persistent attributes.
 - viii. Nested traversals
Complex operations upon the AST can require many subordinate operations. Such subordinate operations can be accommodated using nested traversals. All traversals can operate on any subtree of the AST, and may even be nested arbitrarily. Interestingly, ROSE traversals may also be applied recursively (though care should be take using recursive traversals using accumulator attributes to avoid *over* accumulation).
- (b) Memory Pool traversals
- These traversals visit all IR nodes (including shared IR nodes such as `SgTypes` and `SgSymbols`). By design this traversal can visit ALL IR nodes without the worry of getting into cycles. These traversals are mostly useful for building specialized tools that operate on the AST.
- i. Visit Traversal on Memory Pools
This is a similar traversal as to the Visitor Traversal over the tree in the AST.
 - ii. Classic Object-Oriented Visitor Pattern on Memory Pools
This is similar to the Classic Object-Oriented Visitor Pattern on the AST.
 - iii. IR node Type Traversal on Memory Pools
This is a specialized traversal which visits each type of IR node, but one one

of each type of IR nodes. This specialized traversal is useful for building tools that call static member functions on each type or IR node. A number of memory based tools for ROSE are built using this traversal.

6. AST Query Library

This example translator shows the use of the AST query library to generate a list of function declarations for any input program (and output the list of function names). It can be trivially modified to return a list of any IR node type (C or C++ language construct).

7. Symbol Table Handling (symbolTableHandling.C)

This example shows how to use the symbol tables held within the AST for each scope.

8. AST File I/O (astFileIO_GenerateBinaryFile.C)

This example demonstrates the file I/O for AST. This is part of ROSE support for whole program analysis.

9. Debugging Tips

There are numerous methods ROSE provides to help debug the development of specialized source-to-source translators. This section shows some of the techniques for getting information from IR nodes and displaying it. Show how to use the PDF generator for AST's. This section may contain several subsections.

- (a) Generating the code representing any IR node
- (b) Displaying the source code position of any IR node

• Complex Types

1. Getting the type parameters in function declaration (functionParameterTypes.C)

This example translator builds a list to record the types used in each function. It shows an example of the sort of type information present within the AST. ROSE specifically maintains all type information.

2. Resolving overloaded functions (resolvingOverloadedFunctions.C – C++ specific)

The AST has all type information pre-evaluated, particularly important for C++ applications where type resolution is required for determining function invocation. This example translator builds a list of functions called within each function, showing that overloaded function are fully resolved within the AST. Thus the user is not required to compute the type resolution required to identify which over loaded functions are called.

3. Getting template parameters to a templated class (templateParameters.C – C++ specific)

All template information is saved within the AST. Templated classes and functions are separately instantiated as specializations, as such they can be transformed separately depending upon their template values. This example code shows the template types used the instantiate a specific templated class.

• Program Analysis

1. Recognizing loops within applications (loopRecognition.C)

This example program shows the use of inherited and synthesized attributes form

a list of loop nests and report their depth. The inherited attributes are required to record when the traversal is within outer loop and the synthesized attributes are required to pass the list of loop nests back up of the AST.

2. Generating a CFG (buildCFG.C)
This example shows the generation of a control flow graph within ROSE. The example is intended to be simple. Many other graphs can be built, we need to show them as well.
3. Generating a CG (buildCG.C)
This example shows the generation of a call graph within ROSE.
4. Generating a CH (classHierarchyGraph.C)
This example shows the generation of a class hierarchy graph within ROSE.
5. Building custom graphs of program information
The mechanisms used internally to build different graphs of program data is also made externally available. This section shows how new graphs of program information can be built or existing graphs customized.
6. Database Support (dataBaseUsage.C)
This example shows how to use the optional (see `configure --help`) SQLite database to hold persistent program analysis results across the compilation of multiple files. This mechanism may become less critical as the only mechanism to support global analysis once we can support whole program analysis more generally within ROSE.

- Program Transformations and Optimizations

1. Generating Unique Names for Declarations (generatingUniqueNamesFromDeclaration.C)
A recurring issue in the development of many tools and program analysis is the representation of unique strings from language constructs (functions, variable declarations, etc.). This example demonstrated support in ROSE for the generation of unique names. Names are unique across different ROSE tools and compilation of different files.
2. Command-line processing
ROSE includes mechanism to simplify the processing of command-line arguments so that translators using ROSE can trivially replace compilers within makefiles. This example shows some of the many command-line handling options within ROSE and the ways in which customized options may be added.
 - (a) Recognizing custom command-line options
 - (b) Adding options to internal ROSE command-line driven mechanisms
3. Tailoring the code generation format: how to indent the generated source code and others.
4. AST construction: how to build AST pieces from scratch and attach them to the existing AST tree.
 - (a) Adding a variable declaration (addingVariableDeclaration.C)
Here we show how to add a variable declaration to the input application. Perhaps

we should show this in two ways to make it clear. This is a particularly simple use of the AST IR nodes to build an AST fragment and add it to the application's AST.

- (b) Adding a function (addingFunctionDeclaration.C)
This example program shows the addition of a new function to the global scope. This example is a bit more involved than the previous example.
 - (c) Simple Instrumentor Translator (simpleInstrumentor.C)
This example modifies an input application to place new code at the top and bottom of each block. The output is show with the instrumentation in place in the generated code.
 - (d) Other examples for creating expressions, structures and so on.
5. Handling source comments, preprocessor directives.
 6. Calling the inliner (inlinerExample.C)
This example shows the use of the inliner mechanism within ROSE. The function to be inlined is specified and the transformation upon the AST is done to inline the function where it is called and clean up the resulting code.
 7. Calling the outliner (outlinerExample.C)
This example shows the use of the outliner mechanism within ROSE. A segment of code is selected and a function is generated to hold the resulting code. Any required variables (including global variables) are passed through the generated function's interface. The outliner is a useful part of the empirical optimization mechanisms being developed within ROSE.
 8. Call loop optimizer on set of loops (loopOptimization.C)
This example program shows the optimization of a loop in C. This section contains several subsections each of which shows different sorts of optimizations. There are a large number of loop optimizations only two are shown here, we need to add more.
 - (a) Optimization of Matrix Multiply
 - (b) Loop Fusion Optimizations
 9. Parameterized code translation: How to use command line options and abstract handles to have the translations you want, the order you want, and the behaviors you want.
 10. Program slicing (programSlicingExample.C)
This example shows the interface to the program slicing mechanism within ROSE. Program slicing has been implemented to two ways within ROSE.

FIXME: Does this tutorial still exist?

- Correctness Checking
 1. Code Coverage Analysis (codeCoverage.C)
Code coverage is a useful tool by itself, but is particularly useful when combined with automated detection of bugs in programs. This is part of work with IBM, Haifa.
 2. Bug seeding: how to purposely inject bugs into source code.
- Binary Support

1. Instruction semantics
 2. Binary Analysis
 3. Binary construction
 4. DWarf debug support
- Interacting with Other Tools
 1. Abstract handles: uniform ways of specifying language constructs.
 2. ROSE-HPCT interface: How to annotate AST with performance metrics generated by third-party performance tools.
 3. Tau Performance Analysis Instrumentation (tauInstrumenter.C)
 Tau currently uses an automate mechanism that modified the source code text file. This example shows the modification of the AST and the generation of the correctly instrumented files (which can otherwise be a problem when macros are used). This is part of collaborations with the Tau project.
 4. The Haskell interface: interacting with a function programming language.
 - Parallelism
 1. Shared-memory parallel traversals
 2. Distributed-memory parallel traversals
 3. Parallel checker
 4. Reduction variable recognition

Other examples included come specifically from external collaborations and are more practically oriented. Each is useful as an example because each solves a specific technical problem. More of these will be included over time.

*The following tutorials
no longer exist?*

1. Fortran promotion of constants to double precision (typeTransformation.C)
 Fortran constants are by default single precision, and must be modified to be double precision. This is a common problem in older Fortran applications. This is part of collaborations with LANL to eventually automatically update/modify older Fortran applications.
2. Automated Runtime Library Support (charmSupport.C)
 Getting research runtime libraries into use within large scale applications requires automate mechanism to make minor changes to large amounts of code. This is part of collaborations with the Charm++ team (UIUC).
 - (a) Shared Threaded Variable Detection Instrumentation (interveneAtVariables.C)
 Instrumentation support for variables, required to support detection of threaded bugs in applications.
 - (b) Automated Modification of Function Parameters (changeFunction.C)
 This example program addresses a common problem where an applications function must be modified to include additional information. In this case each function in a threaded library is modified to include additional information to a corresponding wrapper library which instruments the library's use.

*Add make installcheck
e.am to build example
ors using the installed
libraries.*

1.4 ROSE Documentation and Where To Find It

There are three forms of documentation for ROSE, and also a ROSE web Page and email lists. For more detailed information on getting started, see the ROSE User Manual, chapter *Getting Started* for more details).

1. ROSE User Manual

The User Manual presents how to get started with ROSE and documents features of the ROSE infrastructure. The User Manual is found in ROSE/docs/Rose directory, or at:
ROSE User Manual (postscript version, relative link)

2. ROSE Tutorial

The ROSE Tutorial presents a collection of examples of how to use ROSE (found in the ROSE/tutorial directory). The ROSE Tutorial documentation is found in ROSE/docs/Rose/tutorial directory. The tutorial documentation is built in the following steps:

- (a) actual source code for each example translator in the ROSE/tutorial directory is included into the tutorial documentation
- (b) each example is compiled
- (c) inputs to the examples are taken from the ROSE/tutorial directory
- (d) output generated from running each example is placed into the tutorial documentation

Thus the ROSE/tutorial directory contains the exact examples in the tutorial and each example may be modified (changing either the example translators or the inputs to the examples). The ROSE Tutorial can also be found in the ROSE/docs/Rose/tutorial directory (the LaTeX document; ps or pdf file)
: ROSE Tutorial (postscript version, relative link),

3. ROSE HTML Reference: Intermediate Representation (IR) documentation

This web documentation presents the detail interfaces for each IR nodes (documentation generated by Doxygen). The HTML IR documentation is found in ROSE/docs/Rose directory (available as html only):
ROSE HTML Reference (relative link)

4. ROSE Web Page

The ROSE web pages are located at: <http://www.rosecompiler.org>

5. ROSE Email List

The ROSE project maintains an external mailing list (see information at: www.roseCompiler.org and click on the **Mailing Lists** link for how to join).

1.5 Using the Tutorial

First install ROSE (see ROSE User Manual, chapter *Getting Started* for details). Within the ROSE distribution at the top level is the `tutorial` directory. All of the examples in this documentation are represented there with Makefiles and sample input codes to the example translators.

1.6 Required Makefile for Tutorial Examples

*The exampleMakefile
be modified to include
rt for compiling all of
the tutorial examples.*

This section shows an example makefile 1.1 required for the compilation of many of the tutorial example programs using the installed libraries (assumed to be generated from `make install`). The build process can be tested by running `make installcheck` from within the ROSE compile tree. This `makefile` can be found in the compile tree (*not the source tree*) for ROSE in the `tutorial` directory.

```

1  # Example Makefile for ROSE users
2  # This makefile is provided as an example of how to use ROSE when ROSE is
3  # installed (using "make install"). This makefile is tested as part of the
4  # "make distcheck" rule (run as part of tests before any SVN checkin).
5  # The test of this makefile can also be run by using the "make installcheck"
6  # rule (run as part of "make distcheck").
7
8
9  # Location of include directory after "make install"
10 ROSE_INCLUDE_DIR = /home/liao6/daily-test-rose/20091101_120001/install/include
11
12 # Location of Boost include directory
13 BOOST_CPPFLAGS = -pthread -I/home/liao6/opt/boost_1_35_0/include
14
15 # Location of Dwarf include and lib (if ROSE is configured to use Dwarf)
16 ROSE_DWARF_INCLUDES =
17 ROSE_DWARF_LIBS_WITH_PATH =
18
19 # Location of library directory after "make install"
20 ROSE_LIB_DIR = /home/liao6/daily-test-rose/20091101_120001/install/lib
21
22 CC = gcc
23 CXX = g++
24 CPPFLAGS = -I/usr/apps/java/jdk1.6.0_11/include -I/usr/apps/java/jdk1.6.0_11/include/linux
25 #CXXCPPFLAGS = @CXXCPPFLAGS@
26 CXXFLAGS = -g -Wall
27 LDFLAGS =
28
29 ROSE_LIBS = $(ROSE_LIB_DIR)/librose.la
30
31 # Location of source code
32 ROSE_SOURCE_DIR = \
33     /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial
34
35 executableFiles = identityTranslator ASTGraphGenerator \
36     visitorTraversal inheritedAttributeTraversal \
37     synthesizedAttributeTraversal \
38     inheritedAndSynthesizedAttributeTraversal \
39     accumulatorAttributeTraversal persistentAttributes \
40     queryLibraryExample nestedTraversal \
41     loopRecognition \
42     typeInfoFromFunctionParameters \
43     resolveOverloadedFunction templateParameter \
44     instrumentationExample addVariableDeclaration \
45     addFunctionDeclaration loopOptimization \
46     buildCFG debuggingIRnodeToString \
47     debuggingSourceCodePositionInformation \
48     commandlineProcessing \
49     loopNestingInfoProcessing
50
51 # Default make rule to use
52 all: $(executableFiles)
53     @if [ x${ROSE_IN_BUILD_TREE:+present} = xpresent ]; then echo "ROSE_IN_BUILD_TREE should not be set" >&2; exit 1; fi
54
55 # Example of how to use ROSE (linking to dynamic library, which is must faster
56 # and smaller than linking to static libraries). Dynamic linking requires the
57 # use of the "-L$(ROSE_LIB_DIR) -Wl,-rpath" syntax if the LD_LIBRARY_PATH is not
58 # modified to use ROSE_LIB_DIR. We provide two example of this; one using only
59 # the "-lrose -ldbg" libraries, and one using the many separate ROSE libraries.
60 $(executableFiles):
61 #     g++ -I$(ROSE_INCLUDE_DIR) -o $@ $(ROSE_SOURCE_DIR)/%.C -L$(ROSE_LIB_DIR) -Wl,-rpath $(ROSE_LIB_DIR) $(ROSE_LIBS)
62 #     g++ -I$(ROSE_INCLUDE_DIR) -o $@ $(ROSE_SOURCE_DIR)/%.C $(LIBS_WITH_RPATH) $(ROSE_LIBS)
63 #     /bin/sh ../libtool --mode=link $(CXX) $(CPPFLAGS) $(CXXFLAGS) $(LDFLAGS) -I$(ROSE_INCLUDE_DIR) $(BOOST_CPPFLAGS) -o $@ $(ROSE_SOURCE_DIR)/%.C
64 #     /bin/sh ../libtool --mode=link $(CXX) $(CPPFLAGS) $(CXXFLAGS) $(LDFLAGS) -I$(ROSE_INCLUDE_DIR) $(BOOST_CPPFLAGS) $(ROSE_DWARF_INCLUDES) -o $@ $
65
66

```

Figure 1.1: Example Makefile showing how to use an installed version of ROSE (generated by `make install`).

Part I

Working with the ROSE AST

Get familiar with the ROSE AST is the basis for any advanced usage of ROSE. This part of tutorial collects examples for AST visualization, traversal, query, and debugging.

Chapter 2

Identity Translator

Using the input code in Figure 2.2 we now show a translator which builds the AST, generates the source code from the AST, and compiles the generated code using the backend vendor compiler¹. Figure 2.1 shows the source code for this translator, the construction of the AST is identical to the previous code, but we make an explicit call to the ROSE `backend()` function.

```
// Example ROSE Translator: used for testing ROSE infrastructure
#include "rose.h"

int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc,argv);

    // Run internal consistency tests on AST
    AstTests::runAllTests(project);

    // Insert your own manipulation of the AST here...

    // Generate source code from AST and call the vendor's compiler
    return backend(project);
}
```

Figure 2.1: Source code for translator to read an input program and generate an object code (with no translation).

Figure 2.3 shows the generated code from the processing of the `identityTranslator` build using ROSE and using the input file shown in figure 2.2. This example also shows that the output generated from and ROSE translator is a close reproduction of the input; preserving all comments, preprocessor control structure, and most formatting. Note that all macros are expanded in the generated code.

In this trivial case of a program in a single file, the translator compiles the application to build an executable (since `-c` was not specified on the command-line).

¹ Note: that the backend vendor compiler is selected at configuration time.

```
// Example input file for ROSE tutorial
#include <iostream>

typedef float Real;

// Main function
int main()
{
    int x = 0;
    bool value = false;

    // for loop
    for (int i=0; i < 4; i++)
    {
        int x;
    }

    return 0;
}
```

Figure 2.2: Example source code used as input to identity translator.

```
// Example input file for ROSE tutorial
#include <iostream>
typedef float Real;
// Main function

int main()
{
    int x = 0;
    bool value = false;
    // for loop
    for (int i = 0; i < 4; i++) {
        int x;
    }
    return 0;
}
```

Figure 2.3: Generated code, from ROSE identity translator, sent to the backend (vendor) compiler.

Chapter 3

Scopes of Declarations

The scope of a IR nodes may be either stored explicitly in the IR node or obtained through computation through it's parent information in the AST. Figure X shows an example where the variable definition for a variable is the scope of namespace X. The declaration for variable a is in the namespace X. In a more common way the function foo is a member function of B which a declaration appearing in class B, but with a function definition in global scope.

```
namespace X{
    extern int a;
}
int X::a = 0;
class B
{
    void foo();
};
void B::foo() {}
```

In C++, using name qualification the scope of a declaration can be independent of it structural location in the AST. The `get_parent()` member function (available on most IR nodes) communicates the structural information of the original source code (also represented in the AST). The scope information must at times be stored explicitly when it can not be interpreted structurally.

The example in this chapter show how to find the scope of each C++ construct were it make sense. Note that `SgExpression` IR nodes can take there scope from that of the statement where they are found. `SgStatement` and `SgInitializedName` IR nodes are the interesting IR nodes from the point of scope.

The `SgInitializedName` and all `SgStatement` IR nodes have a member function `get_scope()` which returns the scope of the associated IR nodes. The example code in this chapter traverses the AST and reports the scope of any `SgInitializedName` and all `SgStatement` IR nodes. It is intended to provide so simple intuition about what the scope can be expected to be in an application. The example code is also useful as a simple means of exploring the scopes of any other input application.

3.1 Input For Examples Showing Scope Information

Figure 3.1 shows the input example code form this tutorial example.

```
int xyz;  
  
void foo (int x)  
{  
    int y;  
    for (int i=0; i < 10; i++)  
    {  
        int z;  
        z = 42;  
    }  
}
```

Figure 3.1: Example source code used as input to program in codes used in this chapter.

3.2 Generating the code representing any IR node

The following code traverses each IR node and for a `SgInitializedName` of `SgStatement` output the scope information. The input code is shown in figure 3.1, the output of this code is shown in figure 3.3.

```

// This example shows the scope of each statement and name (variable names, base class names, etc.).
#include "rose.h"

class visitorTraversal : public AstSimpleProcessing
{
public:
    virtual void visit(SgNode* n);
};

void visitorTraversal::visit(SgNode* n)
{
    // There are three types of IR nodes that can be queried for scope:
    // - SgStatement, and
    // - SgInitializedName
    SgStatement* statement = isSgStatement(n);
    if (statement != NULL)
    {
        SgScopeStatement* scope = statement->get_scope();
        ROSE_ASSERT(scope != NULL);
        printf ("SgStatement = %12p = %30s has scope = %12p = %s (total number = %d) \n",
            statement, statement->class_name().c_str(),
            scope, scope->class_name().c_str(), (int)scope->numberOfNodes());
    }

    SgInitializedName* initializedName = isSgInitializedName(n);
    if (initializedName != NULL)
    {
        SgScopeStatement* scope = initializedName->get_scope();
        ROSE_ASSERT(scope != NULL);
        printf ("SgInitializedName = %12p = %30s has scope = %12p = %s (total number = %d) \n",
            initializedName, initializedName->get_name().str(),
            scope, scope->class_name().c_str(), (int)scope->numberOfNodes());
    }
}

int
main ( int argc, char* argv[] )
{
    SgProject* project = frontend(argc, argv);
    ROSE_ASSERT (project != NULL);

    // Build the traversal object
    visitorTraversal exampleTraversal;

    // Call the traversal starting at the project node of the AST
    exampleTraversal.traverseInputFiles(project, preorder);

    printf ("Number of scopes (SgScopeStatement) = %d \n", (int)SgScopeStatement::numberOfNodes());
    printf ("Number of scopes (SgBasicBlock) = %d \n", (int)SgBasicBlock::numberOfNodes());

#ifdef 0
    printf ("\n\n");
    printf ("Now output all the symbols in each symbol table \n");
    SageInterface::outputLocalSymbolTables(project);
    printf ("\n\n");
#endif

    return 0;
}

```

Figure 3.2: Example source code showing how to get scope information for each IR node.

```

SgStatement      = 0x8f35bc0 = SgGlobal has scope =
0x8f35bc0 = SgGlobal (total number = 0)
SgStatement      = 0xb7df6008 = SgVariableDeclaration has scope =
0x8f35bc0 = SgGlobal (total number = 0)
SgInitializedName = 0xb7e75b00 = xyz has scope =
0x8f35bc0 = SgGlobal (total number = 0)
SgStatement      = 0xb7ee5a64 = SgFunctionDeclaration has scope =
0x8f35bc0 = SgGlobal (total number = 0)
SgStatement      = 0xb7e9a58c = SgFunctionParameterList has scope =
0x8f35bc0 = SgGlobal (total number = 0)
SgInitializedName = 0xb7e75b88 = x has scope =
0xb7d8b008 = SgFunctionDefinition (total number = 0)
SgStatement      = 0xb7d8b008 = SgFunctionDefinition has scope =
0x8f35bc0 = SgGlobal (total number = 0)
SgStatement      = 0x9078918 = SgBasicBlock has scope =
0xb7d8b008 = SgFunctionDefinition (total number = 0)
SgStatement      = 0xb7df6154 = SgVariableDeclaration has scope =
0x9078918 = SgBasicBlock (total number = 0)
SgInitializedName = 0xb7e75c10 = y has scope =
0x9078918 = SgBasicBlock (total number = 0)
SgStatement      = 0xb7d69008 = SgForStatement has scope =
0x9078918 = SgBasicBlock (total number = 0)
SgStatement      = 0x9098090 = SgForInitStatement has scope =
0xb7d69008 = SgForStatement (total number = 0)
SgStatement      = 0xb7df62a0 = SgVariableDeclaration has scope =
0xb7d69008 = SgForStatement (total number = 0)
SgInitializedName = 0xb7e75c98 = i has scope =
0xb7d69008 = SgForStatement (total number = 0)
SgStatement      = 0x90d5c20 = SgExprStatement has scope =
0xb7d69008 = SgForStatement (total number = 0)
SgStatement      = 0x9078998 = SgBasicBlock has scope =
0xb7d69008 = SgForStatement (total number = 0)
SgStatement      = 0xb7df63ec = SgVariableDeclaration has scope =
0x9078998 = SgBasicBlock (total number = 0)
SgInitializedName = 0xb7e75d20 = z has scope =
0x9078998 = SgBasicBlock (total number = 0)
SgStatement      = 0x90d5c4c = SgExprStatement has scope =
0x9078998 = SgBasicBlock (total number = 0)
Number of scopes (SgScopeStatement) = 0
Number of scopes (SgBasicBlock) = 2

```

Figure 3.3: Output of input code using scopeInformation.C

Chapter 4

AST Graph Generator

What To Learn From This Example This example shows how to generate and visualize the AST from any input program. Each node of the graph in figure 4.3 shows a node of the Intermediate Representation (IR). Each edge shows the connection of the IR nodes in memory. The generated graph shows the connection of different IR nodes to form the AST. The generation of such graphs is appropriate for small input programs, chapter ?? shows a mechanism using PDF files that is more appropriate to larger programs (e.g. 100K lines of code). More information about generation of specialized AST graphs can be found in 6 and custom graph generation in 24.

```
// Example ROSE Translator: used within ROSE/tutorial
#include "rose.h"

int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend( argc, argv );

    generateDOT ( *project );
    return 0;
}
```

Figure 4.1: Example source code to read an input program and generate an AST graph.

The program in figure 4.1 calls an internal ROSE function that traverses the AST and generates an ASCII file in `dot` format. Figure 4.2 shows an input code which is processed to generate a graph of the AST, generating a `dot` file. The `dot` file is then processed using `dot` to generate a postscript file 4.3 (within the `Makefile`). Note that a similar utility program already exists within `ROSE/exampleTranslators` (and includes a utility to output an alternative PDF representation (suitable for larger ASTs) as well). Figure 4.3 (`../../tutorial/test.ps`) can be found in the compile tree (in the tutorial directory) and viewed directly using `ghostview` or any postscript viewer to see more detail.

Figure 4.3 displays the individual C++ nodes in ROSE's intermediate representation (IR). Each circle represents a single IR node, the name of the C++ construct appears in the center of

```
// Templated class declaration used in template parameter example code
template <typename T>
class templateClass
{
    public:
        int x;

        void foo(int);
        void foo(double);
};

// Overloaded functions for testing overloaded function resolution
void foo(int);
void foo(double)
{
    int x = 1;
    int y;

    // Added to allow non-trivial CFG
    if (x)
        y = 2;
    else
        y = 3;
}
```

Figure 4.2: Example source code used as input to generate the AST graph.

the circle, with the edge numbers of the traversal on top and the number of child nodes appearing below. Internal processing to build the graph generates unique values for each IR node, a pointer address, which is displayed at the bottom of each circle. The IR nodes are connected to form a tree, and abstract syntax tree (AST). Each IR node is a C++ class, see SAGE III reference for details, the edges represent the values of data members in the class (pointers which connect the IR nodes to other IR nodes). The edges are labeled with the names of the data members in the classes representing the IR nodes.

*Use this first example
to explain the use of
header files (config.h and
and the code to build the
SgProject object.*




Figure 4.3: AST representing the source code file: `inputCode_ASTGraphGenerator.C`.

Chapter 5

AST Whole Graph Generator

What To Learn From This Example This example shows how to generate and visualize the AST from any input program. This view of the AST includes all additional IR nodes and edges that form attributes to the AST, as a result this graph is not a tree. These graphs are more complex but show significantly more detail about the AST and its additional edges and attributes. Each node of the graph in figure ?? shows a node of the Intermediate Representation (IR). Each edge shows the connection of the IR nodes in memory. The generated graph shows the connection of different IR nodes to form the AST and its additional attributes (e.g types, modifiers, etc). The generation of such graphs is appropriate for very small input programs, chapter ?? shows a mechanism using PDF files that is more appropriate to larger programs (e.g. 100K lines of code). More information about generation of specialized AST graphs can be found in 6 and custom graph generation in 24.

*Viewing these dot files is best done using: **zgrviewer** at <http://zvtn.sourceforge.net/zgrviewer.html>.* This tool permits zooming in and out and viewing isolated parts of even very large graphs. **Zgrviewer** permits a more natural way of understanding the AST and its additional IR nodes than the pdf file displayed in these pages. The few lines of code used to generate the graphs can be used on any input code to better understand how the AST represents different languages and their constructs.

```
// Example ROSE Translator: used within ROSE/tutorial
#include "rose.h"

int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc,argv);

    // To protect against building graphs that are too large an option is
    // provided to bound the number of IR nodes for which a graph will be
    // generated. The layout of larger graphs is prohibitively expensive.
    const int MAX_NUMBER_OF_IR_NODES = 2000;
    generateAstGraph(project,MAX_NUMBER_OF_IR_NODES);
}
```

Figure 5.1: Example source code to read an input program and generate a *whole* AST graph.

The program in figure 5.1 calls an internal ROSE function that traverses the AST and generates an ASCII file in **dot** format. Figure ?? shows an tiny input code which is processed to generate a graph of the AST with its attributes, generating a **dot** file. The **dot** file is then processed using **dot** to generate a pdf file 5.3 (within the **Makefile**). Note that a similar utility program already exists within ROSE/exampleTranslators (and includes a utility to output an alternative PDF representation (suitable for larger ASTs) as well). Figure ?? (../../tutorial/test.ps) can be found in the compile tree (in the tutorial directory) and viewed directly using any pdf or dot viewer to see more detail (**zgrviewer** working with the dot file directly is strongly advised).

Note that AST's can get very large, and that the additional IR nodes required to represent the types, modifiers, etc, can generate visually complex graphs. ROSE contains the mechanisms to traverse these graphs and do analysis on them. In one case the number of IR nodes exceeded 27 million, an analysis was done through a traversal of the graph in 10 seconds on a desktop x86 machine (the memory requirements were 6 Gig). ROSE organizes the IR in ways that permit analysis of programs that can represent rather large ASTs.

```
// Trivial function used to generate graph of AST
// with all types and additional edges shown.
// Graphs of this sort are large, and can be
// viewed using "zgrviewer" for dot files.
int foo()
{
    return 0;
}
```

Figure 5.2: Example tiny source code used as input to generate the small AST graph with attributes.

Figure 5.3 displays the individual C++ nodes in ROSE's intermediate representation (IR). Colors and shapes are used to represent different types or IR nodes. Although only visible using **zgrviewer** the name of the C++ construct appears in the center of each node in the graph, with the names of the data members in each IR node as edge labels. Unique pointer values are included and printed next to the IR node name. These graphs are the single best way to develop an intuitive understanding how language constructs are organized in the AST. In these graphs, the color yellow is used for types (SgType IR nodes), the color green is used for expressions (SgExpression IR nodes), and statements are a number of different colors and shapes to make them more recognizable.

Figure 5.5 shows a graph similar to the previous graph but larger and more complex because it is from a larger code. Larger graphs of this sort are still very useful in understanding how more significant language constructs are organized and reference each other in the AST. Tools such as **zgrviewer** are essential to reviewing and understanding these graphs.




Figure 5.3: AST representing the tiny source code file: inputCode.wholeAST_1.C.

```
// Larger function used to generate graph of AST
// with all types and additional edges shown.
// Graphs of this sort are large, and can be
// viewed using "zgrviewer" for dot files.
int foo ( int x );

int globalVar = 42;

void foobar_A ()
{
    int a = 4;
    int b = a + 2;
    int c = b * globalVar;
    int x;
    x = foo ( c );
    int y = x + 2;
    int z = globalVar * y;
}

void foobar_B ()
{
    int p;
    int i = 4;
    int k = globalVar * (i+2);
    p = foo ( k );
    int r = (p+2) * globalVar;
}
```

Figure 5.4: Example source code used as input to generate a larger AST graph with attributes.




Figure 5.5: AST representing the small source code file: `inputCode_wholeAST_2.C`.

Chapter 6

General AST Graph Generation

What To Learn From This Example This example shows a maximally complete representation of the AST (often in more detail that is useful).

Where chapter 4 presented a ROSE-based translator which presented the AST as a tree, this chapter presents the more general representation of the graph in which the AST is embedded. The AST may be thought of as a subset of a more general graph or equivalently as an AST (a tree in a formal sense) with annotations (extra edges and information), sometimes referred to as a ‘*decorated AST*’.

We present tools for seeing all the IR nodes in the graph containing the AST, including all types (SgType nodes), symbols (SgSymbol nodes), compiler generated IR nodes, and supporting IR nodes. In general it is a specific filtering of this larger graph which is more useful to communicating how the AST is designed and internally connected. We use these graphs for internal debugging (typically on small problems where the graphs are reasonable in size). The graphs presented using these graph mechanism present all back-edges, and demonstrate what IR nodes are shared internally (typically SgType IR nodes).

First a few names, we will call the AST those nodes in the IR that are specified by a traversal using the ROSE traversal (SgSimpleTraversal, etc.). We will call the graph of all IR nodes the *Graph of all IR nodes*. the AST is embedded in the *Graph of all IR nodes*. The AST *is* a tree, while the *graph of all IR nodes* typically not a tree (in a Graph Theory sense) since it typically contains cycles.

We cover the visualization of both the AST and the *Graph of all IR nodes*.

- AST graph
These techniques define ways of visualizing the AST and filtering IR nodes from being represented.
 - Simple AST graphs
 - Colored AST graphs
 - Filtering the graph
The AST graph may be generated for any subtree of the AST (not possible for the graphs of all IR nodes). Additionally runtime options permit null pointers to be ignored. .

FIXME: *Is this true?*

- *Graph of all IR nodes*

These techniques define the ways of visualizing the whole graph of IR nodes and is based on the memory pool traversal as a means to access all IR nodes. Even disconnected portions of the AST will be presented.

- Simple graphs
- Colored graphs
- Filtering the graph

6.1 Whole Graph Generation

This example shows how to generate and visualize the AST from any input program. Each node of the graph in figure 6.3 shows a node of the Intermediate Representation (IR). Each edge shows the connection of the IR nodes in memory. The generated graph shows the connection of different IR nodes to form the AST.

The program in figure 6.1 calls an internal ROSE function that traverses the AST and generates an ASCII file in `dot` format. Figure 6.2 shows an input code which is processed to generate a graph of the AST, generating a `dot` file. The `dot` file is then processed using `dot` to generate a postscript file 6.3 (within the `Makefile`). Note that a similar utility program already exists within ROSE/exampleTranslators (and includes a utility to output an alternative PDF representation (suitable for larger ASTs) as well). Figure 6.3 (`../../tutorial/test.ps`) can be found in the compile tree (in the tutorial directory) and viewed directly using `ghostview` or any postscript viewer to see more detail.

Figure 6.3 displays the individual C++ nodes in ROSE's intermediate representation (IR). Each circle represents a single IR node, the name of the C++ construct appears in the center of the circle, with the edge numbers of the traversal on top and the number of child nodes appearing below. Internal processing to build the graph generates unique values for each IR node, a pointer address, which is displayed at the bottom of each circle. The IR nodes are connected to form a tree, and abstract syntax tree (AST). Each IR node is a C++ class, see SAGE III reference for details, the edges represent the values of data members in the class (pointers which connect the IR nodes to other IR nodes). The edges are labeled with the names of the data members in the classes representing the IR nodes.

```

/*****
 * This example explains how to generate a DOT graph using the
 *   - whole AST traversal
 *   - memory pool traversal
 * In order to reduce the size of the graphs it is possible to filter on both
 * nodes and edges. Coloring of nodes and edges is also possible.
 *****/

#include "rose.h"

using namespace std;

// This functor is derived from the STL functor mechanism

/*****
 * The unary functional
 *   struct filterOnNodes
 * returns an AST_Graph::FunctionalReturnType and takes a std::pair<SgNode*,std::string> as a paramater.
 * The pair represents a variable of type std::string and a variable name.
 * The type AST_Graph::FunctionalReturnType contains the variables
 *   * addToGraph : if false do not graph node or edge, else graph
 *   * DOTOptions : a std::string which sets the color of the node etc.
 *
 * PS!!! The std::string is currently not set to anything useful. DO NOT USE THE STRING.
 *   Maybe it does not make sense in this case and should be removed.
 *****/
struct filterOnNodes: public std::unary_function< pair< SgNode*, std::string >,AST_Graph::FunctionalReturnType >
{
    // This functor filters SgFileInfo objects and IR nodes from the GNU compatability file
    result_type operator() ( argument_type x ) const;
};

//The argument to the function is
filterOnNodes::result_type
filterOnNodes::operator()(filterOnNodes::argument_type x) const
{
    AST_Graph::FunctionalReturnType returnValue;
    //Determine if the node is to be added to the graph. true=yes
    returnValue.addToGraph = true;
    //set colors etc. for the graph Node
    returnValue.DOTOptions = "shape=polygon,regular=0,URL=\"\\N\",tooltip=\"more info at\\N\",sides=4,peripheries=1,color="
    if( isSgProject(x.first) != NULL )
        returnValue.DOTOptions = "shape=ellipse,regular=0,URL=\"\\N\",tooltip=\"more info at\\N\",sides=4,peripheries=1,color="

    //Filter out SgSymbols from the graph
    if ( isSgSymbol(x.first) != NULL )
        returnValue.addToGraph = false;

    if ( isSgType(x.first) != NULL )
        returnValue.addToGraph = false;

    //Filter out compiler generated nodes
    SgLocatedNode* locatedNode = isSgLocatedNode(x.first);
    if ( locatedNode != NULL )
    {
        Sg_File_Info* fileInfo = locatedNode->get_file_info();
        std::string filename(ROSE::stripPathFromFileName(fileInfo->get_filename()));

        if (filename.find("rose_edg_macros_and_functions_required_for_gnu.h") != std::string::npos)
        {
            returnValue.addToGraph = false;
        }

        if (fileInfo->isCompilerGenerated()==true)
        {
            // std::cout << "Is compiler generated\n";
            returnValue.addToGraph = false;
        }
    }

    return returnValue;
}

/*****
 * The binary functional
 *   struct filterOnEdges

```

```
int x;  
#if 0  
int  
main()  
{  
    int x = 0;  
    return 0;  
}  
#endif
```

Figure 6.2: Example source code used as input to generate the AST graph.




Figure 6.3: AST representing the source code file: inputCode_wholeGraphAST.C.

Chapter 7

AST PDF Generator

What To Learn From This Example This example demonstrates a mechanism for generating a visualization of the AST using pdf files. A pdf file is generated and can be viewed using **acroread**. The format is suitable for much larger input programs than the example shown in chapter ???. This mechanism can support the visualization of input files around 100K lines of code.

```
// Example ROSE Translator: used within ROSE/tutorial
#include "rose.h"

int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc,argv);

    generatePDF ( *project );
    return 0;
}
```

Figure 7.1: Example source code to read an input program and generate a PDF file to represent the AST.

The program in figure 7.1 calls an internal ROSE function that traverses the AST and generates an ASCII file in **dot** format. Figure 4.2 shows an input code which is processed to generate a graph of the AST, generating a **pdf** file. The **pdf** file is then processed using **acroread** to generate a GUI for viewing the AST.

Figure 7.3 displays on the left hand side the individual C++ nodes in ROSE's intermediate representation (IR). The page on the right hand side shows that IR nodes member data. Pointers in boxes can be clicked on to navigate the AST (or nodes in the tree hierarchy can be clicked on jump to any location in the AST. This representation shows only the IR nodes that are traversed by the standard traversal (no SgSymbol or SgType IR nodes are presented in this view of the AST).

The output of this translator is shown in figure 7.3. The left hand side of the screen is a tree with click-able nodes to expand/collapse the subtrees. The right hand side of the screen is a

```
// Templated class declaration used in template parameter example code
template <typename T>
class templateClass
{
    public:
        int x;

        void foo(int);
        void foo(double);
};

// Overloaded functions for testing overloaded function resolution
void foo(int);
void foo(double)
{
    int x = 1;
    int y;

    // Added to allow non-trivial CFG
    if (x)
        y = 2;
    else
        y = 3;
}
```

Figure 7.2: Example source code used as input to generate the PDF file of the AST.

description of the data at a particular node in the AST (the node where the user has clicked the left mouse button). This relatively simple view of the AST is useful for debugging transformation and finding information in the AST required by specific sorts of analysis. It is also useful for developing an intuitive feel for what information is in the AST, how it is organized, and where it is stored.




Figure 7.3: Example output from translator which outputs PDF representation of AST.

Chapter 8

Introduction to AST Traversals

An essential operation in the analysis and construction of ASTs is the definition of traversals upon the AST to gather information and modify targeted internal representation (IR) nodes. ROSE includes different sorts of traversals to address the different requirements of numerous program analysis and transformation operations. This section demonstrates the different types of traversals that are possible using ROSE.

ROSE translators most commonly introduce transformations and analysis through a traversal over the AST. Alternatives could be to generate a simpler IR that is more suitable to a specific transformation and either convert modification to that transformation specific IR into changes to the AST or generate source code from the transformation specific IR directly. These approaches are more complex than introducing changes to the AST directly, but may be better for specific transformations.

Traversals represent an essential operation on the AST and there are a number of different types of traversals. The suggested traversals for users are explained in Section 8.2. Section 8.3 introduces specialized traversals (that traverse the AST in different orders and traverse types and symbols), typically not appropriate for most translators (but perhaps appropriate for specialized tools, often internal tools within ROSE).

See the ROSE User Manual for a more complete introduction to the different types of traversals. The purpose of this tutorial is to present examples, but we focus less on the background and philosophy here than in the ROSE User Manual.

This chapter presents a number of ways of traversing the AST of any input source code. These *traversals* permit operations on the AST, which may either read or modify the AST in place. Modifications to the AST will be reflected in the source code generated when the AST is *unparsed*; the code generation phase of the source-to-source process defined by ROSE. Note that for all examples, the input code described in section 8.1 is used to generate all outputs shown with each translator.

8.1 Input For Example Traversals

The code shown in figure 8.1 shows the input code that will be used to demonstrate the traversals in this chapter. It may be modified by the user to experiment with the use of the traversals on

```

// Templated class declaration used in template parameter example code
template <typename T>
class templateClass
{
    public:
        int x;
        void foo(int);
        void foo(double);
};

// Overloaded functions for testing overloaded function resolution
void foo(int);

void foo(double)
{
    int x = 1;
    int y;

    for (int i=0; i < 4; i++)
    {
        int x;
    }

    // Added to allow non-trivial CFG
    if (x)
        y = 2;
    else
        y = 3;
}

int main()
{
    foo(42);
    foo(3.14159265);

    templateClass<char> instantiatedClass;
    instantiatedClass.foo(7);
    instantiatedClass.foo(7.0);

    for (int i=0; i < 4; i++)
    {
        int x;
    }

    return 0;
}

```

Figure 8.1: Example source code used as input to program in traversals shown in this chapter.

alternative input codes.

8.2 Traversals of the AST Structure

This collection of traversals operates on the AST in an order which matches the structure of the AST and the associated source code. These types of traversals are the most common traversals for users to use. A subsequent section of this chapter demonstrated more specialized traversals over all IR nodes (more than just those IR nodes in the AST representing the structure of the source code) that are suitable for some tools, mostly tools built internally within ROSE.

Because the traversals in this section traverse the structure of the source code (see the AST graph presented in the first tutorial example) they are more appropriate for most transformations of the source code. We suggest that the user focus on these traversals which represent the interface we promote for analysis and transformation of the AST, instead of the memory pools traversals which are suitable mostly for highly specialized internal tools. The simple traversals of both kinds have the same interface so the user may easily switch between them with out significant difficulty.

8.2.1 Classic Object-Oriented Visitor Pattern for the AST (Not Yet Implemented)

```
#include "rose.h"

// Classic Visitor Pattern in ROSE (implemented using the traversal over
// the elements stored in the memory pools so it has no cycles and visits
// ALL IR nodes (including all Sg_File_Info, SgSymbols, SgTypes, and the
// static builtin SgTypes).
class ClassicVisitor : public ROSE.VisitorPattern
{
public:
    // Override virtual function defined in base class
    void visit(SgGlobal* globalScope)
    {
        printf ("Found the SgGlobal IR node \n");
    }

    void visit(SgFunctionDeclaration* functionDeclaration)
    {
        printf ("Found a SgFunctionDeclaration IR node \n");
    }
    void visit(SgTypeInt* intType)
    {
        printf ("Found a SgTypeInt IR node \n");
    }

    void visit(SgTypeDouble* doubleType)
    {
        printf ("Found a SgTypeDouble IR node \n");
    }
};

int
main ( int argc, char* argv[] )
{
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT (project != NULL);

    // Classic visitor pattern over the memory pool of IR nodes
    ClassicVisitor visitor_A;
    traverseMemoryPoolVisitorPattern(visitor_A);

    return backend(project);
}
```

Figure 8.2: Example source showing simple visitor pattern.

Figure 8.2 shows the source code for a translator using the classic object-oriented visitor pattern to traverse the AST. *This visitor pattern is not yet implemented except for the memory pool based traversal. It is however expected to appear identical to the classing visitor pattern shown for the memory pool traversal.* Figure 8.3 shows the output from this traversal using the example input source from figure 8.1.

8.2.2 Simple Traversal (no attributes)

Figure 8.4 shows the source code for a translator which traverses the AST. At each node the `visit()` function is called using only the input information represented by the current node. Note that using this simple traversal the only context information available to the visit function is what is stored in its member variables. The only option is to traverse the AST in either pre-order or postorder. The `atTraversalEnd()` function may be defined by the user to do final processing after all nodes have been visited (or to perform preparations before the nodes are visited, in the case of the corresponding `atTraversalStart()` function). Figure 8.5 shows the output from this traversal using the example input source from figure 8.1.

8.2.3 Simple Pre- and Postorder Traversal

Figure 8.6 shows the source code for a translator that traverses the AST without attributes (like the one in the previous subsection), but visiting each node twice, once in preorder (before its children) and once in postorder (after all children). Figure 8.7 shows the output from this traversal using the example input source from figure 8.1.

8.2.4 Inherited Attributes

Figure 8.8 shows the use of inherited attributes associated with each IR node. Within this traversal the attributes are managed by the traversal and exist on the stack. Thus the lifetime of the attributes is only as long as the processing of the IR node and its subtree. Attributes such as this are used to communicate context information **down** the AST and called *Inherited attributes*.

In the example the class `InheritedAttribute` is used to represent inherited attribute. Each instance of the class represents an attribute value. When the AST is traversed we obtain as output the loop nest depth at each point in the AST. The output uses the example input source from figure 8.1.

Note that inherited attributes are passed by-value down the AST. In very rare cases you might want to pass a pointer to dynamically allocated memory as an inherited attribute. In this case you can define the virtual member function `void destroyInheritedValue(SgNode *n, InheritedAttribute inheritedValue)` which is called after the last use of the inherited attribute computed at this node, i.e. after all children have been visited. You can use this function to free the memory allocated for this inherited attribute.

[illegible]

```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// rose.C: Example (default) ROSE Preprocessor: used for testing ROSE infrastructure

#include "rose.h"

class visitorTraversal : public AstSimpleProcessing
{
public:
    visitorTraversal();
    virtual void visit(SgNode* n);
    virtual void atTraversalEnd();
};

visitorTraversal::visitorTraversal()
{
}

void visitorTraversal::visit(SgNode* n)
{
    if (isSgForStatement(n) != NULL)
    {
        printf ("Found a for loop ... \n");
    }
}

void visitorTraversal::atTraversalEnd()
{
    printf ("Traversal ends here. \n");
}

int
main ( int argc, char* argv[] )
{
    if (SgProject::get_verbose() > 0)
        printf ("In visitorTraversal.C: main() \n");

    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT (project != NULL);

    // Build the traversal object
    visitorTraversal exampleTraversal;

    // Call the traversal starting at the project node of the AST
    exampleTraversal.traverseInputFiles(project,preorder);

    return 0;
}

```

Figure 8.4: Example source showing simple visitor pattern.

```

Found a for loop ...
Found a for loop ...
Traversal ends here.

```

Figure 8.5: Output of input file to the visitor traversal.

```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// rose.C: Example (default) ROSE Preprocessor: used for testing ROSE infrastructure

#include "rose.h"

class PreAndPostOrderTraversal : public AstPrePostProcessing
{
public:
    virtual void preOrderVisit(SgNode* n);
    virtual void postOrderVisit(SgNode* n);
};

void PreAndPostOrderTraversal::preOrderVisit(SgNode* n)
{
    if (isSgForStatement(n) != NULL)
    {
        printf ("Entering for loop ... \n");
    }
}

void PreAndPostOrderTraversal::postOrderVisit(SgNode* n)
{
    if (isSgForStatement(n) != NULL)
    {
        printf ("Leaving for loop ... \n");
    }
}

int
main ( int argc, char* argv[] )
{
    if (SgProject::get_verbose() > 0)
        printf ("In prePostTraversal.C: main() \n");

    SgProject* project = frontend(argc, argv);
    ROSE_ASSERT (project != NULL);

    // Build the traversal object
    PreAndPostOrderTraversal exampleTraversal;

    // Call the traversal starting at the project node of the AST
    exampleTraversal.traverseInputFiles(project);

    return 0;
}

```

Figure 8.6: Example source showing simple pre- and postorder pattern.

```

Entering for loop ...
Leaving for loop ...
Entering for loop ...
Leaving for loop ...

```

Figure 8.7: Output of input file to the pre- and postorder traversal.

```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// rose.C: Example (default) ROSE Preprocessor: used for testing ROSE infrastructure

#include "rose.h"

// Build an inherited attribute for the tree traversal to test the rewrite mechanism
class InheritedAttribute
{
public:
    // Depth in AST
    int depth;
    int maxLinesOfOutput;

    // Specific constructors are required
    InheritedAttribute (int x) : depth(x), maxLinesOfOutput(20) {};
    InheritedAttribute ( const InheritedAttribute & X ) : depth(X.depth), maxLinesOfOutput(20){};
};

class visitorTraversal : public AstTopDownProcessing<InheritedAttribute>
{
public:
    // virtual function must be defined
    virtual InheritedAttribute evaluateInheritedAttribute(SgNode* n, InheritedAttribute inheritedAttribute);
};

InheritedAttribute
visitorTraversal::evaluateInheritedAttribute(SgNode* n, InheritedAttribute inheritedAttribute)
{
    static int linesOfOutput = 0;
    if (linesOfOutput++ < inheritedAttribute.maxLinesOfOutput)
        printf ("Depth in AST at %s = %d \n", n->sage_class_name(), inheritedAttribute.depth);

    return InheritedAttribute(inheritedAttribute.depth+1);
}

int
main ( int argc, char* argv[] )
{
    SgProject* project = frontend(argc, argv);
    ROSE_ASSERT (project != NULL);

    // DQ (1/18/2006): Part of debugging
    SgFile & localFile = project->get_file(0);
    localFile.get_file_info()->display("localFile information");

    // Build the inherited attribute
    InheritedAttribute inheritedAttribute(0);

    // Build the traversal object
    visitorTraversal exampleTraversal;

    // Call the traversal starting at the project node of the AST
    exampleTraversal.traverseInputFiles(project, inheritedAttribute);

    // Or the traversal over all AST IR nodes can be called!
    exampleTraversal.traverse(project, inheritedAttribute);

    return 0;
}

```

Figure 8.8: Example source code showing use of inherited attributes (passing context information **down** the AST.


```

Inside of Sg_File_Info::display(localFile information)
  isTransformation                = false
  isCompilerGenerated             = false
  isOutputInCodeGeneration        = false
  isShared                        = false
  isFrontendSpecific              = false
  isSourcePositionUnavailableInFrontend = false
  isCommentOrDirective            = false
  isToken                         = false
  filename = /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode.ExampleTraversals.7.C
  line     = 1 column = 1
Depth in AST at SgSourceFile = 0
Depth in AST at SgGlobal = 1
Depth in AST at SgTemplateDeclaration = 2
Depth in AST at SgFunctionDeclaration = 2
Depth in AST at SgFunctionParameterList = 3
Depth in AST at SgInitializedName = 4
Depth in AST at SgFunctionDeclaration = 2
Depth in AST at SgFunctionParameterList = 3
Depth in AST at SgInitializedName = 4
Depth in AST at SgFunctionDefinition = 3
Depth in AST at SgBasicBlock = 4
Depth in AST at SgVariableDeclaration = 5
Depth in AST at SgInitializedName = 6
Depth in AST at SgAssignInitializer = 7
Depth in AST at SgIntVal = 8
Depth in AST at SgVariableDeclaration = 5
Depth in AST at SgInitializedName = 6
Depth in AST at SgForStatement = 5
Depth in AST at SgForInitStatement = 6
Depth in AST at SgVariableDeclaration = 7

```

Figure 8.9: Output of input file to the inherited attribute traversal.

8.2.5 Synthesized Attributes

```
// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// rose.C: Example (default) ROSE Preprocessor: used for testing ROSE infrastructure

#include "rose.h"

#include <algorithm>
#include <functional>
#include <numeric>

typedef bool SynthesizedAttribute;

class visitorTraversal : public AstBottomUpProcessing<SynthesizedAttribute>
{
public:
    // virtual function must be defined
    virtual SynthesizedAttribute evaluateSynthesizedAttribute (
        SgNode* n, SynthesizedAttributesList childAttributes );
};

SynthesizedAttribute
visitorTraversal::evaluateSynthesizedAttribute ( SgNode* n, SynthesizedAttributesList childAttributes )
{
    // Fold up the list of child attributes using logical or, i.e. the local
    // result will be true iff one of the child attributes is true.
    SynthesizedAttribute localResult =
        std::accumulate(childAttributes.begin(), childAttributes.end(),
            false, std::logical_or<bool>());

    if (isSgForStatement(n) != NULL)
    {
        printf ("Found a for loop ... \n");
        localResult = true;
    }

    return localResult;
}

int
main ( int argc, char* argv[] )
{
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT (project != NULL);

    // Build the traversal object
    visitorTraversal exampleTraversal;

    // Call the traversal starting at the project node of the AST
    SynthesizedAttribute result = exampleTraversal.traverse(project);

    if (result == true)
    {
        printf ("The program contains at least one loop!\n");
    }

    return 0;
}
```

Figure 8.10: Example source code showing use of synthesized attributed (passing analysis information **up** the AST).

Figure 8.10 shows the use of attributes to pass information **up** the AST. The lifetime of the

```
Found a for loop ...  
Found a for loop ...  
The program contains at least one loop!
```

Figure 8.11: Output of input file to the synthesized attribute traversal.

attributes are similar as for inherited attributes. Attributes such as these are called synthesized attributes.

This code shows the code for a translator which does an analysis of an input source code to determine the presence of loops. It returns true if a loop exists in the input code and false otherwise. The list of synthesized attributes representing the information passed up the AST from a node's children is of type `SynthesizedAttributesList`, which is a type that behaves very similarly to `vector<SynthesizedAttribute>` (it supports iterators, can be indexed, and can be used with STL algorithms).

The example determines the existence of loops for a given program.

8.2.6 Accumulator Attributes

```
// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// rose.C: Example (default) ROSE Preprocessor: used for testing ROSE infrastructure

#include "rose.h"

// Build an accumulator attribute, fancy name for what is essentially a global variable :-).
class AccumulatorAttribute
{
public:
    int forLoopCounter;

    // Specific constructors are optional
    AccumulatorAttribute () { forLoopCounter = 0; }
    AccumulatorAttribute ( const AccumulatorAttribute & X ) {}
    AccumulatorAttribute & operator= ( const AccumulatorAttribute & X ) { return *this; }
};

class visitorTraversal : public AstSimpleProcessing
{
public:
    static AccumulatorAttribute accumulatorAttribute;
    virtual void visit(SgNode* n);
};

// declaration required for static data member
AccumulatorAttribute visitorTraversal::accumulatorAttribute;

void visitorTraversal::visit(SgNode* n)
{
    if (isSgForStatement(n) != NULL)
    {
        printf ("Found a for loop ... \n");
        accumulatorAttribute.forLoopCounter++;
    }
}

int
main ( int argc, char* argv[] )
{
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT (project != NULL);

    // Build the traversal object
    visitorTraversal exampleTraversal;

    // Call the traversal starting at the project node of the AST
    // can be specified to be preorder or postorder).
    exampleTraversal.traverseInputFiles(project,preorder);

    printf ("Number of for loops in input application = %d \n",exampleTraversal.accumulatorAttribute.forLoopCounter);

    return 0;
}
```

Figure 8.12: Example source code showing use of accumulator attributes (typically to count things in the AST).

Figure 8.12 shows the use of a different sort of attribute. This attribute has a lifetime equal to the lifetime of the traversal object (much longer than the traversal of any subset of IR nodes). The same attribute is accessible from each IR node. Such attributes are called *accumulator*

```
Found a for loop ...  
Found a for loop ...  
Number of for loops in input application = 2
```

Figure 8.13: Output of input file to the accumulator attribute traversal.

attributes and are semantically equivalent to a global variable. Accumulator attributes act as global variables which can easily be used to count application specific properties within the AST.

Note that due to the limitation that the computation of inherited attributes cannot be made dependent on the values of synthesized attributes, counting operations cannot be implemented by combining these attributes as is usually done in attribute grammars. However, the use of accumulator attributes serves well for this purpose. Therefore all counting-like operations should be implemented using accumulator attributes (= member variables of traversal or processing classes).

Although not shown in this tutorial explicitly, accumulator attributes may be easily mixed with inherited and/or synthesized attributes.

In this example we count the number of for-loops in an input program.

8.2.7 Inherited and Synthesized Attributes

Figure 8.14 shows the combined use of inherited and synthesized attributes. The example source code shows the mixed use of such attributes to list the functions containing loop. Inherited attributes are used to communicate that the traversal is in a function, which the synthesized attributes are used to pass back the existence of loops deeper within the subtrees associated with each function.

List of functions containing loops.

```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
#include "rose.h"

#include <algorithm>
#include <functional>
#include <numeric>

typedef bool InheritedAttribute;
typedef bool SynthesizedAttribute;

class Traversal : public SgTopDownBottomUpProcessing<InheritedAttribute, SynthesizedAttribute>
{
public:
    // Functions required
    InheritedAttribute evaluateInheritedAttribute (
        SgNode* astNode,
        InheritedAttribute inheritedAttribute );

    SynthesizedAttribute evaluateSynthesizedAttribute (
        SgNode* astNode,
        InheritedAttribute inheritedAttribute,
        SubTreeSynthesizedAttributes synthesizedAttributeList );
};

InheritedAttribute
Traversal::evaluateInheritedAttribute (
    SgNode* astNode,
    InheritedAttribute inheritedAttribute )
{
    if (isSgFunctionDefinition(astNode))
    {
        // The inherited attribute is true iff we are inside a function.
        return true;
    }
    return inheritedAttribute;
}

SynthesizedAttribute
Traversal::evaluateSynthesizedAttribute (
    SgNode* astNode,
    InheritedAttribute inheritedAttribute,
    SynthesizedAttributesList childAttributes )
{
    if (inheritedAttribute == false)
    {
        // The inherited attribute is false, i.e. we are not inside any
        // function, so there can be no loops here.
        return false;
    }
    else
    {
        // Fold up the list of child attributes using logical or, i.e. the local
        // result will be true iff one of the child attributes is true.
        SynthesizedAttribute localResult =
            std::accumulate(childAttributes.begin(), childAttributes.end(),
                           false, std::logical_or<bool>());
        if (isSgFunctionDefinition(astNode) && localResult == true)
        {
            printf ("Found a function containing a for loop ...\n");
        }
        if (isSgForStatement(astNode))
        {
            localResult = true;
        }
        return localResult;
    }
}

int
main ( int argc, char* argv[] )
{
    // Build the abstract syntax tree
    SgProject* project = frontend(argc, argv);
    ROSE_ASSERT (project != NULL);

    // Build the inherited attribute
    InheritedAttribute inheritedAttribute = false;

    // Define the traversal
    Traversal myTraversal;

    // Call the traversal starting at the project (root) node of the AST
    myTraversal.traverseInputFiles(project, inheritedAttribute);

    // This program only does analysis, so it need not call the backend to generate code.
    return 0;
}

```

Figure 8.14: Example source code showing use of both inherited and synthesized attributes working together (part 1).

```
Found a function containing a for loop ...  
Found a function containing a for loop ...
```

Figure 8.15: Output of input file to the inherited and synthesized attribute traversal.

8.2.8 Persistent Attributes

Figure 8.16 shows the use of another form of attribute. This attribute has a lifetime which is controlled explicitly by the user; it lives on the heap typically. These attributes are explicitly attached to the IR nodes and are not managed directly by the traversal. These attributes are called *persistent* attributes and are not required to be associated with any traversal. Persistent attributes are useful for storing information across multiple traversals (or permanently within the AST) for later traversal passes.

Persistent attributes may be used at any time and combined with other traversals (similar to accumulator attributes). Traversals may combine any or all of the types of attributes within in ROSE as needed to store, gather, or propagate information within the AST for complex program analysis.


```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// rose.C: Example (default) ROSE Preprocessor: used for testing ROSE infrastructure

#include "rose.h"

class persistentAttribute : public AstAttribute
{
public:
    int value;
    persistentAttribute (int v) : value(v) {}
};

class visitorTraversalSetAttribute : public AstSimpleProcessing
{
public:
    virtual void visit(SgNode* n);
};

void visitorTraversalSetAttribute::visit(SgNode* n)
{
    if (isSgForStatement(n) != NULL)
    {
        printf ("Found a for loop (set the attribute) ... \n");

        // Build an attribute (on the heap)
        AstAttribute* newAttribute = new persistentAttribute(5);
        ROSE_ASSERT(newAttribute != NULL);

        // Add it to the AST (so it can be found later in another pass over the AST)
        n->addNewAttribute("MyNewAttribute",newAttribute);
    }
}

class visitorTraversalReadAttribute : public AstSimpleProcessing
{
public:
    virtual void visit(SgNode* n);
};

void visitorTraversalReadAttribute::visit(SgNode* n)
{
    if (isSgForStatement(n) != NULL)
    {
        printf ("Found a for loop (read the attribute) ... \n");

        // Add it to the AST (so it can be found later in another pass over the AST)
        // AstAttribute* existingAttribute = n->attribute["MyNewAttribute"];
        // DQ (1/2/2006): Added support for new attribute interface.
        // printf ("visitorTraversalReadAttribute::visit(): using new attribute interface \n");
        // AstAttribute* existingAttribute = n->attribute()["MyNewAttribute"];
        // AstAttribute* existingAttribute = n->getAttribute("MyNewAttribute");
        // ROSE_ASSERT(existingAttribute != NULL);

        printf ("Existing attribute at %p value = %d \n",n,dynamic_cast<persistentAttribute*>(existingAttribute)->value);
    }
}

int
main ( int argc, char* argv[] )
{
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT (project != NULL);

    // Build the traversal object to set persistent AST attributes
    visitorTraversalSetAttribute exampleTraversalSettingAttribute;

    // Call the traversal starting at the project node of the AST
    exampleTraversalSettingAttribute.traverseInputFiles(project,preorder);

    // Build the traversal object to read any existing AST attributes
    visitorTraversalReadAttribute exampleTraversalReadingAttribute;

    // Call the traversal starting at the project node of the AST
    exampleTraversalReadingAttribute.traverseInputFiles(project,preorder);

    return 0;
}

```

Figure 8.16: Example source code showing use of persistent attributes used to pass information across multiple passes over the AST.

```
Found a for loop (set the attribute) ...  
Found a for loop (set the attribute) ...  
Found a for loop (read the attribute) ...  
Existing attribute at 0xb7d33008 value = 5  
Found a for loop (read the attribute) ...  
Existing attribute at 0xb7d33090 value = 5
```

Figure 8.17: Output of input file to the persistent attribute traversal showing the passing of information from one AST traversal to a second AST traversal.

8.2.9 Nested Traversals

```
// Example ROSE Translator: used within ROSE/tutorial
#include "rose.h"

class visitorTraversal : public AstSimpleProcessing
{
public:
    virtual void visit(SgNode* n);
};

class nestedVisitorTraversal : public AstSimpleProcessing
{
public:
    virtual void visit(SgNode* n);
};

void visitorTraversal::visit(SgNode* n)
{
    if (isSgFunctionDeclaration(n) != NULL)
    {
        printf ("Found a function declaration ... \n");

        // Build the nested traversal object
        nestedVisitorTraversal exampleTraversal;

        // Call the traversal starting at the project node of the AST (traverse in postorder just to be different)
        // Note that we call the traverse function instead of traverseInputFiles, because we are not starting at
        // the AST root.
        exampleTraversal.traverse(n,postorder);
    }
}

void nestedVisitorTraversal::visit(SgNode* n)
{
    if (isSgFunctionDefinition(n) != NULL)
    {
        printf ("Found a function definition within the function declaration ... \n");
    }
}

int
main ( int argc, char* argv[] )
{
    if (SgProject::get_verbose() > 0)
        printf ("In visitorTraversal.C: main() \n");

    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT (project != NULL);

    // Build the traversal object
    visitorTraversal exampleTraversal;

    // Call the traversal starting at the project node of the AST
    exampleTraversal.traverseInputFiles(project,preorder);

    return 0;
}
```

Figure 8.18: Example source code showing use nested traversals.

Figure 8.18 shows the use of multiple traversals in composition. Figure 8.19 shows the output

```
Found a function declaration ...  
Found a function declaration ...  
Found a function definition within the function declaration ...  
Found a function declaration ...  
Found a function declaration ...  
Found a function declaration ...  
Found a function declaration ...  
Found a function definition within the function declaration ...
```

Figure 8.19: Output of input file to the nested traversal example.

of the nested traversal.

8.2.10 Combining all Attributes and Using Primitive Types

```

int main() {
    int x=1;
    for (int i=1; i<10;i++)
        for (int j=i; j<10;j++)
            for (int k=i; k<10;k++)
                for (int l=i; l<10;l++)
                    for (int m=i; m<10;m++)
                        x++;

    int i=5,j=7;
    while(i>0) {
        while(j>0) {
            x++;
            j--;
            i--;
        }
    }

    i=10;
    do {
        x++;
        i--;
    } while (i>0);

    return x;
}

```

Figure 8.20: Input code with nested loops for nesting info processing

The previous examples have shown cases where attributes were classes, alternatively attributes can be any primitive type (int, bool, etc.). This example demonstrates how to use `AstTopDownBottomUpProcessing` to compute inherited and synthesized attributes, generate pdf and dot output, how to accumulate information, and how to attach attributes to AST nodes in the same pass.

The attributes are used to compute the nesting level and the nesting depth of for/while/do-while loops: The nesting level is computed using an inherited attribute. It holds that $nesting-level(innerloop) = nesting-level(outerloop) + 1$ starting with 1 at the outer most loop. The nesting depth is computed using a synthesized attribute. It holds that $nesting-depth(innerloop) = nesting-level(outerloop) - 1$ starting with 1 at the inner most loop.

To compute the values we use a primitive type (unsigned int). This example also shows how to use `defaultSynthesizedAttribute` to initialize a synthesized attribute of primitive type. The values of the attributes are attached to the AST using `AstAttribute` and the AST node attribute mechanism available at every AST node (which can be accessed with `node->attribute`). (see `loopNestingInfoProcessing.C`)

For the entire program the maximum nesting level (= max nesting depth) is computed as accumulated value using member variable `_maxNestingLevel` of class `LoopNestingInfoProcessing`. We also demonstrate how to customize an `AstAttribute` such that the value of the attribute is printed in a pdf output. (by overriding `toString`, see `LoopNestingInfo` class)

In the generated pdf file (for some C++ input file) the values of the attributes can be viewed for each node (see `printLoopInfo` implementation). Further more we also generate a dot file, to visualize the tree using the graph visualization tool `dot`. The generated file can be converted to

postscript (using dot) and viewed with gv.

8.2.11 Combined Traversals

Performing a large number of program analyses as separate traversals of the AST can be somewhat inefficient as there is some overhead associated with visiting every node several times. ROSE therefore provides a mechanism for combining traversal objects of the same base type and evaluating them in a single traversal of the AST. This is entirely transparent to the individual traversal object, so existing code can be reused with the combination mechanism, and analyzers can be developed and tested in isolation and combined when needed.

The one requirement that is placed on traversals to be combined is that they be independent of each other; in particular, this means that they should not modify the AST or any shared global data. Any output produced by the analyzers will be interleaved.

Figure 8.24 shows the source code for a translator that combines three different analyzers into one traversal, each one counting the occurrences of a different type of AST node (as determined by a VariantT value). First three traversals are run after each other, as usual; then three traversal objects are passed (by pointer) to an object of type `AstCombinedSimpleProcessing` using its `addTraversal` method. One then invokes one of the usual traverse methods on this combined object with the same effect as if it had been called for each of the traversal objects individually.

Any operation on the list of analyzers is possible using the `get_traversalPtrListRef` method of the combined processing class that returns a reference to its internal list of analyzers (an object of type `vector<AstSimpleProcessing *>`). Any changes made through this reference will be reflected in further traversals.

In addition to `AstCombinedSimpleProcessing`, there is also a combined class for each of the other types of traversals discussed above: `AstCombinedTopDownProcessing`, `AstCombinedBottomUpProcessing`, etc. Where traversals using attributes are combined, all of the combined traversals must have the same attribute types (i.e. the same template parameters). Attributes are passed to and returned from the combined traversal as a vector.

```

// Author: Markus Schordan, Vienna University of Technology, 2004.
// $Id: loopNestingInfoProcessing.C,v 1.1 2006/04/24 00:22:00 dquinlan Exp $

// #include <string>
// #include <iostream>

#include "rose.h"

using namespace std;

typedef unsigned int NestingLevel;
typedef unsigned int NestingDepth;
typedef NestingLevel InhNestingLevel;
typedef NestingDepth SynNestingDepth;

/*! This class is used to attach information to AST nodes.
   Method 'toString' is overridden and
   called when a pdf file is generated. This allows to display
   the value of an AST node attribute (annotation) in a pdf file.
*/
class NestingLevelAnnotation : public AstAttribute {
public:
    NestingLevelAnnotation(NestingLevel n, NestingDepth d)
        : _nestingLevel(n), _nestingDepth(d) {}
    NestingLevel getNestingLevel() { return _nestingLevel; }
    NestingDepth getNestingDepth() { return _nestingDepth; }
    string toString() {
        ostringstream ss; ss<<_nestingLevel<<","<<_nestingDepth;
        return ss.str();
    }
private:
    NestingLevel _nestingLevel;
    NestingDepth _nestingDepth;
};

/* !
The loop nesting level and nesting depth for each while/dowhile/for
loop nest is computed. It is attached to the AST as annotation and
can be accessed as node->attribute["loopNestingInfo"]
after the processing has been performed.
The maximum nesting level of the whole AST is computed as
"accumulated" value in a member variable and can be accessed with
getMaxNestingLevel().
*/
class LoopLevelProcessing : public AstTopDownBottomUpProcessing<InhNestingLevel, SynNestingDepth> {
public:
    LoopLevelProcessing(): _maxNestingLevel(0) {}

    /*! Performs a traversal of the AST and computes loop-nesting information by using
       inherited and synthesized attributes. The results are attached to the AST as
       annotation.
    */
    void attachLoopNestingAnnotation(SgProject* node) { traverseInputFiles(node, 0); }

    /*! Returns the maximum nesting level of the entire AST (of the input file).
       Requires attachLoopNestingAnnotation (to be called before)
    */
    NestingLevel getMaxNestingLevel() { return _maxNestingLevel; }

protected:
    /*! computes the nesting level
    InhNestingLevel evaluateInheritedAttribute(SgNode*, InhNestingLevel);
    /*! computes the nesting depth
    SynNestingDepth evaluateSynthesizedAttribute(SgNode*, InhNestingLevel, SynthesizedAttributesList);
    /*! provides the default value 0 for the nesting depth
    SynNestingDepth defaultSynthesizedAttribute(InhNestingLevel inh);
private:
    NestingLevel _maxNestingLevel;
};

NestingLevel
LoopLevelProcessing::evaluateInheritedAttribute(SgNode* node, NestingLevel loopNestingLevel) {

    /*! compute maximum nesting level of entire program in accumulator (member variable)
    if (loopNestingLevel > _maxNestingLevel)
        _maxNestingLevel = loopNestingLevel;

    switch (node->variantT()) {
    case V_SgGotoStatement:

```

Figure 8.21: Example source code showing use of inherited, synthesized, accumulator, and non

```

        cout << "WARNING: Goto statement found. We do not consider goto loops.\n";
// DQ (11/17/2005): Added return statment to avoid g++ warning: control reaches end of non-void function
        return loopNestingLevel;
        break;
    case V_SgDoWhileStmt:
    case V_SgForStatement:
    case V_SgWhileStmt:
        return loopNestingLevel+1;
    default:
        return loopNestingLevel;
    }
}

SynNestingDepth
LoopLevelProcessing::defaultSynthesizedAttribute(InhNestingLevel inh) {
    /*! we do not need the inherited attribute here
       as default value for synthesized attribute we set 0, representing nesting depth 0.
    */
    return 0;
}

SynNestingDepth
LoopLevelProcessing::evaluateSynthesizedAttribute(SgNode* node, InhNestingLevel nestingLevel, SynthesizedAttribute* attribute) {
    {
        if (nestingLevel > _maxNestingLevel)
            _maxNestingLevel = nestingLevel;

        // compute maximum nesting depth of synthesized attributes
        SynNestingDepth nestingDepth = 0;
        for (SynthesizedAttributesList::iterator i = l.begin(); i != l.end(); i++)
        {
            if (*i > nestingDepth) nestingDepth = *i;
        }

        switch (node->variantT())
        {
            case V_SgDoWhileStmt:
            case V_SgForStatement:
            case V_SgWhileStmt:
            {
                nestingDepth++;
                cout << "Nesting level:" << nestingLevel << ", nesting depth:" << nestingDepth << endl;
                break;
            }

            default:
            {
                // DQ (11/17/2005): Nothing to do here, but explicit default in switch avoids lots of warnings.
            }
        }
    }

    // add loop nesting level as annotation to AST
    NestingLevelAnnotation* nla = new NestingLevelAnnotation(nestingLevel, nestingDepth);
    ROSE_ASSERT(nla != NULL);

    // DQ (1/2/2006): Added support for new attribute interface.
    // printf ("LoopLevelProcessing::evaluateSynthesizedAttribute(): using new attribute interface \n");
    #if 0
        if (node->get_attribute() == NULL)
        {
            AstAttributeMechanism* attributePtr = new AstAttributeMechanism();
            ROSE_ASSERT(attributePtr != NULL);
            node->set_attribute(attributePtr);
        }
    #endif
    // node->attribute.add("loopNestingInfo", nla);
    // node->attribute().add("loopNestingInfo", nla);
    node->addNewAttribute("loopNestingInfo", nla);

    /*! return the maximum nesting depth as synthesized attribute
    return nestingDepth;
    }

int main ( int argc, char** argv) {
    // command line parameters are passed to EDG
    // non-EDG parameters are passed (through) to ROSE (and the vendor compiler)
    SgProject* root = frontend(argc, argv);
    LoopLevelProcessing t;

```

Figure 8.22: Example source code showing use of inherited, synthesized, accumulator, and per-


```
Output:
Nesting level:5, nesting depth:1
Nesting level:4, nesting depth:2
Nesting level:3, nesting depth:3
Nesting level:2, nesting depth:4
Nesting level:1, nesting depth:5
Nesting level:2, nesting depth:1
Nesting level:1, nesting depth:2
Nesting level:1, nesting depth:1
Max loop nesting level: 5
```

Figure 8.23: Output code showing the result of using inherited, synthesized, and accumulator attributes.

```

#include <rose.h>

class NodeTypeCounter: public AstSimpleProcessing {
public:
    NodeTypeCounter(enum VariantT variant, std::string typeName)
        : myVariant(variant), typeName(typeName), count(0) {

protected:
    virtual void visit(SgNode *node) {
        if (node->variantT() == myVariant) {
            std::cout << "Found " << typeName << std::endl;
            count++;
        }
    }

    virtual void atTraversalEnd() {
        std::cout << typeName << " total: " << count << std::endl;
    }

private:
    enum VariantT myVariant;
    std::string typeName;
    unsigned int count;
};

int main(int argc, char **argv) {
    SgProject *project = frontend(argc, argv);

    std::cout << "sequential execution of traversals" << std::endl;
    NodeTypeCounter forStatementCounter(V_SgForStatement, "for loop");
    NodeTypeCounter intValueCounter(V_SgIntVal, "int constant");
    NodeTypeCounter varDeclCounter(V_SgVariableDeclaration, "variable declaration");
    // three calls to traverse, executed sequentially
    forStatementCounter.traverseInputFiles(project, preorder);
    intValueCounter.traverseInputFiles(project, preorder);
    varDeclCounter.traverseInputFiles(project, preorder);
    std::cout << std::endl;

    std::cout << "combined execution of traversals" << std::endl;
    AstCombinedSimpleProcessing combinedTraversal;
    combinedTraversal.addTraversal(new NodeTypeCounter(V_SgForStatement, "for loop"));
    combinedTraversal.addTraversal(new NodeTypeCounter(V_SgIntVal, "int constant"));
    combinedTraversal.addTraversal(new NodeTypeCounter(V_SgVariableDeclaration, "variable declaration"));
    // one call to traverse, execution is interleaved
    combinedTraversal.traverseInputFiles(project, preorder);
}

```

Figure 8.24: Example source showing the combination of traversals.

```

sequential execution of traversals
Found for loop
Found for loop
for loop total: 2
Found int constant
Found int constant
Found int constant
Found int constant
Found int constant
Found int constant
Found int constant
Found int constant
Found int constant
Found int constant
int constant total: 10
Found variable declaration
Found variable declaration
Found variable declaration
Found variable declaration
Found variable declaration
Found variable declaration
Found variable declaration
Found variable declaration
variable declaration total: 8

combined execution of traversals
Found variable declaration
Found int constant
Found variable declaration
Found for loop
Found variable declaration
Found int constant
Found int constant
Found variable declaration
Found int constant
Found int constant
Found variable declaration
Found int constant
Found variable declaration
Found int constant
Found for loop
Found variable declaration
Found int constant
Found int constant
Found variable declaration
Found int constant
for loop total: 2
int constant total: 10
variable declaration total: 8

```

Figure 8.25: Output of input file to the combined traversals. Note that the order of outputs changes as execution of several analyzers is interleaved.

8.2.12 Short-Circuiting Traversals

The traversal short-circuit mechanism is a simple way to cut short the traversal of a large AST once specific information has been obtained. It is purely an optimization mechanism, and a bit of a hack, but common within the C++ Boost community. Since the technique works we present it as a way of permitting users to avoid the full traversal of an AST that they might deem to be redundant or inappropriate. We don't expect that this mechanism will be particularly useful to most users and we don't recommend it. It may even at some point not be supported. However, we present it because it is a common technique used in the C++ Boost community and it happens to work (at one point it didn't work and so we have no idea what we fixed that permitted it to work now). We have regarded this technique as a rather ugly hack. It is presented in case you really need it. It is, we think, better than the direct use of lower level mechanisms that are used to support the AST traversal.

```
// Input for translator to show exception-based exiting from a translator.

namespace A
{
    int __go--;
    struct B
    {
        static int __stop--;
    };
};

void foo (void)
{
    extern void bar (int);
    bar (A::__go--);
    bar (A::B::__stop--);
}
```

Figure 8.26: Input code with used to demonstrate the traversal short-circuit mechanism.

Figure 8.27 shows the example code demonstrating a traversal setup to support the short-circuit mechanism (a conventional mechanism used often within the C++ Boost community). The input code shown in figure 8.26 is compiled using the example translator, the output is shown in figure 8.28.

The output shown in figure 8.28 demonstrates the initiation of a traversal over the AST and that traversal being short-circuited after a specific point in the evaluation. The result is that there is no further traversal of the AST after that point where it is short-circuited.

```
// Example of an AST traversal that uses the Boost idiom of throwing
// an exception to exit the traversal early.

#include <rose.h>
#include <string>
#include <iostream>

using namespace std;

// Exception to indicate an early exit from a traversal at some node.
class StopEarly
{
public:
    StopEarly (const SgNode* n) : exit_node_ (n) {}
    StopEarly (const StopEarly& e) : exit_node_ (e.exit_node_) {}

    // Prints information about the exit node.
    void print (ostream& o) const
    {
        if (exit_node_) {
            o << '\t' << (const void *)exit_node_ << ":" << exit_node_>class_name () << endl;
            const SgLocatedNode* loc_n = isSgLocatedNode (exit_node_);
            if (loc_n) {
                const Sg_File_Info* info = loc_n->get_startOfConstruct ();
                ROSE_ASSERT (info);
                o << "\tAt " << info->get_filename () << ":" << info->get_line () << endl;
            }
        }
    }

private:
    const SgNode* exit_node_; // Node at early exit from traversal
};

// Preorder traversal to find the first SgVarRefExp of a particular name.
class VarRefFinderTraversal : public AstSimpleProcessing
{
public:
    // Initiate traversal to find 'target' in 'proj'.
    void find (SgProject* proj, const string& target)
    {
        target_ = target;
        traverseInputFiles (proj, preorder);
    }

    void visit (SgNode* node)
    {
        const SgVarRefExp* ref = isSgVarRefExp (node);
        if (ref) {
            const SgVariableSymbol* sym = ref->get_symbol ();
            ROSE_ASSERT (sym);
            cout << " Visiting SgVarRef " << sym->get_name ().str () << " " << endl;
            if (sym->get_name ().str () == target_) // Early exit at first match.
                throw StopEarly (ref);
        }
    }

private:
    string target_; // Symbol reference name to find.
};

int main (int argc, char* argv[])
{
    SgProject* proj = frontend (argc, argv);
    VarRefFinderTraversal finder;

    // Look for a reference to "--stop--".
    try {
        finder.find (proj, "--stop--");
        cout << "*** Reference to a symbol '--stop--' not found. ***" << endl;
    } catch (StopEarly& stop) {
        cout << "*** Reference to a symbol '--stop--' found. ***" << endl;
        stop.print (cout);
    }

    // Look for a reference to "--go--".
    try {
        finder.find (proj, "--go--");
        cout << "*** Reference to a symbol '--go--' not found. ***" << endl;
    } catch (StopEarly& go) {
        cout << "*** Reference to a symbol '--go--' found. ***" << endl;
        go.print (cout);
    }
}
```

```
Visiting SgVarRef '__go__'
Visiting SgVarRef '__stop__'
*** Reference to a symbol '__stop__' found. ***
    0x8335cc4:SgVarRefExp
    At /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_traversalShortCircuit.C:1
Visiting SgVarRef '__go__'
*** Reference to a symbol '__go__' found. ***
    0x8335c98:SgVarRefExp
    At /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_traversalShortCircuit.C:1
```

Figure 8.28: Output code showing the result of short-circuiting the traversal.

8.3 Memory Pool Traversals

Allocation of IR nodes in ROSE is made more efficient through the use of specialized allocators implemented at member function new operators for each class of the IR in Sage III. Such specialized memory allocators avoid significant fragmentation of memory, provide more efficient packing of memory, improve performance of allocation of memory and IR node access, and additionally provide a secondary mechanism to accessing all the IR nodes. Each IR node has a memory pool which is an STL vector of blocks (a fixed or variable sized array of contiguously stored IR nodes).

The three types of traversals are:

1. ROSE Memory Pool Visit Traversal

This traversal is similar to the one provided by the SimpleProcessing Class (using the visit() function and no inherited or synthesized attributes).

2. Classic Object-Oriented Visitor Pattern for Memory Pool

This is a classic object-oriented visitor pattern.

3. IR node type traversal, visits one type of IR node for all IR types in the AST. This is useful for building specialized tools.

8.3.1 ROSE Memory Pool Visit Traversal

Figure 8.29 shows the source code for a translator which traverses the memory pool containing the AST. At each node the visit() function is called using only the input information represented by the current node. Note that using this simple traversal no context information is available to the visit function. All the IR nodes for a given memory pool are iterated over at one time. The order of the traversal of the different memory pools is random but fixed. Thus the order of the traversal of the IR nodes is in no way connected to the structure of the AST (unlike the previous non-memory pool traversals that were very much tied to the structure of the AST and which matched the structure of the original input source code being compiled).

```

#include "rose.h"

// ROSE Visit Traversal (similar interface as Markus's visit traversal)
// in ROSE (implemented using the traversal over
// the elements stored in the memory pools so it has no cycles and visits
// ALL IR nodes (including all Sg_File_Info, SgSymbols, SgTypes, and the
// static builtin SgTypes).
class RoseVisitor : public ROSE_VisitTraversal
{
public:
    int counter;
    void visit ( SgNode* node);

    RoseVisitor() : counter(0) {}
};

void RoseVisitor::visit ( SgNode* node)
{
    // printf ("roseVisitor::visit: counter %4d node = %s \n",counter,node->class_name().c_str());
    counter++;
}

int
main ( int argc, char* argv[] )
{
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT (project != NULL);

    // ROSE visit traversal
    RoseVisitor visitor;
    visitor.traverseMemoryPool();

    printf ("Number of IR nodes in AST = %d \n",visitor.counter);

    return backend(project);
}

```

Figure 8.29: Example source showing simple visit traversal over the memory pools.

```

Number of IR nodes in AST = 1827

```

Figure 8.30: Output of input file to the visitor traversal over the memory pool.

8.3.2 Classic Object-Oriented Visitor Pattern for Memory Pool

Figure 8.31 shows the source code for a translator which traverses the memory pools containing the AST. At each node the `visit()` function is called using only the input information represented by the current node. Note that using this simple traversal no context information is available to the visit function. The traversal order is the same as in the 8.29.

```
#include "rose.h"

// Classic Visitor Pattern in ROSE (implemented using the traversal over
// the elements stored in the memory pools so it has no cycles and visits
// ALL IR nodes (including all Sg_File_Info, SgSymbols, SgTypes, and the
// static builtin SgTypes).
class ClassicVisitor : public ROSE_VisitorPattern
{
public:
    // Override virtual function defined in base class
    void visit(SgGlobal* globalScope)
    {
        printf ("Found the SgGlobal IR node \n");
    }

    void visit(SgFunctionDeclaration* functionDeclaration)
    {
        printf ("Found a SgFunctionDeclaration IR node \n");
    }
    void visit(SgTypeInt* intType)
    {
        printf ("Found a SgTypeInt IR node \n");
    }

    void visit(SgTypeDouble* doubleType)
    {
        printf ("Found a SgTypeDouble IR node \n");
    }
};

int
main ( int argc, char* argv[] )
{
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT (project != NULL);

    // Classic visitor pattern over the memory pool of IR nodes
    ClassicVisitor visitor_A;
    traverseMemoryPoolVisitorPattern(visitor_A);

    return backend(project);
}
```

Figure 8.31: Example source showing simple visitor pattern.

[illegible]

8.3.3 ROSE IR Type Traversal (uses Memory Pools)

Figure 8.33 shows the source code for a translator which traverses only one type of IR node using the memory pool containing the AST. This traversal is useful for building specialized tools (often tools which only call static functions on each type of IR node).

This example shows the use of an alternative traversal which traverses a representative of each type of IR node just one, but only if it exists in the AST (memory pools). This sort of traversal is useful for building tools that need only operate on static member functions of the IR nodes or need only sample one of each type of IR node present in the AST. this specific example also appears in: *ROSE/src/midend/astDiagnostics/AstStatistics.C*.

The user's use of the traversal is the same as for other ROSE AST traversals except that the `ROSE_VisitTraversal::traverseRepresentativeIRnodes()` member function is called instead of `ROSE_VisitTraversal::traverseMemoryPool()`.

This mechanism can be used to generate more complete reports of the memory consumption of the AST, which is reported on if `-rose:verbose 2` is used. Figure 8.35 shows a partial snapshot of current IR node frequency and memory consumption for a moderate 40,000 line source code file (one file calling a number of header files), sorted by memory consumption. The AST contains approximately 280K IR nodes. Note that the `Sg_File_Info` IR nodes is most frequent and consumes the greatest amount of memory, this reflects our bias toward preserving significant information about the mapping of language constructs back to the positions in the source file to support a rich set of source-to-source functionality. *Note: more complete information about the memory use of the AST in in the ROSE User Manual appendix.*

```

// This example code shows the traversal of IR types not available using the other traversal mechanism.
#include "rose.h"
using namespace std;

// CPP Macro to implement case for each IR node (we could alternatively use a visitor pattern and a function t
#define IR_NODE_VISIT_CASE(X) \
    case V_##X: \
    { \
        X* castNode = is##X(node); \
        int numberOfNodes = castNode->numberOfNodes(); \
        int memoryFootprint = castNode->memoryUsage(); \
        printf ("count = %7d, memory use = %7d bytes, node name = %s \n", numberOfNodes, memoryFootprint, \
        break; \
    }

class RoseIRnodeVisitor : public ROSE_VisitTraversal {
public:
    int counter;
    void visit ( SgNode* node);
    RoseIRnodeVisitor() : counter(0) {}
};

void RoseIRnodeVisitor::visit ( SgNode* node)
{
    // Using a classic visitor pattern should avoid all this casting,
    // but each function must be created separately (so it is wash if
    // we want to do all IR nodes, as we do here).
    switch(node->variantT())
    {
        IR_NODE_VISIT_CASE(Sg_File_Info)
        IR_NODE_VISIT_CASE(SgPartialFunctionType)
        IR_NODE_VISIT_CASE(SgFunctionType)
        IR_NODE_VISIT_CASE(SgPointerType)
        IR_NODE_VISIT_CASE(SgFunctionDeclaration)
        IR_NODE_VISIT_CASE(SgFunctionSymbol)
        IR_NODE_VISIT_CASE(SgSymbolTable)
        IR_NODE_VISIT_CASE(SgInitializedName)
        IR_NODE_VISIT_CASE(SgStorageModifier)
        IR_NODE_VISIT_CASE(SgForStatement)
        IR_NODE_VISIT_CASE(SgForInitStatement)
        IR_NODE_VISIT_CASE(SgCtorInitializerList)
        IR_NODE_VISIT_CASE(SgIfStmt)
        IR_NODE_VISIT_CASE(SgExprStatement)
        IR_NODE_VISIT_CASE(SgTemplateDeclaration)
        IR_NODE_VISIT_CASE(SgTemplateInstantiationDecl)
        IR_NODE_VISIT_CASE(SgTemplateInstantiationDefn)
        IR_NODE_VISIT_CASE(SgTemplateInstantiationMemberFunctionDecl)
        IR_NODE_VISIT_CASE(SgClassSymbol)
        IR_NODE_VISIT_CASE(SgTemplateSymbol)
        IR_NODE_VISIT_CASE(SgMemberFunctionSymbol)

        default:
        {
            printf (" Case not handled: %s \n", node->class_name().c_str());
        }
    }
}

int
main ( int argc, char* argv[] )
{
    // ROSE visit traversal
    SgProject* project = frontend(argc, argv);
    ROSE_ASSERT (project != NULL);

    // ROSE visit traversal
    RoseIRnodeVisitor visitor;
    visitor.traverseRepresentativeIRnodes();
    printf ("Number of types of IR nodes (after building AST) = %d \n", visitor.counter);

    #if 1
    // IR nodes statistics
    if (project->get_verbose() > 1)
        cout << AstNodeStatistics::IRnodeUsageStatistics();
    #endif

    int errorCode = 0;
    errorCode = backend(project);

    return errorCode;
}

```

```

count =      12, memory use =      912 bytes, node name = SgSymbolTable
count =     124, memory use =    16864 bytes, node name = SgInitializedName
count =     124, memory use =     2976 bytes, node name = SgStorageModifier
count =     720, memory use =    31680 bytes, node name = Sg_File_Info
No representative for SgPartialFunctionType found in memory pools
count =     86, memory use =     4816 bytes, node name = SgFunctionType
count =     34, memory use =     1496 bytes, node name = SgPointerType
count =      2, memory use =     272 bytes, node name = SgForStatement
count =      2, memory use =     104 bytes, node name = SgForInitStatement
count =      4, memory use =    1168 bytes, node name = SgCtorInitializerList
count =      1, memory use =     144 bytes, node name = SgIfStmt
count =      9, memory use =     396 bytes, node name = SgExprStatement
count =      6, memory use =    2040 bytes, node name = SgTemplateDeclaration
count =      5, memory use =    1920 bytes, node name = SgTemplateInstantiationDecl
count =      1, memory use =     148 bytes, node name = SgTemplateInstantiationDefn
count =      3, memory use =    1476 bytes, node name = SgTemplateInstantiationMemberFunctionDecl
count =     92, memory use =   40848 bytes, node name = SgFunctionDeclaration
count =      1, memory use =      24 bytes, node name = SgClassSymbol
count =      3, memory use =      72 bytes, node name = SgTemplateSymbol
count =      2, memory use =      48 bytes, node name = SgMemberFunctionSymbol
count =     86, memory use =    2064 bytes, node name = SgFunctionSymbol
Number of types of IR nodes (after building AST) = 0

```

Figure 8.34: Output of input file to the IR Type traversal over the memory pool.

```

AST Memory Pool Statistics: numberOfNodes = 114081 memory consumption = 5019564 node = Sg_File_Info
AST Memory Pool Statistics: numberOfNodes = 31403 memory consumption = 628060 node = SgTypedefSeq
AST Memory Pool Statistics: numberOfNodes = 14254 memory consumption = 285080 node = SgStorageModifier
AST Memory Pool Statistics: numberOfNodes = 14254 memory consumption = 1140320 node = SgInitializedName
AST Memory Pool Statistics: numberOfNodes = 8458 memory consumption = 169160 node = SgFunctionParameterTypeList
AST Memory Pool Statistics: numberOfNodes = 7868 memory consumption = 1101520 node = SgModifierType
AST Memory Pool Statistics: numberOfNodes = 7657 memory consumption = 398164 node = SgClassType
AST Memory Pool Statistics: numberOfNodes = 7507 memory consumption = 2071932 node = SgClassDeclaration
AST Memory Pool Statistics: numberOfNodes = 7060 memory consumption = 282400 node = SgTemplateArgument
AST Memory Pool Statistics: numberOfNodes = 6024 memory consumption = 385536 node = SgPartialFunctionType
AST Memory Pool Statistics: numberOfNodes = 5985 memory consumption = 1388520 node = SgFunctionParameterList
AST Memory Pool Statistics: numberOfNodes = 4505 memory consumption = 1477640 node = SgTemplateInstantiationDecl
AST Memory Pool Statistics: numberOfNodes = 3697 memory consumption = 162668 node = SgReferenceType
AST Memory Pool Statistics: numberOfNodes = 3270 memory consumption = 758640 node = SgCtorInitializerList
AST Memory Pool Statistics: numberOfNodes = 3178 memory consumption = 76272 node = SgMemberFunctionSymbol
AST Memory Pool Statistics: numberOfNodes = 2713 memory consumption = 119372 node = SgPointerType
AST Memory Pool Statistics: numberOfNodes = 2688 memory consumption = 161280 node = SgThrowOp
AST Memory Pool Statistics: numberOfNodes = 2503 memory consumption = 60072 node = SgFunctionSymbol
AST Memory Pool Statistics: numberOfNodes = 2434 memory consumption = 107096 node = SgFunctionTypeSymbol
AST Memory Pool Statistics: numberOfNodes = 2418 memory consumption = 831792 node = SgFunctionDeclaration
AST Memory Pool Statistics: numberOfNodes = 2304 memory consumption = 55296 node = SgVariableSymbol
AST Memory Pool Statistics: numberOfNodes = 2298 memory consumption = 101112 node = SgVarRefExp
AST Memory Pool Statistics: numberOfNodes = 2195 memory consumption = 114140 node = SgSymbolTable
AST Memory Pool Statistics: numberOfNodes = 2072 memory consumption = 721056 node = SgMemberFunctionDeclaration
AST Memory Pool Statistics: numberOfNodes = 1668 memory consumption = 400320 node = SgVariableDeclaration
AST Memory Pool Statistics: numberOfNodes = 1667 memory consumption = 393412 node = SgVariableDefinition
AST Memory Pool Statistics: numberOfNodes = 1579 memory consumption = 101056 node = SgMemberFunctionType
AST Memory Pool Statistics: numberOfNodes = 1301 memory consumption = 31224 node = SgTemplateSymbol
AST Memory Pool Statistics: numberOfNodes = 1300 memory consumption = 364000 node = SgTemplateDeclaration
AST Memory Pool Statistics: numberOfNodes = 1198 memory consumption = 455240 node = SgTemplateInstantiationMemberFunctionDecl
AST Memory Pool Statistics: numberOfNodes = 1129 memory consumption = 54192 node = SgIntVal
AST Memory Pool Statistics: numberOfNodes = 1092 memory consumption = 56784 node = SgAssignInitializer
AST Memory Pool Statistics: numberOfNodes = 1006 memory consumption = 52312 node = SgExpressionRoot

```

Truncated results presented ...

Figure 8.35: Example of output using -rose:verbose 2 (memory use report for AST).

Chapter 9

AST Query

This chapter presents a mechanism for simple queries on the AST. Such queries are typically a single line of code, instead of the class that much be declared and defined when using the traversal mechanism. While the traversal mechanism is more sophisticated and more powerful, the AST Query mechanism is particularly simple to use.

9.1 Simple Queries on the AST

This section demonstrates a simple query on the AST.

The program in figure 9.1 calls an internal ROSE Query Library. Queries of the AST using the query library are particularly simple and often are useful as nested queries within more complex analysis. More information of the ROSE AST Query Library is available within ROSE User Manual.

Using the input program in figure 9.2 the translator processes the code and generates the output in figure 9.3.

FIXME: *Put an example of composition of AST queries into the example input code.*

9.2 Nested Query

This section demonstrates a nested AST query, showing how to use composition in the construction of more elaborate queries from simple ones.

The number of traversals of the AST can be reduced by using nested queries. Nested queries permits queries on the result from a NodeQuery. Another advantage is that nested (combined) queries can be formed to query for information without writing new query, the nested query is a new query.

The program in figure 9.4 calls an internal ROSE Query Library. Two different queries are performed to find all access functions within the AST. The first query is nested, the returned list from a query is used in a traversal, and the second query queries the AST for the same nodes.

Using the input program in figure 9.5 the translator processes the code and generates the output in figure 9.6.

```

// Example ROSE Translator: used within ROSE/tutorial

#include "rose.h"

using namespace std;

int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT(project != NULL);

    // Build a list of functions within the AST
    Rose_STL_Container<SgNode*> functionDeclarationList = NodeQuery::querySubTree (project,V_SgFunctionDeclaration);

    int counter = 0;
    for (Rose_STL_Container<SgNode*>::iterator i = functionDeclarationList.begin(); i != functionDeclarationList.end(); i++)
    {
        // Build a pointer to the current type so that we can call the get_name() member function.
        SgFunctionDeclaration* functionDeclaration = isSgFunctionDeclaration(*i);
        ROSE_ASSERT(functionDeclaration != NULL);

        // DQ (3/5/2006): Only output the non-compiler generated IR nodes
        if ( (*i)->get_file_info()->isCompilerGenerated() == false )
        {
            // output the function number and the name of the function
            printf ("Function #%%2d name is %s at line %d \n",
                    counter++,functionDeclaration->get_name().str(),
                    functionDeclaration->get_file_info()->get_line());
        }
        else
        {
            // Output something about the compiler-generated builtin functions
            printf ("Compiler-generated (builtin) function #%%2d name is %s \n",
                    counter++,functionDeclaration->get_name().str());
        }
    }

    // Note: Show composition of AST queries

    return 0;
}

```

Figure 9.1: Example source code for translator to read an input program and generate a list of functions in the AST (queryLibraryExample.C).


```

// Templated class declaration used in template parameter example code
template <typename T>
class templateClass
{
    public:
        int x;

        void foo(int);
        void foo(double);
};

// Overloaded functions for testing overloaded function resolution
void foo(int);
void foo(double)
{
    int x = 1;
    int y;

    // Added to allow non-trivial CFG
    if (x)
        y = 2;
    else
        y = 3;
}

int main()
{
    foo(42);
    foo(3.14159265);

    templateClass<char> instantiatedClass;
    instantiatedClass.foo(7);
    instantiatedClass.foo(7.0);

    for (int i=0; i < 4; i++)
    {
        int x;
    }

    return 0;
}

```

Figure 9.2: Example source code used as input to program in figure 9.1 (queryLibraryExample.C).

```

Compiler-generated (builtin) function # 0 name is --builtin_copysign
Compiler-generated (builtin) function # 1 name is --builtin_copysignf
Compiler-generated (builtin) function # 2 name is --builtin_copysignl
Compiler-generated (builtin) function # 3 name is --builtin_acosf
Compiler-generated (builtin) function # 4 name is --builtin_acosl
Compiler-generated (builtin) function # 5 name is --builtin_asinf
Compiler-generated (builtin) function # 6 name is --builtin_asinl
Compiler-generated (builtin) function # 7 name is --builtin_atanf
Compiler-generated (builtin) function # 8 name is --builtin_atanl
Compiler-generated (builtin) function # 9 name is --builtin_atan2f
Compiler-generated (builtin) function #10 name is --builtin_atan2l
Compiler-generated (builtin) function #11 name is --builtin_ceilf
Compiler-generated (builtin) function #12 name is --builtin_ceil
Compiler-generated (builtin) function #13 name is --builtin_coshf
Compiler-generated (builtin) function #14 name is --builtin_coshl
Compiler-generated (builtin) function #15 name is --builtin_floorf
Compiler-generated (builtin) function #16 name is --builtin_floorl
Compiler-generated (builtin) function #17 name is --builtin_fmodf
Compiler-generated (builtin) function #18 name is --builtin_fmodl
Compiler-generated (builtin) function #19 name is --builtin_frexp
Compiler-generated (builtin) function #20 name is --builtin_frexp
Compiler-generated (builtin) function #21 name is --builtin_ldexpf
Compiler-generated (builtin) function #22 name is --builtin_ldexpl
Compiler-generated (builtin) function #23 name is --builtin_log10f
Compiler-generated (builtin) function #24 name is --builtin_log10l
Compiler-generated (builtin) function #25 name is --builtin_modff
Compiler-generated (builtin) function #26 name is --builtin_modfl
Compiler-generated (builtin) function #27 name is --builtin_powf
Compiler-generated (builtin) function #28 name is --builtin_powl
Compiler-generated (builtin) function #29 name is --builtin_sinhf
Compiler-generated (builtin) function #30 name is --builtin_sinhl
Compiler-generated (builtin) function #31 name is --builtin_tanf
Compiler-generated (builtin) function #32 name is --builtin_tanl
Compiler-generated (builtin) function #33 name is --builtin_tanhf
Compiler-generated (builtin) function #34 name is --builtin_tanhl
Compiler-generated (builtin) function #35 name is --builtin_powil
Compiler-generated (builtin) function #36 name is --builtin_powi
Compiler-generated (builtin) function #37 name is --builtin_powif
Compiler-generated (builtin) function #38 name is --builtin_strchr
Compiler-generated (builtin) function #39 name is --builtin_strchr
Compiler-generated (builtin) function #40 name is --builtin_strpbrk
Compiler-generated (builtin) function #41 name is --builtin_strstr
Compiler-generated (builtin) function #42 name is --builtin_nansf
Compiler-generated (builtin) function #43 name is --builtin_nans
Compiler-generated (builtin) function #44 name is --builtin_nansl
Compiler-generated (builtin) function #45 name is --builtin_fabs
Compiler-generated (builtin) function #46 name is --builtin_fabsf
Compiler-generated (builtin) function #47 name is --builtin_fabsl
Compiler-generated (builtin) function #48 name is --builtin_cosf
Compiler-generated (builtin) function #49 name is --builtin_cosl
Compiler-generated (builtin) function #50 name is --builtin_sinf
Compiler-generated (builtin) function #51 name is --builtin_sinl
Compiler-generated (builtin) function #52 name is --builtin_sqrtf
Compiler-generated (builtin) function #53 name is --builtin_sqrtl
Compiler-generated (builtin) function #54 name is --builtin_return_address
Compiler-generated (builtin) function #55 name is --builtin_frame_address
Compiler-generated (builtin) function #56 name is --builtin_expect
Compiler-generated (builtin) function #57 name is --builtin_prefetch
Compiler-generated (builtin) function #58 name is --builtin_huge_val
Compiler-generated (builtin) function #59 name is --builtin_huge_valf
Compiler-generated (builtin) function #60 name is --builtin_huge_vall
Compiler-generated (builtin) function #61 name is --builtin_inf
Compiler-generated (builtin) function #62 name is --builtin_inff
Compiler-generated (builtin) function #63 name is --builtin_infl
Compiler-generated (builtin) function #64 name is --builtin_nan
Compiler-generated (builtin) function #65 name is --builtin_nanf
Compiler-generated (builtin) function #66 name is --builtin_nanl
Compiler-generated (builtin) function #67 name is --builtin_nans
Compiler-generated (builtin) function #68 name is --builtin_nansf
Compiler-generated (builtin) function #69 name is --builtin_nansl
Compiler-generated (builtin) function #70 name is --builtin_clz
Compiler-generated (builtin) function #71 name is --builtin_ctz
Compiler-generated (builtin) function #72 name is --builtin_popcount
Compiler-generated (builtin) function #73 name is --builtin_parity
Compiler-generated (builtin) function #74 name is --builtin_ffsl
Compiler-generated (builtin) function #75 name is --builtin_clzl
Compiler-generated (builtin) function #76 name is --builtin_ctzl
Compiler-generated (builtin) function #77 name is --builtin_popcountl
Compiler-generated (builtin) function #78 name is --builtin_parityl
Compiler-generated (builtin) function #79 name is --builtin_ffsl
Compiler-generated (builtin) function #80 name is --builtin_clzll
Compiler-generated (builtin) function #81 name is --builtin_ctzll
Compiler-generated (builtin) function #82 name is --builtin_popcountll

```

```

// Example ROSE Translator: used within ROSE/tutorial

#include "rose.h"

using namespace std;

// Function querySolverAccessFunctions()
// find access functions (function name starts with "get_" or "set_")
NodeQuerySynthesizedAttributeType
querySolverAccessFunctions (SgNode * astNode)
{
    ROSE_ASSERT (astNode != 0);
    NodeQuerySynthesizedAttributeType returnNodeList;

    SgFunctionDeclaration* funcDecl = isSgFunctionDeclaration(astNode);

    if (funcDecl != NULL)
    {
        string functionName = funcDecl->get_name().str();
        if ( (functionName.length() >= 4) && ((functionName.substr(0,4) == "get_") || (functionName.substr(0,4) == "set_")) )
            returnNodeList.push_back (astNode);
    }

    return returnNodeList;
}

// Function printFunctionDeclarationList will print all function names in the list
void printFunctionDeclarationList(Rose_STL_Container<SgNode*> functionDeclarationList)
{
    int counter = 0;
    for (Rose_STL_Container<SgNode*>::iterator i = functionDeclarationList.begin(); i != functionDeclarationList.end(); i++)
    {
        // Build a pointer to the current type so that we can call the get_name() member function.
        SgFunctionDeclaration* functionDeclaration = isSgFunctionDeclaration(*i);
        ROSE_ASSERT(functionDeclaration != NULL);

        // output the function number and the name of the function
        printf ("function name #%d is %s at line %d \n",
            counter++,functionDeclaration->get_name().str(),
            functionDeclaration->get_file_info()->get_line());
    }
}

int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT(project != NULL);

    // Build a list of functions within the AST and find all access functions
    // (function name starts with "get_" or "set_")

    // Build list using a query of the whole AST
    Rose_STL_Container<SgNode*> functionDeclarationList = NodeQuery::querySubTree (project, V_SgFunctionDeclaration);

    // Build list using nested Queries (operating on return result of previous query)
    Rose_STL_Container<SgNode*> accessFunctionsList;
    accessFunctionsList = NodeQuery::queryNodeList (functionDeclarationList,&querySolverAccessFunctions);
    printFunctionDeclarationList(accessFunctionsList);

    // Alternative form of same query building the list using a query of the whole AST
    accessFunctionsList = NodeQuery::querySubTree (project,&querySolverAccessFunctions);
    printFunctionDeclarationList(accessFunctionsList);

    // Another way to query for collections of IR nodes
    VariantVector vv1 = V_SgClassDefinition;
    std::cout << "Number of class definitions in the memory pool is: " << NodeQuery::queryMemoryPool(vv1).size() << std::endl;

    // Another way to query for collections of multiple IR nodes.
    // VariantVector(V_SgType) is internally expanded to all IR nodes derived from SgType.
    VariantVector vv2 = VariantVector(V_SgClassDefinition) + VariantVector(V_SgType);
    std::cout << "Number of class definitions AND types in the memory pool is: " << NodeQuery::queryMemoryPool(vv2).size() << std::endl;

    // Note: Show composition of AST queries

    return 0;
}

```

Figure 9.4: Example source code for translator to read an input program and generate a list of access functions in the AST (nestedQueryExample.C).

```

// Templated class declaration used in template parameter example code
template <typename T>
class templateClass
{
    public:
        int x;

        void foo(int);
        void foo(double);
};

// Overloaded functions for testing overloaded function resolution
void foo(int);
void foo(double)
{
    int x = 1;
    int y;

    // Added to allow non-trivial CFG
    if (x)
        y = 2;
    else
        y = 3;
}

int main()
{
    foo(42);
    foo(3.14159265);

    templateClass<char> instantiatedClass;
    instantiatedClass.foo(7);
    instantiatedClass.foo(7.0);

    for (int i=0; i < 4; i++)
    {
        int x;
    }

    return 0;
}

```

Figure 9.5: Example source code used as input to program in figure 9.4 (nestedQueryExample.C).

```

function name #0 is get_foo at line 0
function name #1 is set_foo at line 0
function name #2 is get_foo at line 28
function name #3 is set_foo at line 29
function name #0 is get_foo at line 0
function name #1 is set_foo at line 0
function name #2 is get_foo at line 28
function name #3 is set_foo at line 29
Number of class definitions in the memory pool is: 1
Number of class definitions AND types in the memory pool is: 168

```

Figure 9.6: Output of input file to the AST query processor (nestedQueryExample.C).

Chapter 10

AST File I/O

Figure 10.1 shows an example of how to use the AST File I/O mechanism. This chapter presents an example translator to write out an AST to a file and then read it back in.

10.1 Source Code for File I/O

Figure 10.1 shows an example translator which reads an input application, forms the AST, writes out the AST to a file, then deletes the AST and reads the AST from the previously written file.

The input code is shown in figure 10.2, the output of this code is shown in figure 10.3.

10.2 Input to Demonstrate File I/O

Figure 10.2 shows the example input used for demonstration of the AST file I/O. In this case we are reusing the example used in the inlining example.

10.3 Output from File I/O

Figure 10.3 shows the output from the example file I/O tutorial example.

10.4 Final Code After Passing Through File I/O

Figure 10.4 shows the same file as the input demonstrating that the file I/O didn't change the resulting generated code. *Much more sophisticated tests are applied internally to verify the correctness of the AST after AST file I/O.*

```

// Example demonstrating function inlining (maximal inlining, up to preset number of inlinings).
#include "rose.h"

using namespace std;

// This is a function in Qing's AST interface
void FixSgProject(SgProject& proj);

int main (int argc, char* argv[])
{
    // Build the project object (AST) which we will fill up with multiple files and use as a
    // handle for all processing of the AST(s) associated with one or more source files.
    SgProject* project = new SgProject(argc, argv);

    // DQ (7/20/2004): Added internal consistency tests on AST
    AstTests::runAllTests(project);

    bool modifiedAST = true;
    int count = 0;

    // Inline one call at a time until all have been inlined. Loops on recursive code.
    do {
        modifiedAST = false;

        // Build a list of functions within the AST
        Rose_STL_Container<SgNode*> functionCallList = NodeQuery::querySubTree (project, V_SgFunctionCallExp);

        // Loop over all function calls
        // for (list<SgNode*>::iterator i = functionCallList.begin(); i != functionCallList.end(); i++)
        Rose_STL_Container<SgNode*>::iterator i = functionCallList.begin();
        while (modifiedAST == false && i != functionCallList.end())
        {
            SgFunctionCallExp* functionCall = isSgFunctionCallExp(*i);
            ROSE_ASSERT(functionCall != NULL);

            // Not all function calls can be inlined in C++, so report if successful.
            bool successfullyInlined = doInline(functionCall);

            if (successfullyInlined == true)
            {
                // As soon as the AST is modified recompute the list of function
                // calls (and restart the iterations over the modified list)
                modifiedAST = true;
            }
            else
            {
                modifiedAST = false;
            }

            // Increment the list iterator
            i++;
        }

        // Quite when we have ceased to do any inline transformations
        // and only do a predefined number of inline transformations
        count++;
    }
    while(modifiedAST == true && count < 10);

    // Call function to postprocess the AST and fixup symbol tables
    FixSgProject(*project);

    // Rename each variable declaration
    renameVariables(project);

    // Fold up blocks
    flattenBlocks(project);

    // Clean up inliner-generated code
    cleanupInlinedCode(project);

    // Change members to public
    changeAllMembersToPublic(project);

    // DQ (3/11/2006): This fails so the inlining, or the AST Interface
    // support, needs more work even though it generated good code.
    // AstTests::runAllTests(project);

    return backend(project);
}

```

```

// This test code is a combination of pass1 and pass7, selected somewhat randomly
// from Jeremiah's test code of his inlining transformation from summer 2004.

int x = 0;

// Function to increment "x"
void incrementX()
{
    x++;
}

int foo()
{
    int a = 0;
    while (a < 5)
    {
        ++a;
    }

    return a + 3;
}

int main(int, char**)
{
    // Two trivial function calls to inline
    incrementX();
    incrementX();

    // Something more interesting to inline
    for (; foo() < 7;)
    {
        x++;
    }

    return x;
}

```

Figure 10.2: Example source code used as input to demonstrate the AST file I/O support.

```

Extending memory pools ... done
Setting data of AST #0

```

Figure 10.3: Output of input code after inlining transformations.

```

// This test code is a combination of pass1 and pass7, selected somewhat randomly
// from Jeremiah's test code of his inlining transformation from summer 2004.
int x = 0;
// Function to increment "x"

void incrementX()
{
    x++;
}

int foo()
{
    int a--0 = 0;
    while(a--0 < 5){
        ++a--0;
    }
    return a--0 + 3;
}

int main(int ,char **)
{
    x++;
    x++;
    // Something more interesting to inline
    for (; true; ) {
        int a--1 = 0;
        while(a--1 < 5){
            ++a--1;
        }
        int rose_temp--7--0 = a--1 + 3;
        bool rose__temp__2 = (bool )(rose_temp--7--0 < 7);
        if (!rose__temp__2) {
            break;
        }
        else {
        }
        x++;
    }
    return x;
}

```

Figure 10.4: Output of input code after file I/O.

Chapter 11

Debugging Techniques

There are numerous methods ROSE provides to help debug the development of specialized source-to-source translators. This section shows some of the techniques for getting information from IR nodes and displaying it. Show how to use the PDF generator for ASTs. This section may contain several subsections. More information about generation of specialized AST graphs to support debugging can be found in 6 and custom graph generation in 24.

11.1 Input For Examples Showing Debugging Techniques

Figure 11.1 shows the input code used for the example translators that report useful debugging information in this chapter.

```
// Example program showing matrix multiply
// (for use with loop optimization tutorial example)

#define N 50

int main()
{
    int i, j, k;
    double a[N][N], b[N][N], c[N][N];

    for (i = 0; i <= N-1; i+=1)
    {
        for (j = 0; j <= N-1; j+=1)
        {
            for (k = 0; k <= N-1; k+=1)
            {
                c[i][j] = c[i][j] + a[i][k] * b[k][j];
            }
        }
    }

    return 0;
}
```

Figure 11.1: Example source code used as input to program in codes showing debugging techniques shown in this section.

11.2 Generating the code from any IR node

Any IR node may be converted to the string that represents its subtree within the AST. It is is a type then it the string will be the value of the type, if it is a statement the value will be the source code associated with that statement, including any sub-statements. To support the generation for strings from IR nodes we use the `unparseToString()` member function. This function strips comments and preprocessor control structure. The resulting string is useful for both debugging and when forming larger strings associated with the specification of transformations using the string-based rewrite mechanism. Using ROSE IR nodes may be converted to string and string converted to AST fragments of IR nodes.

Note that unparsing associated with generating source code for the backend vendor compiler in however as more than just calling the `unparseToString` member function since it introduces comments, preprocessor control structure and formatting.

Figure 11.2 shows a translator which generates a string for a number of predefined IR nodes. Figure 11.1 shows the sample input code and figure 11.5 shows the output from the translator when using the example input application.

11.3 Displaying the source code position of any IR node

This example shows how to obtain information about the position of any IR node relative to where it appeared in the original source code. New IR nodes (or subtrees) that are added to the AST as part of a transformation will be marked as part of a transformation and have no position in the source code. Shared IR nodes (as generated by the AST merge mechanism are marked as shared explicitly (other IR nodes that are shared by definition don't have a `SgFileInfo` object and are thus not marked explicitly as shared).

The example translator to output the source code position is shown in figure 11.4. Using the input code in figure 11.1 the output code is shown in figure 11.5.

```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// rose.C: Example (default) ROSE Preprocessor: used for testing ROSE infrastructure

#include "rose.h"

using namespace std;

int
main ( int argc, char* argv[] )
{
    ios::sync_with_stdio();          // Syncs C++ and C I/O subsystems!

    if (SgProject::get_verbose() > 0)
        printf ("In preprocessor.C: main() \n");

    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT (project != NULL);

    // AST diagnostic tests
    AstTests::runAllTests(const_cast<SgProject*>(project));

    // test statistics
    if (project->get_verbose() > 1)
    {
        cout << AstNodeStatistics::traversalStatistics(project);
        cout << AstNodeStatistics::IRnodeUsageStatistics();
    }

    if (project->get_verbose() > 0)
        printf ("Generate the pdf output of the SAGE III AST \n");
    generatePDF ( *project );

    if (project->get_verbose() > 0)
        printf ("Generate the DOT output of the SAGE III AST \n");
    generateDOT ( *project );

    Rose_STL_Container<SgNode*> nodeList;
    // nodeList = NodeQuery::querySubTree (project, V_SgType, NodeQuery::ExtractTypes);
    nodeList = NodeQuery::querySubTree (project, V_SgForStatement);
    printf ("\nnodeList.size() = %zu \n", nodeList.size());

    Rose_STL_Container<SgNode*>::iterator i = nodeList.begin();
    while (i != nodeList.end())
    {
        printf ("Query node = %p = %s = %s \n", *i, (*i)->sage_class_name(), (*i)->unparseToString().c_str());
        i++;
    }

    return 0;
}

```

Figure 11.2: Example source code showing the output of the string from an IR node. The string represents the code associated with the subtree of the target IR node.

```

nodeList.size() = 3
Query node = 0xb7d13008 = SgForStatement = for(i = 0; i <=(50 - 1); i += 1) {for(j = 0; j <=(50 - 1); j += 1) {for(k = 0; k <=
Query node = 0xb7d13090 = SgForStatement = for(j = 0; j <=(50 - 1); j += 1) {for(k = 0; k <=(50 - 1); k += 1) {(c[i])[j] =(((
Query node = 0xb7d13118 = SgForStatement = for(k = 0; k <=(50 - 1); k += 1) {(c[i])[j] =(((c[i])[j]) +(((a[i])[k]) *((b[k])

```

Figure 11.3: Output of input code using debuggingIRnodeToString.C

```
// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// rose.C: Example (default) ROSE Preprocessor: used for testing ROSE infrastructure

#include "rose.h"

using namespace std;

int
main ( int argc, char* argv[] )
{
    if (SgProject::get_verbose() > 0)
        printf ("In preprocessor.C: main() \n");

    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT (project != NULL);

    Rose_STL_Container<SgNode*> nodeList;
    nodeList = NodeQuery::querySubTree (project, V_SgForStatement);
    printf ("\nnodeList.size() = %zu \n",nodeList.size());

    Rose_STL_Container<SgNode*>::iterator i = nodeList.begin();
    while (i != nodeList.end())
    {
        Sg_File_Info & fileInfo = *((*i)->get_file_info());
        printf ("Query node = %p = %s in %s \n ----- at line %d on column %d \n",
            *i,(*i)->sage_class_name(),fileInfo.get_filename(),
                fileInfo.get_line(), fileInfo.get_col());
        i++;
    }

    if (project->get_verbose() > 0)
        printf ("Calling the backend() \n");

    return 0;
}
```

Figure 11.4: Example source code showing the output of the string from an IR node. The string represents the code associated with the subtree of the target IR node.

```
nodeList.size() = 3
Query node = 0xb7d1a008 = SgForStatement in /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/in
----- at line 11 on column 6
Query node = 0xb7d1a090 = SgForStatement in /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/in
----- at line 13 on column 11
Query node = 0xb7d1a118 = SgForStatement in /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/in
----- at line 15 on column 16
```

Figure 11.5: Output of input code using debuggingSourceCodePositionInformation.C

Part II

Complex Types

This part elaborates some details for handling complex types in ROSE.

Chapter 12

Type and Declaration Modifiers

Most languages support the general concept of modifiers to types, declarations, etc. The keyword *volatile* for example is a modifier to the type where it is used in a declaration. Searching for the modifiers for types and declarations can however be confusing. They are often not where one would expect, and most often because of corner cases in the language that force them to be handled in specific ways.

This example tutorial code is a demonstration of a how to access the *volatile* modifier used in the declaration of types for variables. We demonstrate that the modifier is not present in the `SgVariableDeclaration` or the `SgVariableDefinition`, but is located in the `SgModifierType` used to wrap the type returned from the `SgInitializedName` (the variable in the variable declaration).

12.1 Input For Example Showing use of *volatile* type modifier

Figure 12.1 shows the example input used for demonstration of test for the *volatile* type modifier.

```
// Input example of use of "volatile" type modifier
volatile int a,*b;

void foo()
{
    for (volatile int y = 0; y < 10; y++)
    {
    }
```

Figure 12.1: Example source code used as input to program in codes used in this chapter.

12.2 Generating the code representing the seeded bug

Figure 12.2 shows a code that traverses each IR node and for and `SgInitializedName` IR node checks it type. The input code is shown in figure 12.1, the output of this code is shown in figure 12.3.

```
#include "rose.h"

using namespace std;

class visitorTraversal : public AstSimpleProcessing
{
public:
    void visit(SgNode* n);
};

void visitorTraversal::visit(SgNode* n)
{
    // The "volatile" modifier is in the type of the SgInitializedName
    SgInitializedName* initializedName = isSgInitializedName(n);
    if (initializedName != NULL)
    {
        printf ("Found a SgInitializedName = %s \n", initializedName->get_name().str());
        SgType* type = initializedName->get_type();

        printf ("    initializedName: type = %p = %s \n", type, type->class_name().c_str());
        SgModifierType* modifierType = isSgModifierType(type);
        if (modifierType != NULL)
        {
            bool isVolatile = modifierType->get_typeModifier().get_constVolatileModifier().isVolatile();
            printf ("    initializedName: SgModifierType: isVolatile = %s \n", (isVolatile == true) ? "true" : "false");
        }

        SgModifierNodes* modifierNodes = type->get_modifiers();
        printf ("    initializedName: modifierNodes = %p \n", modifierNodes);
        if (modifierNodes != NULL)
        {
            SgModifierTypePtrVector modifierList = modifierNodes->get_nodes();
            for (SgModifierTypePtrVector::iterator i = modifierList.begin(); i != modifierList.end(); i++)
            {
                printf ("    initializedName: modifiers: i = %s \n", (*i)->class_name().c_str());
            }
        }
    }

    // Note that the "volatile" modifier is not in the SgVariableDeclaration nor the SgVariableDefinition
    SgVariableDeclaration* variableDeclaration = isSgVariableDeclaration(n);
    if (variableDeclaration != NULL)
    {
        bool isVolatile = variableDeclaration->get_declarationModifier().get_typeModifier().get_constVolatileModifier().isVolatile();
        printf ("SgVariableDeclaration: isVolatile = %s \n", (isVolatile == true) ? "true" : "false");
        SgVariableDefinition* variableDefinition = variableDeclaration->get_definition();
        // printf ("variableDefinition = %p \n", variableDefinition);
        if (variableDefinition != NULL)
        {
            bool isVolatile = variableDefinition->get_declarationModifier().get_typeModifier().get_constVolatileModifier().isVolatile();
            printf ("SgVariableDefinition: isVolatile = %s \n", (isVolatile == true) ? "true" : "false");
        }
    }
}

// must have argc and argv here!!
int main(int argc, char * argv[])
{
    SgProject *project = frontend (argc, argv);

    visitorTraversal myvisitor;
    myvisitor.traverseInputFiles(project, preorder);

    return backend(project);
}
```

Figure 12.2: Example source code showing how to detect *volatile* modifier.


```
// Input example of use of "volatile" type modifier
volatile int a;
volatile int *b;

void foo()
{
    for (volatile int y = 0; y < 10; y++) {
    }
}
```

Figure 12.3: Output of input code using volatileTypeModifier.C

Chapter 13

Function Parameter Types

The analysis of functions often requires the query of the function types. This tutorial example shows how to obtain the function parameter types for any function. Note that functions also have a type which is based on their signature, a combination of their return type and functions parameter types. Any functions sharing the same return type and function parameter types have the same function type (the function type, a `SgFunctionType` IR node, will be shared between such functions).

Figure 13.1 shows a translator which reads an application (shown in figure 13.2) and outputs information about the function parameter types for each function, shown in figure 13.3. This information includes the order of the function declaration in the global scope, and name of the function, and the types of each parameter declared in the function declaration.

Note that there are a number of builtin functions defined as part of the GNU g++ and gcc compatibility and these are output as well. These are marked as compiler generated functions within ROSE. The code shows how to differentiate between the two different types. Notice also that instantiated template functions are classified as *compiler generated*.

```

// Example ROSE Translator: used within ROSE/tutorial
#include "rose.h"

using namespace std;

int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT(project != NULL);

    // Build a list of functions within the AST
    Rose_STL_Container<SgNode*> functionDeclarationList = NodeQuery::querySubTree (project,V_SgFunctionDeclaration);

    int functionCounter = 0;
    for (Rose_STL_Container<SgNode*>::iterator i = functionDeclarationList.begin(); i != functionDeclarationList.end(); i++)
    {
        // Build a pointer to the current type so that we can call the get_name() member function.
        SgFunctionDeclaration* functionDeclaration = isSgFunctionDeclaration(*i);
        ROSE_ASSERT(functionDeclaration != NULL);

        // DQ (3/5/2006): Only output the non-compiler generated IR nodes
        if ( (*i)->get_file_info()->isCompilerGenerated() == false )
        {
            SgFunctionParameterList* functionParameters = functionDeclaration->get_parameterList();
            ROSE_ASSERT(functionDeclaration != NULL);

            // output the function number and the name of the function
            printf ("Non-compiler generated function name #%3d is %s \n",functionCounter++,functionDeclaration->get_name());

            SgInitializedNamePtrList & parameterList = functionParameters->get_args();
            int parameterCounter = 0;
            for (SgInitializedNamePtrList::iterator j = parameterList.begin(); j != parameterList.end(); j++)
            {
                SgType* parameterType = (*j)->get_type();
                printf ("    parameterType #%2d = %s \n",parameterCounter++,parameterType->unparseToString());
            }
        }
        else
        {
            printf ("Compiler generated function name #%3d is %s \n",functionCounter++,functionDeclaration->get_name());
        }
    }

    return 0;
}

```

Figure 13.1: Example source code showing how to get type information from function parameters.

```

// Templated class declaration used in template parameter example code
template <typename T>
class templateClass
{
    public:
        int x;

        void foo(int);
        void foo(double);
};

// Overloaded functions for testing overloaded function resolution
void foo(int);
void foo(double)
{
    int x = 1;
    int y;

    // Added to allow non-trivial CFG
    if (x)
        y = 2;
    else
        y = 3;
}

int main ( int argc, char* argv[] )
{
    foo(42);
    foo(3.14159265);

    templateClass<char> instantiatedClass;
    instantiatedClass.foo(7);
    instantiatedClass.foo(7.0);

    for (int i=0; i < 4; i++)
    {
        int x;
    }

    return 0;
}

```

Figure 13.2: Example source code used as input to `typeInfoFromFunctionParameters.C`.

```

Compiler generated function name # 0 is __builtin_copysign
Compiler generated function name # 1 is __builtin_copysignf
Compiler generated function name # 2 is __builtin_copysignl
Compiler generated function name # 3 is __builtin_acosf
Compiler generated function name # 4 is __builtin_acosl
Compiler generated function name # 5 is __builtin_asinf
Compiler generated function name # 6 is __builtin_asinl
Compiler generated function name # 7 is __builtin_atanf
Compiler generated function name # 8 is __builtin_atanl
Compiler generated function name # 9 is __builtin_atan2f
Compiler generated function name # 10 is __builtin_atan2l
Compiler generated function name # 11 is __builtin_ceilf
Compiler generated function name # 12 is __builtin_ceil
Compiler generated function name # 13 is __builtin_coshf
Compiler generated function name # 14 is __builtin_coshl
Compiler generated function name # 15 is __builtin_floorf
Compiler generated function name # 16 is __builtin_floorl
Compiler generated function name # 17 is __builtin_fmodf
Compiler generated function name # 18 is __builtin_fmodl
Compiler generated function name # 19 is __builtin_frexp
Compiler generated function name # 20 is __builtin_frexp
Compiler generated function name # 21 is __builtin_ldexpf
Compiler generated function name # 22 is __builtin_ldexpl
Compiler generated function name # 23 is __builtin_log10f
Compiler generated function name # 24 is __builtin_log10l
Compiler generated function name # 25 is __builtin_modff
Compiler generated function name # 26 is __builtin_modfl
Compiler generated function name # 27 is __builtin_powf
Compiler generated function name # 28 is __builtin_powl
Compiler generated function name # 29 is __builtin_sinhf
Compiler generated function name # 30 is __builtin_sinh
Compiler generated function name # 31 is __builtin_tanf
Compiler generated function name # 32 is __builtin_tanl
Compiler generated function name # 33 is __builtin_tanhf
Compiler generated function name # 34 is __builtin_tanhl
Compiler generated function name # 35 is __builtin_powil
Compiler generated function name # 36 is __builtin_powi
Compiler generated function name # 37 is __builtin_powif
Compiler generated function name # 38 is __builtin_strchr
Compiler generated function name # 39 is __builtin_strchr
Compiler generated function name # 40 is __builtin_strpbrk
Compiler generated function name # 41 is __builtin_strstr
Compiler generated function name # 42 is __builtin_nansf
Compiler generated function name # 43 is __builtin_nans
Compiler generated function name # 44 is __builtin_nansl
Compiler generated function name # 45 is __builtin_fabs
Compiler generated function name # 46 is __builtin_fabsf
Compiler generated function name # 47 is __builtin_fabsl
Compiler generated function name # 48 is __builtin_cosf
Compiler generated function name # 49 is __builtin_cosl
Compiler generated function name # 50 is __builtin_sinf
Compiler generated function name # 51 is __builtin_sinl
Compiler generated function name # 52 is __builtin_sqrtf
Compiler generated function name # 53 is __builtin_sqrtl
Compiler generated function name # 54 is __builtin_return_address
Compiler generated function name # 55 is __builtin_frame_address
Compiler generated function name # 56 is __builtin_expect
Compiler generated function name # 57 is __builtin_prefetch
Compiler generated function name # 58 is __builtin_huge_val
Compiler generated function name # 59 is __builtin_huge_valf
Compiler generated function name # 60 is __builtin_huge_vall
Compiler generated function name # 61 is __builtin_inf
Compiler generated function name # 62 is __builtin_inff
Compiler generated function name # 63 is __builtin_infl
Compiler generated function name # 64 is __builtin_nan
Compiler generated function name # 65 is __builtin_nanf
Compiler generated function name # 66 is __builtin_nanl
Compiler generated function name # 67 is __builtin_nans
Compiler generated function name # 68 is __builtin_nansf
Compiler generated function name # 69 is __builtin_nansl
Compiler generated function name # 70 is __builtin_clz
Compiler generated function name # 71 is __builtin_ctz
Compiler generated function name # 72 is __builtin_popcount
Compiler generated function name # 73 is __builtin_parity
Compiler generated function name # 74 is __builtin_ffsl
Compiler generated function name # 75 is __builtin_clzl
Compiler generated function name # 76 is __builtin_ctzl
Compiler generated function name # 77 is __builtin_popcountl
Compiler generated function name # 78 is __builtin_parityl
Compiler generated function name # 79 is __builtin_ffsl
Compiler generated function name # 80 is __builtin_clzll
Compiler generated function name # 81 is __builtin_ctzll
Compiler generated function name # 82 is __builtin_popcountll

```

Chapter 14

Resolving Overloaded Functions

Figure 14.1 shows a translator which reads an application and reports on the mapping between function calls and function declarations. This is trivial since all overloaded function resolution is done within the frontend and so need not be computed (this is because all type resolution is done in the frontend and stored in the AST explicitly). Other compiler infrastructures often require this to be figured out from the AST, when type resolution is unavailable, and while not too hard for C, this is particularly complex for C++ (due to overloading and type promotion within function arguments).

Figure 14.2 shows the input code used to get the translator. Figure 14.3 shows the resulting output.

```

// Example ROSE Translator: used within ROSE/tutorial
#include "rose.h"

using namespace std;

int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT(project != NULL);

    // Build a list of functions within the AST
    Rose_STL_Container<SgNode*> functionCallList = NodeQuery::querySubTree (project,V_SgFunctionCallExp);

    int functionCounter = 0;
    for (Rose_STL_Container<SgNode*>::iterator i = functionCallList.begin(); i != functionCallList.end(); i++)
    {
        SgExpression* functionExpression = isSgFunctionCallExp(*i)->get_function();
        ROSE_ASSERT(functionExpression != NULL);

        SgFunctionRefExp* functionRefExp = isSgFunctionRefExp(functionExpression);

        SgFunctionSymbol* functionSymbol = NULL;
        if (functionRefExp != NULL)
        {
            // Case of non-member function
            functionSymbol = functionRefExp->get_symbol();
        }
        else
        {
            // Case of member function (hidden in rhs of binary dot operator expression)
            SgDotExp* dotExp = isSgDotExp(functionExpression);
            ROSE_ASSERT(dotExp != NULL);

            functionExpression = dotExp->get_rhs_operand();
            SgMemberFunctionRefExp* memberFunctionRefExp = isSgMemberFunctionRefExp(functionExpression);
            ROSE_ASSERT(memberFunctionRefExp != NULL);

            functionSymbol = memberFunctionRefExp->get_symbol();
        }

        ROSE_ASSERT(functionSymbol != NULL);

        SgFunctionDeclaration* functionDeclaration = functionSymbol->get_declaration();
        ROSE_ASSERT(functionDeclaration != NULL);

        // Output mapping of function calls to function declarations
        printf ("Location of function call #%d at line %d resolved by overloaded function declared at line %d\n",
            functionCounter++,
            isSgFunctionCallExp(*i)->get_file_info()->get_line(),
            functionDeclaration->get_file_info()->get_line());
    }

    return 0;
}

```

Figure 14.1: Example source code showing mapping of function calls to overloaded function declarations.


```

// Templated class declaration used in template parameter example code
template <typename T>
class templateClass
{
    public:
        int x;

        void foo(int);
        void foo(double);
};

// Overloaded functions for testing overloaded function resolution
void foo(int);
void foo(double)
{
    int x = 1;
    int y;

    // Added to allow non-trivial CFG
    if (x)
        y = 2;
    else
        y = 3;
}

int main()
{
    foo(42);
    foo(3.14159265);

    templateClass<char> instantiatedClass;
    instantiatedClass.foo(7);
    instantiatedClass.foo(7.0);

    for (int i=0; i < 4; i++)
    {
        int x;
    }

    return 0;
}

```

Figure 14.2: Example source code used as input to resolveOverloadedFunction.C.

```

Location of function call #0 at line 29 resolved by overloaded function declared at line 14
Location of function call #1 at line 30 resolved by overloaded function declared at line 15
Location of function call #2 at line 33 resolved by overloaded function declared at line 0
Location of function call #3 at line 34 resolved by overloaded function declared at line 0

```

Figure 14.3: Output of input to resolveOverloadedFunction.C.

Chapter 15

Template Parameter Extraction

```
// Example ROSE Translator: used within ROSE/tutorial
#include "rose.h"

using namespace std;

int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT(project != NULL);

    // Build a list of functions within the AST
    Rose_STL_Container<SgNode*> templateInstantiationDeclList =
        NodeQuery::querySubTree ( project, V_SgTemplateInstantiationDecl);

    int classTemplateCounter = 0;
    for (Rose_STL_Container<SgNode*>::iterator i = templateInstantiationDeclList.begin();
         i != templateInstantiationDeclList.end(); i++)
    {
        SgTemplateInstantiationDecl* instantiatedTemplateClass = isSgTemplateInstantiationDecl(*i);
        ROSE_ASSERT(instantiatedTemplateClass != NULL);

        // output the function number and the name of the function
        printf ("Class name #%d is %s \n",
                classTemplateCounter++,
                instantiatedTemplateClass->get_templateName().str());

        const SgTemplateArgumentPtrList& templateParameterList = instantiatedTemplateClass->get_templateArguments();
        int parameterCounter = 0;
        for (SgTemplateArgumentPtrList::const_iterator j = templateParameterList.begin();
             j != templateParameterList.end(); j++)
        {
            printf ("    TemplateArgument #%d = %s \n",parameterCounter++,(*j)->unparseToString().c_str());
        }
    }

    return 0;
}
```

Figure 15.1: Example source code used to extract template parameter information.

Figure 15.1 shows a translator which reads an application and gathers a list of loop nests. At the end of the traversal it reports information about each instantiated template, including the template arguments.

Figure 15.2 shows the input code used to get the translator. Figure 15.3 shows the resulting output.

```
// Templated class declaration used in template parameter example code
template <typename T>
class templateClass
{
    public:
        int x;

        void foo(int);
        void foo(double);
};

int main()
{
    templateClass<char> instantiatedClass;
    instantiatedClass.foo(7);
    instantiatedClass.foo(7.0);

    templateClass<int> instantiatedClassInt;
    templateClass<float> instantiatedClassFloat;
    templateClass<templateClass<char> > instantiatedClassNestedChar;

    for (int i=0; i < 4; i++)
    {
        int x;
    }

    return 0;
}
```

Figure 15.2: Example source code used as input to templateParameter.C.

```
Class name #0 is templateClass
  TemplateArgument #0 = char
Class name #1 is templateClass
  TemplateArgument #0 = int
Class name #2 is templateClass
  TemplateArgument #0 = float
Class name #3 is templateClass
  TemplateArgument #0 = templateClass< char >
```

Figure 15.3: Output of input to templateParameter.C.

Chapter 16

Template Support

This chapter is specific to demonstrating the C++ template support in ROSE. *This section is not an introduction to the general subject of C++ templates.* ROSE provides special handling for C++ templates because template instantiation must be controlled by the compiler.

Templates that require instantiation are instantiated by ROSE and can be seen in the traversal of the AST (and transformed). Any templates that can be instantiated by the backend compiler **and** *are not transformed* are not output within the code generation phase.

FIXME: *Provide a list of when templates are generated internally in the AST and when template instantiations are output.*

16.1 Example Template Code #1

This section presents figure 16.4, a simple C++ source code using a template. It is used as a basis for showing how template instantiations are handled within ROSE.

```
template <typename T>
class X
{
    public:
        void foo();
};

X<int> x;

void X<int >::foo()
{
}
```

Figure 16.1: Example source code showing use of a C++ template.

16.2 Example Template Code #2

This section presents figure 16.4, a simple C++ source code using a template function. It is used as a basis for showing how template instantiations are handled within ROSE.

```

template < typename T >
class X
{
    public :
        void foo ( );
};
class X< int > x;
template<> void X < int > ::foo()
{
}

```

Figure 16.2: Example source code after processing using identityTranslator (shown in figure 2.1).

```

// template function
template <typename T>
void foo( T t )
{
}

// Specialization from user
template<> void foo<int>(int x) {}

int main()
{
    foo(1);
}

```

Figure 16.3: Example source code showing use of a C++ template.

```

// template function
template < typename T >
void foo ( T t )
{
}
// Specialization from user
template<> void foo < int > (int x)
{
}

int main()
{
    foo < int > (1);
    return 0;
}

```

Figure 16.4: Example source code after processing using identityTranslator (shown in figure 2.1).

Part III

Program Analyses

This part exemplifies the use of existing ROSE analyses and how to build customized analyses using ROSE.

Chapter 17

Recognizing Loops

Figures 17.1 and 17.2 show a translator which reads an application and gathers a list of loop nests. At the end of the traversal it reports information about each loop nest, including the function where it occurred and the depth of the loop nest.

Using this translator we can compile the code shown in figure 17.3. The output is shown in figure 17.4.

FIXME: *This example program is unfinished. It will output a list of objects representing information about perfectly nested loops.*

```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// rose.C: Example (default) ROSE Preprocessor: used for testing ROSE infrastructure

#include "rose.h"

class InheritedAttribute
{
public:
    int loopNestDepth;

    InheritedAttribute () : loopNestDepth(0) {};
    InheritedAttribute ( const InheritedAttribute & X ) {};
};

class SynthesizedAttribute
{
public:
    SynthesizedAttribute() {};
};

class Traversal : public SgTopDownBottomUpProcessing<InheritedAttribute, SynthesizedAttribute>
{
public:
    // Functions required
    InheritedAttribute evaluateInheritedAttribute (
        SgNode* astNode,
        InheritedAttribute inheritedAttribute );

    SynthesizedAttribute evaluateSynthesizedAttribute (
        SgNode* astNode,
        InheritedAttribute inheritedAttribute,
        SubTreeSynthesizedAttributes synthesizedAttributeList );
};

InheritedAttribute
Traversal::evaluateInheritedAttribute (
    SgNode* astNode,
    InheritedAttribute inheritedAttribute )
{
    switch (astNode->variantT())
    {
        case V_SgForStatement:
        {
            printf ("Found a SgForStatement \n");

            // This loop is one deeper than the depth of the parent's inherited attribute
            inheritedAttribute.loopNestDepth++;

            break;
        }

        default:
        {
            // g++ needs a block here
        }
    }

    return inheritedAttribute;
}

SynthesizedAttribute
Traversal::evaluateSynthesizedAttribute (
    SgNode* astNode,
    InheritedAttribute inheritedAttribute,

```

Figure 17.1: Example source code showing loop recognition (part 1).

```

SubTreeSynthesizedAttributes synthesizedAttributeList )
{
    SynthesizedAttribute returnAttribute;
    switch(astNode->variantT())
    {
        case V_SgForStatement:
        {
            break;
        }
        default:
        {
            // g++ needs a block here
        }
    }
    return returnAttribute;
}

int
main ( int argc, char* argv[] )
{
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT (project != NULL);

    // Build the inherited attribute
    InheritedAttribute inheritedAttribute;

    Traversal myTraversal;

    // Call the traversal starting at the sageProject node of the AST
    myTraversal.traverseInputFiles(project,inheritedAttribute);

    return 0;
}

```

Figure 17.2: Example source code showing loop recognition (part 2).

```

int main()
{
    int x[4];
    int y[4][4];

    for (int i=0; i < 4; i++)
    {
        x[i] = 7;
    }

    for (int i=0; i < 4; i++)
    {
        for (int j=0; j < 4; j++)
        {
            y[i][j] = 42;
        }
    }

    return 0;
}

```

Figure 17.3: Example source code used as input to loop recognition processor.

```
Found a SgForStatement  
Found a SgForStatement  
Found a SgForStatement
```

Figure 17.4: Output of input to loop recognition processor.

Chapter 18

Virtual CFG

The ROSE virtual control flow graph interface provides a higher level of detail than ROSE’s other control flow graph interfaces. It expresses control flow even within expressions, and handles short-circuited logical and conditional operators properly¹. The interface is referred to as “virtual” because no explicit graph is ever created: only the particular CFG nodes and edges used in a given program ever exist. CFG nodes and edges are value classes (they are copied around by value, reducing the need for explicit memory management).

A CFG node consists of two components: an AST node pointer, and an index of a particular CFG node within that AST node. There can be several CFG nodes corresponding to a given AST node, and thus the AST node pointers cannot be used to index CFG nodes. The particular index values for the different AST node types are explained in Section 18.3.

18.1 Important functions

The main body of the virtual CFG interface is in `virtualCFG.h`; the source code is in `src/frontend/SageIII/virtualCFG/` and is linked into `librose`. The filtered CFG interface explained below is in `filteredCFG.h`, and functions for converting the CFG to a graph in Dot format are in `cfgToDot.h`.

Two functions provide the basic way of converting from AST nodes to CFG nodes. Each `SgNode` has two methods, `cfgForBeginning()` and `cfgForEnd()`, to generate the corresponding CFG nodes. These functions require that the AST node is either an expression, a statement, or a `SgInitializedName`. The beginning node represents the point in the control flow immediately before the construct starts to execute, and the ending node represents the point immediately after the construct has finished executing. Note that these two nodes do not dominate the other CFG nodes in the construct due to goto statements and labels.

18.1.1 Node methods

- `CFGNode(SgNode* node, unsigned int index)`: Build a CFG node from the given AST node and index. Valid index values are in Section 18.3.

¹It assumes operands of expressions are computed in left-to-right order, unlike the actual language semantics, however.

- `toString()`: Produce a string representing the information in the node.
- `toStringForDebugging()`: Similar, but with more internal debugging information.
- `id()`: A C identifier representing the node.
- `getNode()`: Get the underlying AST node.
- `getIndex()`: Get the index (as explained in Section 18.3) for this CFG node within its underlying AST node.
- `outEdges()`: Return a vector of outgoing CFG edges from this node.
- `inEdges()`: Return a vector of CFG edges coming into this node (note that the sources and targets of the edges are not reversed, and so each in edge has its target as the current node).
- `isInteresting()`: See Section 18.6.1.
- Nodes are also comparable using the operators `==`, `!=`, and `<`.


18.1.2 Edge methods

- `toString()`: Produce a string representing the information in the node.
- `toStringForDebugging()`: Similar, but with more internal debugging information.
- `id()`: A C identifier representing the node.
- `source()`: The starting CFG node for this edge.
- `target()`: The ending CFG node for this edge.
- `condition()`: When there are multiple CFG edges from the same starting node, each of them is taken under certain conditions. The `condition()` method returns the condition, of type `EdgeConditionKind`. The possible return values are:
 - `eckUnconditional`: An edge that is always taken.
 - `eckTrue`: True case of a two-way branch (either an `if` statement or a loop)
 - `eckFalse`: False case of a two-way branch
 - `eckCaseLabel`: Case label in a switch statement (key is given by `caseLabel()`)
 - `eckDefault`: Default label of a switch statement
 - `eckDoConditionPassed`: Enter Fortran `do` loop body
 - `eckDoConditionFailed`: Fortran `do` loop finished
 - `eckForallIndicesInRange`: Start testing `forall` mask
 - `eckForallIndicesNotInRange`: End of `forall` loop
 - `eckComputedGotoCaseLabel`: Case in computed `goto` – number needs to be computed separately

- `eckArithmeticIfLess`: Edge for the arithmetic if expression being less than zero
 - `eckArithmeticIfEqual`: Edge for the arithmetic if expression being equal to zero
 - `eckArithmeticIfGreater`: Edge for the arithmetic if expression being greater than zero
-
- `caseLabel()`: For an edge with condition `eckCaseLabel`, an expression representing the key for the case label.
 - `computedGotoCaseIndex()`: The index of this edge's case within a Fortran computed goto (an edge of kind `eckComputedGotoCaseLabel`).
 - `conditionBasedOn()`: The test expression or switch expression that is tested by this edge.
 - `scopesBeingExited()`, `scopesBeingEntered()`: Variables leaving and entering scope during this edge. This information has not been extensively verified, and should not be relied upon.
 - Edges can also be compared using the operators `==` and `!=`. They are not ordered to avoid dependencies on pointer comparison on different computers.

18.2 Drawing a graph of the CFG

FIXME, add example from tutorial/virtualCFG.C



18.3 Index values

FIXME

18.4 Robustness to AST changes

Control flow graph nodes and edges can be kept (i.e., are not invalidated) in many cases when the underlying AST changes. However, there are some limitations to this capability. Changing the AST node that is pointed to by a given CFG node is not safe. CFG nodes for deleted AST nodes are of course invalid, as are those pointing to AST nodes whose parent pointers become invalid.

18.5 Limitations

Although workable for intraprocedural analysis of C code, the virtual CFG code has several limitations for other languages and uses.

18.5.1 Fortran support

The virtual control flow graph includes support for many Fortran constructs, but that support is fairly limited and not well tested. It is not recommended for production use.

18.5.2 Exception handling

The virtual CFG interface does not support control flow due to exceptions or the `setjmp/longjmp` constructs. It does, however, support `break`, `continue`, `goto`, and early returns from functions.

18.5.3 Interprocedural control flow analysis

A limited form of interprocedural control flow analysis is supported. That feature is enabled with a global variable named `interproceduralControlFlowGraph`. Setting that variable to `true` changes the out edges of function calls and the in edges of nodes just after function calls when the function references are known. Although this causes interprocedural behavior, it also leads to a mismatch between the in and out edges between certain pairs of nodes. Solving this problem would require a precomputed call graph for the program, which defeats the goal of not requiring any precomputed or cached information to traverse the control flow graph.

18.6 Node filtering

FIXME

18.6.1 “Interesting” node filter

18.6.2 Arbitrary filtering

Chapter 19

Generating Control Flow Graphs

The control flow of a program is broken into *basic blocks* as nodes with control flow forming edges between the basic blocks. Thus the control flow forms a graph which often labeled edges (true and false), and basic blocks representing sequentially executed code. This chapter presents the Control Flow Graph (CFG) and the ROSE application code for generating such graphs for any function in an input code. The CFG forms a fundamental building block for more complex forms of program analysis.

Figure 19.1 shows the code required to generate the control flow graph for each function of an application. Using the input code shown in figure 19.2 the first function's control flow graph is shown in figure 19.3.

Figure 19.3 shows the control flow graph for the function in the input code in figure 19.2.

```

// Example ROSE Translator: used within ROSE/tutorial

#include "rose.h"
#include <GraphUpdate.h>
#include "CFGImpl.h"
#include "GraphDotOutput.h"
#include "controlFlowGraph.h"
#include "CommandOptions.h"

using namespace std;

// Use the ControlFlowGraph is defined in both PRE
// and the DominatorTreesAndDominanceFrontiers namespaces.
// We want to use the one in the PRE namespace.
using namespace PRE;

class visitorTraversal : public AstSimpleProcessing
{
public:
    virtual void visit(SgNode* n);
};

void visitorTraversal::visit(SgNode* n)
{
    SgFunctionDeclaration* functionDeclaration = isSgFunctionDeclaration(n);
    if (functionDeclaration != NULL)
    {
        SgFunctionDefinition* functionDefinition = functionDeclaration->get_definition();
        if (functionDefinition != NULL)
        {
            SgBasicBlock* functionBody = functionDefinition->get_body();
            ROSE_ASSERT(functionBody != NULL);

            ControlFlowGraph controlflow;

            // The CFG can only be called on a function definition (at present)
            makeCfg(functionDefinition, controlflow);
            string fileName = functionDeclaration->get_name().str();
            fileName += ".dot";
            ofstream dotfile(fileName.c_str());
            printCfgAsDot(dotfile, controlflow);
        }
    }
}

int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc, argv);

    CmdOptions::GetInstance()->SetOptions(argc, argv);

    // Build the traversal object
    visitorTraversal exampleTraversal;

    // Call the traversal starting at the project node of the AST
    exampleTraversal.traverseInputFiles(project, preorder);

    return 0;
}

```

Figure 19.1: Example source code showing visualization of control flow graph.

```

#include <stdio.h>
#include <string.h>
#include <assert.h>

int main(int argc, char *argv[])
{
    int i;
    char buffer[10];
    for (i=0; i < strlen(argv[1]); i++)
    {
        // Buffer overflow for strings of over 9 characters
        assert(i < 10);
        buffer[i] = argv[1][i];
    }
    return 0;
}

#if 0
void
bar(int& w)
{
    ++w;
}

int
main(int, char**)
{
    int z = 3;
    int a = 5 + z + 9;
    int b = (6 - z) * (a + 2) - 3;
    bar(b);
    while (b - 7 > 0)
    {
        b-=5;
        --b;
    }

    do {
        --b; LLL: if (b <= -999) return 0;
    }
    while (b > 2);

    for (b = 0; b < 10; ++b)
        ++z;

    for (int z2 = 7 + z * 5; z2 + 9 < b % 10; ++*(&z2 + 5 - 5))
    {
        (a += 7) += 7;
        ++(++a);
    }
    b = -999;
    goto LLL;
}
#endif

```

Figure 19.2: Example source code used as input to build control flow graph.




Figure 19.3: Control flow graph for function in input code file: inputCode_1.C.

Chapter 20

Dataflow Analysis

The dataflow analysis in Rose is based on the control flow graph (CFG). One type of dataflow analysis is called def-use analysis, which is explained next.

20.1 Def-Use Analysis

The definition-usage (def-use) analysis allows to query the definition and usage for each *control flow node* (CFN). Any statement or expression within ROSE is represented as a sequence of CFN's. For instance, the CFG for the following program

```
int main()
{
    int x = 9;
    x = x + 1;
}
```

Figure 20.1: Example input code.

is illustrated in Figure 20.2.

20.1.1 Def-use Example implementation

The following code shows an example of how the def-use analysis is called:

```
#include "rose.h"
#include "DefUseAnalysis.h"
#include <string>
#include <iostream>
using namespace std;

void runCurrentFile(vector<string> argvList) {
    SgProject* project = frontend(argvList);
    std::cout << ">>>> generate PDF " << endl;
    generatePDF ( *project );
    std::cout << ">>>> start def-use analysis ... " << endl;
```

```

// Call the Def-Use Analysis
DFAnalysis* defuse = new DefUseAnalysis(project);
bool debug = true;
defuse->run(debug);
defuse->dfaToDOT();

NodeQuerySynthesizedAttributeType vars = NodeQuery::querySubTree(project, V_SgInitializedName);
NodeQuerySynthesizedAttributeType::const_iterator i = vars.begin();
for (; i!=vars.end(); ++i) {
    SgInitializedName* initName = isSgInitializedName(*i);
    std::string name = initName->get_qualified_name().str();
    vector<SgNode*> vec = defuse->getDefFor(initName, initName);
    if (vec.size()>0)
        std::cout << " DEF>> Vector entries for " << name << " ( " <<
            initName << " ) : " << vec.size() << std::endl;
}
}

int main( int argc, char * argv[] ) {
    vector<string> argvList(argv, argv + argc);
    runCurrentFile(argvList);
    return 0;
}

```

20.1.2 Accessing the Def-Use Results

For each CFN in the CFG, the definition and usage for variable references can be determined with the public function calls:

```

vector <SgNode*> getDefFor(SgNode*, SgInitializedName*)
vector <SgNode*> getUseFor(SgNode*, SgInitializedName*)

```

where *SgNode** represents any control flow node and *SgInitializedName* any variable (being used or defined at that CFN). The result is a vector of possible CFN's that either define (*getDefFor*) or use (*getUseFor*) a specific variable.

Figure 20.2 shows how the variable *x* is being declared and defined in CFN's between node 1 and 6. Note that the definition is annotated along the edge. For instance at node 6, the edge reads *(6) DEF: x (3) = 5*. This means that variable *x* was declared at CFN 3 but defined at CFN 5.

The second statement *x=x+1* is represented by CFN's from 7 to 12. One can see in the figure that *x* is being re-defined at CFN 11. However, the definition of *x* within the same statement happens at CFN 8. Hence, the definition of the right hand side *x* in the statement is at CFN 5 : *(8) DEF: x (3) = 5*.

Another usage of the def-use analysis is to determine which variables actually are defined at each CFN. The following function allows to query a CFN for all its variables (*SgInitializedNames*) and the positions those variables are defined (*SgNode*):

```

std::multimap <SgInitializedName*, SgNode*> getDefMultiMapFor(SgNode*)
std::multimap <SgInitializedName*, SgNode*> getUseMultiMapFor(SgNode*)

```

All public functions are described in *DefuseAnalysis.h*. To use the def-use analysis, one needs to create an object of the class *DefUseAnalysis* and execute the *run* function. After that, the described functions above help to evaluate definition and usage for each CFN.




Figure 20.2: Def-Use graph for example program.

Chapter 21

Generating the Call Graph (CG)

The formal definition of a call graph is:

'A diagram that identifies the modules in a system or computer program and shows which modules call one another.' IEEE

A call graph shows all function call paths of an arbitrary code. These paths are found by following all function calls in a function, where a function in the graph is represented by a node and each possible function call by an edge (arrow). To make a call graph this process is redone for every called function until all edges are followed and there are no ungraphed functions. ROSE has an in-build mechanism for generating call graphs.

Figure 21 shows the code required to generate the call graph for each function of an application. Using the input code shown in figure 21 the first function's call graph is shown in figure 21.3.

Figure 21.3 shows the call graph for the function in the input code in figure 21.

```

#include "rose.h"
#include <CallGraph.h>
#include <GraphUpdate.h>
using namespace std;

//Function object that determines which functions are to be represented
//in the call graph.
struct keepFunction : public unary_function<bool, SgFunctionDeclaration*>{
public:
    bool operator()(SgFunctionDeclaration* funcDecl){
        bool returnValue = true;

        ROSE_ASSERT(funcDecl != NULL);
        string filename = funcDecl->get_file_info()->get_filename();

        //Filter out functions from the ROSE preinclude header file
        if(filename.find("rose-edg-required-macros-and-functions")!=string::npos)
            returnValue = false;
        //Filter out compiler generated functions
        if(funcDecl->get_file_info()->isCompilerGenerated()==true)
            returnValue=false;

        return returnValue;
    }
};

int
main( int argc, char * argv[] ) {
    RoseTestTranslator test;
    SgProject* project = new SgProject(argc, argv);

    //Construct Call Graph
    CallGraphBuilder CGBuilder( project);
    CGBuilder.buildCallGraph(keepFunction());

    cout << "Generating DOT...\n";
    generateDOT( *project );
    cout << "Done with DOT\n";

    // Use the information in the graph to output a dot file for the call graph
    AstDOTGeneration dotgen;
    dotgen.writeIncidenceGraphToDOTFile( CGBuilder.getGraph() , "callGraph.dot");

    printf ("\nLeaving main program ... \n");
    return 0; // backend(project);
}

```

Figure 21.1: Example source code showing visualization of call graph.

```

// #include <iostream>
// #include <sstream>
// #include <stdio.h>
// #include <stdlib.h>

class A
{
public:
    int f1() {}
    int f2() { pf = &A::f1; return (this->pf)(); }
    int (A::*pf) ();
};

// simple (trivial) example code used to demonstrate the call graph generation
// #include <sstream>

void foo1();
void foo2();
void foo3();
void foo4();

void foo1()
{
    foo1();
    foo2();
    foo3();
    foo4();

    void (*pointerToFunction)();
}

void foo2()
{
    foo1();
    foo2();
    foo3();
    foo4();
}

void foo3()
{
    foo1();
    foo2();
    foo3();
    foo4();
}

void foo4()
{
    foo1();
    foo2();
    foo3();
    foo4();
}

int main()
{
    foo1();
    foo2();
    foo3();
    foo4();

    return 0;
}

```

Figure 21.2: Example source code used as input to build call graph.




Figure 21.3: Call graph for function in input code file: inputCode.BuildCG.C.

Chapter 22

Generating the Class Hierarchy Graph

```
// Example ROSE Preprocessor
// used for testing ROSE infrastructure
#include "rose.h"
#include <CallGraph.h>

using namespace std;

int
main( int argc, char * argv[] )
{
    SgProject* project = new SgProject(argc, argv);

    //Construct class hierarchy graph
    ClassHierarchyWrapper hier( project );

    //Output class hierarchy graph to dot
    AstDOTGeneration dotgen;
    dotgen.writeIncidenceGraphToDOTFile( hier.getClassHierarchyGraph() , "classHier.dot");

    return 0;
}
```

Figure 22.1: Example source code showing visualization of class hierarchy graph.

For C++, because of multiple inheritance, a class hierarchy graph is a directed graph with pointers from a class to a superclass. A superclass is a class which does not inherit from any other class. A class may inherit from a superclass by inheriting from another class which does rather than by a direct inheritance.

Figure 22 shows the code required to generate the class hierarchy graph for each class of an application. Using the input code shown in figure 22 the first function's call graph is shown in figure 22.3.

Figure 22.3 shows the class hierarchy graph for the classes in the input code in figure 22.

```
class A{};  
class B : public A{};  
class C : public B{};
```

Figure 22.2: Example source code used as input to build class hierarchy graph.




Figure 22.3: Class hierarchy graph in input code file: inputCode.ClassHierarchyGraph.C.

Chapter 23

Database Support

This chapter is specific to support in ROSE for persistent storage. ROSE uses the SQLite database and makes it simple to store data in the database for retrieval in later phases of processing large multiple file projects.

FIXME: *Need more information here.*

23.1 ROSE DB Support for Persistent Analysis

This section presents figure 23.3, a simple C++ source code using a template. It is used as a basis for showing how template instantiations are handled within ROSE. An example translator using a database connection to store function information is shown in Fig.23.1 and Fig.23.2. The output by the translator operating on the C++ source code is shown in Fig. 23.4.

23.2 Call Graph for Multi-file Application

This section shows an example of the use of the ROSE Database mechanism where information is stored after processing each file as part of generating the call graph for a project consisting of multiple files. The separate files show in figures 23.3 and ???. These files are processed using the translator in figure ??? to generate the final project call graph shown in figure ???.

FIXME: *This example still needs to be implemented to use the new ROSE call graph generator.*

23.3 Class Hierarchy Graph

This section presents a translator in figure ??, to generate the class hierarchy graph of the example shown in figure ???. The input is a multi-file application show in figure ?? and figure ???. *This example is incomplete.*

FIXME: *This example is still incomplete.*

```

// Example ROSE Translator: used for testing ROSE infrastructure

#include "rose.h"

using namespace std;

// DQ (9/9/2005): Don't include the database by default
// TPS (01Dec2008): Enabled mysql and this fails.
// seems like it is not supposed to be included
#if 0
// #ifdef HAVE_MYSQL
// #include "GlobalDatabaseConnection.h"
// #endif

int main( int argc, char * argv[] )
{
// TPS (01Dec2008): Enabled mysql and this fails.
// seems like it is not supposed to be included
#if 0
// #ifdef HAVE_MYSQL
// Build the Data base
GlobalDatabaseConnection *gDB;
gDB = new GlobalDatabaseConnection( "functionNameDataBase" );
gDB->initialize();
string command = "";
command = command + "CREATE TABLE Functions ( name TEXT, counter );";

Query *q = gDB->getQuery();
q->set( command );
q->execute();

if ( q->success() != 0 )
    cout << "Error creating schema: " << q->error() << "\n";
// Alternative syntax, but does not permit access to error messages and exit codes
// gDB->execute(command.c_str());
// #endif

// Build the AST used by ROSE
SgProject* project = frontend(argc,argv);

// Run internal consistency tests on AST
AstTests::runAllTests(project);

// Build a list of functions within the AST
Rose_STL_Container<SgNode*> functionDeclarationList =
    NodeQuery::querySubTree (project, V_SgFunctionDeclaration);

int counter = 0;
for (Rose_STL_Container<SgNode*>::iterator i = functionDeclarationList.begin();
     i != functionDeclarationList.end(); i++)
{
// Build a pointer to the current type so that we can call
// the get_name() member function.
SgFunctionDeclaration* functionDeclaration = isSgFunctionDeclaration(*i);
ROSE_ASSERT(functionDeclaration != NULL);

SgName func_name = functionDeclaration->get_name();
// Skip builtin functions for shorter output, Liao 4/28/2008
if (func_name.getString().find("_builtin",0)==0)
    continue;

// output the function number and the name of the function
printf ("function name #%d is %s at line %d \n",
        counter++,func_name.str());
}
}
}

```

Figure 23.1: Example translator (part 1) using database connection to store function names.

```

        functionDeclaration->get_file_info()->get_line());

        string functionName = functionDeclaration->get_qualified_name().str();

// TPS (01Dec2008): Enabled mysql and this fails.
// seems like it is not supposed to be included
#if 0
        //#ifdef HAVE_MYSQL
        command = "INSERT INTO Functions values(\"" + functionName + "\", " +
            StringUtility::numberToString(counter) + ");";
        // Alternative interface
        // q->set( command );
        // cout << "Executing: " << q->preview() << "\n";
        // q->execute();
        gDB->execute(command.c_str());
#endif
    }

// TPS (01Dec2008): Enabled mysql and this fails.
// seems like it is not supposed to be included
#if 0
        //#ifdef HAVE_MYSQL
        command = "SELECT * from Functions;";

        // Alternative Interface (using query objects)
        // q << command;
        // q->set(command);
        // cout << "Executing: " << q->preview() << "\n";

        // execute and return result (alternative usage: "gDB->select()")
        Result *res = q->store();
        if ( q->success() != 0 )
            cout << "Error reading values: " << q->error() << "\n";
        else
        {
            // Read the table returned from the query
            // res->showResult();
            for ( Result::iterator i = res->begin(); i != res->end(); i++ )
            {
                // Alternative syntax is possible: "Row r = *i;"
                string functionName = (*i)[0].get_string();
                int counter = (*i)[1];
                printf ("functionName = %s counter = %d \n",functionName.c_str(),counter);
            }
        }

        gDB->shutdown();
    #else
        printf ("Program compiled without data base connection support (add using ROSE configure option) \n");
    #endif

    return 0;
}

```

Figure 23.2: Example translator (part 2) using database connection to store function names.

// This example code is used to record names of functions into the data base.

```

class A
{
    public:
        virtual int f1() = 0;
        virtual int f2() {}
        int f3();
        virtual int f4();
};

int A::f3() { f1(); return f3();}
int A::f4() {}

class B : public A
{
    public:
        virtual int f1();
        virtual int f2() {}
};

int B::f1() {}

class C : public A
{
    public:
        virtual int f1() {}
        int f3() {}
};

class D : public B
{
    public:
        virtual int f2() {}
};

class E : public D
{
    public:
        virtual int f1() { return 5; }
};

class G : public E
{
    public:
        virtual int f1();
};

int G::f1() {}

class F : public D
{
    public:
        virtual int f1() {}
        virtual int f2() {return 5;}
        int f3() {return 2;}
};

class H : public C
{
    public:
        virtual int f1() {}
        virtual int f2() {}
        int f3() {}
};

```

Figure 23.3: Example source code used as input to database example.

```
function name #0 is __sync_lock_test_and_set at line 0
function name #1 is __sync_lock_release at line 0
function name #2 is f1 at line 6
function name #3 is f2 at line 7
function name #4 is f3 at line 8
function name #5 is f4 at line 9
function name #6 is f3 at line 12
function name #7 is f4 at line 13
function name #8 is f1 at line 18
function name #9 is f2 at line 19
function name #10 is f1 at line 22
function name #11 is f1 at line 27
function name #12 is f3 at line 28
function name #13 is f2 at line 34
function name #14 is f1 at line 40
function name #15 is f1 at line 46
function name #16 is f1 at line 49
function name #17 is f1 at line 54
function name #18 is f2 at line 55
function name #19 is f3 at line 56
function name #20 is f1 at line 62
function name #21 is f2 at line 63
function name #22 is f3 at line 64
Program compiled without data base connection support (add using ROSE configure option)
```

Figure 23.4: Output from processing input code through database example dataBaseTranslator23.1.

Chapter 24

Building Custom Graphs

What To Learn From This Example This example shows how to generate custom graphs (typically used for analysis results).

The mechanisms used internally to build different graphs of program data are also made externally available. This section shows how new graphs of program information can be built or existing graphs customized. More information about generation of specialized AST graphs to support debugging can be found in 6.

Figure 24.1 shows a graph representing the highest levels of the ROSE directory tree built using the code shown in figure 24.2. This example is build explicitly in the example code, the script *lsdot* in the *ROSE/scripts/* directory builds such a graph of the directory tree automatically for any directory structure and is used to present the ROSE source directory tree in the *ROSE User Manual*.




Figure 24.1: Graph of top level of ROSE directory tree.

Figure 24.3 shows the same graph but with filtering to tailor the graph by removing nodes. The removal of any node from the graph automatically removes all edges pointing to that node removed and all edges pointing away from the node being removed. This mechanism is provided as a way to customized graphs automatically generated using ROSE (e.g. call graphs, control flow graphs, etc.).

```
// Example of using Qing's graph interface for an arbitrary graph.
```

```
#include "rose.h"
#include <GraphDotOutput.h>
#include <VirtualGraphCreate.h>
using namespace std;

class Node : public MultiGraphElem {
public:
    std::string name;
    Node( std::string n ) : MultiGraphElem( NULL ), name( n ) {}
    virtual std::string toString() const { return name; }
};

class Edge : public MultiGraphElem {
public:
    std::string label;
    Edge ( std::string label = "default edge" ) : MultiGraphElem( NULL ), label( label ) {};
    void Dump() const { printf ("EDGE: label = %s \n",label.c_str()); }
    virtual std::string toString() const { return label; }
};

template <class NodeType, class EdgeType>
class GraphBuilder : public VirtualGraphCreateTemplate<NodeType, EdgeType> {
public:
    void addNode ( NodeType* node );
    void addEdge ( NodeType* src, NodeType* snk, EdgeType* edge );
    GraphBuilder () : VirtualGraphCreateTemplate<NodeType, EdgeType> (NULL) {}
    ~GraphBuilder() { printf (" Inside of ~GraphBuilder() \n"); }
};

template <class NodeType, class EdgeType>
void GraphBuilder<NodeType, EdgeType>::addNode ( NodeType* node )
{ VirtualGraphCreateTemplate<NodeType,EdgeType>::AddNode ( node ); }

template <class NodeType, class EdgeType>
void GraphBuilder<NodeType, EdgeType>::addEdge ( NodeType* src, NodeType* snk, EdgeType* edge )
{ VirtualGraphCreateTemplate<NodeType,EdgeType>::AddEdge ( src, snk, edge ); }

int main( int argc, char * argv[] )
{
    GraphBuilder<Node, Edge> graph;

    Node* rose = new Node("ROSE");
    graph.addNode(rose);
    Node* docs = new Node("docs");
    graph.addNode(docs);
    Node* scripts = new Node("scripts");
    graph.addNode(scripts);
    Node* src = new Node("src");
    graph.addNode(src);
    Node* tests = new Node("tests");
    graph.addNode(tests);
    Node* tools = new Node("tools");
    graph.addNode(tools);
    Node* tutorial = new Node("tutorial");
    graph.addNode(tutorial);
    Node* frontend = new Node("frontend");
    graph.addNode(frontend);
    Node* midend = new Node("midend");
    graph.addNode(midend);
    Node* backend = new Node("backend");
    graph.addNode(backend);
    Node* thirdPartyLibraries = new Node("3rdPartyLibraries");
    graph.addNode(thirdPartyLibraries);
    Node* roseExtensions = new Node("RoseExtensions");
    graph.addNode(roseExtensions);
    Node* roseIndependentSupport = new Node("RoseIndependentSupport"); graph.addNode(roseIndependentSupport);
    Node* rosetta = new Node("ROSETTA");
    graph.addNode(rosetta);
    Node* util = new Node("util");
    graph.addNode(util);

    graph.addEdge(rose, docs, new Edge("subdir1"));
    graph.addEdge(rose, scripts, new Edge("subdir2"));
    graph.addEdge(rose, src, new Edge("subdir3"));
    graph.addEdge(rose, tests, new Edge("subdir4"));
    graph.addEdge(rose, tools, new Edge("subdir5"));
    graph.addEdge(rose, tutorial, new Edge("subdir6"));
    graph.addEdge(src, frontend, new Edge("subdirA"));
    graph.addEdge(src, midend, new Edge("subdirB"));
    graph.addEdge(src, backend, new Edge("subdirC"));
    graph.addEdge(src, thirdPartyLibraries, new Edge("subdirD"));
```




Figure 24.3: Graph of top level of ROSE directory tree with filtering of subtree.

Part IV

Program Transformations and Optimizations

This part gives examples of building source-to-source program transformations and optimizations.

Chapter 25

Generating Unique Names for Declarations

There are many instances where a unique name must be generated for either a function or variable declaration. ROSE defines a mechanism to make the generation of unique names from all `SgDeclarationStatement` IR nodes and the `SgInitializedName` IR node. This simplifies ROSE based applications that require this sort of mechanism. Our experience has found that a significant number of tools require such a mechanism and that its correct implementation can have subtle complex points, thus we have provided one as part of ROSE.

The specific translator described in this chapter traverses an AST and outputs the unique names that can be generated for each declaration showing the use of the unique name generation mechanism. This tool is intended as an example of how to generate unique names using ROSE. Not all IR nodes can be used to generate a unique name. The generated names are unique under the following rules:

1. Any two generated names are the same if the declarations are the same.
Declaration can be the same across files or within the same file. Declarations that are the same can have different location in the same file (be represented multiple times) or be in different files. Language constructs that are the same must follow the One-time Definition Rule (ODR) across files.
2. Declarations in different unnamed scopes (e.g. for loop bodies) will generate different names.
3. Names are the same when generated by different ROSE tools.
Pointer values could be used to generate unique names of all IR nodes, but this would work only within a single invocation of the ROSE based tool. Generated names are not based on internal pointer values and are thus insensitive to pointer values. Generated names of the same declaration are thus the same even if generated from different tools. This allows multiple ROSE tools to inter-operate.

This unique name generation mechanism is only applicable to specific IR nodes, specifically:

- `SgInitializedName`

- SgDeclarationStatement IR nodes:
 - Obvious IR nodes supported:
 - * SgClassDeclaration
 - * SgFunctionDeclaration
 - * SgEnumDeclaration
 - * SgNamespaceDeclarationStatement
 - * SgTypedefDeclaration
 - Less obvious IR nodes not supported (support for these would not make sense):
 - * SgAsmStmt
 - * SgCtorInitializerList
 - * SgFunctionParameterList
 - * SgNamespaceAliasDeclarationStatement
 - * SgPragmaDeclaration
 - * SgTemplateDeclaration (can this have a mangled name?)
 - * SgTemplateInstantiationDirectiveStatement
 - * SgUsingDeclarationStatement
 - * SgUsingDirectiveStatement
 - * SgVariableDeclaration
 - Note that the SgVariableDeclaration contains a list of SgInitializedName nodes and the mangled names are best queried from each SgInitializedName instead of the SgVariableDeclaration.
 - * SgVariableDefinition
- Un-named scopes
 - A number of scopes are un-names and so there is an opportunity to generate non-unique names from declarations in such scopes. To fix this we generate names for each un-named scope to guarantee uniqueness. Nodes handled are:
 - SgForStatement
 - SgBasicBlock
 - SgIfStmt
 - get the complete list ...

Other language constructs can generate unique names as well, but their name could be invalid after certain transformation that move it structurally within the generated source code.

25.1 Example Code Showing Generation of Unique Names

25.2 Input For Examples Showing Unique Name Generation for Variables

Figure 25.1, shows an example translator demonstrating the generation of unique names from declarations in the AST. For each SgInitializedName we generate the mangled name. Figure 25.2

shows the input code and figure 25.3 shows the generated output from the translator (the mangled names from the AST associated with the input application).

25.3 Example Output Showing Unique Variable Names

25.4 Input For Examples Showing Unique Name Generation for Functions

Figure 25.1, shows an example translator demonstrating the generation of unique names from declarations in the AST. For each `SgInitializedName` we generate the mangled name. Figure 25.4 shows the input code and figure 25.5 shows the generated output from the translator (the mangled names from the AST associated with the input application).

25.5 Example Output Showing Unique Function Names

```

// This example shows the generation of unique names from declarations.

// Mangled name demo
//
// This translator queries the AST for all SgInitializedNames and
// SgFunctionDeclarations, and for each one prints (a) the source
// location, (b) the source name of the object, and (c) the mangled
// name.

#include <rose.h>

using namespace std;

// Returns a Sg_File_Info object as a display-friendly string, "[source:line]".
static string toString (const Sg_File_Info* info)
{
    ostringstream info_str;
    if (info)
        info_str << '['
                << info->get_raw_filename ()
                << ":" << info->get_raw_line ()
                << ']' ;
    return info_str.str ();
}

// Displays location and mangled name of an SgInitializedName object.
static void printInitializedName (const SgNode* node)
{
    const SgInitializedName* name = isSgInitializedName (node);
    ROSE_ASSERT (name != NULL);

    if (name->get_file_info()->isCompilerGenerated() == false)
        cout << toString (name->get_file_info ())
              << " "
              << name->get_name ().str ()
              << " -> " << name->get_mangled_name ().str ()
              << endl;
}

// Displays location and mangled name of an SgFunctionDeclaration object.
static void printFunctionDeclaration (const SgNode* node)
{
    const SgFunctionDeclaration* decl = isSgFunctionDeclaration (node);
    ROSE_ASSERT (decl != NULL);

    if (decl->get_file_info()->isCompilerGenerated() == false)
        cout << toString (decl->get_startOfConstruct ())
              << " "
              << decl->get_qualified_name ().str ()
              << " -> " << decl->get_mangled_name ().str ()
              << endl;
}

int main (int argc, char** argv)
{
    SgProject* proj = frontend (argc, argv);

    cout << endl << "***** BEGIN initialized names *****" << endl;
    Rose_STL_Container<SgNode*> init_names = NodeQuery::querySubTree (proj, V_SgInitializedName);
    for_each (init_names.begin (), init_names.end (), printInitializedName);
    cout << "***** END initialized names *****" << endl;

    cout << endl << "***** BEGIN function declarations *****" << endl;
    Rose_STL_Container<SgNode*> func_decls = NodeQuery::querySubTree (proj, V_SgFunctionDeclaration);
    for_each (func_decls.begin (), func_decls.end (), printFunctionDeclaration);
    cout << "***** END function declarations *****" << endl;

    return backend (proj);
}

```

Figure 25.1: Example source code showing the output of mangled name. The string represents the code associated with the subtree of the target IR node.


```

// Input file to test mangling of SgInitializedName objects.

int x;

// Global class
class A
{
    private:
        int x;
    // Nested class
    class B
    {
        private:
            int x;
        public:
            void foo (int x_arg) { int x; }
    };
};

template <typename T>
void
foo (T x_arg)
{
    T x;
    for (x = 0; x < 10; x++)
    {
        T x = 0;
        do {
            // Local class
            class A
            {
                private:
                    // Nested class
                    class B
                    {
                        { T x;
                    };
                public:
                    void foo (T x) {}
            };
            T x = 0;
        }
        while (x > 0);

        do {
            T x = 0;
        }
        while (x > 0);

        // Nested scope
        {
            T x = 0;
        }
    }
}

template void foo<int> (int x);
template void foo<double> (double x);

void bar (void)
{
    for (int x = 0; x != 0; x++)
        for (int x = 0; x != 0; x++)
            for (long x = 0; x != 0; x++)
                ;
    try {
        for (int x = 0; x != 0; x++) ;
    }
    catch (int) {}
    catch (char x) {}
}

```

Figure 25.2: Example source code used as input to program in codes showing debugging techniques shown in this section.

```

**** BEGIN initialized names ****
x --> x
x --> A__scope__x
x --> A__scope__B__scope__x
x.arg --> L2R__ARG1
x --> L2R__scope__SgSS2__scope__x
x.arg --> foo__tas__i__tae__Fb_v_Gb_i_Fe__ARG1
x.arg --> foo__tas__i__tae__Fb_v_Gb_i_Fe__ARG1
x.arg --> foo__tas__d__tae__Fb_v_Gb_d_Fe__ARG1
x.arg --> foo__tas__d__tae__Fb_v_Gb_d_Fe__ARG1
x --> bar__Fb_v_Gb__Fe__scope__SgSS2__scope__SgSS3__scope__x
x --> bar__Fb_v_Gb__Fe__scope__SgSS2__scope__SgSS3__scope__SgSS4__scope__x
x --> bar__Fb_v_Gb__Fe__scope__SgSS2__scope__SgSS3__scope__SgSS4__scope__SgSS5__scope__x
x --> bar__Fb_v_Gb__Fe__scope__SgSS2__scope__SgSS7__scope__SgSS8__scope__x
x --> bar__Fb_v_Gb__Fe__scope__SgSS2__scope__SgSS10__scope__CATCHARG
x --> bar__Fb_v_Gb__Fe__scope__SgSS2__scope__SgSS12__scope__x
x.arg --> foo__tas__i__tae__Fb_v_Gb_i_Fe__ARG1
x --> foo__tas__i__tae__Fb_v_Gb_i_Fe__scope__SgSS2__scope__x
x --> foo__tas__i__tae__Fb_v_Gb_i_Fe__scope__SgSS2__scope__SgSS3__scope__SgSS4__scope__x
x --> L0R__scope__B__scope__x
x --> L3R__ARG1
x --> foo__tas__i__tae__Fb_v_Gb_i_Fe__scope__SgSS2__scope__SgSS3__scope__SgSS4__scope__SgSS5__scope__SgSS6__
x --> foo__tas__i__tae__Fb_v_Gb_i_Fe__scope__SgSS2__scope__SgSS3__scope__SgSS4__scope__SgSS11__scope__SgSS1
x --> foo__tas__i__tae__Fb_v_Gb_i_Fe__scope__SgSS2__scope__SgSS3__scope__SgSS4__scope__SgSS13__scope__x
x.arg --> foo__tas__d__tae__Fb_v_Gb_d_Fe__ARG1
x --> foo__tas__d__tae__Fb_v_Gb_d_Fe__scope__SgSS2__scope__x
x --> foo__tas__d__tae__Fb_v_Gb_d_Fe__scope__SgSS2__scope__SgSS3__scope__SgSS4__scope__x
x --> L1R__scope__B__scope__x
x --> L4R__ARG1
x --> foo__tas__d__tae__Fb_v_Gb_d_Fe__scope__SgSS2__scope__SgSS3__scope__SgSS4__scope__SgSS5__scope__SgSS6__
x --> foo__tas__d__tae__Fb_v_Gb_d_Fe__scope__SgSS2__scope__SgSS3__scope__SgSS4__scope__SgSS11__scope__SgSS1
x --> foo__tas__d__tae__Fb_v_Gb_d_Fe__scope__SgSS2__scope__SgSS3__scope__SgSS4__scope__SgSS13__scope__x
**** END initialized names ****

**** BEGIN function declarations ****
::A::B::foo --> L2R
::foo < int > --> foo__tas__i__tae__Fb_v_Gb_i_Fe_
::foo < int > --> foo__tas__i__tae__Fb_v_Gb_i_Fe_
::foo < double > --> foo__tas__d__tae__Fb_v_Gb_d_Fe_
::foo < double > --> foo__tas__d__tae__Fb_v_Gb_d_Fe_
::bar --> bar__Fb_v_Gb__Fe_
::foo < int > --> foo__tas__i__tae__Fb_v_Gb_i_Fe_
A::foo --> L3R
::foo < double > --> foo__tas__d__tae__Fb_v_Gb_d_Fe_
A::foo --> L4R
**** END function declarations ****

```

Figure 25.3: Output of input code using generatingUniqueNamesFromDeclaration.C

```

// Input file to test mangling of SgFunctionDeclaration objects.

long foobar();
long foobar(int);
long foobar(int y);
long foobar(int x);
long foobar(int x = 0);
long foobar(int xyz)
{
    return xyz;
}

char foobarChar(char);
char foobarChar(char c);

// Input file to test mangling of SgFunctionDeclaration objects.

typedef int value0_t;
typedef value0_t value_t;
namespace N
{
    typedef struct { int a; } s_t;
    class A { public: A () {} virtual void foo (int) {} };
    class B { public: B () {} void foo (value_t) const {} };
    class C : public A { public: C () {} void foo (int) {} void foo (const s_t&) {} };
    void foo (const s_t*) {}
}

typedef N::s_t s2_t;
void foo (value_t);
void foo (s2_t) {}
void foo (float x[]) {}
void foo (value_t, s2_t);

template <typename T>
void foo (T) {}

namespace P
{
    typedef long double type_t;
    namespace Q
    {
        template <typename T>
        void foo (T) {}

        class R
        {
        public:
            R () {}
            template <typename T>
            void foo (T) {}
            void foo (P::type_t) {}
            template <typename T, int x>
            int foo (T) { return x; }
        };
    }
}

template <typename T, int x>
int foo (T) { return x; }

template void foo<char> (char);
template void foo<const value_t *> (const value_t *);
template void P::Q::foo<long> (long);
template void P::Q::R::foo<value_t> (value_t);

```

Figure 25.4: Example source code used as input to program in codes showing debugging techniques shown in this section.

```

***** BEGIN initialized names *****
--> foobar___Fb_l_Gb_i_Fe___ARG1
y --> foobar___Fb_l_Gb_i_Fe___ARG1
x --> foobar___Fb_l_Gb_i_Fe___ARG1
x --> foobar___Fb_l_Gb_i_Fe___ARG1
xyz --> foobar___Fb_l_Gb_i_Fe___ARG1
--> foobarChar___Fb_c_Gb_c_Fe___ARG1
c --> foobarChar___Fb_c_Gb_c_Fe___ARG1
a --> L0R__scope__a
--> L3R__ARG1
--> L4R__ARG1
--> L5R__ARG1
--> L6R__ARG1
--> L7R__ARG1
--> foo___Fb_v_Gb_L1R_Fe___ARG1
--> foo___Fb_v_Gb_L2R_Fe___ARG1
x --> L8R__ARG1
--> foo___Fb_v_Gb_L1R__sep__L2R_Fe___ARG1
--> foo___Fb_v_Gb_L1R__sep__L2R_Fe___ARG2
--> L9R__ARG1
--> foo__tas__c__tae_____Fb_v_Gb_c_Fe___ARG1
--> foo__tas__c__tae_____Fb_v_Gb_c_Fe___ARG1
--> L10R__ARG1
--> L10R__ARG1
--> L11R__ARG1
--> L11R__ARG1
--> L12R__ARG1
--> L12R__ARG1
--> foo__tas__c__tae_____Fb_v_Gb_c_Fe___ARG1
--> L10R__ARG1
--> L11R__ARG1
--> L12R__ARG1
***** END initialized names *****

***** BEGIN function declarations *****
:: foobar --> foobar___Fb_l_Gb_i_Fe_
:: foobar --> foobar___Fb_l_Gb_i_Fe_
:: foobar --> foobar___Fb_l_Gb_i_Fe_
:: foobar --> foobar___Fb_l_Gb_i_Fe_
:: foobar --> foobar___Fb_l_Gb_i_Fe_
:: foobar --> foobar___Fb_l_Gb_i_Fe_
:: foobarChar --> foobarChar___Fb_c_Gb_c_Fe_
:: foobarChar --> foobarChar___Fb_c_Gb_c_Fe_
:: N::A::A --> L13R
:: N::A::foo --> L3R
:: N::B::B --> L14R
:: N::B::foo --> L4R
:: N::C::C --> L15R
:: N::C::foo --> L5R
:: N::C::foo --> L6R
:: N::foo --> L7R
:: foo --> foo___Fb_v_Gb_L1R_Fe_
:: foo --> foo___Fb_v_Gb_L2R_Fe_
:: foo --> L8R
:: foo --> foo___Fb_v_Gb_L1R__sep__L2R_Fe_
:: P::Q::R::R --> L16R
:: P::Q::R::foo --> L9R
:: foo < char > --> foo__tas__c__tae_____Fb_v_Gb_c_Fe_
:: foo < char > --> foo__tas__c__tae_____Fb_v_Gb_c_Fe_
:: foo < const value.t * > --> L10R
:: foo < const value.t * > --> L10R
:: P::Q::foo < long > --> L11R
:: P::Q::foo < long > --> L11R
:: P::Q::R::foo < value.t > --> L12R
:: P::Q::R::foo < value.t > --> L12R
:: foo < char > --> foo__tas__c__tae_____Fb_v_Gb_c_Fe_
:: foo < const value.t * > --> L10R
:: P::Q::foo < long > --> L11R
:: P::Q::R::foo < value.t > --> L12R
***** END function declarations *****

```

Figure 25.5: Output of input code using generatingUniqueNamesFromDeclaration.C

Chapter 26

Command-line Processing Within Translators

ROSE includes mechanism to simplify the processing of command-line arguments so that translators using ROSE can trivially replace compilers within makefiles. This example shows some of the many command-line handling options within ROSE and the ways in which customized options may be added for specific translators.

26.1 Commandline Selection of Files

Overview This example shows the optional processing of specific files selected after the call to the frontend to build the project. First the SgProject is built and *then* the files are selected for processing via ROSE or the backend compiler directly.

This example demonstrates the separation of the construction of a SgProject with valid SgFile objects for each file on the command line, but with an empty SgGlobal scope, and the call to the frontend, called for each SgFile in a separate loop over all the SgFile objects.

```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// rose.C: Example (default) ROSE Preprocessor: used for testing ROSE infrastructure

#include "rose.h"

using namespace std;

int
main ( int argc, char* argv[] )
{
    Rose_STL_Container<string> l = CommandLineProcessing::generateArgListFromArgcArgv (argc, argv);
    printf (" Preprocessor (before): argv = \n%s \n", StringUtility::listToString(l).c_str());

    // Remove certain sorts of options from the command line
    CommandLineProcessing::removeArgs (l,"-edg:");
    CommandLineProcessing::removeArgs (l,"--edg:");
    CommandLineProcessing::removeArgsWithParameters (l,"-edg_parameter:");
    CommandLineProcessing::removeArgsWithParameters (l,"--edg_parameter:");

    // Add a test for a custom command line option
    int integerOptionForVerbose = 0;
    if ( CommandLineProcessing::isOptionWithParameter(l,"-myTranslator:", "(v|verbose)", integerOptionForVerbose) )
    {
        printf ("Turning on my translator's verbose mode (set to %d) \n", integerOptionForVerbose);
    }

    // Adding a new command line parameter (for mechanisms in ROSE that take command lines)

    // printf ("argc = %zu \n", l.size());
    // l = CommandLineProcessing::generateArgListFromArgcArgv (argc, argv);
    // printf ("l.size() = %zu \n", l.size());
    printf (" Preprocessor (after): argv = \n%s \n", StringUtility::listToString(l).c_str());

    // SgProject* project = frontend(argc, argv);
    // ROSE_ASSERT (project != NULL);
    // Generate the source code and compile using the vendor's compiler
    // return backend(project);

    // Build the AST, generate the source code and call the backend compiler ...
    frontend(l);
    return 0;
}

```

Figure 26.1: Example source code showing simple command-line processing within ROSE translator.

```

Preprocessor (before): argv =
/home/liao6/daily-test-rose/20091101_120001/build/tutorial/.libs/lt-commandlineProcessing --edg:no_warnings -w
Turning on my translator's verbose mode (set to 42)
l.size() = 4
Preprocessor (after): argv =
/home/liao6/daily-test-rose/20091101_120001/build/tutorial/.libs/lt-commandlineProcessing -w -c /home/liao6/daily-test-rose/20091101_120001/build/tutorial/.libs/lt-commandlineProcessing

```

Figure 26.2: Output of input code using `commandlineProcessing.C`

Figure 26.3: Example source code showing simple command-line processing within ROSE translator.

Figure 26.4: Output of input code using `commandlineProcessing.C`

Chapter 27

Tailoring The Code Generation Format

Figure 27.1 shows an example of how to use the mechanisms in ROSE to tailor the format and style of the generated code. This chapter presents an example translator that modifies the formatting of the code that is generated within ROSE.

The details of functionality are hidden from the user and a high level interface is provided that permits key parameters to be specified. This example will be made more sophisticated later, for now it just modifies the indentation of nested code blocks (from 2 spaces/block to 5 spaces/block).

27.1 Source Code for Example that Tailors the Code Generation

Figure 27.1 shows an example translator which calls the inliner mechanism. The code is designed to only inline up to ten functions. the list of function calls is recomputed after any function call is successfully inlined.

The input code is shown in figure 27.2, the output of this code is shown in figure 27.3.

27.2 Input to Demonstrate Tailoring the Code Generation

Figure 27.2 shows the example input used for demonstration of how to control the formatting of generated code.

27.3 Final Code After Tailoring the Code Generation

Figure 27.3 shows the results from changes to the formatting of generated code.

```

// This example will be made more sophisticated later, for now it just
// modifies the indentation of nested code blocks (from 2 spaces/block
// to 5 spaces/block).

#include "rose.h"
#include "unparseFormatHelp.h"

class CustomCodeFormat : public UnparseFormatHelp
{
public:
    CustomCodeFormat();
    ~CustomCodeFormat();

    virtual int getLine( SgLocatedNode*, SgUnparse_Info& info, FormatOpt opt);
    virtual int getCol ( SgLocatedNode*, SgUnparse_Info& info, FormatOpt opt);

    // return the value for indentation of code (part of control over style)
    virtual int tabIndent ();

    // return the value for where line wrapping starts (part of control over style)
    virtual int maxLineLength ();

private:
    int defaultLineLength;
    int defaultIndentation;
};

CustomCodeFormat::CustomCodeFormat()
{
    // default values here!
    defaultLineLength = 20;
    defaultIndentation = 5;
}

CustomCodeFormat::~~CustomCodeFormat()
{}

// return: > 0: start new lines; == 0: use same line; < 0: default
int
CustomCodeFormat::getLine( SgLocatedNode*, SgUnparse_Info& info, FormatOpt opt)
{
    // Use default mechanism to select the line where to output generated code
    return -1;
}

// return starting column. if < 0, use default
int
CustomCodeFormat::getCol( SgLocatedNode*, SgUnparse_Info& info, FormatOpt opt)
{
    // Use default mechanism to select the column where to output generated code
    return -1;
}

int
CustomCodeFormat::tabIndent()
{
    // Modify the indentation of the generated code (trivial example of tailoring code generation)
    return defaultIndentation;
}

int
CustomCodeFormat::maxLineLength()
{
    return defaultLineLength;
}

int main (int argc, char* argv[])
{
    // Build the project object (AST) which we will fill up with multiple files and use as a
    // handle for all processing of the AST(s) associated with one or more source files.
    SgProject* project = new SgProject(argc,argv);

    CustomCodeFormat* formatControl = new CustomCodeFormat();

    return backend(project,formatControl);
}

```

Figure 27.1: Example source code showing how to tailor the code generation format.

Figure 27.2: Example source code used as input to program to the tailor the code generation.

Chapter 28

AST Construction

AST construction is a fundamental operation needed for building ROSE source-to-source translators. Several levels of interfaces are available in ROSE for users to build AST from scratch. High level interfaces are recommended to use whenever possible for their simplicity. Low level interfaces can give users the maximum freedom to manipulate some details in AST trees.

This chapter uses several examples to demonstrate how to create AST fragments for common language constructs (such as variable declarations, functions, function calls, etc.) and how to insert them into an existing AST tree. More examples of constructing AST using high level interfaces can be found at *rose/tests/roseTests/astInterfaceTests*. The source files of the high level interfaces are located in *rose/src/frontend/SageIII/sageInterface*.

28.1 Variable Declarations

What To Learn Two examples are given to show how to construct a SAGE III AST subtree for a variable declaration and its insertion into the existing AST tree.

- Example 1. Building a variable declaration using the high level AST construction and manipulation interfaces defined in namespace SageBuilder and SageInterface.

Figure 28.1 shows the high level construction of an AST fragment (a variable declaration) and its insertion into the AST at the top of each block. `buildVariableDeclaration()` takes the name and type to build a variable declaration node. `prependStatement()` inserts the declaration at the top of a basic block node. Details for parent and scope pointers, symbol tables, source file position information and so on are handled transparently.

- Example 2. Building the variable declaration using low level member functions of SAGE III node classes.

Figure 28.2 shows the low level construction of the same AST fragment (for the same variable declaration) and its insertion into the AST at the top of each block. `SgNode` constructors and their member functions are used. Side effects for scope, parent pointers and symbol tables have to be handled by programmers explicitly.

```

// SageBuilder contains all high level buildXXX() functions,
// such as buildVariableDeclaration(), buildLabelStatement() etc.
// SageInterface contains high level AST manipulation and utility functions,
// e.g. appendStatement(), lookupFunctionSymbolInParentScopes() etc.
#include "rose.h"
using namespace SageBuilder;
using namespace SageInterface;

class SimpleInstrumentation:public SgSimpleProcessing
{
public:
    void visit (SgNode * astNode);
};

void
SimpleInstrumentation::visit (SgNode * astNode)
{
    SgBasicBlock *block = isSgBasicBlock (astNode);
    if (block != NULL)
    {
        SgVariableDeclaration *variableDeclaration =
            buildVariableDeclaration ("newVariable", buildIntType ());
        prependStatement (variableDeclaration, block);
    }
}

int
main (int argc, char *argv[])
{
    SgProject *project = frontend (argc, argv);
    ROSE_ASSERT (project != NULL);

    SimpleInstrumentation treeTraversal;
    treeTraversal.traverseInputFiles (project, preorder);

    AstTests::runAllTests (project);
    return backend (project);
}

```

Figure 28.1: AST construction and insertion for a variable using the high level interfaces

```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// Specifically it shows the design of a transformation to instrument source code, placing source code
// at the top and bottom of each basic block.
// Member functions of SAGE III AST node classes are directly used.
// So all details for Sg_File_Info, scope, parent, symbol tables have to be explicitly handled.

#include "rose.h"

class SimpleInstrumentation : public SgSimpleProcessing
{
public:
    void visit ( SgNode* astNode );
};

void
SimpleInstrumentation::visit ( SgNode* astNode )
{
    SgBasicBlock* block = isSgBasicBlock(astNode);
    if (block != NULL)
    {
        // Mark this as a transformation (required)
        Sg_File_Info* sourceLocation = Sg_File_Info::generateDefaultFileInfoForTransformationNode();
        ROSE_ASSERT(sourceLocation != NULL);

        SgType* type = new SgTypeInt();
        ROSE_ASSERT(type != NULL);

        SgName name = "newVariable";

        SgVariableDeclaration* variableDeclaration = new SgVariableDeclaration(sourceLocation, name, type);
        ROSE_ASSERT(variableDeclaration != NULL);

        SgInitializedName* initializedName = *(variableDeclaration->get_variables().begin());

        // DQ (6/18/2007): The unparser requires that the scope be set (for name qualification to work).
        initializedName->set_scope(block);

        // Liao (2/13/2008): AstTests requires this to be set
        variableDeclaration->set_firstNondefiningDeclaration(variableDeclaration);

        ROSE_ASSERT(block->get_statements().size() > 0);

        block->get_statements().insert(block->get_statements().begin(), variableDeclaration);
        variableDeclaration->set_parent(block);

        // Add a symbol to the sybol table for the new variable
        SgVariableSymbol* variableSymbol = new SgVariableSymbol(initializedName);
        block->insert_symbol(name, variableSymbol);
    }
}

int
main ( int argc, char * argv[] )
{
    SgProject* project = frontend(argc, argv);
    ROSE_ASSERT(project != NULL);

    SimpleInstrumentation treeTraversal;
    treeTraversal.traverseInputFiles ( project, preorder );

    AstTests::runAllTests(project);
    return backend(project);
}

```

Figure 28.2: Example source code to read an input program and add a new variable declaration at the top of each block.

```
int main()
{
    for (int i=0; i < 4; i++)
    {
        int x;
    }

    return 0;
}
```

Figure 28.3: Example source code used as input to the translators adding new variable.

```
int main()
{
    int newVariable;
    for (int i = 0; i < 4; i++) {
        int newVariable;
        int x;
    }
    return 0;
}
```

Figure 28.4: Output of input to the translators adding new variable.

Figure 28.3 shows the input code used to test the translator. Figure 28.4 shows the resulting output.

28.2 Expressions

Figure 28.5 shows a translator using the high level AST builder interface to add an assignment statement right before the last statement in a main() function.

Figure 28.6 shows the input code used to test the translator. Figure 28.7 shows the resulting output.

```
// Expressions can be built using both bottomup (recommended ) and topdown orders .
// Bottomup: build operands first , operation later
// Topdown: build operation first , set operands later on .

#include "rose.h"
using namespace SageBuilder;
using namespace SageInterface;

int main (int argc , char *argv[])
{
    SgProject *project = frontend (argc , argv);
    // go to the function body
    SgFunctionDeclaration* mainFunc= findMain(project);

    SgBasicBlock* body= mainFunc->get_definition()->get_body();
    pushScopeStack(body);

    // bottomup: build operands first , create expression later on
    // double result = 2 * (1 - gama * gama);
    SgExpression * init_exp =
        buildMultiplyOp(buildDoubleVal(2.0),
            buildSubtractOp(buildDoubleVal(1.0),
                buildMultiplyOp (buildVarRefExp("gama"), buildVarRefExp("gama")
                    )))
    SgVariableDeclaration* decl = buildVariableDeclaration("result", buildDoubleType(), buildAssignInitializer(init_exp));

    SgStatement* laststmt = getLastStatement(topScopeStack());
    insertStatementBefore(laststmt, decl);

    // topdown: build expression first , set operands later on
    // double result2 = alpha * beta;
    SgExpression * init_exp2 = buildMultiplyOp();
    setLhsOperand(init_exp2, buildVarRefExp("alpha"));
    setRhsOperand(init_exp2, buildVarRefExp("beta"));

    SgVariableDeclaration* decl2 = buildVariableDeclaration("result2", buildDoubleType(), buildAssignInitializer(init_exp2));
    laststmt = getLastStatement(topScopeStack());
    insertStatementBefore(laststmt, decl2);

    popScopeStack();
    AstTests::runAllTests(project);

    //invoke backend compiler to generate object/binary files
    return backend (project);
}
```

Figure 28.5: Example translator to add expressions

```
int main()
{
    double alpha= 0.5;
    double beta = 0.1;
    double gama = 0.7;

    return 0;
}
```

Figure 28.6: Example source code used as input

```
int main()
{
    double alpha = 0.5;
    double beta = 0.1;
    double gama = 0.7;
    double result = 2.00000 * (1.00000 - gama * gama);
    double result2 = alpha * beta;
    return 0;
}
```

Figure 28.7: Output of the input

28.3 Assignment Statements

Figure 28.8 shows a translator using the high level AST builder interface to add an assignment statement right before the last statement in a main() function.

Figure 28.9 shows the input code used to test the translator. Figure 28.10 shows the resulting output.

```
// SageBuilder contains all high level buildXXX() functions,
// such as buildVariableDeclaration(), buildLabelStatement() etc.
// SageInterface contains high level AST manipulation and utility functions,
// e.g. appendStatement(), lookupFunctionSymbolInParentScopes() etc.
#include "rose.h"
using namespace SageBuilder;
using namespace SageInterface;

int main (int argc, char *argv[])
{
    SgProject *project = frontend (argc, argv);

    // go to the function body of main()
    // and push it to the scope stack
    SgFunctionDeclaration* mainFunc= findMain(project);
    SgBasicBlock* body= mainFunc->get_definition()->get_body();
    pushScopeStack(body);

    // build a variable assignment statement: i=9;
    // buildVarRefExp(string varName) will automatically search for a matching variable symbol starting
    // from the current scope to the global scope.
    SgExprStatement* assignStmt = buildAssignStatement(buildVarRefExp("i"),buildIntVal(9));

    // insert it before the last return statement
    SgStatement* lastStmt = getLastStatement(topScopeStack());
    insertStatementBefore(lastStmt, assignStmt);

    popScopeStack();

    //AstTests ensures there is no dangling SgVarRefExp without a mathing symbol
    AstTests::runAllTests(project);
    return backend (project);
}
```

Figure 28.8: Example source code to add an assignment statement

```
int main(int argc, char* argv[])
{
    int i;
    return 0;
}
```

Figure 28.9: Example source code used as input

```
int main(int argc, char *argv[])
{
    int i;
    i = 9;
    return 0;
}
```

Figure 28.10: Output of the input

28.4 Functions

This section shows how to add a function at the top of a global scope in a file. Again, examples for both high level and low level constructions of AST are given.

- Figure 28.11 shows the high level construction of a defining function (a function with a function body). Scope information is passed to builder functions explicitly when it is needed.

```
// This example shows how to construct a defining function (with a function body)
// using high level AST construction interfaces.
//
#include "rose.h"
using namespace SageBuilder;
using namespace SageInterface;

class SimpleInstrumentation : public SgSimpleProcessing
{
public:
    void visit ( SgNode* astNode );
};

void
SimpleInstrumentation::visit ( SgNode* astNode )
{
    SgGlobal* globalScope = isSgGlobal(astNode);
    if (globalScope != NULL)
    {
        // *****
        // Create a parameter list with a parameter
        // *****
        SgName var1_name = "var_name";
        SgReferenceType *ref_type = buildReferenceType(buildIntType());
        SgInitializedName *var1_init_name = buildInitializedName(var1_name, ref_type);
        SgFunctionParameterList* parameterList = buildFunctionParameterList();
        appendArg(parameterList, var1_init_name);

        // *****
        // Create a defining functionDeclaration (with a function body)
        // *****
        SgName func_name = "my-function";
        SgFunctionDeclaration *func = buildDefiningFunctionDeclaration(
            func_name, buildIntType(), parameterList, globalScope);
        SgBasicBlock* func_body = func->get_definition()->get_body();

        // *****
        // Insert a statement in the function body
        // *****
        SgVarRefExp *var_ref = buildVarRefExp(var1_name, func_body);
        SgPlusPlusOp *pp_expression = buildPlusPlusOp(var_ref);
        SgExprStatement* new_stmt = buildExprStatement(pp_expression);

        // insert a statement into the function body
        prependStatement(new_stmt, func_body);
        prependStatement(func, globalScope);
    }
}

int
main ( int argc, char * argv[] )
{
    SgProject* project = frontend(argc, argv);
    ROSE_ASSERT(project != NULL);

    SimpleInstrumentation treeTraversal;
    treeTraversal.traverseInputFiles ( project, preorder );

    AstTests::runAllTests(project);
    return backend(project);
}
```

Figure 28.11: Addition of function to global scope using high level interfaces

- Figure 28.12 shows almost the same high level construction of the defining function, but

with an additional scope stack. Scope information is passed to builder functions implicitly when it is needed.

```
// This example shows how to construct a defining function (with a function body)
// using high level AST construction interfaces.
// A scope stack is used to pass scope information implicitly to some builder functions
#include "rose.h"
using namespace SageBuilder;
using namespace SageInterface;

int
main ( int argc, char * argv[] )
{
    SgProject* project = frontend(argc,argv);
    ROSE_ASSERT(project != NULL);
    SgGlobal *globalScope = getFirstGlobalScope (project);

    //push global scope into stack
    pushScopeStack (isSgScopeStatement (globalScope));

    // Create a parameter list with a parameter
    SgName var1_name = "var_name";
    SgReferenceType *ref_type = buildReferenceType(buildIntType());
    SgInitializedName *var1_init_name = buildInitializedName(var1_name, ref_type);
    SgFunctionParameterList* parameterList = buildFunctionParameterList();
    appendArg (parameterList, var1_init_name);

    // Create a defining functionDeclaration (with a function body)
    SgName func_name = "my_function";
    SgFunctionDeclaration * func = buildDefiningFunctionDeclaration
        (func_name, buildIntType(), parameterList);
    SgBasicBlock* func_body = func->get_definition()->get_body();

    // push function body scope into stack
    pushScopeStack(isSgScopeStatement(func_body));

    // build a statement in the function body
    SgVarRefExp *var_ref = buildVarRefExp(var1_name);
    SgPlusPlusOp *pp_expression = buildPlusPlusOp(var_ref);
    SgExprStatement* new_stmt = buildExprStatement(pp_expression);

    // insert a statement into the function body
    appendStatement(new_stmt);
    // pop function body off the stack
    popScopeStack();

    // insert the function declaration into the scope at the top of the scope stack
    prependStatement(func);
    popScopeStack();

    AstTests::runAllTests(project);
    return backend(project);
}
```

Figure 28.12: Addition of function to global scope using high level interfaces and a scope stack

- The low level construction of the AST fragment of the same function declaration and its insertion is separated into two portions and shown in two figures (Figure 28.13 and Figure 28.14).

Figure 28.29 and Figure 28.30 give the input code and output result for the translators above.

```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// Specifically it shows the design of a transformation to instrument source code, placing source code
// at the top of the source file.

#include "rose.h"

#define TRANSFORMATION_FILE_INFO Sg_File_Info::generateDefaultFileInfoForTransformationNode()

class SimpleInstrumentation : public SgSimpleProcessing
{
public:
    void visit ( SgNode* astNode );
};

void
SimpleInstrumentation::visit ( SgNode* astNode )
{
    SgGlobal* globalScope = isSgGlobal(astNode);
    if (globalScope != NULL)
    {
        // *****
        // Create the functionDeclaration
        // *****
        SgType* func_return_type = new SgTypeInt();
        SgName func_name = "my-function";
        SgFunctionType* func_type = new SgFunctionType(func_return_type, false);
        SgFunctionDeclaration* func = new SgFunctionDeclaration(TRANSFORMATION_FILE_INFO, func_name, func_type);
        SgFunctionDefinition* func_def = new SgFunctionDefinition(TRANSFORMATION_FILE_INFO, func);
        SgBasicBlock* func_body = new SgBasicBlock(TRANSFORMATION_FILE_INFO);

        // set the end source position as transformation generated
        // since the constructors only set the beginning source position by default
        func->set_endOfConstruct(TRANSFORMATION_FILE_INFO);
        func->get_endOfConstruct()->set_parent(func);

        func_def->set_endOfConstruct(TRANSFORMATION_FILE_INFO);
        func_def->get_endOfConstruct()->set_parent(func_def);

        func_body->set_endOfConstruct(TRANSFORMATION_FILE_INFO);
        func_body->get_endOfConstruct()->set_parent(func_body);

        // Sets the body into the definition
        func_def->set_body(func_body);
        // Sets the definition's parent to the declaration
        func_def->set_parent(func);

        // DQ (9/8/2007): Fixup the defining and non-defining declarations
        ROSE_ASSERT(func->get_definingDeclaration() == NULL);
        func->set_definingDeclaration(func);
        ROSE_ASSERT(func->get_definingDeclaration() != NULL);
        ROSE_ASSERT(func->get_firstNondefiningDeclaration() != func);

        // DQ (9/8/2007): We have not build a non-defining declaration, so this should be NULL.
        ROSE_ASSERT(func->get_firstNondefiningDeclaration() == NULL);

        // DQ (9/8/2007): Need to add function symbol to global scope!
        //printf ("Fixing up the symbol table in scope = %p = %s for function = %p = %s \n", globalScope, globalScope->class_name().c_str(), func, func->get_name().c_str());
        SgFunctionSymbol* functionSymbol = new SgFunctionSymbol(func);
        globalScope->insert_symbol(func->get_name(), functionSymbol);
        ROSE_ASSERT(globalScope->lookup_function_symbol(func->get_name()) != NULL);

        // *****
        // Create the InitializedName for a parameter within the parameter list
        // *****
        SgName var1_name = "var_name";

        SgTypeInt* var1_type = new SgTypeInt();
        SgReferenceType* ref_type = new SgReferenceType(var1_type);
        SgInitializer* var1_initializer = NULL;

        SgInitializedName* var1_init_name = new SgInitializedName(var1_name, ref_type, var1_initializer, NULL);
        var1_init_name->set_file_info(TRANSFORMATION_FILE_INFO);

        // DQ (9/8/2007): We now test this, so it has to be set explicitly.
        var1_init_name->set_scope(func_def);

        // DQ (9/8/2007): Need to add variable symbol to global scope!
        //printf ("Fixing up the symbol table in scope = %p = %s for SgInitializedName = %p = %s \n", globalScope, globalScope->class_name().c_str(), var1_init_name, var1_init_name->get_name().c_str());
        SgVariableSymbol* var_symbol = new SgVariableSymbol(var1_init_name);
        func_def->insert_symbol(var1_init_name->get_name(), var_symbol);
    }
}

```

Figure 28.13: Example source code shows addition of function to global scope (part 1).

```

ROSE_ASSERT(func_def->lookup_variable_symbol(var1_init_name->get_name()) != NULL);
ROSE_ASSERT(var1_init_name->get_symbol_from_symbol_table() != NULL);

// Done constructing the InitializedName variable

// Insert argument in function parameter list
ROSE_ASSERT(func != NULL);
// Sg_File_Info * parameterListFileInfo = new Sg_File_Info();
// Sg_File_Info * parameterListFileInfo = Sg_File_Info::generateDefaultFileInfoForTransformationNode();
// SgFunctionParameterList * parameterList = new SgFunctionParameterList(TRANSFORMATION_FILE_INFO);
ROSE_ASSERT(parameterList != NULL);
func->set_parameterList(parameterList);
ROSE_ASSERT(func->get_parameterList() != NULL);
func->get_parameterList()->append_arg(var1_init_name);

// *****
// Insert a statement in the function body
// *****

// create a VarRefExp
// SgVariableSymbol * var_symbol = new SgVariableSymbol(var1_init_name);
// SgVarRefExp * var_ref = new SgVarRefExp(TRANSFORMATION_FILE_INFO, var_symbol);
// var_ref->set_endOfConstruct(TRANSFORMATION_FILE_INFO);
// var_ref->get_endOfConstruct()->set_parent(var_ref);

// create a ++ expression, 0 for prefix ++
// SgPlusPlusOp * pp_expression = new SgPlusPlusOp(TRANSFORMATION_FILE_INFO, var_ref, 0);
// pp_expression->set_endOfConstruct(TRANSFORMATION_FILE_INFO);
// pp_expression->get_endOfConstruct()->set_parent(pp_expression);

// create an expression statement
// SgExprStatement * new_stmt = new SgExprStatement(TRANSFORMATION_FILE_INFO, pp_expression);
// new_stmt->set_endOfConstruct(TRANSFORMATION_FILE_INFO);
// new_stmt->get_endOfConstruct()->set_parent(new_stmt);

#if 0
// DQ (9/8/2007): This is no longer required, SgExpressionRoot is not longer used in the ROSE IR.
// create an expression type
// SgTypeInt * expr_type = new SgTypeInt();

// create an expression root
// SgExpressionRoot * expr_root = new SgExpressionRoot(TRANSFORMATION_FILE_INFO, pp_expression, expr_type);
// expr_root->set_parent(new_stmt);

// DQ (11/8/2006): Modified to reflect use of SgExpression instead of SgExpressionRoot
// new_stmt->set_expression(expr_root);

// pp_expression->set_parent(new_stmt->get_expression());

#endif
// pp_expression->set_parent(new_stmt);

// insert a statement into the function body
// func_body->prepend_statement(new_stmt);

// setting the parent explicitly is not required since it would be done within AST post-processing
// func->set_parent(globalScope);

// scopes of statements must be set explicitly since within C++ they are not guaranteed
// to be the same as that indicated by the parent (see ChangeLog for Spring 2005).
// func->set_scope(globalScope);

// *****
// Insert the function declaration in the code
// *****
// globalScope->prepend_declaration(func);

// Required post processing of AST required to set parent pointers and fixup template names, etc.
// temporaryAstFixes(globalScope);
// AstPostProcessing(globalScope);
}

}

int
main ( int argc, char * argv[] )
{
    SgProject* project = frontend(argc, argv);
    ROSE_ASSERT(project != NULL);

    SimpleInstrumentation treeTraversal;
    treeTraversal.traverseInputFiles ( project, preorder );
}

```

Figure 28.14: Example source code shows addition of function to global scope (part 2).


```
int main()
{
    for (int i=0; i < 4; i++)
    {
        int x;
    }

    return 0;
}
```

Figure 28.15: Example source code used as input to translator adding new function.

```
int my_function(int &var_name)
{
    ++var_name;
}

int main()
{
    for (int i = 0; i < 4; i++) {
        int x;
    }
    return 0;
}
```

Figure 28.16: Output of input to translator adding new function.

28.5 Function Calls

Adding functions calls is a typical task for instrumentation translator.

- Figure 28.17 shows the use of the AST string based rewrite mechanism to add function calls to the top and bottom of each block within the AST.
- Figure 28.18 shows the use of the AST builder interface to do the same instrumentation work.

Figure 28.19 shows the input code used to get the translator. Figure 28.20 shows the resulting output.

Another example shows how to add a function call at the end of each function body. A utility function, *instrumentEndOfFunction()*, from SageInterface name space is used. The interface tries to locate all return statements of a target function and rewriting return expressions with side effects, if there are any. Figure 28.21 shows the translator code. Figure 28.22 shows the input code. The instrumented code is shown in Figure 28.23.

28.6 Creating a 'struct' for Global Variables

*TODO: This tutorial
rel AST manipulation.
d have a more concise
ing SageInterface and
SageBuilder functions.*

This is an example written to support the Charm++ tool. This translator extracts global variables from the program and builds a structure to hold them. The support is part of a number of requirements associated with using Charm++ and AMPL.

Figure 28.24 shows repackaging of global variables within an application into a struct. All reference to the global variables are also transformed to reference the original variable indirectly through the structure. This processing is part of preprocessing to use Charm++.

This example shows the low level handling directly at the level of the IR.

```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// Specifically it shows the design of a transformation to instrument source code, placing source code
// at the top and bottom of each basic block.

#include "rose.h"

using namespace std;

class SimpleInstrumentation : public SgSimpleProcessing
{
public:
    void visit ( SgNode* astNode );
};

void
SimpleInstrumentation::visit ( SgNode* astNode )
{
    SgBasicBlock* block = isSgBasicBlock(astNode);
    if (block != NULL)
    {
        const unsigned int SIZE_OF_BLOCK = 1;
        if (block->get_statements().size() > SIZE_OF_BLOCK)
        {
            // It is up to the user to link the implementations of these functions link time
            string codeAtTopOfBlock = "void myTimerFunctionStart(); myTimerFunctionStart();";
            string codeAtBottomOfBlock = "void myTimerFunctionEnd(); myTimerFunctionEnd();";

            // Insert new code into the scope represented by the statement (applies to SgScopeStatements)
            MiddleLevelRewrite::ScopeIdentifierEnum scope = MidLevelCollectionTypedefs::StatementScope;

            // Insert the new code at the top and bottom of the scope represented by block
            MiddleLevelRewrite::insert(block, codeAtTopOfBlock, scope,
                                     MidLevelCollectionTypedefs::TopOfCurrentScope);
            MiddleLevelRewrite::insert(block, codeAtBottomOfBlock, scope,
                                     MidLevelCollectionTypedefs::BottomOfCurrentScope);
        }
    }
}

int
main ( int argc, char * argv[] )
{
    SgProject* project = frontend(argc, argv);
    ROSE_ASSERT(project != NULL);

    SimpleInstrumentation treeTraversal;
    treeTraversal.traverseInputFiles ( project, preorder );

    AstTests::runAllTests(project);
    return backend(project);
}

```

Figure 28.17: Example source code to instrument any input program.

```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// Specifically it shows the design of a transformation to instrument source code, placing source code
// at the top and bottom of each basic block.

#include "rose.h"
using namespace std;
using namespace SageInterface;
using namespace SageBuilder;

class SimpleInstrumentation:public SgSimpleProcessing
{
public:
    void visit (SgNode * astNode);
};

void
SimpleInstrumentation::visit (SgNode * astNode)
{
    SgBasicBlock *block = isSgBasicBlock (astNode);
    if (block != NULL)
    {
        const unsigned int SIZE_OF_BLOCK = 1;
        if (block->get_statements ().size () > SIZE_OF_BLOCK)
        {
            SgName name1(" myTimerFunctionStart");
            // It is up to the user to link the implementations of these functions link time
            SgFunctionDeclaration *decl_1 = buildNondefiningFunctionDeclaration
                (name1,buildVoidType(),buildFunctionParameterList(),block);
            ((decl_1->get_declarationModifier()).get_storageModifier()).setExtern();

            SgExprStatement* callStmt_1 = buildFunctionCallStmt
                (name1,buildVoidType(), buildExprListExp(),block);

            prependStatement(callStmt_1,block);
            prependStatement(decl_1,block);

            SgName name2(" myTimerFunctionEnd");
            // It is up to the user to link the implementations of these functions link time
            SgFunctionDeclaration *decl_2 = buildNondefiningFunctionDeclaration
                (name2,buildVoidType(),buildFunctionParameterList(),block);
            ((decl_2->get_declarationModifier()).get_storageModifier()).setExtern();

            SgExprStatement* callStmt_2 = buildFunctionCallStmt
                (name2,buildVoidType(), buildExprListExp(),block);

            appendStatement(decl_2,block);
            appendStatement(callStmt_2,block);
        }
    }
}

int
main (int argc, char *argv[])
{
    SgProject *project = frontend (argc, argv);
    ROSE_ASSERT (project != NULL);

    SimpleInstrumentation treeTraversal;
    treeTraversal.traverseInputFiles (project, preorder);

    AstTests::runAllTests (project);
    return backend (project);
}

```

Figure 28.18: Example source code using the high level interfaces

```
// Overloaded functions for testing overloaded function resolution
void foo(double)
{
    int x = 1;
    int y;

    // I think that this case fails currently
    // if (x) y = 1; else y = 2;
}
```

Figure 28.19: Example source code used as input to instrumenting translator.

```
// Overloaded functions for testing overloaded function resolution
void foo(double )
{
    extern void myTimerFunctionStart();
    myTimerFunctionStart();
    int x = 1;
    int y;
    extern void myTimerFunctionEnd();
    myTimerFunctionEnd();
    // I think that this case fails currently
    // if (x) y = 1; else y = 2;
}
```

Figure 28.20: Output of input to instrumenting translator.

```

/*! \brief test instrumentation right before the end of a function
*/
#include "rose.h"
#include <iostream>
using namespace SageInterface;
using namespace SageBuilder;

int main (int argc, char *argv[])
{
    SgProject *project = frontend (argc, argv);

    // Find all function definitions we want to instrument
    std::vector<SgNode* > funcDefList =
        NodeQuery::querySubTree (project, V_SgFunctionDefinition);

    std::vector<SgNode*>::iterator iter;
    for (iter = funcDefList.begin(); iter!= funcDefList.end(); iter++)
    {
        SgFunctionDefinition* cur_def = isSgFunctionDefinition(*iter);
        ROSE_ASSERT(cur_def);
        SgBasicBlock* body = cur_def->get_body();
        // Build the call statement for each place
        SgExprStatement* callStmt1 = buildFunctionCallStmt(" call1",
            buildIntType(), buildExprListExp() ,body);

        // instrument the function
        int i= instrumentEndOfFunction(cur_def->get_declaration(), callStmt1);
        std::cout<<"Instrumented "<<i<<" places. "<<std::endl;

    } // end of instrumentation

    AstTests::runAllTests(project);
    // translation only
    project->unparse();
}

```

Figure 28.21: Example source code instrumenting end of functions

```

/* Example code:
 * a function with multiple returns
 * some returns have expressions with side effects
 * a function without any return
 */
extern int foo();
extern int call1();
int main(int argc, char* argv[])
{
    if (argc>1)
        return foo();
    else
        return foo();
    return 0;
}

void bar()
{
    int i;
}

```

Figure 28.22: Example input code of the instrumenting translator for end of functions.

```
/* Example code:
 * a function with multiple returns
 * some returns have expressions with side effects
 * a function without any return
 */
extern int foo();
extern int call1();

int main(int argc, char *argv[])
{
    if (argc > 1) {
        int rose_temp--1 = foo();
        call1();
        return rose_temp--1;
    }
    else {
        int rose_temp--2 = foo();
        call1();
        return rose_temp--2;
    }
    call1();
    return 0;
}

void bar()
{
    int i;
    call1();
}
```

Figure 28.23: Output of instrumenting translator for end of functions.

```

// ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
// Specifically it shows the design of a transformation to do a transformation specific for Charm++.

#include "rose.h"

using namespace std;

Rose_STL_Container<SgInitializedName*>
buildListOfGlobalVariables ( SgSourceFile* file )
{
    // This function builds a list of global variables (from a SgFile).
    assert( file != NULL );

    Rose_STL_Container<SgInitializedName*> globalVariableList;

    SgGlobal* globalScope = file->get_globalScope();
    assert( globalScope != NULL );
    Rose_STL_Container<SgDeclarationStatement*>::iterator i = globalScope->get_declarations().begin();
    while( i != globalScope->get_declarations().end() )
    {
        SgVariableDeclaration *variableDeclaration = isSgVariableDeclaration(*i);
        if ( variableDeclaration != NULL )
        {
            Rose_STL_Container<SgInitializedName*> & variableList = variableDeclaration->get_variables();
            Rose_STL_Container<SgInitializedName*>::iterator var = variableList.begin();
            while( var != variableList.end() )
            {
                globalVariableList.push_back(*var);
                var++;
            }
        }
        i++;
    }

    return globalVariableList;
}

// This function is not used, but is useful for
// generating the list of all global variables
Rose_STL_Container<SgInitializedName*>
buildListOfGlobalVariables ( SgProject* project )
{
    // This function builds a list of global variables (from a SgProject).

    Rose_STL_Container<SgInitializedName*> globalVariableList;

    const SgFilePtrList& fileList = project->get_fileList();
    SgFilePtrList::const_iterator file = fileList.begin();

    // Loop over the files in the project (multiple files exist
    // when multiple source files are placed on the command line).
    while( file != fileList.end() )
    {
        Rose_STL_Container<SgInitializedName*> fileGlobalVariableList = buildListOfGlobalVariables(isSgSourceFile(*file));

        // DQ (9/26/2007): Moved from std::list to std::vector
        // globalVariableList.merge(fileGlobalVariableList);
        globalVariableList.insert(globalVariableList.begin(), fileGlobalVariableList.begin(), fileGlobalVariableList.end());

        file++;
    }

    return globalVariableList;
}

Rose_STL_Container<SgVarRefExp*>
buildListOfVariableReferenceExpressionsUsingGlobalVariables ( SgNode* node )
{
    // This function builds a list of "uses" of variables (SgVarRefExp IR nodes) within the AST.

    // return variable
    Rose_STL_Container<SgVarRefExp*> globalVariableUseList;

    // list of all variables (then select out the global variables by testing the scope)
    Rose_STL_Container<SgNode*> nodeList = NodeQuery::querySubTree ( node, V_SgVarRefExp );

    Rose_STL_Container<SgNode*>::iterator i = nodeList.begin();
    while( i != nodeList.end() )
    {
        SgVarRefExp *variableReferenceExpression = isSgVarRefExp(*i);

```

Figure 28.24: Example source code shows repackaging of global variables to a struct (part 1).


```

    assert(variableReferenceExpression != NULL);

    assert(variableReferenceExpression->get_symbol() != NULL);
    assert(variableReferenceExpression->get_symbol()->get_declaration() != NULL);
    assert(variableReferenceExpression->get_symbol()->get_declaration()->get_scope() != NULL);

    // Note that variableReferenceExpression->get_symbol()->get_declaration() returns the
    // SgInitializedName (not the SgVariableDeclaration where it was declared)!
    SgInitializedName* variable = variableReferenceExpression->get_symbol()->get_declaration();

    SgScopeStatement* variableScope = variable->get_scope();

    // Check if this is a variable declared in global scope, if so, then save it
    if (isSgGlobal(variableScope) != NULL)
    {
        globalVariableUseList.push_back(variableReferenceExpression);
    }
    i++;
}
return globalVariableUseList;
}

SgClassDeclaration*
buildClassDeclarationAndDefinition (string name, SgScopeStatement* scope)
{
    // This function builds a class declaration and definition
    // (both the defining and nondefining declarations as required).

    // Build a file info object marked as a transformation
    Sg_File_Info* fileInfo = Sg_File_Info::generateDefaultFileInfoForTransformationNode();
    assert(fileInfo != NULL);

    // This is the class definition (the fileInfo is the position of the opening brace)
    SgClassDefinition* classDefinition = new SgClassDefinition(fileInfo);
    assert(classDefinition != NULL);

    // Set the end of construct explicitly (where not a transformation this is the location of the closing brace)
    classDefinition->set_endOfConstruct(fileInfo);

    // This is the defining declaration for the class (with a reference to the class definition)
    SgClassDeclaration* classDeclaration = new SgClassDeclaration(fileInfo, name.c_str(), SgClassDeclaration::e_struct, NULL, classDefinition);
    assert(classDeclaration != NULL);

    // Set the defining declaration in the defining declaration!
    classDeclaration->set_definingDeclaration(classDeclaration);

    // Set the non defining declaration in the defining declaration (both are required)
    SgClassDeclaration* nondefiningClassDeclaration = new SgClassDeclaration(fileInfo, name.c_str(), SgClassDeclaration::e_struct, NULL, NULL);
    assert(classDeclaration != NULL);

    // Set the internal reference to the non-defining declaration
    classDeclaration->set_firstNondefiningDeclaration(nondefiningClassDeclaration);

    // Set the defining and non-defining declarations in the non-defining class declaration!
    nondefiningClassDeclaration->set_firstNondefiningDeclaration(nondefiningClassDeclaration);
    nondefiningClassDeclaration->set_definingDeclaration(classDeclaration);

    // Set the nondefining declaration as a forward declaration!
    nondefiningClassDeclaration->setForward();

    // Don't forget the set the declaration in the definition (IR node constructors are side-effect free!)
    classDefinition->set_declaration(classDeclaration);

    // set the scope explicitly (name qualification tricks can imply it is not always the parent IR node!)
    classDeclaration->set_scope(scope);
    nondefiningClassDeclaration->set_scope(scope);

    // some error checking
    assert(classDeclaration->get_definingDeclaration() != NULL);
    assert(classDeclaration->get_firstNondefiningDeclaration() != NULL);
    assert(classDeclaration->get_definition() != NULL);

    // DQ (9/8/2007): Need to add function symbol to global scope!
    printf ("Fixing up the symbol table in scope = %p = %s for class = %p = %s \n", scope, scope->class_name().c_str(), classDeclaration, classDe
    SgClassSymbol* classSymbol = new SgClassSymbol(classDeclaration);
    scope->insert_symbol(classDeclaration->get_name(), classSymbol);
    ROSE_ASSERT(scope->lookup_class_symbol(classDeclaration->get_name()) != NULL);

```

Figure 28.25: Example source code shows repackaging of global variables to a struct (part 2).

```

    return classDeclaration;
}

SgVariableSymbol*
putGlobalVariablesIntoClass (Rose_STL_Container<SgInitializedName*> & globalVariables, SgClassDeclaration* classDeclaration)
{
    // This function iterates over the list of global variables and inserts them into the input class definition
    SgVariableSymbol* globalClassVariableSymbol = NULL;

    for (Rose_STL_Container<SgInitializedName*>::iterator var = globalVariables.begin(); var != globalVariables.end(); var++)
    {
        printf ("Appending global variable = %s to new globalVariableContainer \n", (*var)->get_name().str());
        SgVariableDeclaration* globalVariableDeclaration = isSgVariableDeclaration((*var)->get_parent());
        assert(globalVariableDeclaration != NULL);

        // Get the global scope from the global variable directly
        SgGlobal* globalScope = isSgGlobal(globalVariableDeclaration->get_scope());
        assert(globalScope != NULL);

        if (var == globalVariables.begin())
        {
            // This is the first time in this loop, replace the first global variable with
            // the class declaration/definition containing all the global variables!
            // Note that initializers in the global variable declarations require modification
            // of the preinitialization list in the class's constructor! I am ignoring this for now!
            globalScope->replace_statement(globalVariableDeclaration, classDeclaration);

            // Build source position information (marked as transformation)
            Sg_File_Info* fileInfo = Sg_File_Info::generateDefaultFileInfoForTransformationNode();
            assert(fileInfo != NULL);

            // Add the variable of the class type to the global scope!
            SgClassType* variableType = new SgClassType(classDeclaration->get_firstNondefiningDeclaration());
            assert(variableType != NULL);
            SgVariableDeclaration* variableDeclaration = new SgVariableDeclaration(fileInfo, "AMPI_globals", variableType);
            assert(variableDeclaration != NULL);

            globalScope->insert_statement(classDeclaration, variableDeclaration, false);

            assert(variableDeclaration->get_variables().empty() == false);
            SgInitializedName* variableName = *(variableDeclaration->get_variables().begin());
            assert(variableName != NULL);

            // DQ (9/8/2007): Need to set the scope of the new variable.
            variableName->set_scope(globalScope);

            // build the return value
            globalClassVariableSymbol = new SgVariableSymbol(variableName);

            // DQ (9/8/2007): Need to add the symbol to the global scope (new testing requires this).
            globalScope->insert_symbol(variableName->get_name(), globalClassVariableSymbol);
            ROSE_ASSERT(globalScope->lookup_variable_symbol(variableName->get_name()) != NULL);
        }
        else
        {
            // for all other iterations of this loop ...
            // remove variable declaration from the global scope
            globalScope->remove_statement(globalVariableDeclaration);
        }

        // add the variable declaration to the class definition
        classDeclaration->get_definition()->append_member(globalVariableDeclaration);
    }

    return globalClassVariableSymbol;
}

void
fixupReferencesToGlobalVariables (Rose_STL_Container<SgVarRefExp*> & variableReferenceList, SgVariableSymbol* globalClassVariableSymbol)
{
    // Now fixup the SgVarRefExp to reference the global variables through a struct
    for (Rose_STL_Container<SgVarRefExp*>::iterator var = variableReferenceList.begin(); var != variableReferenceList.end(); var++)
    {
        assert(*var != NULL);
        // printf ("Variable reference for %s \n", (*var)->get_symbol()->get_declaration()->get_name().str());
    }
}

```

Figure 28.26: Example source code shows repackaging of global variables to a struct (part 3).

```

SgNode* parent = (*var)->get-parent();
assert(parent != NULL);

// If this is not an expression then is likely a meaningless statement such as ("x;")
SgExpression* parentExpression = isSgExpression(parent);
assert(parentExpression != NULL);

// Build the reference through the global class variable ("x" --> "AMPI_globals.x")
// Build source position information (marked as transformation)
Sg_File_Info* fileInfo = Sg_File_Info::generateDefaultFileInfoForTransformationNode();
assert(fileInfo != NULL);

// Build "AMPI_globals"
SgExpression* lhs = new SgVarRefExp(fileInfo, globalClassVariableSymbol);
assert(lhs != NULL);
// Build "AMPI_globals.x" from "x"
SgDotExp* globalVariableReference = new SgDotExp(fileInfo, lhs, *var);
assert(globalVariableReference != NULL);

if (parentExpression != NULL)
{
    // Introduce reference to *var through the data structure

    // case of binary operator
    SgUnaryOp* unaryOperator = isSgUnaryOp(parentExpression);
    if (unaryOperator != NULL)
    {
        unaryOperator->set_operand(globalVariableReference);
    }
    else
    {
        // case of binary operator
        SgBinaryOp* binaryOperator = isSgBinaryOp(parentExpression);
        if (binaryOperator != NULL)
        {
            // figure out if the *var is on the lhs or the rhs
            if (binaryOperator->get_lhs_operand() == *var)
            {
                binaryOperator->set_lhs_operand(globalVariableReference);
            }
            else
            {
                assert(binaryOperator->get_rhs_operand() == *var);
                binaryOperator->set_rhs_operand(globalVariableReference);
            }
        }
        else
        {
            // ignore these cases for now!
            switch (parentExpression->variantT())
            {
                // Where the variable appears in the function argument list the parent is a SgExprListExp
                case V_SgExprListExp:
                {
                    printf("Sorry not implemented, case of global variable in function argument list ... \n");
                    assert(false);
                    break;
                }
                case V_SgInitializer:
                case V_SgRefExp:
                case V_SgVarArgOp:
                default:
                {
                    printf("Error: default reached in switch\n", parentExpression, parentExpression->class_name().c_str());
                    assert(false);
                }
            }
        }
    }
}

parentExpression = %p = %s \n", parentExpression, parentExpression->class_name().c_str());
assert(false);
}
}
}
}
}

#define OUTPUT_NAMES_OF_GLOBAL_VARIABLES 0
#define OUTPUT_NAMES_OF_GLOBAL_VARIABLE_REFERENCES 0

void
transformGlobalVariablesToUseStruct ( SgSourceFile *file )
{

```

Figure 28.27: Example source code shows repackaging of global variables to a struct (part 4).

```

    assert(file != NULL);

    // These are the global variables in the input program (provided as helpful information)
    Rose_STL_Container<SgInitializedName*> globalVariables = buildListOfGlobalVariables(file);

#ifdef OUTPUT_NAMES_OF_GLOBAL_VARIABLES
    printf("global variables (declared in global scope): \n");
    for (Rose_STL_Container<SgInitializedName*>::iterator var = globalVariables.begin(); var != globalVariables.end(); var++)
    {
        printf("    %s \n",(*var)->get_name().str());
    }
    printf("\n");
#endif

    // get the global scope within the first file (currently ignoring all other files)
    SgGlobal* globalScope = file->get_globalScope();
    assert(globalScope != NULL);

    // Build the class declaration
    SgClassDeclaration* classDeclaration = buildClassDeclarationAndDefinition("AMPI_globals_t", globalScope);

    // Put the global variables into the class
    SgVariableSymbol* globalClassVariableSymbol = putGlobalVariablesIntoClass(globalVariables, classDeclaration);

    // Their associated symbols will be located within the project's AST
    // (where they occur in variable reference expressions).
    Rose_STL_Container<SgVarRefExp*> variableReferenceList = buildListOfVariableReferenceExpressionsUsingGlobalVariables(file);

#ifdef OUTPUT_NAMES_OF_GLOBAL_VARIABLE_REFERENCES
    printf("global variables appearing in the application: \n");
    for (Rose_STL_Container<SgVarRefExp*>::iterator var = variableReferenceList.begin(); var != variableReferenceList.end(); var++)
    {
        printf("    %s \n",(*var)->get_symbol()->get_declaration()->get_name().str());
    }
    printf("\n");
#endif

    // Fixup all references to global variable to access the variable through the class ("x" --> "AMPI_globals.x")
    fixupReferencesToGlobalVariables(variableReferenceList, globalClassVariableSymbol);
}

void
transformGlobalVariablesToUseStruct ( SgProject *project )
{
    // Call the transformation of each file (there are multiple SgFile
    // objects when multiple files are specified on the command line!).
    assert(project != NULL);

    const SgFilePtrList& fileList = project->get_fileList();
    SgFilePtrList::const_iterator file = fileList.begin();
    while(file != fileList.end())
    {
        transformGlobalVariablesToUseStruct(isSgSourceFile(*file));
        file++;
    }
}

// *****
//          MAIN PROGRAM
// *****
int
main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc, argv);
    assert(project != NULL);

    // transform application as required
    transformGlobalVariablesToUseStruct(project);

    // Code generation phase (write out new application "rose_<input file name>")
    return backend(project);
}

```

Figure 28.28: Example source code shows repackaging of global variables to a struct (part 5).

```

int x;
int y;
long z;
float pressure;

int main()
{
    int a = 0;
    int b = 0;
    float density = 1.0;

    x++;
    b++;

    x = a + y;

    return 0;
}

```

Figure 28.29: Example source code used as input to translator adding new function.

```

struct AMPI_globals_t
{
    int x;
    int y;
    long z;
    float pressure;
}

;
struct AMPI_globals_t AMPI_globals;

int main()
{
    int a = 0;
    int b = 0;
    float density = (1.0);
    AMPI_globals.x++;
    b++;
    AMPI_globals.x = (a + AMPI_globals.y);
    return 0;
}

```

Figure 28.30: Output of input to translator adding new function.

Chapter 29

Handling Comments, Preprocessor Directives, And Adding Arbitrary Text to Generated Code

What To Learn From These Examples Learn how to access existing comments and CPP directives and modify programs to include new ones. Where such comments can be automated they can be used to explain transformations or for more complex transformations using other tools designed to read the generated comments. Also included is how to add arbitrary text to the generated code (often useful for embedded system programming to support back-end compiler specific functionality).

This chapter deals with comments and preprocessor directives. These are often dropped from compiler infrastructures and ignored by make tools. ROSE takes great care to preserve all comments and preprocessor directives. Where they exist in the input code we save them (note that EDG drops them from their AST) and weave them back into the AST.

Note that *#pragma* is not a CPP directive and is part of the C and C++ grammar, thus represented explicitly in the AST (see `SgPragmaDeclaration`).

29.1 How to Access Comments and Preprocessor Directives

Comments and CPP directives are treated identically within ROSE and are saved as special preprocessor attributes to IR nodes within the AST. Not all IR nodes can have these specific type of attributes, only `SgLocatedNodes` can be associated with such preprocessor attributes. The more general *persistent attribute mechanism* within ROSE is separate from this preprocessor attribute mechanism and is available on a wider selection of IR nodes.

29.1.1 Source Code Showing How to Access Comments and Preprocessor Directives

Figure 29.1 shows an example translator which access the comments and preprocessor directives on each statement. Note that in this example the AST is traversed twice, first header files are ignored and then the full AST (including header files) are traversed (generated additional comments).

The input code is shown in figure 29.2, the output of this code is shown in figure 29.3 for the source file only. Figure 29.4 shows the same input code processed to output comments and preprocessor directives assembled from the source file *and* all header files.

29.1.2 Input to example showing how to access comments and CPP directives

Figure 29.2 shows the example input used for demonstration of how to collect comments and CPP directives.

29.1.3 Comments and CPP Directives collected from source file (skipping headers)

Figure 29.3 shows the results from the collection of comments and CPP directives within the input source file only (without `-rose:collectAllCommentsAndDirectives`).

29.1.4 Comments and CPP Directives collected from source file and all header files

Figure 29.4 shows the results from the collection of comments and CPP directives within the input source file and all headers (with `-rose:collectAllCommentsAndDirectives`).

29.2 Collecting #define C Preprocessor Directives

This example shows how to collect the `#define` directives as a list for later processing.

29.2.1 Source Code Showing How to Collect #define Directives

Figure 29.5 shows an example translator which access the comments and preprocessor directives on each statement. Note that in this example the AST is traversed twice, first header files are ignored and then the full AST (including header files) are traversed (generated additional comments).

The input code is shown in figure 29.6, the output of this code is shown in Figure 29.7 shows the same input code processed to output comments and preprocessor directives assembled from the source file *and* all header files.


```

// Example ROSE Translator: used within ROSE/tutorial

#include "rose.h"

using namespace std;

// Class declaration
class visitorTraversal : public AstSimpleProcessing
{
public:
    virtual void visit(SgNode* n);
};

void visitorTraversal::visit(SgNode* n)
{
    // On each node look for any comments of CPP directives
    SgLocatedNode* locatedNode = isSgLocatedNode(n);
    if (locatedNode != NULL)
    {
        AttachedPreprocessingInfoType* comments = locatedNode->getAttachedPreprocessingInfo();

        if (comments != NULL)
        {
            printf ("Found attached comments (to IR node at %p of type: %s): \n", locatedNode, locatedNode->class_name());
            int counter = 0;
            AttachedPreprocessingInfoType::iterator i;
            for (i = comments->begin(); i != comments->end(); i++)
            {
                printf ("        Attached Comment ##%d in file %s (relativePosition=%s): classification %s : \n%s\n",
                    counter++, (*i)->get_file_info()->get_filenameString().c_str(),
                    ((*i)->getRelativePosition() == PreprocessingInfo::before) ? "before" : "after",
                    PreprocessingInfo::directiveTypeName((*i)->getTypeOfDirective()).c_str(),
                    (*i)->getString().c_str());
            }
        }
        else
        {
            printf ("No attached comments (at %p of type: %s): \n", locatedNode, locatedNode->sage_class_name());
        }
    }
}

int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc, argv);

    // Build the traversal object
    visitorTraversal exampleTraversal;

    // Call the traversal starting at the project node of the AST
    // Traverse all header files and source file (the -rose:collectAllCommentsAndDirectives
    // cmdline option controls if comments and CPP directives are separately extracted
    // from header files).
    exampleTraversal.traverse(project, preorder);

    return 0;
}

```

Figure 29.1: Example source code showing how to access comments.

```
// #include<stdio.h>

#define SOURCE_CODE_BEFORE_INCLUDE_A
#define SOURCE_CODE_BEFORE_INCLUDE_B
#include<inputCode_collectComments.h>
#define SOURCE_CODE_AFTER_INCLUDE_A
#define SOURCE_CODE_AFTER_INCLUDE_B

// main program: collectComments input test code
int main()
{
    return 0;
}
```

Figure 29.2: Example source code used as input to collection of comments and CPP directives.

29.2.2 Input to example showing how to access comments and CPP directives

Figure 29.6 shows the example input used for demonstration of how to collect comments and CPP directives.

29.2.3 Comments and CPP Directives collected from source file and all header files

Figure 29.7 shows the results from the collection of comments and CPP directives within the input source file and all headers (with `-rose:collectAllCommentsAndDirectives`).

29.3 Automated Generation of Comments

Figure 29.8 shows an example of how to introduce comments into the AST which will then show up in the generated source code. The purpose for this is generally to add comments to where transformations are introduced. If the code is read by the use the generated comments can be useful in identifying, marking, and/or explaining the transformation.

This chapter presents an example translator which just introduces a comment at the top of each function. The comment includes the name of the function and indicates that the comment is automatically generated.

Where appropriate such techniques could be used to automate the generation of documentation templates in source code that would be further filled in by the user. In this case the automatically generated templates would be put into the generated source code and a patch formed between the generated source and the original source. The patch could be easily inspected and applied to the original source code to place the documentation templates into the original source. The skeleton of the documentation in the source code could be filled in by the user. The template would have all relevant information obtained by analysis (function parameters, system functions used, security information, side-effects, anything that could come from an analysis of the source code using ROSE).

29.3.1 Source Code Showing Automated Comment Generation

Figure 29.8 shows an example translator which calls the mechanism to add a comment to the IR node representing a function declaration (SgFunctionDeclaration).

The input code is shown in figure 29.9, the output of this code is shown in figure 29.10.

29.3.2 Input to Automated Addition of Comments

Figure 29.9 shows the example input used for demonstration of an automated commenting.

29.3.3 Final Code After Automatically Adding Comments

Figure 29.10 shows the results from the addition of comments to the generated source code.

29.4 Addition of Arbitrary Text to Unparsed Code Generation

This section is different from the comment generation (section 29.3) because it is more flexible and does not introduce any formatting. It also does not use the same internal mechanism, this mechanism supports the addition of new strings or the replacement of the IR node (where the string is attached) with the new string. It is fundamentally lower level and a more powerful mechanism to support generation of tailored output where more than comments, CPP directives, or AST transformation are required. It is also much more dangerous to use.

This mechanism is expected to be used rarely and sparingly since no analysis of the AST is likely to leverage this mechanism and search for code that introduced as a transformation here. Code introduced using this mechanism is for the most part unanalyzable since it would have to be reparsed in the context of the location in the AST where it is attached. (Technically this is possible and is the subject of the existing ROSE AST Rewrite mechanism, but that is a different subject).

Figure 29.11 shows an example of how to introduce arbitrary text into the AST for output by the unparser which will then show up in the generated source code. The purpose for this is generally to add backend compiler or tool specific code generation which don't map to any formal language constructs and so cannot be represented in the AST. However, since most tools that require specialized annotations read them as comments, the mechanism in the previous section 29.3 may be more appropriate. It is because this is not always that case that we have provide this more general mechanism (often useful for embedded system compilers).

29.4.1 Source Code Showing Automated Arbitrary Text Generation

Figure 29.11 shows an example translator which calls the mechanism to add a arbitrary text to the IR node representing a function declaration (SgFunctionDeclaration).

The input code is shown in figure 29.12, the output of this code is shown in figure 29.13.

29.4.2 Input to Automated Addition of Arbitrary Text

Figure 29.12 shows the example input used for demonstration of the automated introduction of text via the unparser.

29.4.3 Final Code After Automatically Adding Arbitrary Text

Figure 29.13 shows the results from the addition of arbitrary text to the generated source code.


```

// Example ROSE Translator: used within ROSE/tutorial

#include "rose.h"

using namespace std;

// Build a synthesized attribute for the tree traversal
class SynthesizedAttribute
{
public:
    // List of #define directives (save the PreprocessingInfo objects
    // so that we have all the source code position information).
    list<PreprocessingInfo*> accumulatedList;

    void display() const;
};

void
SynthesizedAttribute::display() const
{
    list<PreprocessingInfo*>::const_iterator i = accumulatedList.begin();
    while (i != accumulatedList.end())
    {
        printf ("CPP define directive = %s \n",(*i)->getString().c_str());
        i++;
    }
}

class visitorTraversal : public AstBottomUpProcessing<SynthesizedAttribute>
{
public:
    // virtual function must be defined
    virtual SynthesizedAttribute evaluateSynthesizedAttribute (
        SgNode* n, SynthesizedAttributesList childAttributes );
};

SynthesizedAttribute
visitorTraversal::evaluateSynthesizedAttribute ( SgNode* n, SynthesizedAttributesList childAttributes )
{
    SynthesizedAttribute localResult;

    // printf ("In evaluateSynthesizedAttribute(n = %p = %s) \n",n,n->class_name().c_str());

    // Build the list from children (in reverse order to preserve the final ordering)
    for (SynthesizedAttributesList::reverse_iterator child = childAttributes.rbegin(); child != childAttributes.rend();
        {
            localResult.accumulatedList.splice(localResult.accumulatedList.begin(),child->accumulatedList);
        }

    // Add in the information from the current node
    SgLocatedNode* locatedNode = isSgLocatedNode(n);
    if (locatedNode != NULL)
    {
        AttachedPreprocessingInfoType* commentsAndDirectives = locatedNode->getAttachedPreprocessingInfo();

        if (commentsAndDirectives != NULL)
        {
            // printf ("Found attached comments (to IR node at %p of type: %s): \n",locatedNode,locatedNode->class_name())
            // int counter = 0;

            // Use a reverse iterator so that we preserve the order when using push_front to add each directive to the ac
            AttachedPreprocessingInfoType::reverse_iterator i;
            for (i = commentsAndDirectives->rbegin(); i != commentsAndDirectives->rend(); i++)
            {
                // The different classifications of comments and directives are in ROSE/src/frontend/SageIII/rose_attrib
                if ((*i)->getTypeOfDirective() == PreprocessingInfo::CpreprocessorDefineDeclaration)
                {
                    #if 0
                        printf ("      Attached Comment #%d in file %s (relativePosition=%s): classification %s :\n%
                            counter++,(*i)->get_file_info()->get_filenameString().c_str(),
                            ((*i)->getRelativePosition() == PreprocessingInfo::before) ? "before" : "after",
                            PreprocessingInfo::directiveTypeName((*i)->getTypeOfDirective()).c_str(),
                            (*i)->getString().c_str());
                    #endif
                }

                // use push_front() to end up with source ordering of final list of directives
                localResult.accumulatedList.push_front(*i);
            }
        }
    }

    // printf ("localResult after adding current node info \n");
    // localResult.display();

```

```
#define JUST_A_MACRO just_a_macro
#define ANOTHER_MACRO another_macro
```

Figure 29.6: Example source code used as input to collection of comments and CPP directives.

```
CPP define directive = #define max(a,b) ((a) > (b) ? (a) : (b))
CPP define directive = #define maxint(a,b) ({int _a = (a), _b = (b); _a > _b ? _a : _b; })
CPP define directive = #define SOURCE_CODE_BEFORE_INCLUDE_A
CPP define directive = #define SOURCE_CODE_BEFORE_INCLUDE_B
CPP define directive = #define SOURCE_CODE_AFTER_INCLUDE_A
CPP define directive = #define SOURCE_CODE_AFTER_INCLUDE_B
```

Figure 29.7: Output from collection of comments and CPP directives on the input source file and all header files.


```

// Example ROSE Translator: used within ROSE/tutorial
#include "rose.h"

using namespace std;

class visitorTraversal : public AstSimpleProcessing
{
public:
    virtual void visit(SgNode* n);
};

void visitorTraversal::visit(SgNode* n)
{
    SgFunctionDeclaration* functionDeclaration = isSgFunctionDeclaration(n);
    if (functionDeclaration != NULL)
    {
        string comment = string("Auto-comment function name: ") +
            functionDeclaration->get_name().str() +
            " is now a commented function";

        // Note that this function will add the "//" or "/* */" comment syntax as required for C or C++, or Fortran.
        SageInterface::attachComment(functionDeclaration,comment);
    }

    SgValueExp* valueExp = isSgValueExp(n);
    if (valueExp != NULL)
    {
        // Check if there is an expression tree from the original unfolded expression.
        // This is a trivial example of the output of an analysis result.
        string comment = string("Auto-comment value: ") +
            ((valueExp->get_originalExpressionTree() != NULL) ?
                " this IS a constant folded value" : " this is NOT a constant folded value");

        SageInterface::attachComment(valueExp,comment);
    }
}

// Typical main function for ROSE translator
int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc,argv);

    // Build the traversal object
    visitorTraversal exampleTraversal;

    // Call the traversal starting at the project node of the AST
    exampleTraversal.traverseInputFiles(project,preorder);

    return backend(project);
}

```

Figure 29.8: Example source code showing how automate comments.

```
int
foo()
{
    int x = 2;
    return x;
}
```

Figure 29.9: Example source code used as input to automate generation of comments.

```
// Auto-comment function name: foo is now a commented function
int foo()
{
    int x =
// Auto-comment value:  this is NOT a constant folded value
2;
    return x;
}
```

Figure 29.10: Output of input code after automating generation of comments.

```

// Example ROSE Translator: used within ROSE/tutorial
#include "rose.h"

using namespace std;

class visitorTraversal : public AstSimpleProcessing
{
public:
    virtual void visit(SgNode* n);
};

void visitorTraversal::visit(SgNode* n)
{
    SgFunctionDeclaration* functionDeclaration = isSgFunctionDeclaration(n);
    if (functionDeclaration != NULL)
    {
        // This is an example of a XYZ tool specific annotation
        string compilerSpecificDirective = "\n#if XYZ_TOOL\n"
        builtin "\n#endif\n";
        SageInterface::addTextForUnparser(functionDeclaration, compilerSpecificDirective, AstUnparseAttribute::e_before);
    }

    SgValueExp* valueExp = isSgValueExp(n);
    if (valueExp != NULL)
    {
        // Add a backend specific compiler directive
        string compilerSpecificDirective = "\n#if CRAY\n"
        cray_specific_attribute "\n#endif\n";
        SageInterface::addTextForUnparser(valueExp, compilerSpecificDirective, AstUnparseAttribute::e_before);
    }
}

// Typical main function for ROSE translator
int main( int argc, char * argv[] )
{
    // Build the AST used by ROSE
    SgProject* project = frontend(argc, argv);

    // Build the traversal object
    visitorTraversal exampleTraversal;

    // Call the traversal starting at the project node of the AST
    exampleTraversal.traverseInputFiles(project, preorder);

    return backend(project);
}

```

Figure 29.11: Example source code showing how automate the introduction of arbitrary text.

```

int
foo()
{
    int x = 42;
    return x;
}

```

Figure 29.12: Example source code used as input to automate generation of arbitrary text.

```
#if XYZ.TOOL
    "builtin"
#endif

int foo()
{
    int x =
#ifdef CRAY
        cray_specific_attribute
#endif
    42;
    return x;
}
```

Figure 29.13: Output of input code after automating generation of arbitrary text.

Chapter 30

Partial Redundancy Elimination (PRE)

Figure 30.1 shows an example of how to call the Partial Redundancy Elimination (PRE) implemented by Jeremiah Willcock. This transformation is useful for cleaning up code generated from other transformations (used in Qing’s loop optimizations).

30.1 Source Code for example using PRE

Figure 30.1 shows an example translator which calls the PRE mechanism.

The input code is shown in figure 30.2, the output of this code is shown in figure 30.3.

```
// Example translator demonstrating Partial Redundancy Elimination (PRE).

#include "rose.h"
#include "CommandOptions.h"

int main (int argc, char* argv[])
{
    // Build the project object (AST) which we will fill up with multiple files and use as a
    // handle for all processing of the AST(s) associated with one or more source files.
    std::vector<std::string> l = CommandLineProcessing::generateArgListFromArgcArgv(argc, argv);

    CmdOptions::GetInstance()->SetOptions(argc, argv);
    SgProject* project = frontend(l);

    PRE::partialRedundancyElimination(project);

    return backend(project);
}
```

Figure 30.1: Example source code showing how use Partial Redundancy Elimination (PRE).

30.2 Input to Example Demonstrating PRE

Figure 30.2 shows the example input used for demonstration of Partial Redundancy Elimination (PRE) transformation.

```
// Program, based on example in Knoop et al ("Optimal code motion: theory and
// practice", ACM TOPLAS 16(4), 1994, pp. 1117–1155, as cited in Paleri et al
// (see pre.C)), converted to C++

int unknown(); // ROSE bug: including body "return 0;" here doesn't work

void foo() {
    int a, b, c, x, y, z, w;

    if (unknown()) {
        y = a + b;
        a = c;
    // Added by Jeremiah Willcock to test local PRE
        w = a + b;
        a = b;
        x = a + b;
        w = a + b;
        a = c;
    // End of added part
        x = a + b;
    }

    if (unknown()) {
        while (unknown()) {y = a + b;}
    } else if (unknown()) {
        while (unknown()) {}
        if (unknown()) {y = a + b;} else {goto L9;} // FIXME: the PRE code crashes if this isn't in a block
    } else {
        goto L10;
    }

    z = a + b;
    a = c;

    L9: x = a + b;

    L10: 0; // ROSE bug: using return; here doesn't work
}

int unknown() {
    0; // Works around ROSE bug
    return 0;
}

int main(int, char**) {
    foo();
    return 0;
}
```

Figure 30.2: Example source code used as input to program to the Partial Redundancy Elimination (PRE) transformation.

30.3 Final Code After PRE Transformation

Figure 30.3 shows the results from the use of PRE on an the example input code.

```

// Program, based on example in Knoop et al ("Optimal code motion: theory and
// practice", ACM TOPLAS 16(4), 1994, pp. 1117–1155, as cited in Paleri et al
// (see pre.C)), converted to C++
// ROSE bug: including body "return 0;" here doesn't work
extern int unknown();

void foo()
{
// Partial redundancy elimination: cachevar__1 is a cache of (a + b)
int cachevar__1;
int a;
int b;
int c;
int x;
int y;
int z;
int w;
if ((unknown())) {
y = (a + b);
a = c;
// Added by Jeremiah Willcock to test local PRE
w = (a + b);
a = b;
cachevar__1 = (a + b);
x = cachevar__1;
w = cachevar__1;
a = c;
// End of added part
x = (a + b);
}
else {
}
if ((unknown())) {
cachevar__1 = (a + b);
while((unknown())){
y = cachevar__1;
}
}
else if ((unknown())) {
while((unknown())){
}
}
// FIXME: the PRE code crashes if this isn't in a block
if ((unknown())) {
cachevar__1 = (a + b);
y = cachevar__1;
}
else {
goto L9;
}
}
else {
goto L10;
}
z = cachevar__1;
a = c;
L9:
x = (a + b);
L10:
// ROSE bug: using return; here doesn't work
0;
}

int unknown()
{
// Works around ROSE bug
0;
return 0;
}

int main(int ,char **)
{
foo();
return 0;
}

```

Figure 30.3: Output of input code after Partial Redundancy Elimination (PRE) transformation.

Chapter 31

Calling the Inliner

Figure 31.1 shows an example of how to use the inline mechanism. This chapter presents an example translator to to inlining of function calls where they are called. Such transformations are quite complex in a number of cases (one case is shown in the input code; a function call in a for loop conditional test). The details of functionality are hidden from the user and a high level interface is provided.

31.1 Source Code for Inliner

Figure 31.1 shows an example translator which calls the inliner mechanism. The code is designed to only inline up to ten functions. the list of function calls is recomputed after any function call is successfully inlined.

The input code is shown in figure 31.2, the output of this code is shown in figure 31.3.

31.2 Input to Demonstrate Function Inlining

Figure 31.2 shows the example input used for demonstration of an inlining transformation.

31.3 Final Code After Function Inlining

Figure 31.3 shows the results from the inlining of three function calls. The first two function calls are the same, and trivial. The second function call appears in the test of a for loop and is more complex.

```

// Example demonstrating function inlining (maximal inlining, up to preset number of inlinings).
#include "rose.h"

using namespace std;

// This is a function in Qing's AST interface
void FixSgProject(SgProject& proj);

int main (int argc, char* argv[])
{
    // Build the project object (AST) which we will fill up with multiple files and use as a
    // handle for all processing of the AST(s) associated with one or more source files.
    SgProject* project = new SgProject(argc, argv);

    // DQ (7/20/2004): Added internal consistency tests on AST
    AstTests::runAllTests(project);

    bool modifiedAST = true;
    int count = 0;

    // Inline one call at a time until all have been inlined. Loops on recursive code.
    do {
        modifiedAST = false;

        // Build a list of functions within the AST
        Rose_STL_Container<SgNode*> functionCallList = NodeQuery::querySubTree (project, V_SgFunctionCallExp);

        // Loop over all function calls
        // for (list<SgNode*>::iterator i = functionCallList.begin(); i != functionCallList.end(); i++)
        Rose_STL_Container<SgNode*>::iterator i = functionCallList.begin();
        while (modifiedAST == false && i != functionCallList.end())
        {
            SgFunctionCallExp* functionCall = isSgFunctionCallExp(*i);
            ROSE_ASSERT(functionCall != NULL);

            // Not all function calls can be inlined in C++, so report if successful.
            bool successfullyInlined = doInline(functionCall);

            if (successfullyInlined == true)
            {
                // As soon as the AST is modified recompute the list of function
                // calls (and restart the iterations over the modified list)
                modifiedAST = true;
            }
            else
            {
                modifiedAST = false;
            }

            // Increment the list iterator
            i++;
        }

        // Quite when we have ceased to do any inline transformations
        // and only do a predefined number of inline transformations
        count++;
    }
    while(modifiedAST == true && count < 10);

    // Call function to postprocess the AST and fixup symbol tables
    FixSgProject(*project);

    // Rename each variable declaration
    renameVariables(project);

    // Fold up blocks
    flattenBlocks(project);

    // Clean up inliner-generated code
    cleanupInlinedCode(project);

    // Change members to public
    changeAllMembersToPublic(project);

    // DQ (3/11/2006): This fails so the inlining, or the AST Interface
    // support, needs more work even though it generated good code.
    // AstTests::runAllTests(project);

    return backend(project);
}

```

```
// This test code is a combination of pass1 and pass7, selected somewhat randomly
// from Jeremiah's test code of his inlining transformation from summer 2004.

int x = 0;

// Function to increment "x"
void incrementX()
{
    x++;
}

int foo()
{
    int a = 0;
    while (a < 5)
    {
        ++a;
    }

    return a + 3;
}

int main(int, char**)
{
    // Two trivial function calls to inline
    incrementX();
    incrementX();

    // Something more interesting to inline
    for (; foo() < 7;)
    {
        x++;
    }

    return x;
}
```

Figure 31.2: Example source code used as input to program to the inlining transformation.

```

// This test code is a combination of pass1 and pass7, selected somewhat randomly
// from Jeremiah's test code of his inlining transformation from summer 2004.
int x = 0;
// Function to increment "x"

void incrementX()
{
    x++;
}

int foo()
{
    int a__0 = 0;
    while(a__0 < 5){
        ++a__0;
    }
    return a__0 + 3;
}

int main(int ,char **)
{
    x++;
    x++;
    // Something more interesting to inline
    for (; true; ) {
        int a__1 = 0;
        while(a__1 < 5){
            ++a__1;
        }
        int rose_temp__7__0 = a__1 + 3;
        bool rose__temp__2 = (bool )(rose_temp__7__0 < 7);
        if (!rose__temp__2) {
            break;
        }
        else {
        }
        x++;
    }
    return x;
}

```

Figure 31.3: Output of input code after inlining transformations.

Chapter 32

Using the AST Outliner

Outlining is the process of replacing a block of consecutive statements with a function call to a new function containing those statements. Conceptually, outlining the inverse of inlining (Chapter 31). This chapter shows how to use the basic experimental outliner implementation included in the ROSE projects directory.

There are two basic ways to use the outliner. The first is a “user-level” method, in which you may use a special pragma to mark outline targets in the input program, and then call a high-level driver routine to process these pragmas. You can also use command line option to specify outlining targets using abstract handle strings (detailed in Chapter 41). The second method is to call “low-level” outlining routines that operate directly on AST nodes. After a brief example of what the outliner can do and a discussion of its limits (Sections 32.1–32.2), we discuss each of these methods in Sections 32.3 and 32.5, respectively.

32.1 An Outlining Example

Figure 32.1 shows a small program with a pragma marking the outline target, a nested for loop, and Figure 32.2 shows the result. The outliner extracts the loop and inserts it into the body of a new function, and inserts a call to that function. The outlined code’s input and output variables are wrapped up as parameters to this function. We make the following observations about this output.

Placement and forward declarations. The function itself is placed, by default, at the end of the input file to guarantee that it has access to all of the same declarations that were available at the outline target site. The outliner inserts any necessary forward declarations as well, including any necessary **friend** declarations if the outline target appeared in a class member function.

Calling convention. The outliner generates a C-callable function (**extern ‘‘C’’**, with pointer arguments). This design choice is motivated by our need to use the outliner to extract code into external, dynamically loadable library modules.

32.2 Limitations of the Outliner

The main limitation of the outliner implementation is that it can only outline single `SgStatement` nodes. However, since an `SgStatement` node may be a block (*i.e.*, an `SgBasicBlock` node), a “single statement” may actually comprise a sequence of complex statements.

The rationale for restricting to single `SgStatement` nodes is to avoid subtly changing the program’s semantics when outlining code. Consider the following example, in which we wish to outline the middle 3 lines of executable code.

```

    int x = 5;
2 // START outlining here.
    foo (x);
4    Object y (x);
    y.foo ();
6 // STOP outlining here.
    y.bar ();

```

This example raises a number of issues. How should an outliner handle the declaration of `y`, which constructs an object in local scope? It cannot just cut-and-paste the declaration of `y` to the body of the new outlined function because that will change its scope and lifetime, rendering the call to `y.bar()` impossible. Additionally, it may be unsafe to move the declaration of `y` so that it precedes the outlined region because the constructor call may have side-effects that could affect the execution of `foo(x)`. It is possible to heap-allocate `y` inside the body of the

```

namespace N
{
    class A
    {
5      int foo (void) const { return 7; }
      int bar (void) const { return foo () / 2; }
      public:
      int biz (void) const
10     {
        int result = 0;
        #pragma rose_outline
        for (int i = 1; i <= foo (); i++)
            for (int j = 1; j <= bar (); j++)
                result += i * j;
15      return result;
    }
};
}

20 extern "C" int printf (const char* fmt, ...);

int main ()
{
    N::A x;
25    printf ("%d\n", x.biz ()); // Prints '168'
    return 0;
}

```

Figure 32.1: `inputCode_OutlineLoop.cc`: Sample input program. The `#pragma` directive marks the nested for loop for outlining.

```

extern "C" void OUT__1__9202__ (int *resultp__, const void *this__ptr__);
namespace N
{
5   class A
    {
      public: friend void::OUT__1__9202__ (int *resultp__,
                                         const void *this__ptr__);
10   private: inline int foo () const
        {
          return 7;
        }

15   inline int bar () const
        {
          return (this)->foo () / 2;
        }

20   public: inline int biz () const
        {
// //A declaration for this pointer
25   const class A *this__ptr__ = this;
          int result = 0;
          OUT__1__9202__ (&result, &this__ptr__);
          return result;
        }
30   }

    ;
}
35 extern "C"
{
  int printf (const char *fmt, ...);
}

40 int main ()
{
  class N::A x;
// Prints '168'
  printf ("%d\n", x.biz ());
45  return 0;
}

50 extern "C" void OUT__1__9202__ (int *resultp__, const void *this__ptr__)
{
  int &result = *((int *) resultp__);
  const class N::A * &this__ptr__ = *((const class N::A **) this__ptr__);
  for (int i = 1; i <= this__ptr__->foo (); i++)
    for (int j = 1; j <= this__ptr__->bar (); j++)
55     result += (i * j);
}

```

Figure 32.2: `rose_outlined-inputCode_OutlineLoop.cc`: The nested for loop of Figure 32.1 has been outlined.

outlined function so that it can be returned to the caller and later freed, but it is not clear if changing `y` from a stack-allocated variable to a heap-allocated one will always be acceptable, particularly if the developer of the original program has, for instance, implemented a customized

memory allocator. Restricting outlining to well-defined `SgStatement` objects avoids these issues. It is possible to build a “higher-level” outliner that extends the outliner’s basic infrastructure to handle these and other issues.

The outliner cannot outline all possible `SgStatement` nodes. However, the outliner interface provides a routine, `outliner::isOutlineable(s)`, for testing whether an `SgStatement` object `s` is known to satisfy the outliner’s preconditions (see Section 32.5 for details).

32.3 User-Directed Outlining *via* Pragmas

Figure 32.3 shows the basic translator, `outline`, that produces Figure 32.2 from Figure 32.1. This translator extends the identity translator with an include directive on line 5 of Figure 32.3, and a call to the outliner on line 16. All outliner routines live in the `Outliner` namespace. Here, the call to `Outliner::outlineAll(proj)` on line 16 traverses the AST, looks for `#pragma rose_outline` directives, outlines the `SgStatement` objects to which each pragma is attached, and returns the number of outlined objects.

A slightly lower-level outlining primitive. The `Outliner::outlineAll()` routine is a wrapper around calls to a simpler routine, `Outliner::outline()`, that operates on pragmas:

```
Outliner::Result Outliner::outline (SgPragmaDeclaration* s);
```

Given a pragma statement AST node `s`, this routine checks if `s` is a `rose_outline` directive, and if so, outlines the statement with which `s` is associated. It returns a `Outliner::Result` object, which is simply a structure that points to (a) the newly generated outlined function and (b) the statement corresponding to the new function call (*i.e.*, the outlined function call-site). See `Outliner.hh` or the ROSE Programmer’s Reference for more details.

The `Outliner::outlineAll()` wrapper. The advantage of using the wrapper instead of the lower-level primitive is that the wrapper processes the pragmas in an order that ensures the outlining can be performed correctly in-place. This order is neither a preorder nor a postorder traversal, but in fact a “reverse” preorder traversal; refer to the wrapper’s documentation for an explanation.

32.4 Outlining via Abstract Handles

The ROSE AST outliner also allows users to specify outlining targets using abstract handles (details are given in Chapter 41) without relying on planting pragmas into the source code. For the translator (e.g. named `outline`) built from the source shown in Figure 32.3, it accepts a command line option in a form of `-rose:outline:abstract_handle handle_string`. The `outline` program is able to locate a language construct matching the handle string within an input source file and then outline the construct.

For example, a handle string `"ForStatementjposition,12j"` will tell the outliner to outline the for loop at source position line 12.

Another handle, `"FunctionDeclarationjname,initializej::ForStatementjnumbering,2j"` indicates that the outlining target is the second loop within a function named `initializer`. Figure 32.5 shows the outlining results using the first handle (`"ForStatementjposition,12j"`) from an input source file (shown in Figure 32.4). Figure 32.6 shows the results using the second handle string for the same input.


```

//! outline.cc: Demonstrates the pragma-interface of the Outliner.
#include <rose.h>
#include <iostream>

5  #include <Outliner.hh>
   #include <vector>
   #include <string>

   using namespace std;

10  int
   main (int argc, char* argv[])
   {
       //! Accepting command line options to the outliner
       vector<string> argvList (argv, argv+argc);
       Outliner::commandLineProcessing (argvList);

       SgProject* proj = frontend (argvList);
       ROSE_ASSERT (proj);

20  cerr << "[Outlining...]" << endl;
       size_t count = Outliner::outlineAll (proj);

       cerr << "_[Processed_]" << count << "_outline_directives_]" << endl;

25  return backend (proj);
   }

```

Figure 32.3: outline.cc: A basic outlining translator, which generates Figure 32.2 from Figure 32.1. This outliner relies on the high-level driver, `Outliner::outlineAll()`, which scans the AST for outlining pragma directives (`#pragma rose_outline`) that mark outline targets.

```

#define MSIZE 500
int n,m,mits;
double tol,relax=1.0,alpha=0.0543;
double u[MSIZE][MSIZE],f[MSIZE][MSIZE],uold[MSIZE][MSIZE];
5  double dx,dy;

void initialize( )
{
   int i,j, xx,yy;
10  dx = 2.0 / (n-1);
   dy = 2.0 / (m-1);
   for (i=0;i<n;i++)
       for (j=0;j<m;j++)
       {
15  xx=(int)(-1.0 + dx * (i-1));
       yy = (int)(-1.0 + dy * (j-1));
       u[i][j] = 0.0;
       f[i][j] = -1.0*alpha * (1.0-xx*xx)*(1.0-yy*yy)\
               - 2.0*(1.0-xx*xx)-2.0*(1.0-yy*yy);

20  }
}

```

Figure 32.4: inputCode.OutlineLoop2.c: Sample input program without pragmas.

```

#define MSIZE 500
int n;
int m;
int mits;
5 double tol;
double relax = 1.0;
double alpha = 0.0543;
double u[500UL][500UL];
double f[500UL][500UL];
10 double uold[500UL][500UL];
double dx;
double dy;
void OUT__1__8801__(int *ip__,int *jp__,int *xyp__,int *yyp__);

15 void initialize()
{
    int i;
    int j;
    int xx;
    int yy;
20    dx = (2.0 / ((n - 1)));
    dy = (2.0 / ((m - 1)));
    OUT__1__8801__(&i,&j,&xx,&yy);
25 }

void OUT__1__8801__(int *ip__,int *jp__,int *xyp__,int *yyp__)
{
    for ( *ip__ = 0; *ip__ < n; ( *ip__)++)
30     for ( *jp__ = 0; *jp__ < m; ( *jp__)++) {
        *xyp__ = ((int) )((-1.0) + (dx * (( *ip__ - 1)))));
        *yyp__ = ((int) )((-1.0) + (dy * (( *jp__ - 1)))));
        (u[ *ip__ ][ *jp__ ] = 0.0;
        (f[ *ip__ ][ *jp__ ] = (((((-1.0) * alpha) * (1.0 - (( *xyp__ *
*xyp__)))) * (1.0 - (( *yyp__ * *yyp__)))) - (2.0 * (1.0 - (( *xyp__ *
*xyp__)))))) - (2.0 * (1.0 - (( *yyp__ * *yyp__)))));
35     }
}

```

Figure 32.5: `rose.inputCode.OutlineLoop2.c`: The loop at line 12 of Figure 32.12 has been outlined.

32.5 Calling Outliner Directly on AST Nodes

The preceding examples rely on the outliner's `#pragma` interface to identify outline targets. In this section, we show how to call the outliner directly on `SgStatement` nodes from within your translator.

Figure 32.7 shows an example translator that finds all `if` statements and outlines them. A sample input appears in Figure 32.8, with the corresponding output shown in Figure 32.9. Notice that valid preprocessor control structure is accounted for and preserved in the output.

The translator has two distinct phases. The first phase selects all *outlineable* if-statements, using the `CollectOutlineableIfs` helper class. This class produces a list that stores the targets in an order appropriate for outlining them in-place. The second phase iterates over the list of statements and outlines each one. The rest of this section explains these phases, as well as various aspects of the sample input and output.

```

#define MSIZE 500
int n;
int m;
int mits;
5 double tol;
double relax = 1.0;
double alpha = 0.0543;
double u[500UL][500UL];
double f[500UL][500UL];
10 double uold[500UL][500UL];
double dx;
double dy;
void OUT__1__8801__(int i,int *jp--,int *xyp--,int *yyp--);

15 void initialize()
{
    int i;
    int j;
    int xx;
    int yy;
20    dx = (2.0 / ((n - 1)));
    dy = (2.0 / ((m - 1)));
    for (i = 0; i < n; i++)
        OUT__1__8801__(i,&j,&xx,&yy);
25 }

void OUT__1__8801__(int i,int *jp--,int *xyp--,int *yyp--)
{
30    for ( *jp-- = 0; *jp-- < m; ( *jp-- )++) {
        *xyp-- = ((int)((-1.0) + (dx * ((i - 1)))));
        *yyp-- = ((int)((-1.0) + (dy * (( *jp-- - 1)))));
        (u[i])[ *jp-- ] = 0.0;
        (f[i])[ *jp-- ] = (((((-1.0) * alpha) * (1.0 - (( *xyp-- *
*xyp--))) * (1.0 - (( *yyp-- * *yyp--)))) - (2.0 * (1.0 - (( *xyp-- *
*xyp--)))) - (2.0 * (1.0 - (( *yyp-- * *yyp--)))));
35    }
}

```

Figure 32.6: `rose_inputCode_OutlineLoop2b.c`: The 2nd loop within a function named `initialize` from Figure 32.12 has been outlined.

32.5.1 Selecting the *outlineable* if statements

Line 45 of Figure 32.7 builds a list, `ifs` (declared on line 44), of outlineable if-statements. The helper class, `CollectOutlineableIfs` in lines 12–35, implements a traversal to build this list. Notice that a node is inserted into the target list only if it satisfies the outliner’s preconditions; this check is the call to `Outliner::isOutlineable()` on line 28.

The function `Outliner::isOutlineable()` also accepts an optional second boolean parameter (not shown). When this parameter is true and the statement cannot be outlined, the check will print an explanatory message to standard error. Such messages are useful for discovering why the outliner will not outline a particular statement. The default value of this parameter is `false`.

```

// outlineIfs.cc: Calls Outliner directly to outline if statements.
#include <rose.h>
#include <iostream>
#include <set>
5  #include <list>

#include <Outliner.hh>

using namespace std;

10 // Traversal to gather all outlineable SgIfStmt nodes.
class CollectOutlineableIfs : public AstSimpleProcessing
{
public:
15 // Container of list statements in "outlineable" order.
    typedef list<SgIfStmt*> IfList_t;

    // Call this routine to gather the outline targets.
    static void collect (SgProject* p, IfList_t& final)
20 {
        CollectOutlineableIfs collector (final);
        collector.traverseInputFiles (p, postorder);
    }

25 virtual void visit (SgNode* n)
    {
        SgIfStmt* s = isSgIfStmt (n);
        if (Outliner::isOutlineable (s))
            final_targets_.push_back (s);
30 }

private:
    CollectOutlineableIfs (IfList_t& final) : final_targets_ (final) {}
    IfList_t& final_targets_; // Final list of outline targets.
35 };

//=====
int main (int argc, char* argv[])
{
40     SgProject* proj = frontend (argc, argv);
    ROSE_ASSERT (proj);

    #if 1
        // Build a set of outlineable if statements.
45     CollectOutlineableIfs::IfList_t ifs;
        CollectOutlineableIfs::collect (proj, ifs);

        // Outline them all.
        for (CollectOutlineableIfs::IfList_t::iterator i = ifs.begin ();
50             i != ifs.end (); ++i)
            Outliner::outline (*i);
    #else
        printf ("Skipping outlining due to recent move from std::list to std::vector in ROSE\n");
    #endif
55     // Unparse
    return backend (proj);
}

```

Figure 32.7: outlineIfs.cc: A lower-level outlining translator, which calls `Outliner::outline()` directly on `SgStatement` nodes. This particular translator outlines all `SgIfStmt` nodes.

```

#include <iostream>

using namespace std;

5  #define LEAP_YEAR 0

int main (int argc, char* argv[])
{
10     for (int i = 1; i < argc; ++i)
    {
        string month (argv[i]);
        size_t days = 0;
        if (month == "January"
15             || month == "March"
            || month == "May"
            || month == "July"
            || month == "August"
            || month == "October"
            || month == "December")
20             days = 31;
        #if LEAP_YEAR
            else if (month == "February")
                days = 29;
        #else
25             else if (month == "February")
                days = 28;
        #endif
            else if (month == "April"
30                 || month == "June"
                 || month == "September"
                 || month == "November")
                days = 30;
        cout << argv[i] << " " << days << endl;
35     }
    return 0;
}

```

Figure 32.8: `inputCode.Ifs.cc`: Sample input program, without explicit outline targets specified using `#pragma rose_outline`, as in Figures 32.1 and 32.12.

32.5.2 Properly ordering statements for in-place outlining

Each call to `Outliner::outline(*i)` on line 50 of Figure 32.7 outlines a target if-statement `*i` in `if_targets`. However, in order for these statements to be outlined in-place, it is essential to outline the statements in the proper order.


The postorder traversal implemented by the helper class, `CollectOutlineableIfs`, produces the correct ordering. To see why, consider the following example code:

```

1  if (a) // [1]
2  {
    if (b) foo (); // [2]
4  }
    else if (c) // [3]
6  {
    if (d) bar (); // [4]
8  }

```

The corresponding AST is (roughly)



The postorder traversal—2, 4, 3, 1—ensures that child if-statements are outlined before their parents.

32.6 Outliner’s Preprocessing Phase

Internally, the outliner implementation itself has two distinct phases. The first is a *preprocessing phase*, in which an arbitrary outlineable target is placed into a canonical form that is relatively simple to extract. The second phase then creates the outlined function, replacing the original target with a call to the outlined function. It is possible to run just the preprocessing phase, which is useful for understanding or even debugging the outliner implementation.

To call just the preprocessor, simply replace a call to `Outliner::outlineAll(s)` or `Outliner::outline(s)` with a call to `Outliner::preprocessAll(s)` or `Outliner::preprocess(s)`, respectively. The translator in Figure 32.10 modifies the translator in Figure 32.3 in this way to create a preprocessing-only translator.

The preprocessing phase consists of a sequence of initial analyses and transformations that the outliner performs in order to put the outline target into a particular canonical form. Roughly speaking, this form is an enclosing `SgBasicBlock` node, possibly preceded or followed by start-up and tear-down code. Running just the preprocessing phase on Figure 32.1 produces the output in Figure 32.11. In this example, the original loop is now enclosed in two additional `SgBasicBlocks` (Figure 32.11, lines 24–35), the outermost of which contains a declaration that shadows the object’s `this` pointer, replacing all local references to `this` with the new shadow pointer. In this case, this initial transformation is used by the main underlying outliner implementation to explicitly identify all references to the possibly implicit references to `this`.

The preprocessing phase is more interesting in the presence of non-local control flow outside the outline target. Consider Figure 32.12, in which the outline target contains two `break` statements, which require jumping to a regions of code outside the target. We show the preprocessed code in Figure 32.13. The original non-local jumps are first transformed into assignments to a flag, `EXIT_TAKEN_` (lines 18–20 and 26–29), and then relocated to a subsequent block of code (lines 38–53) with their execution controlled by the value of the flag. The final outlined result appears in Figure 32.14; the initial preprocessing simplifies this final step of extracting the outline target.

```

#include <iostream>
using namespace std;
#define LEAP_YEAR 0
extern "C" void OUT_1_7994__(void *monthp__, size_t *daysp__);
5 extern "C" void OUT_2_7994__(void *monthp__, size_t *daysp__);
extern "C" void OUT_3_7994__(void *monthp__, size_t *daysp__);

int main(int argc, char *argv[])
{
10   for (int i = 1; i < argc; ++i) {
        std::string month(((argv[i])));
        size_t days = (0);
        OUT_3_7994__(&month, &days);
        (( *(&std::cout) << ((argv[i]) << " ") << days) << std::endl;
15   }
    return 0;
}

20 extern "C" void OUT_1_7994__(void *monthp__, size_t *daysp__)
{
    std::string &month = *((std::string *)monthp__);
    size_t &days = *((size_t *)daysp__);
    if (((month=="April" || month=="June") || month=="September") || month=="November")
25     days = (30);
}

extern "C" void OUT_2_7994__(void *monthp__, size_t *daysp__)
30 {
    std::string &month = *((std::string *)monthp__);
    size_t &days = *((size_t *)daysp__);
    #if 1 /* #if LEAP_YEAR ... #else */
    if (month=="February")
35     days = (28);
    else
    #endif
    OUT_1_7994__(&month, &days);
40 }

extern "C" void OUT_3_7994__(void *monthp__, size_t *daysp__)
{
    std::string &month = *((std::string *)monthp__);
    size_t &days = *((size_t *)daysp__);
45     if ((((((month=="January" || month=="March") || month=="May") || month=="July") || month=="August") || month=="October"
        days = (31);
        else
        #if LEAP_YEAR
50     #else
        {
        #endif /* #if LEAP_YEAR ... #else */
        OUT_2_7994__(&month, &days);
        }
55 }

```

Figure 32.9: rose.inputCode.Ifcs.cc: Figure 32.8, after outlining using the translator in Figure 32.7.

```

// outlinePreproc.cc: Shows the outliner's preprocessor-only phase.
#include <rose.h>
#include <iostream>

5  #include <Outliner.hh>

    using namespace std;

    int
10  main (int argc, char* argv[])
    {
        SgProject* proj = frontend (argc, argv);
        ROSE_ASSERT (proj);

15  #if 1
        cerr << "[Running_outliner's_preprocessing_phase_only...]" << endl;
        size_t count = Outliner::preprocessAll (proj);
        cerr << "[Processed_" << count << "_outline_directives.]" << endl;
    #else
20  printf ("Skipping_outlining_due_to_recent_move_from_std::list_to_std::vector_in_ROSE_\n");
    #endif

        cerr << "[Unparsing...]" << endl;
        return backend (proj);
25  }

```

Figure 32.10: `outlinePreproc.cc`: The basic translator of Figure 32.3, modified to execute the Outliner's preprocessing phase only. In particular, the original call to `Outliner::outlineAll()` has been replaced by a call to `Outliner::preprocessAll()`.


```

namespace N
{
    class A
    {
5      private: inline int foo () const
        {
10         return 7;
        }

        inline int bar () const
        {
15         return (this)->foo () / 2;
        }

        public: inline int biz () const
20        {
        // //A declaration for this pointer
        const class A *this_ptr = this;
        int result = 0;

25 #pragma rose_outline
        {
            for (int i = 1; i <= this_ptr->foo (); i++)
                for (int j = 1; j <= this_ptr->bar (); j++)
                    result += (i * j);
30        }
        return result;
        }
35    }
    ;
}

extern "C"
40 {
    int printf (const char *fmt, ...);
}

int main ()
45 {
    class N::A x;
    // Prints '168'
    printf ("%d\n", x.biz ());
    return 0;
50 }

```

Figure 32.11: `rose_outlined_pp-inputCode_OutlineLoop.cc`: Figure 32.1 after outline preprocessing only, *i.e.*, specifying `-rose:outline:preproc-only` as an option to the translator of Figure 32.3.

```
#include <iostream>

size_t factorial (size_t n)
{
5   size_t i = 1;
   size_t r = 1;
   while (1)
   {
10  #pragma rose_outline
      if (i <= 1)
          break; // Non-local jump #1
      else if (i >= n)
          break; // Non-local jump #2
      else
15      r *= ++i;
   }
   return r;
}

20 int main (int argc, char* argv[])
{
   std::cout << "7! = " << factorial (7) << std::endl; // Prints 5040
   return 0;
}
```

Figure 32.12: `inputCode.OutlineNonLocalJumps.cc`: Sample input program, with an outlining target that contains two non-local jumps (here, `break` statements).

```

#include <iostream>

size_t factorial (size_t n)
{
5   size_t i = (1);
   size_t r = (1);
   while ((1))
   {
10  #pragma rose_outline
      {
        int EXIT_TAKEN_ = 0;
        {
15         if (i <= (1))
            {
              EXIT_TAKEN_ = 1;
              goto NON_LOCAL_EXIT_;
            }
          else if (i >= n)
20         {
              EXIT_TAKEN_ = 2;
              goto NON_LOCAL_EXIT_;
            }
          else
25         {
              r *= ++i;
              NON_LOCAL_EXIT_++;
            }
          if (EXIT_TAKEN_ == 1)
30         {
              // Non-local jump #1
              break;
            }
          else
35         {
              if (EXIT_TAKEN_ == 2)
              {
                // Non-local jump #2
                break;
              }
              else
40             {
                {
                  {
45                   }
                }
              }
            }
          }
        }
      }
    }
  }
  return r;
}

50 int main (int argc, char *argv[])
   {
   // Prints 5040
   ((*(&std::cout)) << "7!==" ) << factorial ((7)) << std::endl;
   return 0;
55 }

```

Figure 32.13: `rose-outlined_pp-inputCode-OutlineNonLocalJumps.cc`: The non-local jump example of Figure 32.12 after outliner preprocessing, but before the actual outlining. The non-local jump is handled by an additional flag, `EXIT_TAKEN_`, which indicates what non-local jump is to be taken.

```

#include <iostream>
extern "C" void OUT_1_10109_ (size_t * np_, size_t * ip_, size_t * rp_,
                             int *EXIT_TAKEN_p_);

5  size_t factorial (size_t n)
  {
    size_t i = (1);
    size_t r = (1);
    while ((1))
10    {
      {
        int EXIT_TAKEN_ = 0;
        OUT_1_10109_ (&n, &i, &r, &EXIT_TAKEN_);
        if (EXIT_TAKEN_ == 1)
15        {
          // Non-local jump #1
          break;
        }
        else
20        {
          if (EXIT_TAKEN_ == 2)
          {
            // Non-local jump #2
            break;
25          }
          else
          {
            {
              }
            }
30          }
        }
      }
    }
    return r;
  }

35 int main (int argc, char *argv[])
  {
    // Prints 5040
    ((*(&std::cout)) << "7!==" ) << factorial ((7)) << std::endl;
40    return 0;
  }

extern "C" void OUT_1_10109_ (size_t * np_, size_t * ip_, size_t * rp_,
                             int *EXIT_TAKEN_p_)
45  {
    size_t & n = *((size_t *) np_);
    size_t & i = *((size_t *) ip_);
    size_t & r = *((size_t *) rp_);
50    int &EXIT_TAKEN_ = *((int *) EXIT_TAKEN_p_);
    if (i <= (1))
    {
      EXIT_TAKEN_ = 1;
      goto NON_LOCAL_EXIT_;
55    }
    else if (i >= n)
    {
      EXIT_TAKEN_ = 2;
      goto NON_LOCAL_EXIT_;
60    }
    else
    {
      r *= ++i;
      NON_LOCAL_EXIT_;
    }
  }

```

Figure 32.14: rose_outlined-inputCode_OutlineNonLocalJumps.cc: Figure 32.12 after outlining.

Chapter 33

Loop Optimization

This section is specific to loop optimization and show several tutorial examples using the optimization mechanisms within ROSE.

FIXME: *We might want to reference Qing's work explicitly since this is really just showing off here work.*

33.1 Example Loop Optimizer

Simple example translator showing use of pre-defined loop optimizations.

Figure 33.1 shows the code required to call some loop optimizations within ROSE. The translator that we build for this tutorial is simple and takes the following command line options to control which optimizations are done.

FIXME: *We are not running performance tests within this tutorial, but perhaps we could later.*

```
-ic1 :loop interchange for more reuses
-bk1/2/3 <blocksize> :block outer/inner/all loops
-fs1/2 :single/multi-level loop fusion for more reuses
-cp <copydim> :copy array
-fs0 : loop fission
-splitloop: loop splitting
-unroll [locond] [nvar] <unrollsize> : loop unrolling
-bs <stmtsize> : break up statements in loops
-annot <filename>:
    Read annotation from a file which defines side effects of functions
-arracc <funcname> :
    Use special function to denote array access (the special function can be replaced
    with macros after transformation). This option is for circumventing complex
    subscript expressions for linearized multi-dimensional arrays.
-opt <level=0> : The level of loop optimizations to apply (By default, only the outermost
    level is optimized).
-ta <int> : Max number of nodes to split for transitive dependence analysis (to limit the
    overhead of transitive dep. analysis)
-clsize <int> : set cache line size in evaluating spatial locality (affect decisions in
    applying loop optimizations)
-reuse_dist <int> : set maximum distance of reuse that can exploit cache (used to evaluate
```

temporal locality of loops)

```

2  // LoopProcessor:
3  //   Assume no aliasing
4  //   apply loop opt to the bodies of all function definitions
5
6  // =====
7
8  #include "rose.h"
9
10 #include <AstInterface-ROSE.h>
11 #include "LoopTransformInterface.h"
12 #include "CommandOptions.h"
13
14 using namespace std;
15
16 int
17 main ( int argc, char * argv[] )
18 {
19     vector<string> argvList(argv, argv + argc);
20     CmdOptions::GetInstance()->SetOptions(argvList);
21     SetLoopTransformOptions(argvList);
22     AssumeNoAlias aliasInfo;
23
24     SgProject* project = new SgProject(argvList);
25
26     // Loop over the number of files in the project
27     int filenum = project->numberOfFiles();
28     for (int i = 0; i < filenum; ++i)
29     {
30         SgSourceFile* file = isSgSourceFile(project->get_fileList()[i]);
31         SgGlobal *root = file->get_globalScope();
32         SgDeclarationStatementPtrList& declList = root->get_declarations ();
33
34         // Loop over the declaration in the global scope of each file
35         for (SgDeclarationStatementPtrList::iterator p = declList.begin(); p != declList.end(); ++p)
36         {
37             SgFunctionDeclaration *func = isSgFunctionDeclaration(*p);
38             if (func == NULL)
39                 continue;
40             SgFunctionDefinition *defn = func->get_definition();
41             if (defn == NULL)
42                 continue;
43
44             SgBasicBlock *stmts = defn->get_body();
45             AstInterfaceImpl faImpl(stmts);
46             AstInterface fa(&faImpl);
47
48             // This will do as much fusion as possible (finer grained
49             // control over loop optimizations uses a different interface).
50             LoopTransformTraverse( fa, AstNodePtrImpl(stmts), aliasInfo);
51
52             // JJW 10-29-2007 Adjust for iterator invalidation and possible
53             // inserted statements
54             p = std::find(declList.begin(), declList.end(), func);
55             assert (p != declList.end());
56         }
57     }
58
59     // Generate source code from AST and call the vendor's compiler
60     return backend(project);
61 }

```

Figure 33.1: Example source code showing use of loop optimization mechanisms.

33.2 Matrix Multiply Example

Using the matrix multiply example code shown in figure 33.2, we run the loop optimizer in figure 33.1 and generate the code shown in figure 33.3.

```
2  // Example program showing matrix multiply
   // (for use with loop optimization tutorial example)
4  #define N 50
6  int main()
   {
8      int i,j , k;
      double a[N][N] , b[N][N] , c[N][N];
10     for (i = 0; i <= N-1; i+=1)
12         {
            for (j = 0; j <= N-1; j+=1)
14                 {
                    for (k = 0; k <= N-1; k+=1)
16                         {
                                c[i][j] = c[i][j] + a[i][k] * b[k][j];
18                         }
                    }
20         }
22     return 0;
   }
```

Figure 33.2: Example source code used as input to loop optimization processor.


```

2  int min2(int a0,int a1)
   {
4   return a0 < a1?a0 : a1;
   }
6
   // Example program showing matrix multiply
8   // (for use with loop optimization tutorial example)
#define N 50
10
11  int main()
12  {
13     int i;
14     int j;
15     int k;
16     double a[50UL][50UL];
17     double b[50UL][50UL];
18     double c[50UL][50UL];
19     int _var_0;
20     int _var_1;
21     for (_var_1 = 0; _var_1 <= 49; _var_1 += 16) {
22         for (_var_0 = 0; _var_0 <= 49; _var_0 += 16) {
23             for (k = 0; k <= 49; k += 1) {
24                 for (i = _var_1; i <= min2(49,_var_1 + 15); i += 1) {
25                     for (j = _var_0; j <= min2(49,_var_0 + 15); j += 1) {
26                         (c[i])[j] = (((c[i])[j]) + (((a[i])[k]) * ((b[k])[j]))));
27                     }
28                 }
29             }
30         }
31     }
32     return 0;
33 }

```

Figure 33.3: Output of loop optimization processor showing matrix multiply optimization (using options: `-bk1 -fs0`).

33.3 Loop Fusion Example

Using the loop fusion example code shown in figure 33.4, we run the loop optimizer in figure 33.1 and generate the code shown in figure 33.5.

```

2  main() {
4      int x[30], i;
6      for (i = 1; i <= 10; i += 1) {
8          x[2 * i] = x[2 * i + 1] + 2;
10     }
12     for (i = 1; i <= 10; i += 1) {
14         x[2 * i + 3] = x[2 * i] + i;
16     }
18 }

```

Figure 33.4: Example source code used as input to loop optimization processor.

```

2  int main()
3  {
4      int x[30UL];
5      int i;
6      for (i = 1; i <= 11; i += 1) {
7          if (i <= 10) {
8              x[2 * i] = ((x[(2 * i) + 1]) + 2);
9          }
10         else {
11             if (i >= 2) {
12                 x[(2 * (-1 + i)) + 3] = ((x[2 * (-1 + i)]) + (-1 + i));
13             }
14             else {
15                 ;
16             }
17         }
18     }
19     return 0;
20 }

```

Figure 33.5: Output of loop optimization processor showing loop fusion (using options: `-fs2`).

33.4 Example Loop Processor (LoopProcessor.C)

This section contains a more detail translator which uses the command-line for input of specific loop processing options and is more sophisticated than the previous translator used to handle the previous two examples.

Figure 33.6 shows the code required to call the loop optimizations within ROSE. The translator that we build for this tutorial is simple and takes command line parameters to control which optimizations are done.

```

2  #include "rose.h"
   #include <general.h>

4  #include "pre.h"
   #include "finiteDifferencing.h"

6

8  // DQ (1/2/2008): I think this is no longer used!
   // #include "copy_unparser.h"

10 #include "rewrite.h"
12 #include <CommandOptions.h>
   #include <AstInterface.ROSE.h>
14 #include <LoopTransformInterface.h>
   #include <AnnotCollect.h>
16 #include <OperatorAnnotation.h>

18 using namespace std;

20 #ifdef USE_OMEGA
   #include <DepTestStatistics.h>
22
   extern DepTestStatistics DepStats;
24 #endif

26 extern bool DebugAnnot();
   extern void FixFileInfo(SgNode* n);
28 class UnparseFormatHelp;
   class UnparseDelegate;
30 void unparseProject( SgProject* project, UnparseFormatHelp* unparseHelp /*= NULL*/, UnparseDelegate* repl
   /*= NULL */);

32 void PrintUsage( char* name)
   {
34     cerr << name << " _<options>_" << "<program_name>" << "\n";
       cerr << "-gobj: _generate_object_file\n";
36       cerr << "-orig: _copy_non-modified_statements_from_original_file\n";
       cerr << "-splitloop: _applying_loop_splitting_to_remove_conditionals_inside_loops\n";
38       cerr << ReadAnnotation::get_inst()->OptionString() << endl;
       cerr << "-pre: _apply_partial_redundancy_elimination\n";
40       cerr << "-fd: _apply_finite_differencing_to_array_index_expressions\n";
       PrintLoopTransformUsage( cerr );
42   }

```

Figure 33.6: Detailed example source code showing use of loop optimization mechanisms (loop-Processor.C part 1).

```

2  bool GenerateObj()
3  {
4      return CmdOptions::GetInstance()->HasOption("-gobj");
5  }
6
7
8  int
9  main ( int argc ,  char * argv[] )
10 {
11
12     if (argc <= 1) {
13         PrintUsage(argv[0]);
14         return -1;
15     }
16     #if 0
17         CmdOptions::GetInstance()->SetOptions(argc , argv);
18         SetLoopTransformOptions(argc , argv);
19
20         OperatorSideEffectAnnotation *funcInfo =
21             OperatorSideEffectAnnotation::get_inst();
22         funcInfo->register_annot();
23         ReadAnnotation::get_inst()->read();
24         AssumeNoAlias aliasInfo;
25
26         vector<string> argvList(argv , argv + argc);
27         SgProject sageProject ( argvList);
28     #else
29         // DQ (2/10/2008): Using command-line support similar to that in tests/roseTests/loopProcessor
30         vector<string> argvList(argv , argv + argc);
31         SetLoopTransformOptions(argvList);
32         CmdOptions::GetInstance()->SetOptions(argvList);
33
34     #ifndef USEOMEGA
35         DepStats.SetFileName( buffer.str());
36     #endif
37
38     OperatorSideEffectAnnotation *funcInfo =
39         OperatorSideEffectAnnotation::get_inst();
40     funcInfo->register_annot();
41     ReadAnnotation::get_inst()->read();
42     if (DebugAnnot())

```

Figure 33.7: loopProcessor.C source code (Part 2).

33.5 Matrix Multiplication Example (mm.C)

Using the matrix multiplication example code shown in figure 33.8, we run the loop optimizer in figure 33.6 and generate the code shown in figure 33.9.

```

2  #define N 50
4  void printmatrix( double x[][N]);
   void initmatrix( double x[][N], double s);
6
   main()
8  {
   int i,j,k;
10  double a[N][N], b[N][N], c[N][N];
12
   double s;
   s = 235.0;
14  initmatrix(a, s);
   s = 321.0;
16  initmatrix(b, s);
18
   printmatrix(a);
   printmatrix(b);
20  for (i = 0; i <= N-1; i+=1) {
       for (j = 0; j <= N-1; j+=1) {
22         for (k = 0; k <= N-1; k+=1) {
             c[i][j] = c[i][j] + a[i][k] * b[k][j];
24         }
       }
26     }
28     printmatrix(c);
   }

```

Figure 33.8: Example source code used as input to loopProcessor, show in figure 33.6.

```

2  int min2(int a0,int a1)
   {
4   return a0 < a1?a0 : a1;
   }
6
   #define N 50
8   extern void printmatrix(double x[][50UL]);
   extern void initmatrix(double x[][50UL],double s);
10
11  int main()
12  {
13     int i;
14     int j;
15     int k;
16     double a[50UL][50UL];
17     double b[50UL][50UL];
18     double c[50UL][50UL];
19     double s;
20     int _var_0;
21     int _var_1;
22     s = 235.0;
23     initmatrix(a,s);
24     s = 321.0;
25     initmatrix(b,s);
26     printmatrix(a);
27     printmatrix(b);
28     for (_var_1 = 0; _var_1 <= 49; _var_1 += 16) {
29         for (_var_0 = 0; _var_0 <= 49; _var_0 += 16) {
30             for (k = 0; k <= 49; k += 1) {
31                 for (i = _var_1; i <= min2(49,_var_1 + 15); i += 1) {
32                     for (j = _var_0; j <= min2(49,_var_0 + 15); j += 1) {
33                         (c[i][j] = (((c[i][j]) + ((a[i][k]) * ((b[k][j])))));
34                     }
35                 }
36             }
37         }
38     }
39     printmatrix(c);
40     return 0;
41 }

```

Figure 33.9: Output of loopProcessor using input from figure 33.8 (using options: `-bk1 -fs0`).

33.6 Matrix Multiplication Example Using Linearized Matrices (dgemm.C)

Using the matrix multiplication example code shown in figure 33.10, we run the loop optimizer in figure 33.6 and generate the code shown in figure 33.11.

```

2  // Function prototype
   void dgemm(double *a, double *b, double *c, int n);
4
   // Function definition
6  void dgemm(double *a, double *b, double *c, int n)
   {
8      int i, j, k;

10     // int n;

12     for (k=0; k<n; k+=1){
13         for (j=0; j<n; j+=1){
14             for (i=0; i<n; i+=1){
15                 c[j*n+i]=c[j*n+i]+a[k*n+i]*b[j*n+k];
16             }
17         }
18     }
   }

```

Figure 33.10: Example source code used as input to loopProcessor, show in figure 33.6.

```

2  int min2(int a0,int a1)
3  {
4      return a0 < a1?a0 : a1;
5  }
6
7  // Function prototype
8  extern void dgemm(double *a,double *b,double *c,int n);
9  // Function definition
10
11 void dgemm(double *a,double *b,double *c,int n)
12 {
13     int i;
14     int j;
15     int k;
16     int _var_0;
17     int _var_1;
18     for (_var_1 = 0; _var_1 <= -1 + n; _var_1 += 16) {
19         for (_var_0 = 0; _var_0 <= -1 + n; _var_0 += 16) {
20             for (i = 0; i <= -1 + n; i += 1) {
21                 for (k = _var_1; k <= min2(-1 + n, _var_1 + 15); k += 1) {
22                     for (j = _var_0; j <= -15 + min2(-1 + n, _var_0 + 15); j += 16) {
23                         int _var_2 = j;
24                         c[(j * n) + i] = ((c[(j * n) + i]) + ((a[(k * n) + i]) * (b[(j * n) + k])));
25                         _var_2 = 1 + _var_2;
26                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
27                         _var_2 = 1 + _var_2;
28                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
29                         _var_2 = 1 + _var_2;
30                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
31                         _var_2 = 1 + _var_2;
32                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
33                         _var_2 = 1 + _var_2;
34                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
35                         _var_2 = 1 + _var_2;
36                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
37                         _var_2 = 1 + _var_2;
38                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
39                         _var_2 = 1 + _var_2;
40                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
41                         _var_2 = 1 + _var_2;
42                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
43                         _var_2 = 1 + _var_2;
44                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
45                         _var_2 = 1 + _var_2;
46                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
47                         _var_2 = 1 + _var_2;
48                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
49                         _var_2 = 1 + _var_2;
50                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
51                         _var_2 = 1 + _var_2;
52                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
53                         _var_2 = 1 + _var_2;
54                         c[( _var_2 * n) + i] = ((c[( _var_2 * n) + i]) + ((a[(k * n) + i]) * (b[( _var_2 * n) + k])));
55                     }
56                     for (; j <= min2(-1 + n, _var_0 + 15); j += 1) {
57                         c[(j * n) + i] = ((c[(j * n) + i]) + ((a[(k * n) + i]) * (b[(j * n) + k])));
58                     }
59                 }
60             }
61         }
62     }

```

Figure 33.11: Output of loopProcessor using input from figure 33.10 (using options: `-bk1 -unroll nvar 16`).

33.7 LU Factorization Example (lufac.C)

Using the LU factorization example code shown in figure 33.12, we run the loop optimizer in figure 33.6 and generate the code shown in figure 33.13.

```

1  double abs(double x) { if (x < 0) return -x; else return x; }
2
3  #define n 50
4  void printmatrix( double x[][n]);
5  void initmatrix( double x[][n], double s);
6
7  main(int argc, char* argv[]) {
8  int p[n], i, j, k;
9  double a[n][n], mu, t;
10
11  initmatrix(a, 5.0);
12  printmatrix(a);
13
14  for (k = 0; k<=n-2; k+=1) {
15      p[k] = k;
16      mu = abs(a[k][k]);
17      for (i = k+1; i <= n-1; i+=1) {
18          if (mu < abs(a[i][k])) {
19              mu = abs(a[i][k]);
20              p[k] = i;
21          }
22      }
23
24      for (j = k; j <= n-1; j+=1) {
25          t = a[k][j];
26          a[k][j] = a[p[k]][j];
27          a[p[k]][j] = t;
28      }
29
30      for (i = k+1; i <= n-1; i+=1) {
31          a[i][k] = a[i][k]/a[k][k];
32      }
33      for (j = k+1; j <= n-1; j+=1) {
34          for (i = k+1; i <= n-1; i+=1) {
35              a[i][j] = a[i][j] - a[i][k]*a[k][j];
36          }
37      }
38  }
39
40  printmatrix(a);
41  }

```

Figure 33.12: Example source code used as input to loopProcessor, show in figure 33.6.

```

2  double abs(double x)
3  {
4      if (x < (0))
5          return -x;
6      else
7          return x;
8  }

10 #define n 50
11 extern void printmatrix(double x[][50UL]);
12 extern void initmatrix(double x[][50UL], double s);

14 int main(int argc, char *argv[])
15 {
16     int p[50UL];
17     int i;
18     int j;
19     int k;
20     double a[50UL][50UL];
21     double mu;
22     double t;
23     initmatrix(a, 5.0);
24     printmatrix(a);
25     for (k = 0; k <= 48; k += 1) {
26         p[k] = k;
27         mu = abs(((a[k])[k]));
28         for (i = 1 + k; i <= 49; i += 1) {
29             if (mu < abs(((a[i])[k]))) {
30                 mu = abs(((a[i])[k]));
31                 p[k] = i;
32             }
33         }
34         for (j = k; j <= 49; j += 1) {
35             t = ((a[k])[j]);
36             (a[k])[j] = ((a[p[k]])[j]);
37             (a[p[k]])[j] = t;
38         }
39         for (i = 1 + k; i <= 49; i += 1) {
40             (a[i])[k] = (((a[i])[k]) / ((a[k])[k]));
41         }
42         for (j = 1 + k; j <= 49; j += 1) {
43             for (i = 1 + k; i <= 49; i += 1) {
44                 (a[i])[j] = (((a[i])[j]) - ((a[i])[k]) * ((a[k])[j])));
45             }
46         }
47     }
48     printmatrix(a);
49     return 0;
50 }

```

Figure 33.13: Output of loopProcessor using input from figure 33.12 (using options: `-bk1 -fs0 -splitloop -annotation`).

33.8 Loop Fusion Example (tridvpk.C)

Using the loop fusion example code shown in figure 33.14, we run the loop optimizer in figure 33.6 and generate the code shown in figure 33.15.

```

2  #define n 100
3
4  double a[n], b[n], c[n], d[n], e[n];
5  double tot[n][n];
6  double dux[n][n][n], duy[n][n][n], duz[n][n][n];
7
8  main()
9  {
10     int i,j,k;
11     for ( j=0; j <=n-1; j+=1)
12         for ( i=0; i<=n-1; i+=1)
13             duz[i][j][0] = duz[i][j][0]*b[0];
14
15     for (k=1; k<=n-2; k+=1)
16         for ( j = 0; j <= n-1; j+=1)
17             for ( i=0; i<=n-1; i+=1)
18                 duz[i][j][k]=(duz[i][j][k]-a[k]*duz[i][j][k-1])*b[k];
19
20     for ( j=0; j <=n-1; j+=1)
21         for ( i=0; i<=n-1; i+=1)
22             tot[i][j] = 0;
23
24     for ( k=0; k<=n-2; k+=1)
25         for ( j=0; j <=n-1; j+=1)
26             for ( i=0; i<=n-1; i+=1)
27                 tot[i][j] = tot[i][j] + d[k]*duz[i][j][k];
28
29     for ( j=0; j <=n-1; j+=1)
30         for ( i=0; i<=n-1; i+=1)
31             duz[i][j][n-1] = (duz[i][j][n-1] - tot[i][j])*b[n-1];
32
33     for ( j=0; j <=n-1; j+=1)
34         for ( i=0; i<=n-1; i+=1)
35             duz[i][j][n-2]=duz[i][j][n-1] - e[n-2]*duz[i][j][n-1];
36
37     for (k=n-3; k>=0; k+=-1)
38         for (j = 0; j <= n-1; j+=1)
39             for (i=0; i<=n-1; i+=1)
40                 duz[i][j][k] = duz[i][j][k] - c[k]*duz[i][j][k+1] - e[k]*duz[i][j][n-1];
41 }

```

Figure 33.14: Example source code used as input to loopProcessor, show in figure 33.6.

```

2  #define n 100
3  double a[100UL];
4  double b[100UL];
5  double c[100UL];
6  double d[100UL];
7  double e[100UL];
8  double tot[100UL][100UL];
9  double dux[100UL][100UL][100UL];
10 double duy[100UL][100UL][100UL];
11 double duz[100UL][100UL][100UL];
12
13 int main()
14 {
15     int i;
16     int j;
17     int k;
18     for (i = 0; i <= 99; i += 1) {
19         for (j = 0; j <= 99; j += 1) {
20             (tot[i])[j] = (0);
21             ((duz[i])[j])[0] = (((duz[i])[j])[0]) * (b[0]));
22             for (k = 0; k <= 98; k += 1) {
23                 if (k >= 1) {
24                     ((duz[i])[j])[k] = (((duz[i])[j])[k]) - ((a[k]) * (((duz[i])[j])[k - 1])) * (b[k]));
25                 }
26                 else {
27                     (tot[i])[j] = (((tot[i])[j]) + ((d[k]) * (((duz[i])[j])[k])));
28                 }
29                 ((duz[i])[j])[100 - 1] = (((duz[i])[j])[100 - 1]) - ((tot[i])[j]) * (b[100 - 1]));
30                 ((duz[i])[j])[100 - 2] = (((duz[i])[j])[100 - 2]) - ((e[100 - 2]) * (((duz[i])[j])[100 - 1]));
31                 for (k = 97; k >= 0; k += -1) {
32                     ((duz[i])[j])[k] = (((duz[i])[j])[k]) - ((c[k]) * (((duz[i])[j])[k + 1])) - ((e[k]) * (((duz[i])[j])[k + 1])));
33                 }
34             }
35         }
36     }
37     return 0;
38 }

```

Figure 33.15: Output of loopProcessor input from figure 33.14 (using options: **-fs2 -ic1 -opt 1**).

Chapter 34

Parameterized Code Translation

This chapter gives examples of using ROSE’s high level loop translation interfaces to perform parameterized loop transformations, including loop unrolling, interchanging and tiling. The motivation is to give users the maximized flexibility to orchestrate code transformations on the targets they want, the order they want, and the parameters they want. One typical application scenario is to support generating desired code variants for empirical tuning.

The ROSE internal interfaces (declared within the SageInterface namespace) to call loop transformations are:

- *bool loopUnrolling (SgForStatement *loop, size_t unrolling_factor)*: This function needs two parameters: one for the loop to be unrolled and the other for the unrolling factor.
- *bool loopInterchange (SgForStatement *loop, size_t depth, size_t lexicoOrder)*: The loop interchange function has three parameters, the first one to specify a loop which starts a perfectly-nested loop and is to be interchanged, the 2nd for the depth of the loop nest to be interchanged, and finally the lexicographical order for the permutation.
- *bool loopTiling (SgForStatement *loopNest, size_t targetLevel, size_t tileSize)* The loop tiling interface needs to know the loop nest to be tiled, which loop level to tile, and the tile size for the level.

For efficiency concerns, those functions only perform the specified translations without doing any legitimacy check. It is up to the users to make sure the transformations won’t generate wrong code. We will soon provide interfaces to do the eligibility check for each transformation.

We also provide standalone executable programs (loopUnrolling, loopInterchange, and loopTiling under ROSE.INSTALL/bin) for the transformations mentioned above so users can directly use them via command lines and abstract handles (explained in Chapter 41) to orchestrate transformations they want.

34.1 Loop Unrolling

Figure 34.1 gives an example input code for loopUnrolling.

An example command line to invoke loop unrolling on the example can look like the following:

```
int a[100][100];
2 int main(void)
{
4     int j;
    for (int i=0; i<100; i++)
6         for (j=0; j<100; j++)
            {
8                 int k=3;
                a[i][j]=i+j+k;
10            }
    return 0;
12 }
```

Figure 34.1: Example source code used as input to loopUnrolling

```
# unroll a for statement 5 times. The loop is a statement at line 6 within
# an input file.
loopUnrolling -c inputloopUnrolling.C \
-rose:loopunroll:abstract_handle "Statement<position,6>" -rose:loopunroll:factor 5
```

Two kinds of output can be expected after loop unrolling. One (Shown in Figure 34.2) is the case that the loop iteration count is known at compile-time and can be evenly divisible by the unrolling factor. The other case (Shown in Figure 34.3 is when the divisibility is unknown and a fringe loop has to be generated to run possible leftover iterations.

```

2   int a[100UL][100UL];
3
4   int
5   main ()
6   {
7       int j;
8       for (int i = 0; i < 100; i++)
9       {
10          for (j = 0; j <= 99; j += 5)
11          {
12              int k = 3;
13              (a[i])[j] = ((i + j) + k);
14              {
15                  int k = 3;
16                  (a[i])[j + 1] = ((i + (j + 1)) + k);
17              }
18              {
19                  int k = 3;
20                  (a[i])[j + 2] = ((i + (j + 2)) + k);
21              }
22              {
23                  int k = 3;
24                  (a[i])[j + 3] = ((i + (j + 3)) + k);
25              }
26              {
27                  int k = 3;
28                  (a[i])[j + 4] = ((i + (j + 4)) + k);
29              }
30          }
31      }
32      return 0;
33  }

```

Figure 34.2: Output for a unrolling factor which can divide the iteration space evenly

```

2   int a[100UL][100UL];
3
4   int
5   main ()
6   {
7       int j;
8       for (int i = 0; i < 100; i++)
9       {
10          // iter_count = (ub-lb+1)%step ==0?(ub-lb+1)/step: (ub-lb+1)/step+1;
11          // fringe = iter_count%unroll_factor==0 ? 0:unroll_factor*step
12          int _lu_fringe = 3;
13          for (j = 0; j <= 99 - _lu_fringe; j += 3)
14          {
15              int k = 3;
16              (a[i])[j] = ((i + j) + k);
17              {
18                  int k = 3;
19                  (a[i])[j + 1] = ((i + (j + 1)) + k);
20              }
21              {
22                  int k = 3;
23                  (a[i])[j + 2] = ((i + (j + 2)) + k);
24              }
25          }
26          for (; j <= 99; j += 1)
27          {
28              int k = 3;
29              (a[i])[j] = ((i + j) + k);
30          }
31      }
32      return 0;

```

Figure 34.3: Output for the case when divisibility is unknown at compile-time

34.2 Loop Interchange

Figure 34.4 gives an example input code for loopInterchange.

```

void OUT_1_6119__(int ri, double *rp, int stencil_size, int hypr_m, const double *Ap_0)
2 {
4     int si, ii, jj, kk;
    // the following 4-level loop nest is to be interchanged
    for (si = 0; si < stencil_size; si++)
6         for (kk = 0; kk < hypr_m; kk++)
            for (jj = 0; jj < hypr_m; jj++)
8                 for (ii = 0; ii < hypr_m; ii++)
                    rp[(ri + ii) + jj + kk] -= Ap_0[ii + jj + kk];
10 }

```

Figure 34.4: Example source code used as input to loopInterchange

An example command line to invoke loop interchange:

```

# interchange a loop nest starting from the first loop within the input file,
# interchange depth is 4 and
# the lexicographical order is 1 (swap the innermost two levels)
loopInterchange -c inputloopInterchange.C -rose:loopInterchange:abstract_handle \
"ForStatement<numbering,1>" -rose:loopInterchange:depth 4 \
-rose:loopInterchange:order 1

```

Figure 34.5 shows the output.

```

2 void OUT_1_6119__(int ri, double *rp, int stencil_size, int hypr_m, const double *Ap_0)
3 {
4     int si;
5     int ii;
6     int jj;
7     int kk;
8     // the following 4-level loop nest is to be interchanged
9     for (si = 0; si < stencil_size; si++)
10         for (kk = 0; kk < hypr_m; kk++)
11             for (ii = 0; ii < hypr_m; ii++)
12                 for (jj = 0; jj < hypr_m; jj++)
13                     rp[((ri + ii) + jj) + kk] -= (Ap_0[(ii + jj) + kk]);
14 }

```

Figure 34.5: Output for loop interchange

34.3 Loop Tiling

Figure 34.6 gives an example input code for loopTiling.

```

1  #define N 100
2  int i,j,k;
3  double a[N][N],b[N][N],c[N][N];
4
5  int main()
6  {
7      for (i = 0; i < N; i++)
8          for (j = 0; j < N; j++)
9              for (k = 0; k < N; k++)
10                 c[i][j] = c[i][j] + a[i][k] * b[k][j];
11     return 0;
12 }

```

Figure 34.6: Example source code used as input to loopTiling

An example command line to invoke loop tiling:

```

# Tile the loop with a depth of 3 within the first loop of the input file
# tile size is 5
loopTiling -c inputloopTiling.C -rose:loopTiling:abstract_handle \
"ForStatement<numbering,1>" -rose:loopTiling:depth 3 -rose:loopTiling:tilesize 5

```

Figure 34.7 shows the output.

```

1  #define N 100
2  int i;
3  int j;
4  int k;
5  double a[100UL][100UL];
6  double b[100UL][100UL];
7  double c[100UL][100UL];
8
9  int main()
10 {
11     int _lt_var_k;
12     for (_lt_var_k = 0; _lt_var_k <= 99; _lt_var_k += 5) {
13         for (i = 0; i < 100; i++)
14             for (j = 0; j < 100; j++)
15                 for (k = _lt_var_k; k <= (((99 < (_lt_var_k + 5 - 1)) ? 99 : (_lt_var_k + 5 - 1))); k += 1) {
16                     (c[i][j] = (((c[i][j]) + ((a[i][k]) * ((b[k][j])))));
17                 }
18     }
19     return 0;
20 }

```

Figure 34.7: Output for loop tiling

Part V

Correctness Checking

Tutorials of using ROSE to help program correctness checking or debugging.

Chapter 35

Code Coverage

This translator is part of ongoing collaboration with IBM on the support of code coverage analysis tools for C, C++ and F90 applications. the subject of code coverage is much more complex than this example code would cover. The following web site: <http://www.bullseye.com/coverage.html> contains more information and is the source for the descriptions below. Code coverage can include:

- Statement Coverage
This measure reports whether each executable statement is encountered.
- Decision Coverage
This measure reports whether boolean expressions tested in control structures (such as the if-statement and while-statement) evaluated to both true and false. The entire boolean expression is considered one true-or-false predicate regardless of whether it contains logical-and or logical-or operators. Additionally, this measure includes coverage of switch-statement cases, exception handlers, and interrupt handlers.
- Condition Coverage
Condition coverage reports the true or false outcome of each boolean sub-expression, separated by logical-and and logical-or if they occur. Condition coverage measures the sub-expressions independently of each other.
- Multiple Condition Coverage
Multiple condition coverage reports whether every possible combination of boolean sub-expressions occurs. As with condition coverage, the sub-expressions are separated by logical-and and logical-or, when present. The test cases required for full multiple condition coverage of a condition are given by the logical operator truth table for the condition.
- Condition/Decision Coverage
Condition/Decision Coverage is a hybrid measure composed by the union of condition coverage and decision coverage. This measure was created at Boeing and is required for aviation software by RCTA/DO-178B.

- **Modified Condition/Decision Coverage**
This measure requires enough test cases to verify every condition can affect the result of its encompassing decision.
- **Path Coverage**
This measure reports whether each of the possible paths in each function have been followed. A path is a unique sequence of branches from the function entry to the exit.
- **Function Coverage**
This measure reports whether you invoked each function or procedure. It is useful during preliminary testing to assure at least some coverage in all areas of the software. Broad, shallow testing finds gross deficiencies in a test suite quickly.
- **Call Coverage**
This measure reports whether you executed each function call. The hypothesis is that faults commonly occur in interfaces between modules.
- **Linear Code Sequence and Jump (LCSAJ) Coverage**
This variation of path coverage considers only sub-paths that can easily be represented in the program source code, without requiring a flow graph. An LCSAJ is a sequence of source code lines executed in sequence. This "linear" sequence can contain decisions as long as the control flow actually continues from one line to the next at run-time. Sub-paths are constructed by concatenating LCSAJs. Researchers refer to the coverage ratio of paths of length n LCSAJs as the test effectiveness ratio (TER) $n+2$.
- **Data Flow Coverage**
This variation of path coverage considers only the sub-paths from variable assignments to subsequent references of the variables.
- **Object Code Branch Coverage**
This measure reports whether each machine language conditional branch instruction both took the branch and fell through.
- **Loop Coverage**
This measure reports whether you executed each loop body zero times, exactly once, and more than once (consecutively). For do-while loops, loop coverage reports whether you executed the body exactly once, and more than once. The valuable aspect of this measure is determining whether while-loops and for-loops execute more than once, information not reported by others measure.
- **Race Coverage**
This measure reports whether multiple threads execute the same code at the same time. It helps detect failure to synchronize access to resources. It is useful for testing multi-threaded programs such as in an operating system.
- **Relational Operator Coverage**
This measure reports whether boundary situations occur with relational operators (j , $j=$, $j<$, $j=>$). The hypothesis is that boundary test cases find off-by-one errors and mistaken uses of wrong relational operators such as j instead of $j=$.

- Weak Mutation Coverage

This measure is similar to relational operator coverage but much more general [Howden1982]. It reports whether test cases occur which would expose the use of wrong operators and also wrong operands. It works by reporting coverage of conditions derived by substituting (mutating) the program's expressions with alternate operators, such as "-" substituted for "+", and with alternate variables substituted.

- Table Coverage

This measure indicates whether each entry in a particular array has been referenced. This is useful for programs that are controlled by a finite state machine.

The rest of this text must be changed to refer to the code coverage example within ROSE/-tutorial.

Figure 35 shows the low level construction of a more complex AST fragment (a function declaration) and its insertion into the AST at the top of each block. Note that the code does not handle symbol table issues, yet.

Building a function in global scope.

```

2 // ROSE is a tool for building preprocessors, this file is an example preprocessor built with ROSE.
3 // Specifically it shows the design of a transformation to instrument source code, placing source code
4 // at the top and bottom of each basic block.
5
6 #include "rose.h"
7
8 using namespace std;
9
10 /*
11  * Design of this code.
12  * Inputs: source code (file.C)
13  * Outputs: instrumented source code (rose-file.C and file.o)
14
15  * Properties of instrumented source code:
16  * 1) added declaration for coverage support function
17  *    (either forward function declaration or a #include to include a header file).
18  * 2) Each function in the source program is instrumented to include a call to the
19  *    coverage support function/
20  */
21
22 // Global variables so that the global function declaration can be reused to build
23 // each function call expression in the AST traversal to instrument all functions.
24 SgFunctionDeclaration* globalFunctionDeclaration = NULL;
25 SgFunctionType* globalFunctionType = NULL;
26 SgFunctionSymbol* functionSymbol = NULL;
27
28 // Simple ROSE traversal class: This allows us to visit all the functions and add
29 // new code to instrument/record their use.
30 class SimpleInstrumentation : public SgSimpleProcessing
31 {
32 public:
33     // required visit function to define what is to be done
34     void visit ( SgNode* astNode );
35 };
36
37 // Code to build function declaration: This declares Shmuel's function call which
38 // will be inserted (as a function call) into each function body of the input
39 // application.
40 void buildFunctionDeclaration (SgProject* project)
41 {
42     // *****
43     // Create the functionDeclaration
44     // *****
45
46     // SgGlobal* globalScope = project->get_file(0).get_root();
47     SgSourceFile* sourceFile = isSgSourceFile(project->get_fileList()[0]);
48     ROSE_ASSERT(sourceFile != NULL);
49     SgGlobal* globalScope = sourceFile->get_globalScope();
50     ROSE_ASSERT(globalScope != NULL);
51
52     Sg_File_Info * file_info = Sg_File_Info::generateDefaultFileInfoForTransformationNode();
53     SgType * function_return_type = new SgTypeVoid();
54
55     SgName function_name = "coverageTraceFunc1";
56     SgFunctionType * function_type = new SgFunctionType(function_return_type, false);
57     SgFunctionDeclaration * functionDeclaration = new SgFunctionDeclaration(file_info, function_name, function_type);
58
59     // DQ (9/8/2007): Fixup the defining and non-defining declarations
60     ROSE_ASSERT(functionDeclaration->get_definingDeclaration() == NULL);
61     functionDeclaration->set_definingDeclaration(functionDeclaration);
62     ROSE_ASSERT(functionDeclaration->get_definingDeclaration() != NULL);
63     ROSE_ASSERT(functionDeclaration->get_firstNondefiningDeclaration() != functionDeclaration);
64
65     // DQ (9/8/2007): We have not build a non-defining declaration, so this should be NULL.
66     ROSE_ASSERT(functionDeclaration->get_firstNondefiningDeclaration() == NULL);
67
68     // DQ (9/8/2007): Need to add function symbol to global scope!
69     printf ("Fixing up the symbol table in scope %p for function %p\n", globalScope, globalScope->class_name().c_str());
70     functionSymbol = new SgFunctionSymbol(functionDeclaration);
71     globalScope->insert_symbol(functionDeclaration->get_name(), functionSymbol);
72     ROSE_ASSERT(globalScope->lookup_function_symbol(functionDeclaration->get_name()) != NULL);
73
74     // *****
75     // Create the InitializedName for a parameter within the parameter list
76     // *****
77     SgName var1_name = "textString";

```

Figure 35.1: Example source code shows instrumentation to call a test function from the top of each function body in the application (part 1).


```

2     SgTypeChar * var1_type           = new SgTypeChar();
3     SgPointerType * pointer_type     = new SgPointerType(var1_type);
4     SgInitializer * var1_initializer = NULL;
5     SgInitializedName * var1_init_name = new SgInitializedName(var1_name, pointer_type, var1_initializer, NULL);
6     var1_init_name->set_file_info(Sg_File_Info::generateDefaultFileInfoForTransformationNode());

7
8     // Insert argument in function parameter list
9     ROSE_ASSERT(functionDeclaration != NULL);
10    ROSE_ASSERT(functionDeclaration->get_parameterList() != NULL);
11
12    ROSE_ASSERT(functionDeclaration->get_parameterList() != NULL);
13    functionDeclaration->get_parameterList()->append_arg(var1_init_name);
14
15    // Set the parent node in the AST (this could be done by the AstPostProcessing
16    functionDeclaration->set_parent(globalScope);
17
18    // Set the scope explicitly (since it could be different from the parent?)
19    // This can't be done by the AstPostProcessing (unless we relax some constraints)
20    functionDeclaration->set_scope(globalScope);
21
22    // If it is not a forward declaration then the unparser will skip the ";" at the end (need to fix this better)
23    functionDeclaration->setForward();
24    ROSE_ASSERT(functionDeclaration->isForward() == true);
25
26    // Mark function as extern "C"
27    functionDeclaration->get_declarationModifier().get_storageModifier().setExtern();
28    functionDeclaration->set_linkage("C"); // This mechanism could be improved!
29
30    globalFunctionType = function_type;
31    globalFunctionDeclaration = functionDeclaration;
32
33    // Add function declaration to global scope!
34    globalScope->prepend_declaration(globalFunctionDeclaration);
35
36    // functionSymbol = new SgFunctionSymbol(globalFunctionDeclaration);
37    // All any modifications to be fixed up (parents etc)
38    // AstPostProcessing(project); // This is not allowed and should be fixed!
39    AstPostProcessing(globalScope);
40
41    }
42
43    #if 0
44    // DQ (12/1/2005): This version of the visit function handles the special case of
45    // instrumentation at each function (a function call at the top of each function).
46    // At IBM we modified this to be a version which instrumented every block.
47
48    void
49    SimpleInstrumentation::visit ( SgNode* astNode )
50    {
51        SgFunctionDeclaration* functionDeclaration = isSgFunctionDeclaration(astNode);
52        SgFunctionDefinition* functionDefinition = functionDeclaration != NULL ? functionDeclaration->get_definition() : NULL;
53        if (functionDeclaration != NULL && functionDefinition != NULL)
54        {
55            // It is up to the user to link the implementations of these functions link time
56            string functionName = functionDeclaration->get_name().str();
57            string fileName = functionDeclaration->get_file_info()->get_filename();
58
59            // Build a source file location object (for construction of each IR node)
60            // Note that we should not be sharing the same Sg_File_Info object in multiple IR nodes.
61            Sg_File_Info * file_info = Sg_File_Info::generateDefaultFileInfoForTransformationNode();
62
63            SgFunctionSymbol* functionSymbol = new SgFunctionSymbol(globalFunctionDeclaration);
64            SgFunctionRefExp* functionRefExpression = new SgFunctionRefExp(file_info, functionSymbol, globalFunctionType);
65            SgExprListExp* expressionList = new SgExprListExp(file_info);
66
67            string converageFunctionInput = functionName + string("_in_") + fileName;
68            SgStringVal* functionNameStringValue = new SgStringVal(file_info, (char*)converageFunctionInput.c_str());
69            expressionList->append_expression(functionNameStringValue);
70            SgFunctionCallExp* functionCallExp = new SgFunctionCallExp(file_info, functionRefExpression, expressionList, globalFunctionType);
71
72            // create an expression type
73            SgTypeVoid* expr_type = new SgTypeVoid();
74
75            // create an expression root
76            // SgExpressionRoot * expr_root = new SgExpressionRoot(file_info, functionCallExp, expr_type);
77
78            // create an expression statement
79            SgExprStatement* new_stmt = new SgExprStatement(file_info, functionCallExp);
80
81            // expr_root->set_parent(new_stmt);

```

Figure 35.2: Example source code shows instrumentation to call a test function from the top of each function body in the application (part 2).

```

2      // new_stmt->set_expression_root(expr_root);
      // functionCallExp->set_parent(new_stmt->get_expression_root());
4      functionCallExp->set_parent(new_stmt);
6      // insert a statement into the function body
      functionDefinition->get_body()->prepend_statement(new_stmt);
8
10     #if 0
      // This shows the alternative use of the ROSE Rewrite Mechanism to do the same thing!
      // However, the performance is not as good as the version written above (more directly
      // building the IR nodes).
14     // string codeAtTopOfBlock = "void printf(char*); printf(\"FUNCTION_NAME in FILE_NAME \\n\");";
      string codeAtTopOfBlock = "coverageTraceFunc1(\"FUNCTION_NAME_in_\"FILE_NAME\")";
16
      string functionTarget = "FUNCTION_NAME";
      string fileTarget
18         = "FILE_NAME";
20
      codeAtTopOfBlock.replace(codeAtTopOfBlock.find(functionTarget),functionTarget.size(),functionName);
      codeAtTopOfBlock.replace(codeAtTopOfBlock.find(fileTarget),fileTarget.size(),fileName);
22
      // printf ("codeAtTopOfBlock = %s \\n",codeAtTopOfBlock.c_str());
      printf ("%s_in_%s\\n",functionName.c_str(),fileName.c_str());
24
      // Insert new code into the scope represented by the statement (applies to SgScopeStatements)
      MiddleLevelRewrite::ScopeIdentifierEnum scope = MidLevelCollectionTypedefs::StatementScope;
26
      SgBasicBlock* functionBody = functionDefinition->get_body();
      ROSE_ASSERT(functionBody != NULL);
30
      // Insert the new code at the top of the scope represented by block
      MiddleLevelRewrite::insert(functionBody,codeAtTopOfBlock,scope, MidLevelCollectionTypedefs::TopOfCurrentScope);
32
34 #endif
    }
36 }
38 #endif
39
40 void
SimpleInstrumentation::visit ( SgNode* astNode ) {
42     SgBasicBlock *block = NULL;
      block = isSgBasicBlock(astNode);
      if (block != NULL) {
44         // It is up to the user to link the implementations of these functions link time
      Sg_File_Info *fileInfo = block->get_file_info();
      string fileName = fileInfo->get_filename();
      int lineNumber = fileInfo->get_line();
46
      // Build a source file location object (for construction of each IR node)
      // Note that we should not be sharing the same Sg_File_Info object in multiple IR nodes.
      Sg_File_Info * newCallfileInfo = Sg_File_Info::generateDefaultFileInfoForTransformationNode();
50
      ROSE_ASSERT(functionSymbol != NULL);
      SgFunctionRefExp* functionRefExpression = new SgFunctionRefExp(newCallfileInfo, functionSymbol, globalFunctionType);
      SgExprListExp* expressionList
52         = new SgExprListExp(newCallfileInfo);
54
      string codeLocation = fileName + "-" + StringUtility::numberToString(lineNumber);
      SgStringVal* functionNameStringValue = new SgStringVal(newCallfileInfo, (char*)codeLocation.c_str());
      expressionList->append_expression(functionNameStringValue);
56
      SgFunctionCallExp* functionCallExp = new SgFunctionCallExp(newCallfileInfo, functionRefExpression, expressionList, globalFunctionType);
58
      // create an expression type
      // SgTypeVoid* expr_type = new SgTypeVoid();
      // create an expression root
      // SgExpressionRoot * expr_root = new SgExpressionRoot(newCallfileInfo, functionCallExp, expr_type);
60
      // create an expression statement
      SgExprStatement* new_stmt = new SgExprStatement(newCallfileInfo, functionCallExp);
62
      // expr_root->set_parent(new_stmt);
      // new_stmt->set_expression(expr_root);
      // functionCallExp->set_parent(new_stmt->get_expression());
      functionCallExp->set_parent(new_stmt);
64
      // insert a statement into the function body
      block->prepend_statement(new_stmt);
66
68 }
}

```

Figure 35.3: Example source code shows instrumentation to call a test function from the top of each function body in the application (part 3).

```

1  void foo()
2  {
3      // Should detect that foo IS called
4      if (true) {
5          int x = 3;
6      }
7      else {
8          int x = 4;
9      }
10 }

12 void foobar()
13 {
14     int y = 4;
15     switch (y) {
16         case 1:
17             //hello world
18             break;
19         case 2:
20
21         case 3:
22
23         default: {
24             //
25         }
26     }

28     // Should detect that foobar is NOT called
29 }

30 int main()
31 {
32     if (true) {
33         foo();
34     }
35     return 0;
36 }

```

Figure 35.4: Example source code used as input to translator adding new function.

```

    extern "C" void coverageTraceFunc1(char *textString);
2
void foo()
4 {
    coverageTraceFunc1("/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode.ExampleCodeCov
6 // Should detect that foo IS called
    if (true) {
8         coverageTraceFunc1("/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode.ExampleCodeCov
        int x = 3;
10    }
    else {
12        coverageTraceFunc1("/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode.ExampleCodeCov
        int x = 4;
14    }
16 }

18 void foobar()
{
20     coverageTraceFunc1("/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode.ExampleCodeCov
    int y = 4;
22     switch(y){
        coverageTraceFunc1("/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode.ExampleCodeCov
24         case 1:
{
26             coverageTraceFunc1("/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode.ExampleCodeCov
//hello world
28             break;
        }
30         default:
{
32             coverageTraceFunc1("/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode.ExampleCodeCov
{
34             coverageTraceFunc1("/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode.ExampleCodeCov
//
36         }
    }
38 }
// Should detect that foobar is NOT called
40 }

42 int main()
44 {
46     coverageTraceFunc1("/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode.ExampleCodeCov
    if (true) {
        coverageTraceFunc1("/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode.ExampleCodeCov
48    }
    foo();
50    return 0;
}

```

Figure 35.5: Output of input to translator adding new function.

Chapter 36

Bug Seeding

Bug seeding is a technique used to construct example codes from existing codes which can be used to evaluate tools for the finding bugs in randomly selected existing applications. The idea is to seed an existing application with a known number of known bugs and evaluate the bug finding or security tool based on the percentage of the number of bugs found by the tool. If the bug finding tool can identify all known bugs then there can be some confidence that the tool detects all bugs of that type used to seed the application.

This example tutorial code is a demonstration of a more complete technique being developed in collaboration with NIST to evaluate tools for finding security flaws in applications. It will in the future be a basis for testing of tools built using ROSE, specifically Compass, but the techniques are not in any way specific to ROSE or Compass.

36.1 Input For Examples Showing Bug Seeding

Figure ?? shows the example input used for demonstration of bug seeding as a transformation.

```
2  void foobar()
3  {
4      // Static array declaration
5      float array[10];
6
7      array[0] = 0;
8
9      for (int i=0; i < 5; i++)
10     {
11         array[i] = 0;
12     }
13 }
```

Figure 36.1: Example source code used as input to program in codes used in this chapter.

36.2 Generating the code representing the seeded bug

Figure 36.2 shows a code that traverses each IR node and for and modifies array reference index expressions to be out of bounds. The input code is shown in figure 36.1, the output of this code is shown in figure 36.3.

```

// This example demonstrates the seeding of a specific type
// of bug (buffer overflow) into any existing application to
// test bug finding tools.
4
#include "rose.h"
using namespace SageBuilder;
using namespace SageInterface;
8
namespace SeedBugsArrayIndexing {
10
class InheritedAttribute
12 {
    public:
14     bool isLoop;
16     bool isVulnerability;
    InheritedAttribute() : isLoop(false), isVulnerability(false) {}
    InheritedAttribute(const InheritedAttribute & X) : isLoop(X.isLoop), isVulnerability(X.isVulnerability) {}
18 };

20 class BugSeeding : public SgTopDownProcessing<InheritedAttribute>
    {
    public:
22         InheritedAttribute evaluateInheritedAttribute (
24             SgNode* astNode,
26             InheritedAttribute inheritedAttribute );
28
    InheritedAttribute
    BugSeeding::evaluateInheritedAttribute (
30         SgNode* astNode,
32         InheritedAttribute inheritedAttribute )
    {
34         // Use this if we only want to seed bugs in loops
        bool isLoop = inheritedAttribute.isLoop ||
            (isSgForStatement(astNode) != NULL) ||
36            (isSgWhileStmt(astNode) != NULL) ||
            (isSgDoWhileStmt(astNode) != NULL);
38         // Add Fortran support
        isLoop = isLoop || (isSgFortranDo(astNode) != NULL);
40
42         // Mark future nodes in this subtree as being part of a loop
        inheritedAttribute.isLoop = isLoop;

44         // To test this on simple codes, optionally allow it to be applied everywhere
        bool applyEveryWhere = true;

46         if (isLoop == true || applyEveryWhere == true)
            {
48             // The inherited attribute is true iff we are inside a loop and this is a SgPtrArrRefExp.
            SgPtrArrRefExp *arrayReference = isSgPtrArrRefExp(astNode);
            if (arrayReference != NULL)
            {
52                 // Mark as a vulnerability
                inheritedAttribute.isVulnerability = true;

54                 // Now change the array index (to seed the buffer overflow bug)
                SgVarRefExp* arrayVarRef = isSgVarRefExp(arrayReference->get_lhs_operand());
56                 ROSE_ASSERT(arrayVarRef != NULL);
                ROSE_ASSERT(arrayVarRef->get_symbol() != NULL);
                SgInitializedName* arrayName = isSgInitializedName(arrayVarRef->get_symbol()->get_declaration());
58                 ROSE_ASSERT(arrayName != NULL);
                SgArrayType* arrayType = isSgArrayType(arrayName->get_type());
                ROSE_ASSERT(arrayType != NULL);
                SgExpression* arraySize = arrayType->get_index();
60                 SgTreeCopy copyHelp;
                // Make a copy of the expression used to hold the array size in the array declaration.
                SgExpression* arraySizeCopy = isSgExpression(arraySize->copy(copyHelp));
                ROSE_ASSERT(arraySizeCopy != NULL);
62                 // This is the existing index expression
                SgExpression* indexExpression = arrayReference->get_rhs_operand();
                ROSE_ASSERT(indexExpression != NULL);
64                 // Build a new expression: "array[n]" --> "array[n+arraySizeCopy]", where the arraySizeCopy is a size of "array"
                SgExpression* newIndexExpression = buildAddOp(indexExpression, arraySizeCopy);
66                 // Substitute the new expression for the old expression
                arrayReference->set_rhs_operand(newIndexExpression);
68             }
69         }
70     }
71     return inheritedAttribute;
72 }
73
74 int
75 main (int argc, char *argv[])
76 {
77     SgProject *project = frontend (argc, argv);
78     ROSE_ASSERT (project != NULL);
79
80     SeedBugsArrayIndexing::BugSeeding treeTraversal;
81     SeedBugsArrayIndexing::InheritedAttribute inheritedAttribute;
82
83     treeTraversal.traverseInputFiles (project, inheritedAttribute);
84
85     // Running internal tests (optional)
86     AstTests::runAllTests (project);
87
88     // Output the new code seeded with a specific form of bug.
89     return backend (project);
90 }

```

Figure 36.2: Example source code showing how to seed bugs.

```
2  void foobar()  
3  {  
4  // Static array declaration  
5      float array[10UL];  
6      array[0 + 10UL] = (0);  
7      for (int i = 0; i < 5; i++) {  
8          array[i + 10UL] = (0);  
9      }  
10 }
```

Figure 36.3: Output of input code using seedBugsExample.arrayIndexing.C

Part VI

Binary Support

Tutorials of using ROSE to handle binary executable files.

Chapter 37

Instruction Semantics

The Instruction Semantics layer in ROSE can be used to “evaluate” instructions and is controlled by a policy that defines the details of what “evaluate” means. For instance, given the following “xor” instruction, the X86InstructionSemantics class specifies that the value of the “eax” and “edx” registers are read, those two 32-bit values are xor’d together, and the 32-bit result is then written to the “eax” register. The policy defines what a 32-bit value is (it could be an integer, some representation of a constant, etc), how it is read and written to the registers, and how to compute an xor.

```
xor eax, edx
```

ROSE has a collection instruction semantic classes, one for each architecture. It also has a small collection of policies. This chapter briefly describes a policy that tracks constant values.

37.1 The FindConstantsPolicy Class

The FindConstantsPolicy is used to track constant values across an instruction trace. The basic idea is that ROSE “executes” the instructions one at a time in the instruction semantics layer, identifies constants, performs operations on those constants, and assigns constants to registers and memory locations. Each constant also maintains information about which instructions led to that particular constant’s existence.

A “constant” is an abstract datum that has a known integer value, or a name corresponding to some unknown value, or a name and a known integer offset. Names take the form of the letter “v” (for “value”) followed by a unique integer. Known values are represented as signed hexadecimal values in the output.

The findConstants.C program in the tests/roseTests/binaryTests directory (which is described herein) takes each function and processes the instructions of that function in address order. It makes no attempt to follow branches or any other kind of control flow, but serves to demonstrate a simple way to track constants.

```
1 #define \_\_STDC_FORMAT_MACROS
2 #include "rose.h"
```

```

3  #include "findConstants.h"
4  #include <inttypes.h>
5
6  /* Returns the function name if known, or the address as a string otherwise. */
7  static std::string
8  name\_or\_addr(const SgAsmFunctionDeclaration *f)
9  {
10     if (f->get\_name()!="")
11         return f->get\_name();
12
13     char buf[128];
14     SgAsmBlock *first\_bb = isSgAsmBlock(f->get\_statementList().front());
15     sprintf(buf, "0x%"PRIx64, first\_bb->get\_id());
16     return buf;
17 }
18
19 class AnalyzeFunctions : public SgSimpleProcessing {
20 public:
21     AnalyzeFunctions(SgProject *project) {
22         traverse(project, postorder);
23     }
24     void visit(SgNode *node) {
25         SgAsmFunctionDeclaration *func = isSgAsmFunctionDeclaration(node);
26         if (func) {
27             std::cout <<"=====\n"
28                 <<"Constant propagation in function \"" <<name\_or\_addr(func) <<"\"\\n"
29                 <<"=====\n";
30             FindConstantsPolicy policy;
31             X86InstructionSemantics<FindConstantsPolicy, XVariablePtr> t(policy);
32             std::vector<SgNode*> instructions = NodeQuery::querySubTree(func, V\_SgAsmx86Instruc
33             for (size\_t i=0; i<instructions.size(); i++) {
34                 SgAsmx86Instruction *insn = isSgAsmx86Instruction(instructions[i]);
35                 ROSE\_ASSERT(insn);
36                 t.processInstruction(insn);
37                 RegisterSet rset = policy.currentRset;
38                 std::cout <<unparseInstructionWithAddress(insn) <<"\\n"
39                     <<rset;
40             }
41         }
42     }
43 };
44
45 int main(int argc, char *argv[]) {
46     AnalyzeFunctions(frontend(argc, argv));
47 }

```

Lines 30 through 40 are the main meat of the example. For each function, we construct a fresh policy. Since the policy holds the values of registers and memory, this resets them all to an initial state having unknown values. The instruction semantics engine depends on the policy, so we also create a new one for each function.

Then we loop over the instructions of the function in order of their addresses at lines 33 through 40. Each instruction is processed in turn by the `X86InstructionSemantics` object, adjusting the state of the associated policy.

Finally, the assembly language instruction is output followed by the values contained in the registers as a result of processing the instruction.

37.2 Sample Output

Here's some abbreviated output from running the “findConstants” test on a binary executable:

```

1  =====
2  Constant propagation in function "_init"
3  =====
4  0x80482c8:push    ebp
5      ax = v62
6      cx = v63
7      dx = v64
8      bx = v65
9      sp = v66-0x4 [from 0x80482c8:push    ebp]
10     bp = v67
11     si = v68
12     di = v69
13     es = v70
14     cs = v71
15     ss = v72
16     ds = v73
17     fs = v74
18     gs = v75
19     cf = v76
20     ?1 = v77
21     pf = v78
22     ?3 = v79
23     af = v80
24     ?5 = v81
25     zf = v82
26     sf = v83
27     tf = v84
28     if = v85
29     df = v86
30     of = v87
31     iopl0 = v88

```

```

32     iopl1 = v89
33     nt = v90
34     ?15 = v91
35     memory = {
36         size=4; addr=v66-0x4 [from 0x80482c8:push    ebp]; value=v67
37     }

```

Line 4 indicates that the instruction “push ebp” is located at address 0x80482c8 and the following lines show the contents of registers and known memory addresses following execution of the “push.” One can readily see that each register has a unique constant of unknown value by virtue of each constant having a unique name. The stack pointer register (sp) has the constant “v66-0x4” obtained from this very instruction. If we had printed the registers prior to executing the “push” we would have seen that the original sp constant was “v66”. Therefore, this “push” instruction reduced the value of sp by four.

Line 36 indicates that the four bytes beginning at memory address “v66-0x4” (which happens to be the constant stored in the stack pointer register at line 9) contain the value “v67” (which is the constant stored in the bp register at line 10).

Therefore, it can be determined that “push ebp” decrements the stack pointer by four bytes, then copies a 32-bit value from the bp register to the memory pointed to by the new stack pointer.

```

1  0x80482c9:mov    ebp, esp
2      ax = v62
3      cx = v63
4      dx = v64
5      bx = v65
6      sp = v66-0x4 [from 0x80482c8:push    ebp]
7      bp = v66-0x4 [from 0x80482c8:push    ebp]
8      si = v68
9      di = v69
10     es = v70
11     cs = v71
12     ss = v72
13     ds = v73
14     fs = v74
15     gs = v75
16     cf = v76
17     ?1 = v77
18     pf = v78
19     ?3 = v79
20     af = v80
21     ?5 = v81
22     zf = v82
23     sf = v83
24     tf = v84
25     if = v85

```

```

26     df = v86
27     of = v87
28     iopl0 = v88
29     iopl1 = v89
30     nt = v90
31     ?15 = v91
32     memory = {
33         size=4; addr=v66-0x4 [from 0x80482c8:push    ebp]; value=v67
34     }

```

The output after the “mov ebp, esp” instruction at address 0x80482c9 subsequent to the “push ebp” that we just saw, shows that the new stack pointer has been copied into the “bp” register and that nothing else has changed. A more interesting instruction follows...

```

1  0x80482cb:sub    esp, 0x8
2      ax = v62
3      cx = v63
4      dx = v64
5      bx = v65
6      sp = v66-0xc [from 0x80482cb:sub    esp, 0x8]
7      bp = v66-0x4 [from 0x80482c8:push    ebp]
8      si = v68
9      di = v69
10     es = v70
11     cs = v71
12     ss = v72
13     ds = v73
14     fs = v74
15     gs = v75
16     cf = -v193-0x1 [from 0x80482cb:sub    esp, 0x8]
17     ?1 = v77
18     pf = -v187-0x1 [from 0x80482cb:sub    esp, 0x8]
19     ?3 = v79
20     af = -v191-0x1 [from 0x80482cb:sub    esp, 0x8]
21     ?5 = v81
22     zf = v190 [from 0x80482cb:sub    esp, 0x8]
23     sf = v189 [from 0x80482cb:sub    esp, 0x8]
24     tf = v84
25     if = v85
26     df = v86
27     of = v197 [from 0x80482cb:sub    esp, 0x8]
28     iopl0 = v88
29     iopl1 = v89
30     nt = v90
31     ?15 = v91
32     memory = {

```

```

33         size=4; addr=v66-0x4 [from 0x80482c8:push    ebp]; value=v67
34     }

```

The “sub esp, 0x8” subtracts eight from the value of the stack pointer register and then stores the result in the stack pointer register. This can be seen by the fact that the constant stored in the “sp” register has changed from “v66-0x4” to “v66-0xc.” One can also see that various flags have been modified, although we don’t know the values of any of them.

```

1  0x80482ce:call    0x8048364
2      ax = v62
3      cx = v63
4      dx = v64
5      bx = v65
6      sp = v66-0x10 [from 0x80482ce:call    0x8048364]
7      bp = v66-0x4  [from 0x80482c8:push    ebp]
8      si = v68
9      di = v69
10     es = v70
11     cs = v71
12     ss = v72
13     ds = v73
14     fs = v74
15     gs = v75
16     cf = -v193-0x1 [from 0x80482cb:sub     esp, 0x8]
17     ?1 = v77
18     pf = -v187-0x1 [from 0x80482cb:sub     esp, 0x8]
19     ?3 = v79
20     af = -v191-0x1 [from 0x80482cb:sub     esp, 0x8]
21     ?5 = v81
22     zf = v190 [from 0x80482cb:sub     esp, 0x8]
23     sf = v189 [from 0x80482cb:sub     esp, 0x8]
24     tf = v84
25     if = v85
26     df = v86
27     of = v197 [from 0x80482cb:sub     esp, 0x8]
28     iopl0 = v88
29     iopl1 = v89
30     nt = v90
31     ?15 = v91
32     memory = {
33         size=4; addr=v66-0x10 [from 0x80482ce:call    0x8048364]; value=0x80482d3 [from 0x80482ce
34         size=4; addr=v66-0x4  [from 0x80482c8:push    ebp]; value=v67
35     }

```

Now we get to our first branch-type instruction, a “call” to a particular address. Instruction semantics describe what the call instruction does to the registers and memory, but does not actually execute a call or process the called instructions. That means that a “ret” was not

processed and thus we should see the return address sitting on the stack. In fact, we do: the stack pointer has been decremented by another four bytes and the memory address to which the stack pointer points contains the address of the instruction immediately after the “call”.

37.3 Building on Instruction Semantics

The X86InstructionSemantics class and the policy classes can be extended to handle special cases. For instance, the X86InstructionSemantics class processes the “rep stosd” instruction in such a way that only one iteration of the “stosd” is considered. Sometimes it’s more useful to process the entire repeated sequence in one step rather than iterating through the loop. Subclassing X86InstructionSemantics to override individual instructions or classes of instructions is simple. The subclass should redefine the “translate” method to do whatever is necessary for certain instructions while delegating to the superclass for all remaining instructions. For example:

```
/* Augments super::translate() to override rep\_stos instructions */
virtual void translate(SgAsmx86Instruction *insn) {
    switch (insn->get\_kind()) {
        case x86\_rep\_stosb: updateIP(insn); rep\_stos\_semantics<1>(insn); break;
        case x86\_rep\_stosw: updateIP(insn); rep\_stos\_semantics<2>(insn); break;
        case x86\_rep\_stosd: updateIP(insn); rep\_stos\_semantics<4>(insn); break;
        default: super::translate(insn); break;
    }
}
```

It’s also possible to subclass the policies. For instance, if you need to do something special for binary AND operations on the stack pointer you could override the “and_” method in the policy.

Chapter 38

Binary Analysis

This chapter discusses the capabilities of ROSE to read, analyze and transform (transformations to the binary file format) binary executables.

In the following sections we use a small example that demonstrates various features of Binary-Rose. The source code of our binary example is:

```
2  #include <stdlib.h>
3
4  int main(int argc, char** argv) {
5      int* arr = (int*) malloc( sizeof(int)*10);
6
7      int i=0;
8      for (i=0; i<10;++i) {
9          arr[i]=5;
10     }
11     int x = arr[12];
12 }
```

Figure 38.1: Example source code.

Much larger binaries can be analyzed, but such larger binary executables are more difficult to present (in this tutorial).

38.1 Loading binaries

Binary support in ROSE is currently based on two front-ends:

1. A custom build *ROSE Disassembler* (for ARM, x86, and PowerPC), and
2. *IdaPro-mysql*

38.1.1 ROSE Disassembler

The following code reads in a binary and creates a binary ROSE AST:

```
SgProject* project = frontend(argc,argv);
ROSE_ASSERT (project != NULL);
```

38.1.2 IdaPro-mysql

A binary processed by IdaPro needs to be processed into a MySQL database (DB). With that DB, the following lines create a binary ROSE AST:

```
// create RoseBin object with DB specific information
RoseBin* roseBin = new RoseBin(def_host_name,
                               def_user_name,
                               def_password,
                               def_db_name);

RoseBin_Arch::arch=RoseBin_Arch::bit32;
RoseBin_OS::os_sys=RoseBin_OS::linux_op;
RoseBin_OS_VER::os_ver=RoseBin_OS_VER::linux_26;
RoseBin_Def::RoseAssemblyLanguage=x86;
// connect to the DB
roseBin->connect_DB(socket);
// query the DB to retrieve all data
SgAsmNode* globalBlock = roseBin->retrieve_DB_IDAPRO();
// close the DB
roseBin->close_DB();

// traverse the AST and test it
roseBin->test();
```

38.2 The AST

The binary AST can now be unparsed to represent assembly instructions, cf. Figure 38.2:

```
SgAsmGenericFile* file = project->get_file(0).get_binaryFile();
RoseBin_unparse* unparser = new RoseBin_unparse();
unparser->init(file->get_global_block(), fileName);
unparser->unparse();
```

To visualize the binary AST, we can use the following lines to write the AST out to a .dot format:

```
string filename='_binary_tree.dot';
AST_BIN_Traversal* trav = new AST_BIN_Traversal();
trav->run(file->get_global_block(), filename);
```

38.3 The ControlFlowGraph

Based on a control flow traversal of the binary AST, a separate control flow graph is created that can be used for further analyses:

```
// forward or backward analysis ?
bool forward = true;
// when creating a visual representation, visualized edges?
bool edges = true;
// visualize multiple edges or merge edges between same nodes to one edge?
bool mergedEdges = false;
// create DotGraph Object or/and GmlGraph Object
RoseBin_DotGraph* dotGraph = new RoseBin_DotGraph();
RoseBin_GMLGraph* gmlGraph = new RoseBin_GMLGraph();
char* cfgFileNameDot = 'cfg.dot';
char* cfgFileNameGml = 'gml.dot';
RoseBin_ControlFlowAnalysis* cfanalysis = new RoseBin_ControlFlowAnalysis(
                                                file->get_global_block(), forward, NULL, edges);
cfanalysis->run(dotGraph, cfgFileNameDot, mergedEdges);
cfanalysis->run(gmlGraph, cfgFileNameGml, mergedEdges);
```

The control flow graph of our example is represented in Figure 38.3. The graph shows different functions represented purple, containing various instructions. Instructions within a function are represented within the same box. Common instructions are represented yellow. Green instructions are jumps and pink instructions calls and returns. Respectively, blue edges are call relationships and red edges return relationships. Black edges represent plain controlflow from one instruction to the next.

38.4 DataFlow Analysis

Based on the control flow many forms of dataflow analysis may be performed. The code to perform the dataflow analysis looks as follows:

```
string dfgFileName = "dfg.dot";
forward = true;
bool printEdges = true;
// choose between a interprocedural and intraprocedural dataflow analysis
bool interprocedural = true;
RoseBin_DataFlowAnalysis* dfanalysis = new RoseBin_DataFlowAnalysis(
    file->get_global_block(), forward, NULL);
dfanalysis->init(interprocedural, printEdges);
dfanalysis->run(dotGraph, dfgFileName, mergedEdges);
```

Dataflow analyses available are:

38.4.1 Def-Use Analysis

Definition-Usage is one way to compute dataflow information about a binary program. Figure 38.4 shows a typical dataflow graph with additional definition and usage information visualized at the edges.

38.4.2 Variable Analysis

This analysis helps to detect different types within a binary. Currently, we use this analysis to detect interrupt calls and their parameters together with the def-use analysis.

This allows us to track back the value of parameters to the calls, such as `eax` and therefore determine whether a interrupt call is for instance a write or read.

Another feature is the buffer overflow analysis. By traversing the CFG, we can detect buffer overflows. The black node in 38.4 shows such a buffer overflow, cf. source code above.

38.5 Dynamic Analysis

Recent work in ROSE has added support for dynamic analysis and for mixing of dynamic and static analysis using the Intel Pin framework. This optional support in ROSE requires a configure option (`--with-IntelPin=<path>`). The `path` in the configure option is the **absolute path** to the top level directory of the location of the Intel Pin distribution. This support for Intel Pin has only been tested on a 64bit Linux system using the most recent distribution of Intel Pin (version 2.6).

Note: The dwarf support in ROSE is currently incompatible with the dwarf support in Intel Pin. A message in the configuration of ROSE will detect if both support for Dwarf and Intel Pin are both specified and exit with an error message that they are incompatible options.

See `tutorial/intelPin` directory for examples using static and dynamic analysis. These example will be improved in the future, at the moment they just call the generation of the binary AST.

Note: We have added a fix to Intel Pin `pin.H` file:

```
// DQ (3/9/2009): Avoid letting "using" declarations into header files.
#ifndef REQUIRE_PIN_TO_USE_NAMESPACES
using namespace LEVEL_PINCLIENT;
#endif
```

so that the namespace of Intel Pin would not be a problem for ROSE. The development team have suggested that they may fix their use of "using" declarations for namespaces in their header files.

Also note that the path must be absolute since it will be the prefix for the **pin** executable to be run in the internal tests and anything else might be a problem if the path does not contain the current directory ("."). Or, perhaps we should test for this in the future.

Note 2: Linking to `libdwarf.a` is a special problem. Both ROSE and Intel Pin use `libdwarf.a` and both build shared libraries that link to the static version of the library (`libdwarf.a`). This is a problem in building Pin Tools since both the PinTool and `librose.so` will use a statically linked dwarf library (internally). This causes the first use of dwarf to fail, because there are then two versions of the same library in place. The solution is to force at most one static version of the library and let the other one be a shared library.

Alternatively both the Pin tool and `librose.so` can be built using the shared version of dwarf (`libdwarf.so`). There is a makefile rule in `libdwarf` to build the shared version of the library, but the default is to only build the static library (`libdwarf.a`), so use `make make libdwarf.so` to build the shared library. So we allow ROSE to link to the `libdwarf.a` (statically), which is how ROSE has always worked (this may be revisited in the future). And we force the Pin tool to link using the shared dwarf library (`libdwarf.so`). *Note: The specification of the location of `libdwarf.so` in the Intel Pin directory structure is problematic using `rpath`, so for the case of using the Intel Pin package with ROSE please set the `LD_LIBRARY_PATH` explicitly (a better solution using `rpath` may be made available in the future).*

```

/* Interpretation ELF */
2  /* Block 0x0 */
   /* Function _init at 0x8048278 */
4  /* Block 0x8048278 */
   0x08048278 55          |U      | :: 0x8048278:push    ebp _____ /*
   /*
6  0x08048279 89 e5      |..     | :: 0x8048279:mov     ebp, esp _____ /*
   /*
   0x0804827b 83 ec 08    |...    | :: 0x804827b:sub     esp, 0x8 _____ /*
   /*
8  0x0804827e e8 61 00 00 00 |.a...  | :: 0x804827e:call    0x80482e4 <call_gmon_start>
   /* Block 0x8048283 */
10 0x08048283 e8 b8 00 00 00 |..... | :: 0x8048283:call    0x8048340 <frame_dummy>
   /* Block 0x8048288 */
12 0x08048288 e8 d3 01 00 00 |..... | :: 0x8048288:call    0x8048460 <__do_global_ctors_aux>
   /* Block 0x804828d */
14 0x0804828d c9          |.      | :: 0x804828d:leave   _____ /*
   /*
   0x0804828e c3          |.      | :: 0x804828e:ret     _____ /*
   /*
16 /* Block 0x804828f */
   0x0804828f 00 ff      |..     | :: 0x804828f:add     bh, bh _____ /*
   /*
18 0x08048291 35 a0 95 04 08 |5....  | :: 0x8048291:xor     eax, 0x80495a0 _____ /*
   /*
   0x08048296 ff 25 a4 95 04 08 |.%.... | :: 0x8048296:jmp     DWORD PTR ds:[0x80495a4] _____ /*
   /*
20 /* Function 8048290 at 0x8048290 */
   /* Block 0x8048290 */
22 0x08048290 ff 35 a0 95 04 08 |.5.... | :: 0x8048290:push    DWORD PTR ds:[0x80495a0] _____ /*
   /*
   /* Block 0x804829c */
24 0x0804829c 00 00      |..     | :: 0x804829c:add     BYTE PTR ds:[eax], al _____ /*
   /*
   0x0804829e 00 00      |..     | :: 0x804829e:add     BYTE PTR ds:[eax], al _____ /*
   /*
26 /* Function malloc at 0x80482a0 */
   /* Block 0x80482a0 */
28 0x080482a0 ff 25 a8 95 04 08 |.%.... | :: 0x80482a0:jmp     DWORD PTR ds:[0x80495a8] _____ /*
   /*
   /* Block 0x80482a6 */
30 0x080482a6 68 00 00 00 00 |h....  | :: 0x80482a6:push    0x0 _____ /*
   /*
   0x080482ab e9 e0 ff ff ff |..... | :: 0x80482ab:jmp     0x8048290 _____ /*
   /*
32 /* Function _libc_start_main at 0x80482b0 */
   /* Block 0x80482b0 */
34 0x080482b0 ff 25 ac 95 04 08 |.%.... | :: 0x80482b0:jmp     DWORD PTR ds:[0x80495ac] _____ /*
   /*
   /* Block 0x80482b6 */
36 0x080482b6 68 08 00 00 00 |h....  | :: 0x80482b6:push    0x8 _____ /*
   /*
   0x080482bb e9 d0 ff ff ff |..... | :: 0x80482bb:jmp     0x8048290 _____ /*
   /*
38 /* Function _start at 0x80482c0 */
   /* Block 0x80482c0 */
40 0x080482c0 31 ed      |1.     | :: 0x80482c0:xor     ebp, ebp _____ /*
   /*
   0x080482c2 5e          |^      | :: 0x80482c2:pop     esi _____ /*
   /*
42 0x080482c3 89 e1      |..     | :: 0x80482c3:mov     ecx, esp _____ /*
   /*

```

Figure 38.2: Assembly code.

Figure 38.3: Controlflow graph for example program.

Figure 38.4: Dataflowflow graph for example program.

Chapter 39

Binary Construction

ROSE is normally used in such a way that a file (source code or binary) is parsed to construct an AST, then operations are performed on the AST, and the modified AST is unparsed to create a new source or binary file. However, it is also possible to construct an AST explicitly without parsing and then use that AST to generate the output. The AST construction interface for binary files was designed so that working files could be created simply, while still providing methods to control the finer details of the resulting file.

The example in this chapter shows how to construct a statically linked ELF executable containing a small “.text” section that simply causes the process to exit with a specific non-zero value.

39.1 Constructors

The AST node constructors are designed to construct the tree from the root down, and thus generally take the parent node as an argument. Nodes that refer to other nodes as prerequisites also take those prerequisites as arguments. For instance, an ELF Relocation Section is a child of the ELF File Header but also needs an ELF Symbol Table and therefore takes both objects as constructor arguments.

39.2 Read-Only Data Members

When two or more file formats have a similar notion then that notion is represented in a base class. However, part of the information may continue to survive in the specialized class. In these situations modifications to the specialized data will probably be overridden by the generic values from the base class. For instance, all formats have a notion of byte order which is represented in the base class `SgAsmGenericHeader` as little- or big-endian (an enumeration constant). The ELF specification provides an 8-bit unsigned field to store the byte order and therefore has potentially more than two possibilities. Any value assigned to the ELF-specific byte order will likely be overwritten by the generic byte order before the AST is unparsed.

A similar situation arises with section offsets, sizes, memory mappings, permissions, etc. The `SgAsmGenericSection` class represents ELF Sections, ELF Segments, PE Objects, and other

39.5 Constructing the ELF Segment Table

ELF executable files always have an ELF Segment Table (also called the ELF Program Header Table), which usually appears immediately after the ELF File Header. The ELF Segment Table describes contiguous regions of the file that should be memory mapped by the loader. ELF Segments don't have names—names are imparted to the segment by virtue of the segment also being described by the ELF Section Table, which we'll create later.

Being a contiguous region of the file, an ELF Segment Table (`SgAsmElfSegmentTable`) is derived from `SgAsmGenericSection`. All non-header sections have a header as a parent, which we supply as an argument to the constructor. Since all ELF Segments will be children of the ELF File Header rather than children of the ELF Segment Table, we could define the ELF Segment Table at the end rather than here. But defining it now is an easy way to get it located in its usual location immediately after the ELF File Header.

```
SgAsmElfSegmentTable *segtab = new SgAsmElfSegmentTable(fhdr);
```

39.6 Constructing the .text Section

ROSE doesn't treat a ".text" section as being anything particularly special—it's just a regular `SgAsmElfSection`, which derives from `SgAsmGenericSection`. However, in this example, we want to make sure that our ".text" section gets initialized with some instructions. The easiest way to do that is to specialize `SgAsmElfSection` and override or augment a few of the virtual functions.

We need to override two functions. First, the `calculate_sizes()` function should return the size we need to store the instructions. We'll treat the instructions as an array of entries each entry being one byte of the instruction stream. In other words, each "entry" is one byte in length consisting of one required byte and no optional bytes.

We need to also override the `unparse()` method since the base class will just fill the ".text" section with zeros. The `SgAsmGenericSection::write` method we use will write the instructions starting at the first byte of the section.

Finally, we need to augment the `reallocate()` method. This method is responsible for allocating space in the file for the section and performing any other necessary pre-unparsing actions. We don't need to allocate space since the base class's method will take care of that in conjunction with our version of `calculate_sizes()`, but we do need to set a special ELF flag (`SHF_ALLOC`) in the ELF Segment Table entry for this section. There's a few ways to accomplish this. We do it this way because the ELF Section Table Entry is not created until later and we want to demonstrate how to keep all .text-related code in close proximity.

```
class TextSection : public SgAsmElfSection {
public:
    TextSection(SgAsmElfFileHeader *fhdr, size_t ins_size, const unsigned char *ins_bytes)
    : SgAsmElfSection(fhdr), ins_size(ins_size), ins_bytes(ins_bytes)
    {}

    virtual rose_addr_t calculate_sizes(size_t *entsize, size_t *required, size_t *optional, size_t *entcount)
    {
        if (entsize) *entsize = 1; /* an "entry" is one byte of instruction */
        if (required) *required = 1; /* each "entry" is also stored in one byte of the file */
        if (optional) *optional = 0; /* there is no extra data per instruction byte */
    }
};
```

```

if (entcount) *entcount = ins_size;          /* number of "entries" is the total instruction
return ins_size;                             /* return value is section size required */
    }
    virtual bool reallocate() {
bool retval = SgAsmElfSection::reallocate();    /* returns true if size or position of any secti
SgAsmElfSectionTableEntry *ste = get_section_entry();
ste->set_sh_flags(ste->get_sh_flags() | 0x02); /* set the SHF_ALLOC bit */
return retval;
    }
    virtual void unparse(std::ostream &f) const {
write(f, 0, ins_size, ins_bytes);              /* Write the instructions at offset zero in sect
    }
    size_t ins_size;
    const unsigned char *ins_bytes;
};

```

The section constructors and reallocators don't worry about alignment issues—they always allocate from the next available byte. However, instructions typically need to satisfy some alignment constraints. We can easily adjust the file offset chosen by the constructor, but we also need to tell the reallocator about the alignment constraint. Even if we didn't ever resize the ".text" section the reallocator could be called for some other section in such a way that it needs to move the ".text" section to a new file offset.

For the purpose of this tutorial we want to be very picky about the location of the ELF Segment Table. We want it to immediately follow the ELF File Header without any intervening bytes of padding. At the current time, the ELF File Header has a size of one byte and will eventually be reallocated. When we reallocate the header the subsequent sections will need to be shifted to higher file offsets. When this happens, the allocator shifts them all by the same amount taking care to satisfy all alignment constraints, which means that an alignment constraint of byte bytes on the ".text" section will induce a similar alignment on the ELF Segment Table. Since we don't want that, the best practice is to call `reallocate()` now, before we create the ".text" section.

```

ef->reallocate();                             /* Give existing sections a chance to al
static const unsigned char instructions[] = {0xb8, 0x01, 0x00, 0x00, 0x00, 0xbb, 0x56, 0x00, 0x00, 0
SgAsmElfSection *text = new TextSection(fhdr, NELMTS(instructions), instructions);
text->set_purpose(SgAsmGenericSection::SP_PROGRAM);    /* Program-supplied text/data/etc. */
text->set_offset(ALIGN_UP(text->get_offset(), 4));    /* Align on an 8-byte boundary */
text->set_file_alignment(4);                        /* Tell reallocator about alignment cons
text->set_mapped_alignment(4);                      /* Alignment constraint for memory mappi
text->set_mapped_rva(base_va+text->get_offset());    /* Mapped address is based on file offse
text->set_mapped_size(text->get_size());             /* Mapped size is same as file size */
text->set_mapped_rperm(true);                       /* Readable */
text->set_mapped_wperm(false);                      /* Not writable */
text->set_mapped_xperm(true);                       /* Executable */

```

At this point the text section doesn't have a name. We want to name it ".text" and we want those characters to eventually be stored in the ELF file in a string table which we'll

provide later. In ELF, section names are represented by the section's entry in the ELF Section Table as an offset into an ELF String Table for a NUL-terminated ASCII string. ROSE manages strings using the `SgAsmGenericString` class, which has two subclasses: one for strings that aren't stored in the executable file (`SgAsmBasicString`) and one for strings that are stored in the file (`SgAsmStoredString`). Both are capable of string an `std::string` value and querying its byte offset (although `SgAsmBasicString::get_offset()` will always return `SgAsmGenericString::unallocated`). Since we haven't added the ".text" section to the ELF Section Table yet the new section has an `SgAsmBasicString` name. We can assign a string to the name now and the string will be allocated in the ELF file when we've provided further information.

```
text->get_name()->set_string(".text");
```

The ELF File Header needs to know the virtual address at which to start running the program. In ROSE, virtual addresses can be attached to a specific section so that if the section is ever moved the address is automatically updated. Some formats allow more than one entry address which is why the method is called `add_entry_rva()` rather than `set_entry_rva()`. ELF, however, only allows one entry address.

```
rose_rva_t entry_rva(text->get_mapped_rva(), text);
fhdr->add_entry_rva(entry_rva);
```

39.7 Constructing a LOAD Segment

ELF Segments define parts of an executable file that should be mapped into memory by the loader. A program will typically have a LOAD segment that begins at the first byte of the file and continues through the last instruction (in our case, the end of the ".text" section) and which is mapped to virtual address 0x400000.

We've already created the ELF Segment Table, so all we need to do now is create an ELF Segment and add it to the ELF Segment Table. ELF Segments, like ELF Sections, are represented by `SgAsmElfSection`. An `SgAsmElfSection` is an ELF Section if it has an entry in the ELF Section Table, and/or it's an ELF Segment if it has an entry in the ELF Segment Table. The methods `get_section_entry()` and `get_segment_entry()` retrieve the actual entries in those tables.

Recall that the constructor creates new sections located at the current end-of-file and containing one byte. Our LOAD segment needs to have a different offset and size.

```
SgAsmElfSection *seg1 = new SgAsmElfSection(fhdr);
seg1->get_name()->set_string("LOAD");
seg1->set_offset(0);
seg1->set_size(text->get_offset() + text->get_size());
seg1->set_mapped_rva(base_va);
seg1->set_mapped_size(seg1->get_size());
seg1->set_mapped_rperm(true);
seg1->set_mapped_wperm(false);
seg1->set_mapped_xperm(true);
segtab->add_section(seg1);
```

```
/* ELF Segments are represented by SgAsmElfSection
/* Segment names aren't saved (but useful for debug
/* Starts at beginning of file */
/* Extends to end of .text section */
/* Typically mapped by loader to this memory address
/* Make mapped size match size in the file */
/* Readable */
/* Not writable */
/* Executable */
/* Add definition to ELF Segment Table */
```

39.8 Constructing a PAX Segment

This documentation shows how to construct a generic ELF Segment, giving it a particular file offset and size. ELF Segments don't have names stored in the file, but we can assign a name to the AST node to aid in debugging—it just won't be written out. When parsing an ELF file, segment names are generated based on the type stored in the entry of the ELF Segment Table. For a PAX segment we want this type to be PT_PAX_FLAGS (the default is PT_LOAD).

```
SgAsmElfSection *pax = new SgAsmElfSection(fhdr);
pax->get_name()->set_string("PAX Flags");           /* Name just for debugging */
pax->set_offset(0);                                  /* Override address to be at zero rather
pax->set_size(0);                                    /* Override size to be zero rather than
segtab->add_section(pax);                            /* Add definition to ELF Segment Table */
pax->get_segment_entry()->set_type(SgAsmElfSegmentTableEntry::PT_PAX_FLAGS);
```

39.9 Constructing a String Table

An ELF String Table always corresponds to a single ELF Section of class SgAsmElfStringSection and thus you'll often see the term "ELF String Section" used interchangeably with "ELF String Table" even though they're two unique but closely tied classes internally.

When the ELF String Section is created a corresponding ELF String Table is also created under the covers. Since string tables manage their own memory in response to the strings they contain, one should never adjust the size of the ELF String Section (it's actually fine to enlarge the section and the new space will become free space in the string table).

ELF files typically have multiple string tables so that section names are in a different section than symbol names, etc. In this tutorial we'll create the section names string table, typically called ".shstrtab", but use it for all string storage.

```
SgAsmElfStringSection *shstrtab = new SgAsmElfStringSection(fhdr);
shstrtab->get_name()->set_string(".shstrtab");
```

39.10 Constructing an ELF Section Table

We do this last because we want the ELF Section Table to appear at the end of the file and this is the easiest way to achieve that. There's really not much one needs to do to create the ELF Section Table other than provide the ELF File Header as a parent and supply a string table.

The string table we created above isn't activated until we assign it to the ELF Section Table. The first SgAsmElfStringSection added to the SgAsmElfSectionTable becomes the string table for storing section names. It is permissible to add other sections to the table before adding the string table.

```
SgAsmElfSectionTable *sectab = new SgAsmElfSectionTable(fhdr);
sectab->add_section(text);                          /* Add the .text section */
sectab->add_section(shstrtab);                       /* Add the string table to store section
```


39.11 Allocating Space

Prior to calling `unparse()`, we need to make sure that all sections have a chance to allocate space for themselves, and perform any other operations necessary. It's not always possible to determine sizes at an earlier time, and most constructors would have declared sizes of only one byte.

The `reallocate()` method is defined in the `SgAsmGenericFile` class since it operates over the entire collection of sections simultaneously. In other words, if a section needs to grow then all the sections located after it in the file need to be shifted to higher file offsets.

```
ef->reallocate();
```

The `reallocate()` method has a shortcoming (as of 2008-12-19) in that it might not correctly update memory mappings in the case when the mapping for a section is inferred from the mapping of a containing segment. This can happen in our example since the ".text" section's memory mapping is a function of the LOAD Segment mapping. The work-around is to adjust mappings for these situations and then call `reallocate()` one final time. This final `reallocate()` call won't move any sections, but should always be the last thing to call before `unparsing()` (it gives sections a chance to update data dependencies which is not possible during `unparse()` due to its const nature).

```
text->set_mapped_rva(seg1->get_mapped_rva()+(text->get_offset()-seg1->get_offset()));
ef->reallocate(); /*won't resize or move things this time since we didn't modify much since the last call to r
```

39.12 Produce a Debugging Dump

A debugging dump can be made with the following code. This dump will not be identical to the one produced by parsing and dumping the resulting file since we never parsed a file (a dump contains some information that's parser-specific).

```
ef->dump(stdout);
SgAsmGenericSectionPtrList all = ef->get_sections(true);
for (size_t i=0; i<all.size(); i++) {
    fprintf(stdout, "Section %zu:\n", i);
    all[i]->dump(stdout, "    ", -1);
}
```

39.13 Produce the Executable File

The executable file is produced by unparsing the AST.

```
std::ofstream f("a.out");
ef->unparse(f);
```

Note that the resulting file will not be created with execute permission—that must be added manually.

Chapter 40

Dwarf Debug Support

DWARF is a widely used, standardized debugging data format. DWARF was originally designed along with ELF, although it is independent of object file formats. The name is a pun on "ELF" that has no official meaning but "may be an acronym for 'Debug With Attributed Record Format'". See Wikipedia for more information about the Dwarf debug format.

This chapter presents the support in ROSE for Dwarf 3 debug information; its representation in the AST and its use in binary analysis tools. This work is part of general work to support as much information as possible about binaries.

In the following sections we use a small example (see figure 40.1) that demonstrates various features of Dwarf. The source code of our binary example is:

```
2  // Test code to demonstration of dwarf support.
2  // Designed to be small because Dwarf is verbose.
4  namespace example_namespace
5  {
6      int a;
7  };
8
10 int main()
11 {
12     int x = 42;
13
14     // Loops are not recognised in Dwarf...
14     for (int i = 0; i < 10; i++)
16     {
16         x = (x % 2) ? x * 2 : x + 1;
18     }
20     return 0;
21 }
```

Figure 40.1: Example source code used to generate Dwarf AST for analysis.

Much larger binaries can be analyzed, but such larger binary executables are more difficult to present (in this tutorial).

40.1 ROSE AST of Dwarf IR nodes

ROSE tools process the binary into an AST that is used to represent all the information in the binary executable. Figure 40.2 shows the subset of that AST (which includes the rest of the binary file format and the disassembled instructions) that is specific to Dwarf. A command line option (`-rose:visualize_dwarf_only`) is used to restrict the generated dot file visualization to just the Dwarf information. This option is used in combination with `-rose:read_executable_file_format_only` to process only the binary file format (thus skipping the instruction disassembly).

40.2 Source Position to Instruction Address Mapping

One of the valuable parts of Dwarf is the mapping between the source lines and the instruction addresses at a statement level (provided in the `.debug_line` section). Even though Dwarf does not represent all statements in the source code, the mapping is significantly finer granularity than that provided at only the function level by the symbol table (which identifies the functions by instruction address, but not the source file line numbers; the later requires source code analysis).

The example code in 40.3 shows the mapping between the source code lines and the instruction addresses.

KME: This need to be
o correctly return sets
nd sets of addresses in
be a second interface.

Output from the compilation of this test code and running it with the example input results in the output shown in figure 40.4. This output shows the binary executables instruction address range (binary compiled on Linux x86 system), the range of lines of source code used by the binary executable, the mapping of a source code range of line numbers to the instruction addresses, and the mapping of a range of instruction addresses to the source code line numbers.




Figure 40.2: Dwarf AST (subset of ROSE binary AST).

```

#include "rose.h"
2
int
4 main(int argc, char** argv)
{
    SgProject* project = frontend(argc, argv);
    ROSE_ASSERT (project != NULL);
    8
    // This is controlled by using the --with-dwarf configure command line option.
    10 #if USE_ROSE_DWARF_SUPPORT
    12     // The input file is the binary file...
    int binary_file_id = project->get_file_list()[0]->get_file_info()->get_file_id();
    14
    // Increment to get the next file id (for the source file, instead of the binary file)
    16 int source_file_id = binary_file_id + 1;

    std::string binaryFilename = Sg_File_Info::getFilenameFromID(binary_file_id);
    printf ("file_id=%d binaryFilename=%s\n", binary_file_id, binaryFilename.c_str());
    20
    std::string sourceFilename = Sg_File_Info::getFilenameFromID(source_file_id);
    22 printf ("file_id=%d sourceFilename=%s\n", source_file_id, sourceFilename.c_str());

    24 // Compute the source line range from the instructions in the binary executable
    std::pair<LineColumnFilePosition, LineColumnFilePosition> sourceFileRange;
    26 sourceFileRange = SgAsmDwarfLineList::sourceCodeRange( source_file_id );

    28 printf ("\nSource_file_line_number_range_for:\n--file=%s(id=%d)\n--[(line=%d,col=%d),(line=%d,
        sourceFilename.c_str(), source_file_id,
    30 sourceFileRange.first.first, sourceFileRange.first.second,
        sourceFileRange.second.first, sourceFileRange.second.second);
    32

    // Compute the binary executable instruction address range
    34 std::pair<uint64_t, uint64_t> addressRange = SgAsmDwarfLineList::instructionRange();
    printf ("\nBinary_instruction_address_range=(0x%lx, 0x%lx)\n", addressRange.first, addressRange.second);
    36

    int minLine = sourceFileRange.first.first;
    38 int maxLine = sourceFileRange.second.first;
    int columnNumber = -1;
    40

    printf ("\nInstruction_addresses_computed_from_source_positions:\n");
    42 // Iterate over line numbers to map back to instruction addresses
    for (int lineNumber = minLine - 2; lineNumber <= maxLine + 2; lineNumber++)
    44 {
        // Out of range values generate the next address or NULL.
        46 FileIdLineColumnFilePosition s(source_file_id, std::pair<int, int>(lineNumber, columnNumber));
        uint64_t instructionAddress = SgAsmDwarfLineList::sourceCodeToAddress(s);
        48 printf ("---sourceCodeToAddress(%d,%d,%d)=0x%lx\n", s.first, s.second.first, s.second.second, instruc
    }

    50 uint64_t minInstructionAddress = addressRange.first;
    52

    // Iterate over the addresses of the binary and compute the source code line numbers (limit the range so the
    54 printf ("\nSource_lines_computed_from_address_range(truncated_to_keep_output_short):\n");
    for (uint64_t address = minInstructionAddress - 1; address < minInstructionAddress + 25; address++)
    56 {
        FileIdLineColumnFilePosition s_map = SgAsmDwarfLineList::addressToSourceCode(address);
        58 printf ("---addressToSourceCode:address=0x%lx=(%d,%d,%d)\n", address, s_map.first, s_map.second.first, s_map.second.second);
    }

    60 #else
    printf ("\nROSE must be configured with --with-dwarf=<path to libdwarf> to use Dwarf support.\n\n");
    62 #endif

    64 printf ("\nProgram_Terminated_Normally!\n\n");

    66 // Skip call to backend since this is just an analysis.
    return backend(project);
    68 }

```

Figure 40.3: Example source code (typical for reading in a binary or source file).

```
2 ROSE must be configured with --with-dwarf=<path to libdwarf> to use Dwarf support.
4
6 Program Terminated Normally!
```

Figure 40.4: Example source code (typical for reading in a binary or source file).

Part VII

Interacting with Other Tools

How to build interoperable tools using ROSE.

Chapter 41

Abstract Handles to Language Constructs

This chapter describes a reference design and its corresponding implementation for supporting abstract handles to language constructs in source code and optimization phases. It can be used to facilitate the interoperability between compilers and tools. We define an abstract handle as a representation for a unique language construct in a specific program. Interoperability between tools is achieved by writing out the abstract handles as strings and reading them within other tools to build the equivalent abstract handle.¹

The idea is to define identifiers for unique statements, loops, functions, and other language constructs in source code. Given the diverse user requirements, an ideal specification should include multiple forms to specify a language construct.

Currently, we are interested in the following forms for specifying language constructs:

- Source file position information including path, filename, line and column number etc. GNU standard source position from http://www.gnu.org/prep/standards/html_node/Errors.html presents some examples.
- Global or local numbering of specified language construct in source file (e.g. 2nd "do" loop in a global scope). The file is itself specified using an abstract handle (typically generated from the file name).
- Global or local names of constructs. Some language constructs, such as files, function definitions and namespace, have names which can be used as their handle within a context.
- Language-specific label mechanisms. These include named constructs in Fortran, numbered labels in Fortran, and statement labels in C and C++, etc.

¹Abstract Handles are not appropriate for program analysis since they are not intended to be used to capture the full structure of a program. Instead, Abstract Handles represent references to language constructs in a program, capturing only a program's local structure; intended to support interoperability between source based tools (including compilers). We don't advise the use of abstract handles in an aggressive way to construct an alternative intermediate representation (IR) for a full program.

In addition to human-readable forms, compilers and tools can generate internal IDs for language constructs. It is up to compiler/tool developers to provide a way to convert their internal representations into human-readable formats.

Abstract Handles can have any of the human-readable or machine-generated forms. A handle can be used alone or combined with other handles to specify a language construct. A handle can also be converted from one form to another (e.g. from a compiler specific form to an human readable form relative to the source position; filename, line number, etc.). Abstract handles can have different lifetimes depending on their use and implementation. An abstract handle might be required to be persistent if it is used to reference a language construct that would be optimized over multiple executions of one or more different tools. Where as an abstract-handle might be internally generated only for purposes of optimizations used in a single execution (e.g. optimization within a compiler).

41.1 Use Case

A typical use can for Abstract Handles might be for a performance tool to identify a collection of loops in functions that are computationally intensive and to construct Abstract Handles that refer to this specific loops. Then pass the Abstract Handles to a second tool that might analyze the source code and/or the binary executable to evaluate if the computational costs are reasonable or if optimizations might be possible. The specific goal of the Abstract Handles is to support these sorts of uses within autotuning using diverse tools used and/or developed as part of autotuning research within the DOE SciDAC PERI project.

41.2 Syntax

A possible grammar for abstract handles could be:

```
/* a handle is a single handle item or a link of them separated by ::, or
other delimiters */
handle ::= handle_item | handle '::' handle_item

/* Each handle item consists of construct_type and a specifier.
Or it can be a compiler generated id of any forms. */

handle_item ::= construct_type specifier | compiler_generated_handle

/*
Construct types are implementation dependent.
An implementation can support a subset of legal constructs or all of them.
We define a minimum set of common construct type names here and
will grow this list as needed.
*/
construct_type ::= Project|SourceFile|FunctionDeclaration|ForStatement|...

/* A specifier is used to locate a particular construct
```

```

    e.g: <name, "foo">
*/

specifier ::= '<' specifier_type ',' specifier_value '>'

/* tokens for specifier types could be name, position, numbering, label, etc.
specifier type is necessary to avoid ambiguity for specifier values,
because a same value could be interpreted in different specifier types otherwise
*/

specifier_type ::= name | position | numbering | label

/* Possible values for a specifier */

specifier_value ::= string_lit | int_lit | position_value | label_value

/*A label could be either integer or string */
label_value ::= int_lit | string_lit

/* Start and end source line and column information
e.g.: 13.5-55.4, 13, 13.5 , 13.5-55 */
position_value ::= line_number[ '.' column_number ][ '-' line_number[ '.' column_number ] ]

/* Integer value: one or more digits */
int_lit ::= [0-9]+

/* String value: start with a letter, followed by zero or more letters or digits */
string_lit ::= [a-z][a-z0-9]*

```

41.3 Examples

We give some examples of language handles using the syntax mentioned above. Canonical AST's node type names are used as the construct type names. Other implementations can use their own construct type names.

- A file handle consisting of only one handle item:

```
SourceFile<name, "/home/PERI/test111.f">
```

- A function handle using a named handle item, combined with a parent handle using a name also:

```
SourceFile<name, "/home/PERI/test111.f">::FunctionDeclaration<name, "foo">
```

- A function handle using source position (A function starting at line 12, column 1 till line 30, column 1 within a file):

```
SourceFile<name, "/home/PERI/test111.f">::FunctionDeclaration<position, "12.1-30.1">
```

- A function handle using numbering (The first function definition in a file):

```
SourceFile<name, "/home/PERI/test111.f">::FunctionDeclaration<numbering, 1>
```

- A return statement using source position (A return statement at line 100):

```
SourceFile<name, "/home/PERI/test222.c">::ReturnStatement<position, "100">
```

- A loop using numbering information (The second loop in function main()):

```
SourceFile<name, "/home/PERI/test222.c">::FunctionDeclaration<name, "main">::  
ForStatement<numbering, 2>
```

- A nested loop using numbering information (The first loop inside the second loop in function main()):

```
SourceFile<name, "/home/PERI/test222.c">::FunctionDeclaration<name, "main">::  
ForStatement<numbering, 2>::ForStatement<numbering, 1>
```

41.4 Reference Implementation

Abstract Handles are fundamentally compiler and tool independent, however to clarify the concepts, provide meaningful examples, a working reference implementation we have provided a reference implementation in ROSE. The source files are located in *src/midend/abstractHandle* in the ROSE distribution. A generic interface (*abstract_handle.h* and *abstract_handle.cpp*) provides data structures and operations for manipulating abstract handles using source file positions, numbering, or names. Any compilers and tools can have their own implementations using the same interface.

41.4.1 Connecting to ROSE

A ROSE adapter (*roseAdapter.h* and *roseAdapter.cpp*) using the interface is provided as a concrete implementation for the maximum capability of the implementation (within a source-to-source compiler). Figure 41.1 shows the code (using ROSE) to generate abstract handles for loops in an input source file (as in Figure 41.2). Abstract handle constructors generate handles from abstract nodes, which are implemented using ROSE AST nodes. Source position is used by default to generate a handle item. Names or numbering are used instead when source position information is not available. The Constructor can also be used to generate a handle item using a specified handle type (numbering handles in the example). Figure 41.3 is the output showing the generated handles for the loops.

```

2  /*
   Example code to generate abstract handles for language constructs
4  by Liao, 10/6/2008
   */
6  #include "rose.h"
   #include <iostream>
8  #include "abstract_handle.h"
   #include "roseAdapter.h"
10 #include <string.h>

12 using namespace std;
   using namespace AbstractHandle;
14
   // a global handle for the current file
16 static abstract_handle* file_handle = NULL;

18 class visitorTraversal : public AstSimpleProcessing
   {
20     protected:
         virtual void visit(SgNode* n);
22     };

24 void visitorTraversal::visit(SgNode* n)
   {
26     SgForStatement* forloop = isSgForStatement(n);

28     if (forloop)
       {
30         cout<<"Creating_handles_for_a_loop_construct..."<<endl;
           //Create an abstract node
32         abstract_node* anode= buildroseNode(forloop);

34         //Create an abstract handle from the abstract node
           //Using source position specifiers by default
36         abstract_handle * ahandle = new abstract_handle(anode);
           cout<<ahandle->toString()<<endl;

38         // Create handles based on numbering specifiers within the file
40         abstract_handle * bhandle = new abstract_handle(anode,e_numbering,file_handle);
           cout<<bhandle->toString()<<endl<<endl;
42     }
   }

44 int main(int argc, char * argv[])
   {
46     SgProject *project = frontend (argc, argv);

48     //Generate a file handle
50     abstract_node * file_node = buildroseNode((project->get_fileList())[0]);
       file_handle = new abstract_handle(file_node);

52     //Generate handles for language constructs
54     visitorTraversal myvisitor;
       myvisitor.traverseInputFiles(project,preorder);
56
   // Generate source code from AST and call the vendor's compiler
58     return backend(project);
   }

```

Figure 41.1: Example 1: Generated handles for loops: using constructors with or without a specified handle type.

```

2  /* test input for generated abstract handles */
   int a[100][100][100];

4  void foo()
   {
6      int i,j,k;
       for (i=0;i++;i<100)
8          for (j=0;j++;j<100)
               for (k=0;k++;k<100)
10             a[i][j][k]=i+j+k;

12         for (i=0;i++;i<100)
               for (j=0;j++;j<100)
14             for (k=0;k++;k<100)
                   a[i][j][k]+=5;
16     }

```

Figure 41.2: Example 1: Example source code with some loops, used as input.

```

Creating handles for a loop construct...
2  Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
   1/sourcetree/tutorial/inputCode_AbstractHandle1.cpp>::ForStatement<position,7.3-
4  10.25>
   Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
6  1/sourcetree/tutorial/inputCode_AbstractHandle1.cpp>::ForStatement<numbering,2>

8  Creating handles for a loop construct...
   Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
10 1/sourcetree/tutorial/inputCode_AbstractHandle1.cpp>::ForStatement<position,8.5-
   10.25>
12  Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
   1/sourcetree/tutorial/inputCode_AbstractHandle1.cpp>::ForStatement<numbering,2>
14

16  Creating handles for a loop construct...
   Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
18 1/sourcetree/tutorial/inputCode_AbstractHandle1.cpp>::ForStatement<position,9.7-
   10.25>
20  Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
   1/sourcetree/tutorial/inputCode_AbstractHandle1.cpp>::ForStatement<numbering,3>

22  Creating handles for a loop construct...
   Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
24 1/sourcetree/tutorial/inputCode_AbstractHandle1.cpp>::ForStatement<position,12.3
   -15.22>
26  Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
   1/sourcetree/tutorial/inputCode_AbstractHandle1.cpp>::ForStatement<numbering,4>
28

30  Creating handles for a loop construct...
   Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
32 1/sourcetree/tutorial/inputCode_AbstractHandle1.cpp>::ForStatement<position,13.5
   -15.22>
34  Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
   1/sourcetree/tutorial/inputCode_AbstractHandle1.cpp>::ForStatement<numbering,5>

36  Creating handles for a loop construct...
   Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
38 1/sourcetree/tutorial/inputCode_AbstractHandle1.cpp>::ForStatement<position,14.7
   -15.22>
40  Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
   1/sourcetree/tutorial/inputCode_AbstractHandle1.cpp>::ForStatement<numbering,6>

```

Figure 41.3: Example 1: Abstract handles generated for loops.

A second example (shown in Figure 41.4) demonstrates how to create handles using user-specified strings representing handle items for language constructs within a source file (shown in Figure 41.5). This is particularly useful to grab internal language constructs from handles provided by external software tools. The output of the example is given in Figure 41.6.

```

2  /*
3  Example code to generate language handles from input strings about
4  * source position information
5  * numbering information
6
7  by Liao, 10/9/2008
8  */
9  #include "rose.h"
10 #include <iostream>
11 #include <string.h>
12 #include "abstract_handle.h"
13 #include "roseAdapter.h"
14
15 using namespace std;
16 using namespace AbstractHandle;
17
18 int main(int argc, char * argv[])
19 {
20     SgProject *project = frontend (argc, argv);
21
22     // Generate a file handle from the first file of the project
23     abstract_node* file_node= buildroseNode((project->get_fileList())[0]);
24     abstract_handle* handle0 = new abstract_handle(file_node);
25     cout<<" Created a file handle:\n"<<handle0->toString()<<endl<<endl;;
26
27     //Create a handle to a namespace given its name and parent handle
28     string input1="NamespaceDeclarationStatement<name,space1>";
29     abstract_handle* handle1 = new abstract_handle(handle0,input1);
30     cout<<" Created a handle:\n"<<handle1->toString()<<endl<<endl;
31     cout<<" It points to:\n"<<handle1->getNode()->toString()<<endl<<endl;
32
33     // Create a handle within the file, given a string specifying
34     // its construct type (class declaration) and source position
35     string input="ClassDeclaration<position,4.3-9.2>";
36     abstract_handle* handle2 = new abstract_handle(handle0,input);
37
38     cout<<" Created a handle:\n"<<handle2->toString()<<endl<<endl;
39     cout<<" It points to:\n"<<handle2->getNode()->toString()<<endl<<endl;;
40
41     // find the second function declaration within handle2
42     abstract_handle handle3(handle2,"FunctionDeclaration<numbering,2>");
43
44     cout<<" Created a handle:\n"<<handle3.toString()<<endl<<endl;
45     cout<<" It points to:\n"<<handle3.getNode()->toString()<<endl;
46
47     // Generate source code from AST and call the vendor's compiler
48     return backend(project);
49 }

```

Figure 41.4: Example 2: Generated handles from strings representing handle items.

```

    void bar(int x);
2  namespace space1
    {
4      class A
        {
6          public:
            void bar(int x);
8            void foo();
        };
10 }

```

Figure 41.5: Example 2: Source code with some language constructs.

```

Created a file handle:
2  Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
1/sourcetree/tutorial/inputCode_AbstractHandle2.cpp>
4
Created a handle:
6  Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
1/sourcetree/tutorial/inputCode_AbstractHandle2.cpp>::NamespaceDeclarationStatem
8  ent<name,space1>

10 It points to:
    namespace space1{class ::space1::A {public: void bar(int x);void foo();};}
12
Created a handle:
14 Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
1/sourcetree/tutorial/inputCode_AbstractHandle2.cpp>::ClassDeclaration<position ,
16 4.3-9.2>

18 It points to:
    class ::space1::A {public: void bar(int x);void foo();};
20
Created a handle:
22 Project<numbering,1>::SourceFile<name,/home/liao6/daily-test-rose/20091101_12000
1/sourcetree/tutorial/inputCode_AbstractHandle2.cpp>::ClassDeclaration<position ,
24 4.3-9.2>::MemberFunctionDeclaration<numbering,2>

26 It points to:
    public: void space1::A::foo();

```

Figure 41.6: Example 2: Handles generated from string and their language constructs.

41.4.2 Connecting to External Tools

A third example is provided to demonstrate how to use the abstract interface with any other tools, which may have less features in terms of supported language constructs and their correlations compared to a compiler. Assume a tool operating on some simple for-loops within an arbitrary source file (the input file is not shown in this example). Such a tool might have an internal data structure representing loops; such as that in given in Figure 41.7. We will show how the tool specific data structure for loops can be used to generate abstract handles and output as strings that can be used by other tools which use abstract handles (which would generate the abstract handles by reading the strings).

```

2  /*
   * A toy loop data structure demonstrating a thin client of abstract handles:
   * A simplest loop tool which keeps a tree of loops in a file
   */
4  #ifndef my_loop_INCLUDED
6  #define my_loop_INCLUDED

8  #include <string>
   #include <vector>
10 class MyLoop
   {
12 public:
       std::string sourceFileName;
14       size_t line_number;
       std::vector<MyLoop*> children;
16       MyLoop* parent;
   };
18 #endif

```

Figure 41.7: Example 3: A simple data structure used to represent a loop in an arbitrary tool.

An adapter (`loopAdapter.h` and `loopAdapter.cpp`) using the proposed abstract handle interface is given in `src/midend/abstractHandle`. It provides a concrete implementation for the interface for the simple loops and adds a node to support file nodes (Compared to a full-featured IR for a compiler, the file node is an additional detail for tools without data structures to support files). The test program is given in Figure 41.8. Again, it creates a top level file handle first. Then a loop handle (`loop_handle1`) is created within the file handle using its relative numbering information. The `loop_handle2` is created from from its string format using file position information (using GNU standard file position syntax). The `loop_handle3` uses its relative numbering information within `loop_handle1`.

The output of the program is shown in Figure 41.9. It demonstrates the generated strings to represent the abstract handles in the arbitrary code operated upon by the tool. Interoperability is achieved by another tool reading in the generated string representation to generate an abstract handle to the same source code language construct.

```

#include <iostream>
2 #include <string>
#include <vector>
4 #include "abstract_handle.h"
#include "myloop.h"
6 #include "loopAdapter.h"

8 using namespace std;
using namespace AbstractHandle;

10
11 int main()
12 {
13     //-----Preparing the internal loop representation-----
14     // declare and initialize a list of loops using MyLoop
15     // The loop tool should be able to generate its representation from
16     // source code somehow. We fill it up manually here.
17     vector <MyLoop* > loops;
18
19     MyLoop loop1, loop2, loop3;
20     loop1.sourceFileName="file1.c";
21     loop1.line_number = 7;
22     loop1.parent = NULL;
23     loop2.sourceFileName="file1.c";
24     loop2.line_number = 8;
25     loop2.parent=&loop1;
26     loop1.children.push_back(&loop2);
27     loop3.sourceFileName="file1.c";
28     loop3.line_number = 12;
29     loop3.parent=NULL;
30     loops.push_back(&loop1);
31     loops.push_back(&loop3);
32
33     //----- using abstract handles-----
34     //Generate the abstract handle for the source file
35     fileNode* fileNode = new fileNode("file1.c");
36     fileNode->setMLoops(loops);
37     abstract_handle* file_handle = new abstract_handle(fileNode);
38     cout<<"Created_a_file_handle:"<<endl<<file_handle->toString()<<endl;

40     //Create a loop handle within the file using numbering info.
41     abstract_node* loop_node1= new loopNode(&loop1);
42     abstract_handle* loop_handle1= new abstract_handle(loop_node1,e-numbering,file_handle);
43     cout<<"Created_a_loop_handle:"<<endl<<loop_handle1->toString()<<endl;

44     //Create another loop handle within a file using its source position information
45     string input1("ForStatement<position,12>");
46     abstract_handle* loop_handle2= new abstract_handle(file_handle,input1);
47     cout<<"Created_a_loop_handle:"<<endl<<loop_handle2->toString()<<endl;

50     //Create yet another loop handle within a loop using its relative numbering information
51     string input2("ForStatement<numbering,1>");
52     abstract_handle* loop_handle3= new abstract_handle(loop_handle1,input2);
53     cout<<"Created_a_loop_handle:"<<endl<<loop_handle3->toString()<<endl;

54     return 0;
55 }

```

Figure 41.8: Example 3: A test program for simple loops' abstract handles.

```
bash-3.00: ./testMyLoop
2 Created a file handle:
  SourceFile<name,file1.c>
4 Created a loop handle:
  SourceFile<name,file1.c>::ForStatement<numbering,1>
6 Created a loop handle:
  SourceFile<name,file1.c>::ForStatement<position,12>
8 Created a loop handle:
  SourceFile<name,file1.c>::ForStatement<numbering,1>::ForStatement<numbering,1>
```

Figure 41.9: Example 3: Output of the test program for simple loops' abstract handles (as strings).

41.5 Summary

Abstract handles are low level mechanisms to support multiple tools to exchange references to source code. Several examples are used to present the different features of abstract handles. Importantly, the specification of abstract handles is tool independent. A reference implementation is provided and is publically available within the ROSE compiler framework. We encourage debate on the pros and cons of this concept to support interoperability of tools which must pass references to source code between them. This work is expected to a small piece of the infrastructure to suport autotuning research.

Chapter 42

ROSE-HPCToolKit Interface

ROSE-HPCToolKit is designed to read in performance data generated by HPCToolkit (and recently GNU gprof) and annotate ROSE AST with performance metrics. It is included in the ROSE distribution and enabled by default if an existing installation of the Gnome XML library, libxml2 (<http://xmlsoft.org>) can be detected by ROSE's configure script. Or it can be enabled explicitly by specifying the `--enable-rosehpct` option when running configure.

The HPCToolkit (<http://www.hipersoft.rice.edu/hpctoolkit>) is a set of tools for analyzing the dynamic performance behavior of applications. It includes a tool that instruments a program's binary, in order to observe CPU hardware counters during execution; additional post-processing tools attribute the observed data to statements in the original source code. HPCToolkit stores this data and the source attributions in XML files. In this chapter, we give an overview of simple interfaces in ROSE that can read this data and attach it to the AST.

GNU gprof is a basic but easy to use profiling tool. It produces an execution profile of applications. gprof's output is a flat profile for each function by default, which is not very interesting to us. We use a line-by-line output with full file path information generated by using option `-l -L` with gprof.

42.1 An HPCToolkit Example Run

Consider the sample source program shown in Figures 42.1–42.2. This program takes an integer n on the command line, and has a number of loops whose flop and memory-operation complexity are either $\Theta(n)$ or $\Theta(n^2)$. For this example, we would expect the loop nest at line 56, which has $O(n^2)$ cost, to be the most expensive loop in the program for large n .

Suppose we use the HPCToolkit to profile this program, collecting cycle counts and floating-point instructions.¹ HPCToolkit will generate one XML file for each metric.

A schema specifying the format of these XML files appears in Figure 42.3. In essence, this schema specifies that the XML file will contain a structured, abstract representation of the program in terms of abstract program entities such as “modules,” “procedures,” “loops,” and “statements.” Each of these entities may have line number information and a “metric” value.

¹In this example, HPCToolkit uses the PAPI to read CPU counters (<http://icl.cs.utk.edu/papi>).

(Refer to the HPCToolkit documentation for more information.) This schema is always the first part of an HPCToolkit-generated XML profile data file.

We ran HPCToolkit on the program in Figures 42.1–42.2, and collected cycle and flop counter data. The actual XML files storing this data appear in Figures 42.4 and 42.5. By convention, these metrics are named according to their PAPI symbolic name, as shown on line 67 in both Figures 42.4 and 42.5. According to the cycle data on line 90 of Figure 42.4, the most expensive statement in `profiled.c` is line 62 of Figure 42.1, as expected.


```

#include <stdio.h>
#include <stdlib.h>
#include <string.h>

5  typedef double val_t;

    static val_t *
    gen (size_t n)
    {
10     val_t* x = (val_t *) malloc (sizeof(val_t) * n);
        if (x != NULL)
        {
            size_t i;
            for (i = 0; i < n; i++)
15             x[i] = (val_t)1.0 / n;
        }
        return x;
    }

20 static val_t
dot (size_t n, const val_t* x, const val_t* y)
{
    size_t i;
    val_t sum;
25     for (i = 0, sum = 0.0; i < n; i++)
        sum += x[i] * y[i];
    return sum;
}

30 static size_t
max (size_t n, const val_t* x)
{
    size_t i;
    size_t i_max;
35     val_t v_max;

    if (n <= 0)
        return 0;

40     v_max = x[0];
    i_max = 0;
    for (i = 1; i < n; i++)
        if (x[i] > v_max)
        {
45             v_max = x[i];
            i_max = i;
        }
    return i_max;
}

50 static void
mv (size_t n, const val_t* A, const val_t* x, val_t* y)
{
    size_t j;
55     memset (y, 0, sizeof(val_t) * n);
    for (j = 0; j < n; j++)
    {
        const val_t* Ap;
        register val_t xj = x[j];
        size_t i;
60         for (i = 0, Ap = A + j*n; i < n; i++, Ap++)
            y[i] += Ap[0] * xj;
    }
}

```

Figure 42.1: profiled.c (part 1 of 2): Sample input program, profiled using the HPCToolkit.

```

int
main (int argc, char* argv[])
{
    size_t n;
70    val_t* x;
    val_t* y;
    val_t* A;
    size_t i;

75    /* outputs */
    val_t sum;
    size_t i_max;
    val_t y_max;

80    if (argc != 2)
    {
        fprintf (stderr, "usage: %s <n>\n", argv[0]);
        return 1;
    }
85    n = atoi (argv[1]);
    if (n <= 0)
        return 1;

    A = gen (n * n);
90    x = gen (n);
    y = gen (n);

    if (A == NULL || x == NULL || y == NULL)
    {
95        fprintf (stderr, "***_Out_of_memory_***\n");
        return 1;
    }

    sum = 0;
100    for (i = 0; i < n; i++)
        sum += dot (n, x, y);
    mv (n, A, x, y);
    i_max = max (n, y);
    y_max = y[i_max];
105    printf ("%g %lu %g\n", sum, (unsigned long)i_max, y_max);

    return 0;
}
110 /* eof */

```

Figure 42.2: `profiled.c` (part 2 of 2): Sample input program, profiled using the HPCToolkit.

```

<?xml version="1.0"?>
<!DOCTYPE PROFILE [
  <!-- Profile: correlates profiling info with program structure. -->
  <ELEMENT PROFILE (PROFILEHDR, PROFILEPARAMS, PROFILESCOPETREE)>
5  <ATTLIST PROFILE
      version CDATA #REQUIRED>
  <ELEMENT PROFILEHDR (#PCDATA)>
  <ELEMENT PROFILEPARAMS (TARGET, METRICS)>
  <ELEMENT TARGET EMPTY>
10  <ATTLIST TARGET
      name CDATA #REQUIRED>
  <ELEMENT METRICS (METRIC)+>
  <ELEMENT METRIC EMPTY>
  <ATTLIST METRIC
15      shortName CDATA #REQUIRED
      nativeName CDATA #REQUIRED
      period CDATA #REQUIRED
      units CDATA #IMPLIED
      displayName CDATA #IMPLIED
20      display (true|false) #IMPLIED>
  <ELEMENT PROFILESCOPETREE (PGM)*>
  <!-- This is essentially the PGM dtd with M element added. -->
  <ELEMENT PGM (G|LM|F|M)+>
  <ATTLIST PGM
25      n CDATA #REQUIRED>
  <!-- Groups create arbitrary sets of other elements except PGM. -->
  <ELEMENT G (G|LM|F|P|L|S|M)*>
  <ATTLIST G
      n CDATA #IMPLIED>
30  <!-- Runtime load modules for PGM (e.g., DSOs, exe) -->
  <ELEMENT LM (G|F|M)*>
  <ATTLIST LM
      n CDATA #REQUIRED>
  <!-- Files contain procedures and source line info -->
35  <ELEMENT F (G|P|L|S|M)*>
  <ATTLIST F
      n CDATA #REQUIRED>
  <!-- Procedures contain source line info
      n: processed name; ln: link name -->
40  <ELEMENT P (G|L|S|M)*>
  <ATTLIST P
      n CDATA #REQUIRED
      ln CDATA #IMPLIED
      b CDATA #IMPLIED
45      e CDATA #IMPLIED>
  <!-- Loops -->
  <ELEMENT L (G|L|S|M)*>
  <ATTLIST L
      b CDATA #IMPLIED
50      e CDATA #IMPLIED>
  <!-- Statement/Statement range -->
  <ELEMENT S (M)*>
  <ATTLIST S
      b CDATA #REQUIRED
55      e CDATA #IMPLIED
      id CDATA #IMPLIED>
  <ELEMENT M EMPTY>
  <ATTLIST M
      n CDATA #REQUIRED
60      v CDATA #REQUIRED>
]>

```

Figure 42.3: XML schema for HPCToolkit data files: This schema, prepended to each of the HPCToolkit-generated XML files, describes the format of the profiling data. This particular schema was generated by HPCToolkit 1.0.4.

```

<PROFILE version="3.0">
<PROFILEHDR></PROFILEHDR>
<PROFILEPARAMS>
65   <TARGET name="example" />
      <METRICS>
        <METRIC shortName="0" nativeName="PAPL.TOT.CYC" displayName="PAPL.TOT.CYC" period="32767" units="PAPL.event" />
      </METRICS>
    </PROFILEPARAMS>
70   <PROFILESOPETREE>
      <PGM n="example">
        <LM n="/home/vuduc2/projects/ROSE/tmp/xml/xerces-c/hpctif/examples/data/01/example">
          <F n="./profiled.c">
            <P n="main">
75              <S b="15">
                <M n="0" v="163835" />
              </S>
              <S b="25">
                <M n="0" v="65534" />
80              </S>
              <S b="26">
                <M n="0" v="65534" />
              </S>
            </P>
            <P n="mv">
85              <S b="61">
                <M n="0" v="65534" />
              </S>
              <S b="62">
90              <M n="0" v="327670" />
              </S>
            </P>
          </F>
        </LM>
75   </PGM>
80   </PROFILESOPETREE>
85   </PROFILE>

```

Figure 42.4: PAPL.TOT.CYC.xml: Sample cycle counts observed during profiling, generated from running the HPCToolkit on profiled.c (Figures 42.1–42.2.) These lines would appear after the schema shown in Figure 42.3.

```

<PROFILE version="3.0">
<PROFILEHDR></PROFILEHDR>
<PROFILEPARAMS>
65   <TARGET name="example" />
      <METRICS>
        <METRIC shortName="0" nativeName="PAPI_FP_OPS" displayName="PAPI_FP_OPS" period="32767" units="PAPI_events" />
      </METRICS>
    </PROFILEPARAMS>
70   <PROFILESOPETREE>
    <PGM n="example">
      <LM n="/home/vuduc2/projects/ROSE/tmp/xml/xerces-c/hpctif/examples/data/01/example">
        <F n="/profiled.c">
          <P n="main">
75            <S b="25">
              <M n="0" v="32767" />
            </S>
            <S b="26">
              <M n="0" v="98301" />
80            </S>
          </P>
          <P n="mv">
            <S b="61">
              <M n="0" v="131068" />
85            </S>
            <S b="62">
              <M n="0" v="262136" />
            </S>
          </P>
90        </F>
      </LM>
    </PGM>
  </PROFILESOPETREE>
</PROFILE>

```

Figure 42.5: PAPI_FP_OPS.xml: Sample flop counts observed during profiling, generated from running the HPCToolkit on profiled.c (Figures 42.1–42.2.) These lines would appear after the schema shown in Figure 42.3.

42.2 Attaching HPCToolkit Data to the ROSE AST

To attach the data of Figures 42.4 and 42.5 to the AST, we augment a basic ROSE translator with two additional calls, as shown in Figure 42.6, lines 47–48 and 54. We describe these calls below.

42.2.1 Calling ROSE-HPCT

We must first include `rosehpct/rosehpct.hh`, as shown on line 6 of Figure 42.6. All ROSE-HPCT routines and intermediate data structures reside in the `RoseHPCT` namespace.

Next, lines 47–48 of Figure 42.6 store the contents of the raw XML file into an intermediate data structure of type `RoseHPCT::ProgramTreeList_t`. The `RoseHPCT::loadProfilingFiles()` routine processes command-line arguments, extracting ROSE-HPCT-specific options that specify the files. We discuss these options in Section 42.4.

Line 54 of Figure 42.6, attaches the intermediate profile data structure to the ROSE AST. The `RoseHPCT::attachMetrics()` routine creates new persistent attributes that store the counter data.² The attributes are named using the metric name taken from the XML file (see lines 67 of Figures 42.4–42.5); in this example, the attributes are named `PAPL_TOT_CYC` and `PAPL_FP_OPS`. Following the conventions of persistent attribute mechanism as described in Chapter 8, the attributes themselves are of type `RoseHPCT::MetricAttr`, which derives from the `AstAttribute` type.

42.2.2 Retrieving the attribute values

We retrieve the attribute values as described in Chapter 8. In particular, given a located node with cycle and flop attribute values, the `printFlopRate()` routine defined in lines 11–42 of Figure 42.6 prints the source position, AST node type, and estimated flops per cycle. We call `printFlopRate()` for each expression statement (`SgExpressionStmt`), for-initializer (`SgForInitStatement`), and for-statement (`SgForStatement`) in lines 59–66 of Figure 42.6. The output is shown in Figure 42.7.

Inspecting the output carefully, you may notice seeming discrepancies between the values shown and the values that appear in the XML files, or other values which seem unintuitive. We explain how these values are derived in Section 42.2.3.

This example dumps the AST as a PDF file, as shown on line 68 of Figure 42.6. You can inspect this file to confirm where attributes have been attached. We show an example of such a page in Figure 42.8. This page is the `SgExprStatement` node representing the sum-accumulate on line 26 of Figure 42.1.

42.2.3 Metric propagation

The example program in Figure 42.6 dumps metric values at each expression statement, for-initializer, and for-statement, but the input XML files in Figure 42.4–42.5 only attribute the profile data to “statements” that are not loop constructs. (The `<S ...>` XML tags refer to statements, intended to be “simple” non-scoping executable statements; a separate `<L ...>` tag

²The last parameter to `RoseHPCT::attachMetrics()` is a boolean that, when true, enables verbose (debugging) messages to standard error.

would refer to a loop.) Since the XML file specifies statements only by source line number, `RoseHPCT::attachMetrics()` attributes measurements to AST nodes in a heuristic way.

For example, lines 78–80 of Figure 42.4 indicate that all executions of the “simple statements” of line 25 of the original source (Figure 42.1) accounted for 65534 observed cycles, and that line 26 accounted for an additional 65534 cycles. In the AST, there are multiple “statement” and expression nodes that occur on line 25; indeed, Figure 42.7 lists 4 such statements.

The ROSE-HPCT modules uses a heuristic which only assigns `<S ...>` metric values to non-scoping nodes derived from `SgStatement`. When multiple `SgStatement` nodes occur at a particular source line, ROSE-HPCT simply attaches the metric to each of them. But only one of them will be used for propagating metrics to parent scopes.

How is the measurement of 65534 cycles attributed to all of the AST nodes corresponding to line 25 of Figure 42.1? Indeed, line 25 actually “contains” four different `SgStatement` nodes: an `SgForStatement` representing the whole loop on lines 25–26, an `SgForInitStatement` (initializer), and two `SgExprStatements` (one which is a child of the `SgForInitStatement`, and another for the for-loop’s test expression). The loop’s increment is stored in the `SgForStatement` node as an `SgExpression`, not an `SgStatement`. The `SgForStatement` node is a scoping statement, and so it “receives” none of the 65534 cycles. Since the increment is not a statement and one of the `SgExprStatements` is a child of the initializer, this leaves only two direct descendants of the `SgForStatement`—the initializer and the test expression statement—among which to divide the 65534 cycles. Thus, each receives 32767 cycles. The initializer’s `SgExprStatement` child gets the same 32767 as its parent, since the two nodes are equivalent (see first two cases of Figure 42.7).

For the entire loop on lines 25–26 of Figure 42.1, the original XML files attribute 65534 cycles to line 25, and another 65534 cycles to line 26 (see Figure 42.4). Moreover, the XML files do not attribute any costs to this loop *via* an explicit `<L ...>` tag. Thus, the best we can infer is that the entire for-statement’s costs is the sum of its immediate child costs; in this case, 131068 cycles. The `RoseHPCT::attachMetrics()` routine will heuristically accumulate and propagate metrics in this way to assign higher-level scopes approximate costs.

The `RoseHPCT::attachMetrics()` routine automatically propagates metric values through parent scopes. A given metric attribute, `RoseHPCT::MetricAttr* x`, is “derived” through propagation if `x->isDerived()` returns true. In fact, if you call `x->toString()` to obtain a string representation of the metric’s value, two asterisks will be appended to the string as a visual indicator that the metric is derived. We called `RoseHPCT::MetricAttr::toString()` on lines 27 and 29 of Figure 42.6, and all of the `SgForStatement` nodes appearing in the output in Figure 42.7 are marked as derived.

Alternatively, you can call `RoseHPCT::attachMetricsRaw()`, rather than calling `RoseHPCT::attachMetrics()`. The “raw” routine takes the same arguments but only attaches the raw data, *i.e.*, without attempting to propagate metric values through parent scopes.

42.3 Working with GNU gprof

ROSE-HPCT can also accept the line-by-line profiling output generated by GNU gprof. Currently, we only use the self seconds associated with each line and attach them to ROSE AST as AST attributes named `WALLCLK`.

A typical session to generate compatible gprof profiling file for ROSE-HPCT is given below:

```
[liao@codes]$ gcc -g seq-pi.c -pg
```

```
[liao@codes]$ ./a.out
[liao@codes]$ gprof -l -L a.out gmon.out &>profile.result
```

-l tells gprof to output line-by-line profiling information and -L causes gprof to output full file path information.

An excerpt of an output file looks like the following:

Flat profile:

Each sample counts as 0.01 seconds.

%	cumulative	self		self	total	
time	seconds	seconds	calls	Ts/call	Ts/call	name
38.20	8.84	8.84				jacobi (/home/liao6/temp/jacobi.c:193 @ 804899c)
36.43	17.27	8.43				jacobi (/home/liao6/temp/jacobi.c:196 @ 8048a3f)
11.00	19.82	2.54				jacobi (/home/liao6/temp/jacobi.c:188 @ 804893e)
5.66	21.12	1.31				jacobi (/home/liao6/temp/jacobi.c:187 @ 8048968)
3.93	22.04	0.91				jacobi (/home/liao6/temp/jacobi.c:197 @ 8048a71)
3.24	22.79	0.75				jacobi (/home/liao6/temp/jacobi.c:191 @ 8048a7f)
0.95	23.00	0.22				jacobi (/home/liao6/temp/jacobi.c:186 @ 8048976)
0.50	23.12	0.12				jacobi (/home/liao6/temp/jacobi.c:187 @ 8048935)
0.09	23.14	0.02				jacobi (/home/liao6/temp/jacobi.c:190 @ 8048a94)
0.00	23.14	0.00	1	0.00	0.00	driver (/home/liao6/temp/jacobi.c:91 @ 8048660)
0.00	23.14	0.00	1	0.00	0.00	error_check (/home/liao6/temp/jacobi.c:220 @ 8048b7c)
0.00	23.14	0.00	1	0.00	0.00	initialize (/home/liao6/temp/jacobi.c:116 @ 8048722)
0.00	23.14	0.00	1	0.00	0.00	jacobi (/home/liao6/temp/jacobi.c:160 @ 8048892)

42.4 Command-line options

The call to `RoseHPCT::loadProfilingFiles()` on line 49 of Figure 42.6 processes and extracts ROSE-HPCT-specific command-line options. To generate the output in this chapter, we invoked Figure 42.6 with the following command-line:

```
./attachMetrics \
-rose:hpctprof /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/PAPI_TOT_C
-rose:hpctprof /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/PAPI_FP_OP
-rose:hpcteqpath ./home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT\
-c /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/profiled.c
```

The main option is `-rose:hpct:prof <file>`, which specifies the HPCToolkit-generated XML file containing metric data. Here, we use this option twice to specify the names of the cycle and flop data files (Figures 42.4–42.5). To accept gprof output file, please use another option `-rose:gprof:linebyline <file>`. This option cannot be used with `-rose:hpct:prof <file>` currently.

We need the other option, `-rose:hpct:eqpath <A>=`, to specify how paths in the HPC-Toolkit XML files can be mapped to file paths in the ROSE AST. This option allows users to generate performance files on one machine and analyze the results on another machine. In this example, the XML files specify the source file as, “./profiled.c” (line 73 of Figures 42.4 and 42.5); the “eqpath” command-line option above remaps the relative path “.” to an absolute path as it would appear in the ROSE AST. Another example is to use the same performance file even after the original source tree is moved to another location. ROSE-HPCT can still correctly match performance data if the root source paths are given as `-rose:hpct:eqpath <oldRootPath>=<newRootPath>`.

Yet another option `-rose:hpct:enable_debug` is provided to display runtime debugging information such as metrics reading, attaching, and propagating. It also adds performance metrics into the ROSE output source file as source comments as shown below. Users can examine the source comments to make sure performance metrics are attached and propagated properly. As we can see, ROSE-HPCT attaches each performance metric to each matching statement. If there are multiple statements showing in the same line, the same metric will be attached to each of them. The metric propagation step will only propagate one of them to upper-level language constructs to ensure the correctness.

```
/* ROSE-HPCT propagated metrics WALLCLK:18.95[SgForStatement at 0xb7beb218] */
for (
/* ROSE-HPCT raw data: Statement WALLCLK:0.02@File jacobi.c 190-0 -> SgForInitStatement 0x94e8d08 at 190 */
i = 1;
/* ROSE-HPCT raw data: Statement WALLCLK:0.02@File jacobi.c 190-0 -> SgExprStatement 0x94516d8 at 190 */
i < (n - 1); i++)
/* ROSE-HPCT propagated metrics WALLCLK:18.93[SgForStatement at 0xb7beb29c] */
for (
/* ROSE-HPCT raw data: Statement WALLCLK:0.75@File jacobi.c 191-0 -> SgForInitStatement 0x94e8d38 at 191 */
j = 1;
/* ROSE-HPCT raw data: Statement WALLCLK:0.75@File jacobi.c 191-0 -> SgExprStatement 0x9451728 at 191 */
j < (m - 1); j++)
/* ROSE-HPCT propagated metrics WALLCLK:18.18[SgBasicBlock at 0x93f60b4] */
{
/* ROSE-HPCT raw data: Statement WALLCLK:8.84@File jacobi.c 193-0 -> SgExprStatement 0x9451750 at 193 */
resid = (((ax * ((( *uold)[i - 1])[j]) + (( *uold)[i + 1])[j])) + (ay * ((( *uold)[i])[j - 1])
+ ((( *uold)[i])[j + 1]))) + (b * ((( *uold)[i])[j])) - ((( *f)[i])[j]) / b);
/* ROSE-HPCT raw data: Statement WALLCLK:8.43@File jacobi.c 196-0 -> SgExprStatement 0x9451778 at 196 */
(( *u)[i])[j] = ((( *uold)[i])[j]) - (omega * resid);
/* ROSE-HPCT raw data: Statement WALLCLK:0.91@File jacobi.c 197-0 -> SgExprStatement 0x94517a0 at 197 */
error = (error + (resid * resid));
}
```

```

// attachMetrics.cc — Sample translator showing how to attach
// HPCToolkit data to the ROSE AST.

#include "rose.h"
5 #include <iostream>
#include <list>
#include <rosehpct/rosehpct.hh>

using namespace std;

10 // Prints the estimated flops/cycle at a located node.
static void printFlopRate (const SgNode* n)
{
    const SgLocatedNode* n_loc = isSgLocatedNode (n);
15     if (n_loc
        && n_loc->attributeExists ("PAPITOT_CYC")
        && n_loc->attributeExists ("PAPIFP_OPS"))
    {
        // Extract attributes.
20         const RoseHPCT::MetricAttr* cycles_attr =
            dynamic_cast<const RoseHPCT::MetricAttr*> (n->getAttribute ("PAPITOT_CYC"));
        const RoseHPCT::MetricAttr* flops_attr =
            dynamic_cast<const RoseHPCT::MetricAttr*> (n->getAttribute ("PAPIFP_OPS"));
        ROSE_ASSERT (cycles_attr && flops_attr);

25         // Get the metric values, as doubles and strings.
        double cycles = cycles_attr->getValue ();
        string cycles_s = const_cast<RoseHPCT::MetricAttr*> (cycles_attr)->toString ();
        double flops = flops_attr->getValue ();
30         string flops_s = const_cast<RoseHPCT::MetricAttr*> (flops_attr)->toString ();

        // Print node pointer/type, parent, estimated flop rate, and source position.
        const SgNode* n_par = n_loc->get_parent ();
        cout << (const void *)n_loc << ":<" << n_loc->class_name () << ">"
35         << "_(Par=" << (const void *)n_par << ":<" << n_par->class_name () << ">)"
        << "_((" << flops_s << "_(flops)"
        << "_((" << cycles_s << "_(cy)"
        << "_((" << flops / cycles << "_(flops/cy" << endl
        << "_([" << n_loc->get_startOfConstruct ()->get_raw_filename ()
40         << ":'<" << n_loc->get_startOfConstruct ()->get_raw_line () << "]"
        << endl;
    }
}

45 int main (int argc, char* argv[])
{
    vector<string> argvList(argv, argv+argc);
    cerr << "[Loading_HPCToolkit_or_Gprof_profiling_data...]" << endl;
    RoseHPCT::ProgramTreeList_t profiles
50     = RoseHPCT::loadProfilingFiles(argvList);

    cerr << "[Building_the_ROSE_AST...]" << endl;
    SgProject* proj = frontend (argvList);

55     cerr << "[Attaching_metrics_to_the_AST...]" << endl;
    RoseHPCT::attachMetrics (profiles, proj, proj->get_verbose () > 0);

    cerr << "[Estimating_flop_execution_rates...]" << endl;
    typedef Rose_STL_Container<SgNode*> NodeList_t;

60     NodeList_t estmts = NodeQuery::querySubTree (proj, V_SgExprStatement);
    for_each (estmts.begin (), estmts.end (), printFlopRate);

    NodeList_t for_inits = NodeQuery::querySubTree (proj, V_SgForInitStatement);
65     for_each (for_inits.begin (), for_inits.end (), printFlopRate);

    NodeList_t fors = NodeQuery::querySubTree (proj, V_SgForStatement);
    for_each (fors.begin (), fors.end (), printFlopRate);

70     cerr << "[Dumping_a_PDF...]" << endl;
    generatePDF (*proj);

    // DQ (1/2/2008): This output appears to have provided enough synchronization in
    // the output to allow -j32 to work. Since I can't debug the problem further for
75     // now I will leave it.
    cerr << "[Calling_backend...]" << endl;
    return backend (proj);
}

```

Figure 42.6: attachMetrics.cc: Sample translator to attach HPCToolkit metrics to the AST.

```

0xa101e14:<SgExprStatement> (Par=0xb7bf3090:<SgForStatement>) = (16383.5 flops) / (32767 cy) ~= 0.5 flops/cy
[/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/profiled.c:25]
0xa101e40:<SgExprStatement> (Par=0xb7bf3090:<SgForStatement>) = (98301 flops) / (65534 cy) ~= 1.5 flops/cy
[/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/profiled.c:26]
0xa10207c:<SgExprStatement> (Par=0xb7bf3228:<SgForStatement>) = (65534 flops) / (32767 cy) ~= 2 flops/cy
[/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/profiled.c:61]
0xa1020a8:<SgExprStatement> (Par=0xb7bf3228:<SgForStatement>) = (262136 flops) / (327670 cy) ~= 0.8 flops/cy
[/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/profiled.c:62]
0xa10cb54:<SgForInitStatement> (Par=0xb7bf3090:<SgForStatement>) = (16383.5 flops) / (32767 cy) ~= 0.5 flops/cy
[/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/profiled.c:25]
0xa10cbf0:<SgForInitStatement> (Par=0xb7bf3228:<SgForStatement>) = (65534 flops) / (32767 cy) ~= 2 flops/cy
[/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/profiled.c:61]
0xb7bf3090:<SgForStatement> (Par=0x9ff14a0:<SgBasicBlock>) = (131068** flops) / (131068** cy) ~= 1 flops/cy
[/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/profiled.c:25]
0xb7bf31a0:<SgForStatement> (Par=0x9ff1620:<SgBasicBlock>) = (393204** flops) / (393204** cy) ~= 1 flops/cy
[/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/profiled.c:56]
0xb7bf3228:<SgForStatement> (Par=0x9ff16a0:<SgBasicBlock>) = (393204** flops) / (393204** cy) ~= 1 flops/cy
[/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/profiled.c:61]

```

Figure 42.7: Sample output, when running `attachMetrics.cc` (Figure 42.6) with the XML inputs in Figures 42.4–42.5. Here, we only show the output sent to standard output (*i.e.*, `cout` and not `cerr`).

```

pointer:0xb7d01cf0
SgVariableDeclaration
/home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/roseHPCT/profiled.c 23:3
IsTransformation:0
IsOutputInCodeGeneration:0
Declaration mangled name: _variable_declaration__variable_type_size_tUi__typedef_declaration_variab

```

[Click here to go to the parent node](#)

```

SgNode* p_parent : 0x9ff14a0
bool p_isModified : 1
$CLASSNAME* p_freepointer : 0xffffffff
Sg_File_Info* p_startOfConstruct : 0xa0a0df4
Sg_File_Info* p_endOfConstruct : 0xa0a0e20
AttachedPreprocessingInfoType* p_attachedPreprocessingInfoPtr : 0
AstAttributeMechanism* p_attributeMechanism : 0xa227e88
SgLabelRefExp* p_numeric_label : 0
int p_source_sequence_value : 1073
unsigned int o_decl_attributes : 0

```

Figure 42.8: Sample PDF showing attributes.

Chapter 43

TAU Instrumentation

Tau is a performance analysis tool from University of Oregon. They have mechanisms for automating instrumentation of the source code's text file directly, but these can be problematic in the presence of macros. We present an example of instrumentation combined with code generation to provide a more robust means of instrumentation for source code. This work is preliminary and depends upon two separate mechanisms for the rewrite of the AST (one high level using strings and one low level representing a more direct handling of the AST at the IR level).

43.1 Input For Examples Showing Information using Tau

Figure 43.1 shows the example input used for demonstration of Tau instrumentation.

43.2 Generating the code representing any IR node

Figure 43.2 shows a code that traverses each IR node and for a `SgInitializedName` of `SgStatement` output the scope information. The input code is shown in figure 43.2, the output of this code is shown in figure 43.3.

```

// #include <math.h>
2 // #include <stdlib.h>

4 double foo(double x)
5 {
6     double theValue = x;
7     theValue*= x;
8     return theValue;
9 }

10 int main(int argc, char* argv[])
11 {
12     int j,i;
13     double tSquared,t;
14     t = 1.0;
15
16     tSquared = t*t;
17
18     i = 1000;
19     for( j=1; j < i; j += 2)
20     {
21         tSquared += 1.0;
22         tSquared += foo(2.2);
23     }
24
25     return 0;
26 }
```

Figure 43.1: Example source code used as input to program in codes used in this chapter.

```

// Demonstration of instrumentation using the TAU performance monitoring tools (University of Oregon)
2
#include "rose.h"
4
using namespace std;
6
#define NEW_FILE_INFO Sg_File_Info::generateDefaultFileInfoForTransformationNode()
8
SgClassDeclaration*
10 getProfilerClassDeclaration (SgProject* project)
{
12     // Note that it would be more elegant to look this up in the Symbol table (do this next)

14     SgClassDeclaration* returnClassDeclaration = NULL;
    Rose_STL_Container<SgNode*> classDeclarationList = NodeQuery::querySubTree (project, V_SgClassDeclaration);
16     for (Rose_STL_Container<SgNode*>::iterator i = classDeclarationList.begin(); i != classDeclarationList.end(); i++)
    {
18         // Need to cast *i from SgNode to at least a SgStatement
        SgClassDeclaration* classDeclaration = isSgClassDeclaration(*i);
20         ROSE_ASSERT (classDeclaration != NULL);

22         // printf ("In getProfilerClassDeclaration(): classDeclaration->get_name() = %s \n", classDeclaration->get_name().s

24         if (classDeclaration->get_name() == "Profiler")
            returnClassDeclaration = classDeclaration;
26     }

28     ROSE_ASSERT(returnClassDeclaration != NULL);
    return returnClassDeclaration;
30 }

32
int
34 main( int argc, char * argv[] )
{
36     // This test code tests the AST rewrite mechanism to add TAU Instrumention to the AST.

38     SgProject* project = frontend(argc, argv);

40     // Output the source code file (as represented by the SAGE AST) as a PDF file (with bookmarks)
    // generatePDF(*project);
42
    // Output the source code file (as represented by the SAGE AST) as a DOT file (graph)
44     // generateDOT(*project);

46     // Allow ROSE translator options to influence if we transform the AST
    if ( project->get_skip_transformation() == false )
48     {
        // NOTE: There can be multiple files on the command line and each file has a global scope

50         MiddleLevelRewrite::ScopeIdentifierEnum scope
= MidLevelCollectionTypedefs::StatementScope;
52         MiddleLevelRewrite::PlacementPositionEnum locationInScope = MidLevelCollectionTypedefs::TopOfCurrentScope;

54         // Add a TAU include directive to the top of the global scope
        Rose_STL_Container<SgNode*> globalScopeList = NodeQuery::querySubTree (project, V_SgGlobal);
56         for (Rose_STL_Container<SgNode*>::iterator i = globalScopeList.begin(); i != globalScopeList.end(); i++)
        {
58             // Need to cast *i from SgNode to at least a SgStatement
            SgGlobal* globalScope = isSgGlobal(*i);
60             ROSE_ASSERT (globalScope != NULL);

62             // TAU does not seem to compile using EDG or g++ (need to sort this out with Brian)
            // MiddleLevelRewrite::insert(globalScope, "#define PROFILING_ON \n#include<TAU.h> \n", scope, locationInScope);
64             // MiddleLevelRewrite::insert(globalScope, "#include<TAU.h> \n", scope, locationInScope);
            MiddleLevelRewrite::insert(globalScope, "#define _PROFILING_ON_1_\n#define _TAU_STDCXXLIB_1_\n#include<TAU.h>");
66         }

68     #if 1
        // Now get the class declaration representing the TAU type with which to build variable declarations
        SgClassDeclaration* tauClassDeclaration = getProfilerClassDeclaration(project);
70         ROSE_ASSERT(tauClassDeclaration != NULL);
        SgClassType* tauType = tauClassDeclaration->get_type();
72         ROSE_ASSERT(tauType != NULL);

74         // Get a constructor to use with the variable declaration (anyone will due for code generation)
        SgMemberFunctionDeclaration* memberFunctionDeclaration = SageInterface::getDefaultConstructor(tauClassDeclaration);
76         ROSE_ASSERT(memberFunctionDeclaration != NULL);

78         // Add the instrumentation to each function
        Rose_STL_Container<SgNode*> functionDeclarationList = NodeQuery::querySubTree (project, V_SgFunctionDeclaration);
80         for (Rose_STL_Container<SgNode*>::iterator i = functionDeclarationList.begin(); i != functionDeclarationList.end(); i++)
        {
            SgFunctionDeclaration* functionDeclaration = isSgFunctionDeclaration(*i);
82

```

```
Test Failed!
```

Figure 43.3: Output of input code using tauInstrumenter.C

Chapter 44

The Haskell Interface

ROSE’s Haskell interface allows the user to analyse and transform the Sage III IR from Haskell, a statically typed pure functional programming language. See <http://www.haskell.org/>.

The interface exposes almost all Sage III APIs to Haskell, allowing the user to call whichever APIs are required. The interface also supports an AST traversal mechanism inspired by Haskell’s *scrap your boilerplate* design pattern.

The Haskell interface also provides a convenient mechanism for a user to rapidly experiment with the ROSE IR. GHC’s command-line interpreter `ghci` can be used to explore the IR interactively by invoking API methods at will.

The Haskell interface relies on the Glasgow Haskell Compiler (GHC). It is auto-configured so long as the GHC binaries are in your `$PATH`. If not, you will need to supply the path to the binaries at configure time with the option `--with-haskell=bindir`, where *bindir* is the path to GHC’s `bin` directory.

After installation, ROSE is available as a standard Haskell package named `rose`. This means that you can supply the flag `-package rose` to the Haskell compiler in order to make the extension available for use.

To understand the usage of the interface, it is crucial to grasp how the concept of *monads* works in Haskell. For a useful tutorial on monads, the reader is referred to the “All About Monads” tutorial found at http://www.haskell.org/all_about_monads/.

The simplest Haskell-based ROSE program is the identity translator, whose code is listed in Figure 44.1.

```

1  module Main where
2
3  import ROSE
4  import System
5
6  main = do
7      project <- frontend ==<< getArgs
8      exitWith ==<< backend project
```

Figure 44.1: Haskell version of identity translator.

44.1 Traversals

As previously mentioned, the traversal mechanism is inspired by the scrap-your-boilerplate pattern. Our implementation of the scrap-your-boilerplate pattern provides both *transformation* and *query* traversals. A transformation traversal applies a global transformation to a tree by applying a given function to each tree node, whereas a query traversal derives a result from a tree using a function that produces a result from a node together with a *combinator* which combines the results from several nodes (for example in a summation query, the combinator may be the addition function).

In order to carry out a traversal, two steps are necessary. Firstly one must build a *type extension*, a type-generic function built from one or more type-specific functions. Secondly one must employ a *generic traversal combinator* which applies the type extension throughout the program.

In our interface type extensions for transformations are built using the functions `mkMn`, which builds a type extension from a type-specific function, and `extMn`, which extends an existing type extension with a type-specific function. Likewise `mkMqn` and `extMqn` for queries. These functions perform static and dynamic type checking such that they will only call the type-specific functions when it is safe to do so.

The two generic traversal combinators are `everywhereMc` and `everythingMc`. They take two arguments: the type extension and the tree to be traversed. `everywhereMc` returns the transformed tree, and `everythingMc` the result of the query.

Tying everything together, Figure 44.2 shows an example of a simple constant folding transformation.

44.2 Further Reading

Reference documentation for the interface is available on ROSE's website at:

http://www.rosecompiler.org/ROSE_HaskellAPI/

```

2  module Main where
3
4  import Data.Maybe
5  import Control.Monad
6  import System
7  import Data.DataMc
8  import ROSE
9  import ROSE.Sage3
10 import Time
11
12 simplifyAddOp :: SgAddOp () -> IO (SgExpression ())
13 simplifyAddOp = simplify (+)
14
15 simplifySubtractOp :: SgSubtractOp () -> IO (SgExpression ())
16 simplifySubtractOp = simplify (-)
17
18 simplifyMultiplyOp :: SgMultiplyOp () -> IO (SgExpression ())
19 simplifyMultiplyOp = simplify (*)
20
21 simplifyDivideOp :: SgDivideOp () -> IO (SgExpression ())
22 simplifyDivideOp = simplify div
23
24 simplify op n | n == nullSgNode = return (upSgExpression n)
25               | otherwise = do
26   lhs <- binaryOpGetLhsOperand n
27   rhs <- binaryOpGetRhsOperand n
28   lhsInt <- isSgIntVal lhs
29   rhsInt <- isSgIntVal rhs
30   if isJust lhsInt && isJust rhsInt then do
31     lhsVal <- intValGetValue (fromJust lhsInt)
32     rhsVal <- intValGetValue (fromJust rhsInt)
33     let sum = lhsVal `op` rhsVal
34     fi <- sgNullFile
35     liftM upSgExpression (newIntVal fi sum (show sum))
36   else
37     return (upSgExpression n)
38
39 main :: IO ()
40 main = do
41   time1 <- getClockTime
42   prj <- frontend ==<< getArgs
43   time2 <- getClockTime
44   putStrLn ("Frontend took " ++ show (diffClockTimes time2 time1))
45   everywhereMc (mkMn simplifyAddOp 'extMn' simplifySubtractOp
46                 'extMn' simplifyMultiplyOp 'extMn' simplifyDivideOp) prj
47   time3 <- getClockTime
48   putStrLn ("Traversal took " ++ show (diffClockTimes time3 time2))
49   exitWith ==<< backend prj

```

Figure 44.2: Haskell version of constant folding transformation.

Part VIII

Parallelism

Topics relevant to shared or distributed parallel computing using ROSE.

Chapter 45

Shared-Memory Parallel Traversals

Besides the traversal classes introduced in Chapter 8, ROSE also includes classes to run multi-threaded traversals to make use of multi-CPU systems with shared memory (such as typical multicore desktop systems). These shared memory traversals are like the combined traversal classes in that they run several small traversal classes simultaneously; the difference is that here different visit functions may be executed concurrently on different CPUs, while the combined traversals always execute visit functions sequentially.

Because of this similarity, the public interface for the parallel traversals is a superset of the combined traversal interface. For each `Ast*Processing` class there is an `AstSharedMemoryParallel*Processing` class that provides an interface for adding traversals to its internal list, getting a reference to the internal list, and for starting the combined traversal. The `traverse()` method performs the same combined traversal as in the corresponding `AstCombined*Processing` class, and the new `traverseInParallel()` method (with the same signature as `traverse()`) must be used to start a parallel traversal. (We currently do not provide `traverseWithinFileInParallel()` and `traverseInputFilesInParallel()` that would be needed to make the parallel processing classes a fully-featured drop-in replacement for other classes.)

A example of how to use the parallel traversal classes is given in Figure 45.1 (note the similarity to Figure 8.24 on page 62). A group of traversal objects is executed first in combined mode and then in parallel threads.

It is the user's responsibility to make sure that the actions executed in the parallel traversal are thread-safe. File or terminal I/O may produce unexpected results if several threads attempt to write to the same stream at once. Allocation of dynamic memory (including the use of ROSE or standard C++ library calls that allocate memory) may defeat the purpose of multi-threading as such calls will typically be serialized by the library.

Two member functions in each `AstSharedMemoryParallel*Processing` class are available to tune the performance of the parallel traversals. The first is `void set_numberOfThreads(size_t threads)` which can be used to set the number of parallel threads. The default value for this parameter is 2. Our experiments suggest that even on systems with more than two CPUs, running more than two traversal threads in parallel does not typically increase performance

```

#include <rose.h>
2
class NodeTypeTraversal: public AstSimpleProcessing {
4 public:
    NodeTypeTraversal(enum VariantT variant, std::string typeName)
        : myVariant(variant), typeName(typeName) {
6     }
8
protected:
10     virtual void visit(SgNode *node) {
        if (node->variantT() == myVariant) {
12             std::cout << "Found_" << typeName;
            if (SgLocatedNode *loc = isSgLocatedNode(node)) {
14                 Sg_File_Info *fi = loc->get_startOfConstruct();
                if (fi->isCompilerGenerated()) {
16                     std::cout << ":-_compiler_generated";
                } else {
18                     std::cout << ":-_" << fi->get_filenameString()
                        << ":-_" << fi->get_line();
20                 }
            }
22             std::cout << std::endl;
        }
24     }

private:
26     enum VariantT myVariant;
28     std::string typeName;
    };
30
int main(int argc, char **argv) {
32     SgProject *project = frontend(argc, argv);

34     std::cout << "combined_execution_of_traversals" << std::endl;
    AstSharedMemoryParallelSimpleProcessing parallelTraversal(5);
36     parallelTraversal.addTraversal(new NodeTypeTraversal(V_SgForStatement, "for_loop"));
    parallelTraversal.addTraversal(new NodeTypeTraversal(V_SgIntVal, "int_constant"));
38     parallelTraversal.addTraversal(new NodeTypeTraversal(V_SgVariableDeclaration, "variable_declaration"));
    parallelTraversal.traverse(project, preorder);
40     std::cout << std::endl;

42     std::cout << "shared-memory_parallel_execution_of_traversals" << std::endl;
    parallelTraversal.traverseInParallel(project, preorder);
44 }

```

Figure 45.1: Example source showing the shared-memory parallel execution of traversals.

because the memory bandwidth is saturated.

The second function is `void set_synchronizationWindowSize(size_t windowSize)`. This sets a parameter that corresponds to the size of a ‘window’ of AST nodes that the parallel threads use to synchronize. The value is, in effect, the number of AST nodes that are visited by each thread before synchronizing. Smaller values may in theory result in more locality and therefore better cache utilization at the expense of more time spent waiting for other threads. In practice, synchronization overhead appears to dominate caching effects, so making this parameter too small inhibits performance. The default value is 100000; any large values will result in comparable execution times.


```

combined execution of traversals
2 Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:17
4 Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
Found for loop: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:20
6 Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:20
8 Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:20
Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
10 Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:27
Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:29
12 Found variable declaration: compiler generated
Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:34
14 Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:38
16 Found for loop: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:41
Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
18 Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:41
Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:41
20 Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:46
22
shared-memory parallel execution of traversals
24 Found for loop: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:20
Found for loop: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:41
26 Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:17
Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:20
28 Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:20
Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:27
30 Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:29
Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:34
32 Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:38
Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:41
34 Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:41
Found int constant: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_18.C:46
36 Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
38 Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
40 Found variable declaration: compiler generated
Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
42 Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1
Found variable declaration: /home/liao6/daily-test-rose/20091101_120001/sourcetree/tutorial/inputCode_ExampleTraversals_1

```

Figure 45.2: Output of input file to the shared-memory parallel traversals. Output may be garbled depending on the multi-threaded behavior of the underlying I/O libraries.

Chapter 46

Distributed-Memory Parallel Traversals

ROSE provides an experimental distributed-memory AST traversal mechanism meant for very large scale program analysis. It allows you to distribute expensive program analyses among a distributed-memory system consisting of many processors; this can be a cluster or a network of workstations. Different processes in the distributed system will get different parts of the AST to analyze: Each process is assigned a number of defining function declarations in the AST, and a method implemented by the user is invoked on each of these. The parts of the AST outside of function definitions are shared among all processes, but there is no guarantee that all function definitions are visible to all processes.

The distributed memory analysis framework uses the MPI message passing library for communicating attributes among processes. You will need an implementation of MPI to be able to build and run programs using distributed memory traversals; consult your documentation on how to run MPI programs. (This is often done using a program named `mpirun`, `mpiexecute`, or similar.)

Distributed memory analyses are performed in three phases:

1. A top-down traversal (the ‘pre-traversal’) specified by the user runs on the shared AST outside of function definitions. The inherited attributes this traversal computes for defining function declaration nodes in the AST are saved by the framework for use in the next phase.
2. For every defining function declaration, the user-provided `analyzeSubtree()` method is invoked; these calls run concurrently, but on different function declarations, on all processors. It takes as arguments the AST node for the function declaration and the inherited attribute computed for this node by the pre-traversal. Within `analyzeSubtree()` any analysis features provided by ROSE can be used. This method returns the value that will be used as the synthesized attribute for this function declaration in the bottom-up traversal (the ‘post-traversal’).

However, unlike normal bottom-up traversals, the synthesized attribute is not simply copied in memory as the AST is distributed. The user must therefore provide the methods `serializeAttribute()` and `deserializeAttribute()`. These compute a serialized

representation of a synthesized attribute, and convert such a representation back to the user's synthesized attribute type, respectively. A serialized attribute is a pair of an integer specifying the size of the attribute in bytes and a pointer to a region of memory of that size that will be copied byte by byte across the distributed system's communication network. Attributes from different parts of the AST may have different sizes. As serialization of attributes will often involve dynamic memory allocation, the user can also implement the `deleteSerializedAttribute()` method to such dynamic memory after the serialized data has been copied to the communication subsystem's internal buffer.

Within the `analyzeSubtree()` method the methods `numberOfProcesses()` and `myID()` can be called. These return the total number of concurrent processes, and an integer uniquely identifying the currently running process, respectively. The ID ranges from 0 to one less than the number of processes, but has no semantics other than that it is different for each process.

3. Finally, a bottom-up traversal is run on the shared AST outside of function definitions. The values returned by the distributed analyzers in the previous phase are used as synthesized attributes for function definition nodes in this traversal.

After the bottom-up traversal has finished, the `getFinalResults()` method can be invoked to obtain the final synthesized attribute. The `isRootProcess()` method returns true on exactly one designated process and can be used to perform output, program transformations, or other tasks that are not meant to be run on each processor.

Figure 46.1 gives a complete example of how to use the distributed memory analysis framework. It implements a trivial analysis that determines for each function declaration at what depth in the AST it can be found and what its name is. Figure 46.2 shows the output produced by this program when running using four processors on some input files.

```

2 // This is a small example of how to use the distributed memory traversal mechanism. It computes a list of function
  // definitions in a program and outputs their names, their depth in the AST, and the ID of the process that found it.

4 #include <rose.h>
  #include "DistributedMemoryAnalysis.h"

6 // The pre-traversal runs before the distributed part of the analysis and is used to propagate context information down
  // to the individual function definitions in the AST. Here, it just computes the depth of nodes in the AST.
8 class FunctionNamesPreTraversal: public AstTopDownProcessing<int>
10 {
11 protected:
12     int evaluateInheritedAttribute(SgNode *, int depth)
13     {
14         return depth + 1;
15     }
16 };

18 // The post-traversal runs after the distributed part of the analysis and is used to collect the information it
  // computed. Here, the synthesized attributes computed by the distributed analysis are strings representing information
  // about functions. These strings are concatenated by the post-traversal (and interleaved with newlines where necessary).
20 class FunctionNamesPostTraversal: public AstBottomUpProcessing<std::string>
22 {
23 protected:
24     std::string evaluateSynthesizedAttribute(SgNode *node, SynthesizedAttributesList synAttributes)
25     {
26         std::string result = "";
27         SynthesizedAttributesList::iterator s;
28         for (s = synAttributes.begin(); s != synAttributes.end(); ++s)
29         {
30             std::string &str = *s;
31             result += str;
32             if (str.size() > 0 && str[str.size()-1] != '\n')
33                 result += "\n";
34         }
35         return result;
36     }

38     std::string defaultSynthesizedAttribute()
39     {
40         return "";
41     }
42 };

44 // This is the distributed part of the analysis. The DistributedMemoryTraversal base class is a template taking an
  // inherited and a synthesized attribute type as template parameters; these are the same types used by the pre- and
  // post-traversals.
46 class FunctionNames: public DistributedMemoryTraversal<int, std::string>
48 {
49 protected:
50     // The analyzeSubtree() method is called for every defining function declaration in the AST. Its second argument is the
  // inherited attribute computed for this node by the pre-traversal, the value it returns becomes the synthesized
  // attribute used by the post-traversal.
52     std::string analyzeSubtree(SgFunctionDeclaration *funcDecl, int depth)
53     {
54         std::string funcName = funcDecl->get_name().str();
55         std::stringstream s;
56         s << "process_" << myID() << ":_at_depth_" << depth << ":_function_" << funcName;
57         return s.str();
58     }

60 // The user must implement this method to pack a synthesized attribute (a string in this case) into an array of bytes
  // for communication. The first component of the pair is the number of bytes in the buffer.
62     std::pair<int, void*> serializeAttribute(std::string attribute) const
63     {
64         int len = attribute.size() + 1;
65         char *str = strdup(attribute.c_str());
66         return std::make_pair(len, str);
67     }

70 // This method must be implemented to convert the serialized data to the application's synthesized attribute type.
  std::string deserializeAttribute(std::pair<int, void*> serializedAttribute) const
72 {
73     return std::string((const char *) serializedAttribute.second);
74 }

76 // This method is optional (the default implementation is empty). Its job is to free memory that may have been
  // allocated by the serializeAttribute() method.
78     void deleteSerializedAttribute(std::pair<int, void*> serializedAttribute) const
79     {
80         std::free(serializedAttribute.second);
81     }
82 };

```

```
----- found the following functions: -----  
process 0: at depth 3: function il  
process 0: at depth 5: function head  
process 0: at depth 5: function eq  
process 1: at depth 3: function headhead  
process 1: at depth 3: function List  
process 1: at depth 3: function find  
process 1: at depth 3: function head  
process 2: at depth 3: function operator!=  
process 2: at depth 3: function find  
process 2: at depth 3: function head  
process 2: at depth 3: function fib  
process 3: at depth 3: function xform  
process 3: at depth 3: function func  
process 3: at depth 3: function f  
process 3: at depth 3: function g  
process 3: at depth 3: function deref  
-----
```

Figure 46.2: Example output of a distributed-memory analysis running on four processors.

Chapter 47

Parallel Checker

This Chapter is about the project *DistributedMemoryAnalysisCompass*, which runs Compass Checkers in Parallel, i.e. shared, combined and distributed.

47.1 Different Implementations

The project contains the following files:

- `parallel_functionBased_ASTBalance` contains the original implementation, which is based on an AST traversal that is balanced based on the number of nodes in each function. Then the functions are distributed over all processors. It contains as well the original interfaces to the shared and combined traversal work.
- `parallel_file_compass` distributed on the granularity level of files.
- `parallel_functionBased_dynamicBalance` is the implementation of dynamically scheduling functions across processors. In addition, this algorithm weights the functions first and then sorts them in descending order according to their weight.
- `parallel_compass` performs dynamic scheduling based on nodes. The nodes are weighted and then sorted. This algorithm allows the greatest scalability.

47.2 Running through PSUB

The following represents a typical script to run `parallel_compass` on 64 processors using `CXX_Grammer`. `CXX_Grammer` is a binary ROSE AST representation of a previously parsed program. We specify 65 processors because processor 0 does only communication and no computation. Furthermore, we ask for 17 nodes of which each has 8 processors giving us a total of 136 possible processes. We only need 65 but still want to use this configuration. This will average out our 65 processes over 17 nodes, resulting in about 4 processors per node. This trick is used because the AST loaded into memory takes about 400 MB per process. We end up with 1600MB per node.

```
#!/bin/bash
# Sample LCRM script to be submitted with psub
#PSUB -r ncxx65 # sets job name (limit of 7 characters)
#PSUB -b nameofbank # sets bank account
#PSUB -ln 17 # == defines the amount of nodes needed
#PSUB -o ~/log.log
#PSUB -e ~/log.err
#PSUB -tM 0:05 # Max time 5 min runtime
#PSUB -x # export current env var settings
#PSUB -nr # do NOT rerun job after system reboot
#PSUB -ro # send output log directly to file
#PSUB -re # send err log directly to file
#PSUB -mb # send email at execution start
#PSUB -me # send email at execution finish
#PSUB -c zeus
#PSUB # no more psub commands
# job commands start here
set echo
echo LCRM job id = $PSUB_JOBID
cd ~/new-src/build-rose/projects/DistributedMemoryAnalysisCompass/
srun -n 65 ./parallel_compass -load ~/CXX_Grammar.ast
echo "ALL DONE"
```

There are a few tricks that could be considered. Prioritization is based on the amount of time and nodes requested. If less time is specified, it is more likely that a job runs very soon, as processing time becomes available.

To submit the job above, use *psub file-name*. To check the job in the queue, use *squeue* and to cancel the job use *mjobctl -c job-number*.

Chapter 48

Reduction Recognition

Figure 48.1 shows a translator which finds the first loop of a main function and recognizes reduction operations and variables within the loop. A reduction recognition algorithm (`ReductionRecognition()`) is implemented in the `SageInterface` namespace and follows the C/C++ reduction restrictions defined in the OpenMP 3.0 specification.

```
2  // Test reduction recognition
3  #include "rose.h"
4  #include <iostream>
5  #include <set>
6
7  using namespace std;
8
9  int main(int argc, char * argv[])
10 {
11     SgProject *project = frontend (argc, argv);
12     //Find main() function
13     SgFunctionDeclaration* func = SageInterface::findMain(project);
14     ROSE_ASSERT(func != NULL);
15     SgBasicBlock* body = func->get_definition()->get_body();
16
17     //Find the first loop
18     Rose_STL_Container<SgNode*> node_list = NodeQuery::querySubTree(body, V_SgForStatement);
19     SgForStatement* loop = isSgForStatement(*(node_list.begin()));
20     ROSE_ASSERT(loop != NULL);
21
22     //Collect reduction variables and operations
23     std::set< std::pair< SgInitializedName*, VariantT> > reductions;
24     std::set< std::pair< SgInitializedName*, VariantT> >::const_iterator iter;
25     SageInterface::ReductionRecognition(loop, reductions);
26
27     // Show the results
28     cout<<"Reduction_recognition_results:"<<endl;
29     for (iter=reductions.begin(); iter!=reductions.end(); iter++)
30     {
31         std::pair< SgInitializedName*, VariantT> item = *iter;
32         cout<<"\tvariable:_"<<item.first->unparseToString()<<"\toperation:"<<getVariantName(item.second)<<endl;
33     }
34     return backend(project);
35 }
```

Figure 48.1: Example source code showing reduction recognition.

Using this translator we can compile the code shown in figure 48.2. The output is shown in figure 48.3.

```

    int a[100], sum;
2  int main()
    {
4      int i, sum2, yy, zz;
        sum = 0;
6      for (i=0; i<100; i++)
        {
8          int xx;
            a[i]=i;
10         sum = a[i]+ sum;
            xx++;
12         yy=0;
            yy--;
14         zz*=a[i];
        }
16     return 0;
    }

```

Figure 48.2: Example source code used as input to loop reduction recognition processor.

```

Reduction recognition results:
2      variable: sum    operation:SgAddOp
      variable: zz     operation:SgMultAssignOp

```

Figure 48.3: Output of input to reduction recognition processor.

Part IX

Tutorial Summary

Summary of the ROSE tutorials.

Chapter 49

Tutorial Wrap-up

This tutorial has shown the construction and simple manipulation of the AST as part of the construction of the source-to-source translators using ROSE. Much more complex translators are possible using ROSE, but they are not such that they present well as part of a tutorial with short example programs. The remaining chapters of the tutorial include examples of translators built using ROSE as part of active collaborations with external research groups.

FIXME: *Reference the User Manual, HTML Doxygen generated documentation, unresolved issues, etc. Reference other work currently using ROSE (ANL, Cornell in the future), academic collaborations.*

Appendix

This appendix includes information useful in supporting the ROSE Tutorial.

49.1 Location of To Do List

This was an older location for the Tutorial Tod List. We now keep the Tod list in the `ROSE/docs/testDoxygen/ProjectToDoList.docs` in the section called: `ROSE Tutorial Todo List`.

49.2 Abstract Grammar

In this section we show an abstract grammar for the ROSE AST. The grammar generates the set of all ASTs. On the left hand side of a production we have a non-terminal that corresponds to an inner node of the class hierarchy. On the right hand side of a production we have either one non-terminal or one terminal. The terminal corresponds to a leaf-node where the children of the respective node are listed as double-colon separated pairs, consisting of an access name (= name for get function) and a name that directly corresponds to the class of the child. Details like pointers are hidden. The asterisk shows where lists of children (containers) are used in the ROSE AST. For each terminal, a name followed by '(' and ')', a variant exists in ROSE with the prefix `V_` that can be obtained by using the function `variantT()` on a node. Note, that concrete classes of AST nodes directly correspond to terminals and base classes to non-terminals.

```
START:SgNode
SgNode : SgSupport
      | SgLocatedNode
      | SgSymbol
      ;

SgSupport : SgName()
          | SgSymbolTable()
          | SgInitializedName ( initptr:SgInitializer )
          | SgFile ( root:SgGlobal ( declarations:SgDeclarationStatement* ) )
          | SgProject ( fileList:SgFile ( root:SgGlobal ( declarations:SgDeclarationStatement* ) ) )
          | SgOptions()
          | SgBaseClass ( base_class:SgClassDeclaration )
          | SgTemplateParameter ( expression:SgExpression, defaultExpressionParameter:SgExpression,
```

```

        templateDeclaration:SgTemplateDeclaration(),
        defaultTemplateDeclarationParameter:SgTemplateDeclaration() )
| SgTemplateArgument ( expression:SgExpression,
        templateInstantiation:SgTemplateInstantiationDecl
        ( definition:SgClassDefinition ) )
| SgFunctionParameterTypeList()
| SgAttribute
| SgModifier
;

SgAttribute : SgPragma()
| SgBitAttribute
;

SgBitAttribute : SgFuncDecl_attr()
| SgClassDecl_attr()
;

SgModifier : SgModifierNodes()
| SgConstVolatileModifier()
| SgStorageModifier()
| SgAccessModifier()
| SgFunctionModifier()
| SgUPC_AccessModifier()
| SgSpecialFunctionModifier()
| SgElaboratedTypeModifier()
| SgLinkageModifier()
| SgBaseClassModifier()
| SgDeclarationModifier()
;

SgLocatedNode : SgStatement
| SgExpression
;

SgStatement : SgExprStatement ( expression_root:SgExpressionRoot ( operand_i:SgExpression ) )
| SgLabelStatement()
| SgCaseOptionStmt ( key_root:SgExpressionRoot ( operand_i:SgExpression ),
        body:SgBasicBlock ( statements:SgStatement* ) )
| SgTryStmt ( body:SgBasicBlock ( statements:SgStatement* ),
        catch_statement_seq_root:SgCatchStatementSeq ( catch_statement_seq:SgStatement* ) )
| SgDefaultOptionStmt ( body:SgBasicBlock ( statements:SgStatement* ) )
| SgBreakStmt()
| SgContinueStmt()
| SgReturnStmt ( expression_root:SgExpressionRoot ( operand_i:SgExpression ) )
| SgGotoStatement()

```



```

| SgSpawnStmt ( the_func_root:SgExpressionRoot ( operand_i:SgExpression ) )
| SgForInitStatement ( init_stmt:SgStatement* )
| SgCatchStatementSeq ( catch_statement_seq:SgStatement* )
| SgClinkageStartStatement()
| SgDeclarationStatement
| SgScopeStatement
;

SgDeclarationStatement :
    SgVariableDeclaration ( variables:SgInitializedName ( initptr:SgInitializer ) )
  | SgVariableDefinition ( vardefn:SgInitializedName ( initptr:SgInitializer ),
                        bitfield:SgUnsignedLongVal() )
  | SgEnumDeclaration()
  | SgAsmStmt ( expr_root:SgExpressionRoot ( operand_i:SgExpression ) )
  | SgTemplateDeclaration()
  | SgNamespaceDeclarationStatement ( definition:SgNamespaceDefinitionStatement
                                    ( declarations:SgDeclarationStatement* )
                                    )
  | SgNamespaceAliasDeclarationStatement()
  | SgUsingDirectiveStatement()
  | SgUsingDeclarationStatement()
  | SgFunctionParameterList ( args:SgInitializedName ( initptr:SgInitializer ) )
  | SgCtorInitializerList ( ctors:SgInitializedName ( initptr:SgInitializer ) )
  | SgPragmaDeclaration ( pragma:SgPragma() )
  | SgClassDeclaration
  | SgFunctionDeclaration
;

SgClassDeclaration : SgTemplateInstantiationDecl ( definition:SgClassDefinition )
;

SgFunctionDeclaration :
    SgTemplateInstantiationFunctionDecl ( parameterList:SgFunctionParameterList
                                       ( args:SgInitializedName ( initptr:SgInitializer ) ),
                                       definition:SgFunctionDefinition
                                       ( body:SgBasicBlock ( statements:SgStatement* ) )
                                       )
  | SgMemberFunctionDeclaration
;

SgMemberFunctionDeclaration :
    SgTemplateInstantiationMemberFunctionDecl ( parameterList:SgFunctionParameterList
                                              ( args:SgInitializedName ( initptr:SgInitializer ) ),
                                              definition:SgFunctionDefinition
                                              ( body:SgBasicBlock ( statements:SgStatement* ) ),
                                              CtorInitializerList:SgCtorInitializerList
    )

```

```

                                ( ctors:SgInitializedName ( initptr:SgInitializer
                                )
;

SgScopeStatement : SgGlobal ( declarations:SgDeclarationStatement* )
| SgBasicBlock ( statements:SgStatement* )
| SgIfStmt ( conditional:SgStatement,
            true_body:SgBasicBlock ( statements:SgStatement* ),
            false_body:SgBasicBlock ( statements:SgStatement* ) )
| SgForStatement ( for_init_stmt:SgForInitStatement ( init_stmt:SgStatement* ),
                  test_expr_root:SgExpressionRoot ( operand_i:SgExpression ),
                  increment_expr_root:SgExpressionRoot ( operand_i:SgExpression ),
                  loop_body:SgBasicBlock ( statements:SgStatement* ) )
| SgFunctionDefinition ( body:SgBasicBlock ( statements:SgStatement* ) )
| SgWhileStmt ( condition:SgStatement, body:SgBasicBlock ( statements:SgStatement* ) )
| SgDoWhileStmt ( condition:SgStatement, body:SgBasicBlock ( statements:SgStatement* ) )
| SgSwitchStatement ( item_selector_root:SgExpressionRoot ( operand_i:SgExpression ),
                     body:SgBasicBlock ( statements:SgStatement* ) )
| SgCatchOptionStmt ( condition:SgVariableDeclaration
                     ( variables:SgInitializedName ( initptr:SgInitializer ) ),
                     body:SgBasicBlock ( statements:SgStatement* ) )
;

SgClassDefinition : SgTemplateInstantiationDefn ( members:SgDeclarationStatement* )
;

SgExpression : SgExprListExp ( expressions:SgExpression* )
| SgVarRefExp()
| SgClassNameRefExp()
| SgFunctionRefExp()
| SgMemberFunctionRefExp()
| SgFunctionCallExp ( function:SgExpression, args:SgExprListExp ( expressions:SgExpression* ) )
| SgSizeOfOp ( operand_expr:SgExpression )
| SgConditionalExp ( conditional_exp:SgExpression,
                    true_exp:SgExpression,
                    false_exp:SgExpression )
| SgNewExp ( placement_args:SgExprListExp ( expressions:SgExpression* ),
            constructor_args:SgConstructorInitializer(
                                args:SgExprListExp(expressions:SgExpression*)
                                ),
            builtin_args:SgExpression )
| SgDeleteExp ( variable:SgExpression )
| SgThisExp()

```

```

| SgRefExp()
| SgVarArgStartOp ( lhs_operand:SgExpression, rhs_operand:SgExpression )
| SgVarArgOp ( operand_expr:SgExpression )
| SgVarArgEndOp ( operand_expr:SgExpression )
| SgVarArgCopyOp ( lhs_operand:SgExpression, rhs_operand:SgExpression )
| SgVarArgStartOneOperandOp ( operand_expr:SgExpression )
| SgInitializer
| SgValueExp
| SgBinaryOp
| SgUnaryOp
;

SgInitializer :
    SgAggregateInitializer ( initializers:SgExprListExp ( expressions:SgExpression* ) )
    | SgConstructorInitializer ( args:SgExprListExp ( expressions:SgExpression* ) )
    | SgAssignInitializer ( operand_i:SgExpression )
;

SgValueExp : SgBoolValExp()
| SgStringVal()
| SgShortVal()
| SgCharVal()
| SgUnsignedCharVal()
| SgWcharVal()
| SgUnsignedShortVal()
| SgIntVal()
| SgEnumVal()
| SgUnsignedIntVal()
| SgLongIntVal()
| SgLongLongIntVal()
| SgUnsignedLongLongIntVal()
| SgUnsignedLongVal()
| SgFloatVal()
| SgDoubleVal()
| SgLongDoubleVal()
;

SgBinaryOp : SgArrowExp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgDotExp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgDotStarOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgArrowStarOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgEqualityOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgLessThanOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgGreaterThanOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgNotEqualOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgLessOrEqualOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )

```

```

| SgGreaterOrEqualOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgAddOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgSubtractOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgMultiplyOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgDivideOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgIntegerDivideOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgModOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgAndOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgOrOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgBitXorOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgBitAndOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgBitOrOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgCommaOpExp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgLshiftOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgRshiftOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgPtrArrRefExp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgScopeOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgAssignOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgPlusAssignOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgMinusAssignOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgAndAssignOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgIorAssignOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgMultAssignOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgDivAssignOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgModAssignOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgXorAssignOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgLshiftAssignOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
| SgRshiftAssignOp ( lhs_operand_i:SgExpression, rhs_operand_i:SgExpression )
;

SgUnaryOp : SgExpressionRoot ( operand_i:SgExpression )
| SgMinusOp ( operand_i:SgExpression )
| SgUnaryAddOp ( operand_i:SgExpression )
| SgNotOp ( operand_i:SgExpression )
| SgPointerDerefExp ( operand_i:SgExpression )
| SgAddressOfOp ( operand_i:SgExpression )
| SgMinusMinusOp ( operand_i:SgExpression )
| SgPlusPlusOp ( operand_i:SgExpression )
| SgBitComplementOp ( operand_i:SgExpression )
| SgCastExp ( operand_i:SgExpression )
| SgThrowOp ( operand_i:SgExpression )
;

SgSymbol : SgVariableSymbol()
| SgClassSymbol ( declaration:SgClassDeclaration )
| SgTemplateSymbol ( declaration:SgTemplateDeclaration() )

```

```

| SgEnumSymbol ( declaration:SgEnumDeclaration() )
| SgEnumFieldSymbol()
| SgLabelSymbol ( declaration:SgLabelStatement() )
| SgDefaultSymbol()
| SgNamespaceSymbol ( declaration:SgNamespaceDeclarationStatement
                      ( definition:SgNamespaceDefinitionStatement
                        ( declarations:SgDeclarationStatement* )
                      )
                      )
| SgFunctionSymbol
;

SgFunctionSymbol : SgMemberFunctionSymbol ( declaration:SgFunctionDeclaration )
;

SgPartialFunctionType :
    SgPartialFunctionModifierType ( ref_to:SgReferenceType, ptr_to:SgPointerType,
                                    modifiers:SgModifierNodes(), typedefs:SgTypedefSeq,
                                    return_type:SgType, orig_return_type:SgType )
;

```

This grammar was generated with GRATO, a grammar transformation tool, written by Markus Schordan. The input is a representation generated by ROSETTA. Several other versions of the grammar can be generated as well, such as eliminating nested tree nodes by introducing auxiliary non-terminals, introducing base types as non-terminals etc. Additionally from that grammar we can also generate grammars that can be used with yacc/bison, Coco, and other attribute grammar tools, as well as tree grammar based tools such as burg (requires a transformation to a binary tree).

Glossary

We define terms used in the ROSE manual which might otherwise be unclear.

FIXME: Define the following terms: *IR node, Inherited Attribute, Synthesized Attribute, Accumulator Attribute, AST Traversal*

- **AST** Abstract Syntax Tree. A very basic understanding of an AST is the entry level into ROSE.
- **Attribute** User defined information (objects) associated with IR nodes. Forms of attributes include: accumulator, inherited, persistent, and synthesized. Both inherited and synthesized attributes are managed automatically on the stack within a traversal. Accumulator attributes are typically something semantically equivalent to a global variable (often a static data member of a class). Persistent attributes are explicitly added to the AST and are managed directly by the user. As a result, they can persist across multiple traversals of the AST. Persistent attributes are also saved in the binary file I/O, but only if the user provides the attribute specific `pack()` and `unpack()` virtual member functions. See the ROSE User Manual for more information, and the ROSE Tutorial for examples.
- **CFG** As used in ROSE, this is the Control Flow Graph, not Context Free Grammar or anything else.
- **EDG** Edison Design Group (the commercial company that produces the C and C++ front-end that is used in ROSE).
- **IR** Intermediate Representation (IR). The IR is the set of classes defined within SAGE III that allow an AST to be built to define any application in C, C++, and Fortran application.
- **Query** (as in AST Query) Operations on the AST that return answers to questions posed about the content or context in the AST.
- **ROSE** A project that covers both research in optimization and a specific infrastructure for handling large scale C, C++, and Fortran applications.
- **Rosetta** A tool (written by the ROSE team) used within ROSE to automate the generation of the SAGE III IR.
- **SAGE++ and SAGE II** An older object-oriented IR upon which the API of SAGE III IR is based.
- **Semantic Information** What abstractions mean (short answer). (This might be better as a description of what kind of semantic information ROSE could take advantage, not a definition.)

- **Telescoping Languages** A research area that defines a process to generate domain-specific languages from a general purpose languages.
- **Transformation** The process of automating the editing (either reconfiguration, addition, or deletion; or some combination) of input application parts to build a new application. In the context of ROSE, all transformations are source-to-source.
- **Translator** An executable program (in our context built using ROSE) that performs source-to-source translation on an existing input application source to generate a second (generated) source code file. The second (generated) source code is then typically provided as input to a vendor provided compiler (which generates object code or an executable program).
- **Traversal** The process of operating on the AST in some order (usually pre-order, post-order, out of order [randomly], depending on the traversal that is used). The ROSE user builds a traversal from base classes that do the traversal and execute a function, or a number of functions, provided by the user.