

Templates (Beta)

By: Mosh Hamedani

Showing / hiding elements

```
<div [hidden]="courses.length == 0"></div>
```

```
<div *ngIf="courses.length > 0"></div>
```

```
<div [ngSwitch]="viewMode">
  <template [ngSwitchWhen]="‘map’" ngSwitchDefault>
    ...
  </template>
  <template [ngSwitchWhen]="‘list’">
    ...
  </template>
</div>
```

Pipes

```
{{ course.title | uppercase }} -> ANGULAR COURSE
{{ course.students | number }} -> 1,234
{{ course.rating | number:'2.2-2' }} -> 04.97
{{ course.price | currency:'USD':true }} -> $99.95
{{ course.releaseDate | date:'MMM yyyy' }} -> Mar 2016
{{ course | json }}
```

Templates (Beta)

By: Mosh Hamedani

Creating Custom Pipes

```
import {Pipe, PipeTransform} from 'angular2/core';
```

```
@Pipe({ name: 'summary' })
export class SummaryPipe implements PipeTransform {
    transform(value: string, args: string[]) {
    }
}
```

In the host component

```
@Component({
    pipes: [SummaryPipe]
})
```

Applying multiple classes dynamically

```
<i [ngClass]="{
    active: isActive,
    disabled: isDisabled
}"></i>
```

Templates (Beta)

By: Mosh Hamedani

Applying multiple styles dynamically

```
<button
  [ngStyle]="{
    backgroundColor: canSave ? 'blue' : 'gray',
    color: canSave ? 'white' : 'black'
  }"></button>
```

Elvis operator

```
{{ task.assigned?.role?.name }}
```

Inserting content from the outside

```
<ng-content></ng-content>
```

Multiple content placeholders

```
<ng-content select=".heading"></ng-content>
<ng-content select=".body"></ng-content>
```