



Nice



## EL-SC-150

### System Controller

The Nice EL-SC-150 System Controller offers robust performance at a price point that creates new opportunities for smaller to moderate sized installations—providing a single point of control and automation for media, climate, lighting, security, surveillance, and more.

Pair with the Nice EL-IO-200 as cost effective way of adding control connections to another area.

Where a universal remote would only provide access to media, lighting or climate, the EL-SC-150 enables intelligent integration of additional home systems to provide real value.

And with all control conducted via the award-winning Nice smart home management user interface, the EL-SC-150 delivers an exceptional experience.

- Improved performance with ARM big. LITTLE architecture that integrates dual-core and quad-core processors
- HDMI 2.0 for 4K 60Hz output with HDCP 1.4/2.2 support
- H.265 video decoding capability up to 4K resolution
- Increased USB power to resolve drive issues

WORKS WITH  
**ELANOS**

# EL-SC-150 System Controller



## Features

- **Compatibility**  
Integrated IP, serial, and infrared control in a one-box design.
- **Multi-platform Experience**  
Consistent themes and layouts across all devices, including Nice touch panels, remotes, and mobile apps.
- **Reliable**  
Ultra-efficient, fanless design with no moving parts delivering long-lasting, reliable operation.
- **Audio Output**  
Allows video doorbells to play chimes throughout the home audio system.
- **Video**  
Compatible with H.264 and H.265 image compression and 4K 60Hz HDCP 1.4/2.2 HDMI out for OSD.
- **Flexible**  
The compact design allows installation in cabinets, structured wiring cabinets, or behind a display.
- **PoE or Wi-Fi Connection**  
Allows for placement flexibility. Power over ethernet capability built-in reduces the amount of cables needed.

## Specifications

|                        |                                                             |
|------------------------|-------------------------------------------------------------|
| RS-232                 | (1) RJ-45 Connector                                         |
| Sense Input            | (1) 3.5mm Connector                                         |
| IR Output              | (3) 3.5mm connectors (Mono), - 12V DC                       |
| Audio                  | (1) 3.5mm Connectors (Studio)                               |
| On-Screen Display      | (1) HDMI 2.0 for 4K 60Hz output with HDCP 1.4/2.2 support   |
| USB                    | (1) USB A Connector                                         |
| Ethernet               | (1) RJ-45 PoE Connector                                     |
| Wi-Fi                  | 802.11 b/g/n frequencies 5745-5825 and 2400-2483.5          |
| Software Compatibility | Requires Core Module 8.9 or above                           |
| Updates                | Managed by Management Cloud                                 |
| Power                  | Included Power Supply, 120/240VAC input 12VDC 1A output     |
| Temperature            | 32°F to 131°F                                               |
| Operating Humidity     | 90% Maximum (Non-Condensing)                                |
| Mounting               | Free standing, Wall mount, Structured wiring cabinet        |
| Product Dimensions     | (in): 6.9375 W x 1.25 H x 5 D<br>(mm): 176 W x 31 H x 126 D |
| Product Weight         | 0.8 lb / 0.36 Kg                                            |
| Certifications         | CE, FCC, C-Tick                                             |
| Warranty               | 2 Year                                                      |

### PACKAGE CONTENTS

- (1) EL-SC-150
- (1) 12vDC Power Supply
- (1) Quick Start Guide

