

The KX-4605 is a passive high performance cinema subwoofer, with dual 18 inch drivers. The enclosure is in a lowline format ideally suited to being positioned under the screen.

The bass driver features a 3 inch voice coil, combined with large aggregate vent area, to deliver efficient low frequency output at high power with minimal power compression and unwanted vent noise. Proprietary Krix 'X' bracing locks the front and rear of the enclosure together to improve structural rigidity and reduce internal standing waves.

Building on a long and successful history within the cinema industry, our in-house research, development and manufacturing team deliver a strong focus on quality and rigorous production standards. Every speaker that leaves Krix has been fully tested, tight production tolerances are upheld to ensure best-in-class product quality and reliability.

## FEATURES

- 12mm peak to peak linear cone excursion capability
- Three generously proportioned 150mm vents
- Binding posts sized to accommodate up to 8mm cable



| Product type                                      | Commercial cinema subwoofer         |
|---------------------------------------------------|-------------------------------------|
| Frequency range                                   | 28 - 200 Hz                         |
| Sensitivity (2.83V / 1m Half Space <sup>1</sup> ) | 106 dB                              |
| Input power rating <sup>2</sup>                   | 800 W                               |
| Impedance                                         | 4 Ω                                 |
| Product code                                      | KX-4605                             |
| Dimensions (mm)                                   | 600 (H) x 1200 (W) x 600 (D) mm     |
| Dimensions (inches)                               | 26 ½ (H) x 47 ¼ (W) x 27 (D) inches |
| Net weight (kg)                                   | 70kg                                |
| Net weight (lbs)                                  | 155 lbs                             |

## DETAILED SPECIFICATIONS

| Product code                              | KX-4605                                                                                                                                 |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <b>Sensitivity</b>                        |                                                                                                                                         |
| 1 W/m, Free space                         | 97 dB                                                                                                                                   |
| 1 W/m, Half space <sup>1</sup>            | 103 dB                                                                                                                                  |
| 2.83 V/m, Free space                      | 100 dB                                                                                                                                  |
| 2.83 V/m, Half space <sup>1</sup>         | 106 dB                                                                                                                                  |
| <b>Impedance</b>                          |                                                                                                                                         |
| Nominal                                   | 4 $\Omega$                                                                                                                              |
| Minimum                                   | 3.3 $\Omega$                                                                                                                            |
| <b>Maximum Input Voltage</b> <sup>3</sup> | 57 V                                                                                                                                    |
| <b>Maximum Input Power</b>                |                                                                                                                                         |
| Continuous <sup>2</sup>                   | 800 W                                                                                                                                   |
| Peak                                      | 3200 W                                                                                                                                  |
| <b>Recommended Processing</b>             | Subsonic 30 Hz, >12 dB/oct                                                                                                              |
| <b>Transducers</b>                        | 2 x 18 inch (455mm) paper cone bass driver, 3 inch coil, powerful vented magnet system                                                  |
| <b>Enclosure</b>                          | Vented B4 alignment tuned to 32 Hz, Krix proprietary 'X bracing', optimally damped with polyester fibre, MDF black vinyl finish.        |
| <b>Terminals</b>                          | Krix proprietary, high current binding posts featuring an 8mm hole to accept large diameter cable. High visibility polarity indicators. |

## NOTES

- All measurements and specifications are made in accordance with AES2-2012 and in a form compatible with Dolby® Atmos™ calculator.
  - Due to continued development, specifications may change without notice.
1. Half space sensitivity based on partial increase due to rear wall loading at low frequencies estimated from the directivity index over operating frequency range.
  2. Maximum AES continuous power capacity (AES2-2012) band limited test signal duration of two hours.
  3. RMS voltage required to deliver the maximum continuous power to the loudspeaker, IEC shaped pink noise with duration of two hours.

# KX-4605

COMMERCIAL CINEMA SUBWOOFER

## KX-4605

DETAILED DIMENSIONS



