



The KX-5996 further enhances the performance of Krix patented horn arrays with the addition of an ultra high frequency horn. The ultra high frequency element significantly improves high frequency pattern control and extension to deliver the ultimate in clarity and definition. Using sophisticated loudspeaker modelling techniques, the acoustic loading and pattern control have been engineered to achieve industry leading low distortion and smooth directivity characteristics.

Building on a long and successful history within the cinema industry, Krix's in-house research, development and manufacturing team deliver a strong focus on quality and rigorous production standards. Every speaker is comprehensively tested in an advanced acoustic measurement chamber. Tight production tolerances are upheld to ensure best-in-class product quality and reliability.

FEATURES

- The additional ultra high frequency horn permits all drivers to work within their piston operating range for the best possible horn loading, delivering the smoothest possible frequency response, matched directivity control and dialogue intelligence across the critical vocal range. The midrange horn featuring dual 6 inch neodymium drivers and dual KX-2690 LF element provides the highest possible output level.
- Patented constant directivity horn technology for precision coverage and extremely uniform frequency response. The result is that every seat in the cinema experiences improvements in clarity and definition.
- Krix proprietary 'X Bracing' system within the low frequency enclosure for standing wave suppression and reduced panel resonance.
- Krix engineered bass driver featuring, large ferrite magnet structure, dual aluminium shorting rings and symmetrical gap geometry for minimum distortion at all levels.



System options	Tri-amplified passive crossover			Full Quad-Amplified			
Product code	KX-5996.T			KX-5996.Q			
Frequency	Low	Mid	High	Low	Mid	High	U. High
Sensitivity (2.83 V/m, Half space ²)	116 dB	114 dB	111 dB	116 dB	114 dB	111 dB	104 dB
Input power rating ²	2500 W	360 W	160 W	2500 W	360 W	130 W	55 W
Impedance	4 x 4 Ω	4 Ω	8 Ω	4 x 4 Ω	4 Ω	8 Ω	8 Ω
Crossover frequency	350Hz (Low - Mid) 1600Hz (Mid - High)			350Hz (Low - Mid) 1600Hz (Mid - High) 6000 (High - U. High)			
Frequency range	32 – 19,000 Hz (-6 dB)						
Nominal dispersion	90° Horizontal, 40° Vertical						
Dimensions	3600 (H) x 1200 (W) x 460 (D) mm			141 ¾ (H) x 47 ¼ (W) x 18 (D) inches			
Net weight	274 kg			603 lbs			

DETAILED SPECIFICATIONS

	Low Frequency		Horn system
Part Number ⁵	KX-2690 (x2)	KX-3982.T	KX-3982.Q
Sensitivity			
1 W/m, Free space	105 dB ¹	111 dB (MF) 111 dB (HF)	111 dB (MF) 111 dB (HF) 104 dB (UHF)
1 W/m, Half space ³	108 dB ¹	111 dB (MF) 111 dB (HF)	111 dB (MF) 111 dB (HF) 104 dB (UHF)
2.83 V/m, Free space	113 dB	114 dB (MF) 111 dB (HF)	114 dB (MF) 111 dB (HF) 104 dB (UHF)
2.83 V/m, Half space ³	116 dB	114 dB (MF) 111 dB (HF)	114 dB (MF) 111 dB (HF) 104 dB (UHF)
Impedance			
Nominal	4 x 4 Ω	4 Ω (MF) 8 Ω (HF)	4 Ω (MF) 8 Ω (HF) 8 Ω (UHF)
Minimum	4.0 Ω	4.1 Ω (MF) 6.0 Ω (HF)	4.1 Ω (MF) 7.4 Ω (HF) 7.2 Ω (UHF)
Maximum Input Voltage ⁴			
	50 V	38 V (MF) 36 V (HF)	38 V (MF) 32 V (HF) 21 V (UHF)
Maximum Input Power			
Continuous ²	2500 W	360 W (MF) 160 W (HF)	360 W (MF) 130 W (HF) 55 W (UHF)
Peak	10000 W	1440 W (MF) 640 W (HF)	1440 W (MF) 520 W (HF) 220 W (UHF)
Recommended Processing	Subsonic 30 Hz, >12 dB/oct		Contact Krix for details
Low frequency transducers	8 x 380 mm (15 inch) paper cone driver, ferrite magnet, vented pole piece, 75 mm (3 inch) edge wound copper voice coil, dual aluminium shorting rings.		
Low frequency enclosure	Vented B4 alignment tuned to 36 Hz, Krix proprietary 'X bracing', optimally damped with polyester fibre, MDF black vinyl finish.		
Mid & High frequency transducers	2 x 152 mm (6 inch) paper cone drivers, neodymium magnet, 44 mm (1 ¾ inch) voice coil. 1 x 100mm (4 inch) ferrite magnet compression driver, titanium diaphragm, edge wound aluminium voice coil on high temperature polyimide former. 1 x 44 mm (1 ¾ inch) compression driver, ferrite magnet, treated polyethylene diaphragm, edge wound aluminium voice coil on treated Nomex former and unique (patented) phase plug architecture.		
Horns	90° x 40° constant directivity, thermoset resin reinforced with glass fibre.		
Horn enclosure	Rear enclosure volume selected to match horn acoustic loading. Internally braced and optimally damped with polyester fibre.		
Horn bracket	Tilt 0° to 15° downwards: Swivel ±15° degrees.		
Terminals	Krix proprietary, high current binding posts featuring an 8mm hole to accept large diameter cable. High visibility polarity indicators.		

NOTES

- All measurements and specifications are made in accordance with AES2-2012 and in a form compatible with Dolby® Atmos™ calculator.
 - Due to continued development, specifications may change without notice.
 - Manufactured and sold under US Patents 7,044,265 B2 and 2011/0153282 A1.
- Sensitivity measurements adjusted to the nominal 1W input power, calculated from the real part of the electrical input impedance over the operating frequency range.
 - Maximum AES continuous power capacity (AES2-2012) band limited test signal duration of two hours.
 - Half space sensitivity based on partial increase due to rear wall loading at low frequencies estimated from the directivity index over operating frequency range.
 - RMS voltage required to deliver the maximum continuous power to the loudspeaker, IEC shaped pink noise with duration of two hours.
 - The KX-5996 is shipped in three parts comprising of two KX-2690 (Low Frequency components) and one KX-3982 (Horn system component)

KX-5996

4-WAY SCREEN CINEMA SYSTEM

DETAILED DIMENSIONS



