



ISR FUSION 20 - SPECIFICATIONS

	ISR Fusion 20	
Main Features	Auro-3D / Dolby Atmos / DTS:X Pro / IMAX Enhanced / MPEG-H / Sony 360 Reality Audio StormXT channel expander All grades Dirac Live licence included Dirac Live Active Room Treatment supporting speakers StormMonitoring - remote monitoring	✓ / ✓ / ✓ / ✓ ✓ ✓ Unlimited ✓
Multichannel / Surround Processing	Output channels Decoding / upmixing channels Input sampling rate supported Post processing sampling rate Dirac Live runtime with high resolution mixed-phase filters Bass management : Standard & Expert Flexible bass routing (up to 6 zones, Expert mode) Multi-subwoofer channels Multi-way crossover (6 to 48 dB/oct, Linkwitz-Riley, Butterworth) Parametric EQ per channel	20 20 up to 192 kHz 48 kHz ✓ ✓ ✓ Unlimited up to 4 per channel up to 20 filters
HDMI	HDMI inputs / outputs Standard Matrix capability for multi-room 8K / 4K120, rec BT709 and rec BT2020 High Dynamic Range : HDR10 / HDR10+ / HLG / Dolby Vision Color space and subsampling Deep color (12 bpc) Max. resolution support (40 Gbps) 3D / OSD ARC / eARC	7/2 HDMI2.1a / HDCP2.3 ✓ ✓ ✓ / ✓ / ✓ / ✓ RGB, YCbCr, 4:4:4, 4:2:2, 4:2:0 ✓ 8K/4K 120fps ✓ / ✓ ✓ / ✓
Audio Inputs	Streaming: Roon ready end point Digital input: coaxial / optical Analog stereo inputs, balanced : XLR Analog stereo inputs, unbalanced: RCA	✓ 3 / 3 1 4
Audio Outputs	Analog main outputs, amplified (ch 1 to 16) Analog main outputs, balanced (ch 17 to 20) Stereo downmix Zone2 outputs	5-way binding posts XLR Digital Optical
Amplifier specifications	Max Power per channel (p-rated), 1% THD, Single Ended (SE) outputs Max Power per channel, 1% THD _n , Bridged Tied Load (BTL) outputs (Up to 3 configurable) Continuous Power capability Peak Power Capability (CEA-490-A) THD+N, 5W, SE SNR, 5W, SE SNR, p-rated, SE	150W (8ohm) / 300W (4ohm) 500W (8ohm) / 500W (4ohm) 2000W 2500W < 0,0015 % > 100 dB > 115 dB
Set-up Management	Audio zone configuration Individual theater and zone source selection (Main & Zone2) Theater and zones listening presets Dirac Live profiles Backup and restore of set-up Firmware update via USB / network	✓ ✓ Unlimited 10 per Theater / Zone ✓ ✓ / ✓
Control Inputs / Outputs	USB type A (upgrade and monitoring) Ethernet / Wi-Fi Output trigger control IR remote ports, in / out (input loop through) IR remote control sensor in front panel	2 ✓ / - 4 (out) 1 / 1 ✓
Control / Custom Installation	Front panel display Advanced control via front panel Web-based product configurator TCP/IP API based control StormRemote control application (iOS / Android) Crestron, Control4, Savant, RTI, ELAN home automation drivers Logitech Harmony IR database integration IR remote control handset	✓ (TFT 5") ✓ ✓ ✓ ✓ ✓ ✓ ✓
Power Supply	Voltage range Type Range selection	100V to 240V SMPS Universal
Casing	Home / rack (removable ears) Net weight (kg / lbs) Size Dimensions D x L x H - no ears, no feet (cm) Ears : +4 cm (2 x 2 cm) - Feet : + 2 cm Dimensions - with box (cm)	✓ / ✓ 16 / 35,3 4RU 49,1 x 44,2 x 17,4 62 x 54 x 30

All trademarks are the property of their respective owners. The information and product specifications contained in this datasheet are subject to change at any time without notice. StormAudio accepts no liability or responsibility for any errors or omissions in the information on this datasheet or for damages resulting from relying on the content of this datasheet.