

The Nice logo consists of a solid blue square with the word "Nice" in white, sans-serif font centered within it.

EL-4K-VIP-ACM

4K UHD Video Over IP Advanced Control Module



Premium video using visually lossless technology

The Nice EL-4K-VIP-ACM Premium Video over IP (VIP) platform distributes HDMI video over a 1Gb Network switch using visually lossless technology. The Nice EL-4K-VIP-ACM Advanced Control Module integrates 4K Video Over IP into the Nice smart home control and automation system.

Nice drivers built into each products firmware simplify product installation and negate the need for an understanding of complex network infrastructures.

The Nice EL-4K-VIP-ACM includes a web interface module for control and configuration of the system when not used with Nice home control system that features 'Drag & Drop' source selection with video preview and independent routing of IR, RS-232, USB / KVM, Audio, and Video.

WORKS WITH ELAN
CONTROL SYSTEMS
ELAN
a Nice brand

EL-4K-VIP-ACM 4K UHD Video Over IP Advanced Control Module



Features

- Designed to work with the Nice smart home control and automation platform
- Optional web interface module for configuration and control of the Nice Video Over IP (VIP) systems when used without the Nice system
- Optional intuitive drag & drop source selection with video preview feature for active monitoring of system status when used without the Nice system
- Advanced signal management for independent routing of IR, Rs-232, USB, audio and video
- Auto system configuration
- 2x RJ45 LAN connections to bridge existing network to VIP video distribution network
- Better system performance as network traffic is separated
- No advanced network setup required
- Independent IP address per LAN connection
- Allows simplified TCP / IP control of VIP system
- RS-232 integration for control of VIP system
- IR integration for control of VIP system
- Powered with PoE (Power over Ethernet) using a PoE Switch
- Local 12V power supply (optional) should Ethernet switch not support PoE
- Support for IOS and Android App control
- 3rd Party drivers available for all major home control brands

Specifications

Control Ethernet port	1 x LAN RJ45 connector
Video Ethernet port	1 x LAN RJ45 connector (1 x PoE support 9W)
RS-232 serial port	1x DB-9, female
I/O port	1 x 6-pin Phoenix connector (reserved for future use)
IR control port	1x 3.5mm stereo jack
Dimensions (W x D x H)	96mm x 110mm x 26mm
Shipping weight (Kit)	0.6 Kg
Operating temperature	32°F to 104°F (0°C to 40°C)
Storage temperature	-4°F to 140°F (-20°C to 60°C)

