

Nice

EL-4KHDBT-KIT-70-ARC-18G

HDBaseT Extender



Outstanding value utilizing CSC technology powered by the matrix up to lengths of 100m (4K 70m)

The Nice EL-4KHDBT-Kit-70-ARC-18G HDMI 2.0 4K 60Hz 4:4:4 (18Gbps) HDCP 2.2 HDBaseT ARC kit offers market leading features and outstanding value utilizing CSC technology. The product extends HDMI, Bi-directional IR and RS-232 and is powered by the matrix up to lengths of 100m (4K 70m).

The receiver features ARC support when used with a compatible Nice matrix analog stereo and Optical Toslink audio breakout. 4K HDBaseT ARC extender set offers market leading features for the custom installation industry.

WORKS WITH ELAN
CONTROL SYSTEMS
ELAN
a Nice brand

EL-4KHDBT-KIT-70-ARC-18G HDBaseT Extender



Features

- Advanced HDBaseT Technology offering uncompressed video and audio with zero latency
- Extends HDMI 4K60 4:4:4 up to 70m over a single CAT cable
- Supports 4K UHD Video up to 70m (3840 x 2160 @30Hz 4:4:4, 4096 x 2160 @24Hz 4:4:4, and 4K @60Hz 4:2:0)
- Supports ARC (Audio Return Channel) from connected display via HDMI ARC or optical digital input*
- Supports all known HDMI audio formats including Dolby TrueHD, Dolby Atmos, Dolby digital Plus and DTS-HD Master Audio transmission
- Bi-direction IR pass-through
- Bi directional RS-232 pass-through
- Supplied with Nice IR receiver and emitter
- Supports bi-directional PoC (Power over Cable) to power extenders from either transmitter or receiver end
- HDCP 2.2 compliant with smart EDID management

*Please note: When using an eARC display, only 2 channel PCM audio is supported

Specifications

EL-4KHDBT-TX-70-ARC-18G	
Video Input Connectors	1 x HDMI Type a, female
Video Output Connectors	1 x HDBaseT RJ45 connector 1 HDMI Type A, female
RS-232 Serial Port	1 x 3-pin Phoenix connector
Audio Output Ports	1 x Optical (S / PDIF), 1x 3.5mm L/R analog audio
IR Input Port	1 x 3.5mm stereo jack
IR Output Port	1 x 3.5mm mono jack
Product Upgrade	1 x Micro-USB female
EL-4KHDBT-KIT-70-ARC-18G	
Power Supply	1 x 24V / 125A DC, 4-pin DIN connector
Box dimensions (W x D x H)	248mm x 151mm x 103mm
Shipping Weight	1 kg
Operating Temperature	23°F to 131°F (-5°C to +55°C)
Storage Temperature	-13°F to 158°F (-25°C to +70°C)

EL-4KHDBT-RX-70-ARC-18G	
Video Input connectors	1 x HDBaseT RJ45 connector
Video Output Connectors	1 x HDMI type A, female
Audio Input Ports	1 x Optical (S/PDIF)
Audio Output Ports	1 x Optical (S/PDIF), 1 x 3.5mm L/R analog audio
RS-232 Port	1 x 3-pin Phoenix connector
IR Input Port	1 x 3.5mm stereo jack
IR Output Port	1 x 3.5mm mono jack
Product Upgrade	1 x Micro-USB, female
Casing Dimensions (W x D x H)	135mm x 105mm x 25mm

PACKAGE CONTENTS

- (1) EL-4KHDBT-TX-70-ARC-18G
- (1) EL-4KHDBT-RX-70-ARC-18G
- (1) 24V/1.25A DC Power supply
- (1) IR Emitter
- (1) IR Receiver
- (1) Mounting bracket set
- (1) Quick reference guide



Niceforyou.com

©2023 Nice North America LLC. All rights reserved.
All other products or name brands are trademarks of their respective holders.

1146547313 Rev-A 09/23