

The Nice logo consists of a solid blue square with the word "Nice" in white, sans-serif font centered within it.

EL-IPD-PRE-SIO

Network Audio Interface



Nice

EL-IPD-PRE-SIO Network Audio Interface

Delivers audio over a standard local area network from a single source

The Nice EL-IPD-PRE-SIO Network Audio Interface enables the delivery of bidirectional audio over a standard local area network. Send audio from a single remote source to a Nice enabled amplifier or preamplifier to a second amplifier. The Nice IP-enabled audio distribution simplifies whole house audio distribution and enhances the intelligent home by

delivering high quality audio over an existing network. Easily scaling from a single chassis solution to a decentralized multi-chassis/multi-source implementation, Nice IP audio distribution meets the needs for projects of any size.

WORKS WITH ELAN
CONTROL SYSTEMS
ELAN[®]
a Nice brand

EL-IPD-PRE-SIO Network Audio Interface



Features

- **Three available inputs**
 - Optical TOSLINK
 - Coaxial RCA
 - Analog RCA
- **Pre-amp outputs**
 - Analog RCA
 - Subwoofer RCA
- **Bidirectional Audio Networking**

Audio over a standard local area network using Dante® Audio Networking

Specifications

Power	802.3af or 802.3at Type 1 or DC 5v, 2A
Inputs	3available, selectable at installation 1. Optical TOSLINK 2. Coaxial RCA 3. Analog RCA
Outputs	Analog RCA Subwoofer RCA
Network	100 Mbps Ethernet (PoE) DHCP Enabled by Default 1 RJ45 Jack
Dimensions	(in) 7.01W x 1.09H x 4.13D (cm) 17.80W x 2.79H x 10.5D
Weight	0.65 lbs / 0.29 Kg

