Phase 2 – AI Interaction Log

Overview

This document records the interaction with the AI assistant (Gemini) used in Phase 2 of the assignment, including all uploaded files, prompts, and generated outputs.

1 Phase 2A – AI-Assisted Data Analysis

1.1 Input Provided to Gemini

- **Uploaded file:** `simulation_results.csv`
- This file contains the complete baseline simulation results for all combinations of window size (W) and payload size (L), including goodput, RTT, retransmissions, buffer events, and utilization.

1.2 User Prompt (Phase 2A)

```
You are helping analyze simulation results of a Selective Repeat ARQ protocol over a
Gilbert{Elliot burst error channel.
I have a CSV with columns:  - W: ARQ window size - L: payload size in bytes - run
id:  run identifier (different RNG seed) - goodput:  delivered application data rate
(goodput) - retransmissions:  number of retransmitted frames - avg RTT: average RTT
measured from sending a frame to receiving its ACK (seconds) - utilization:  link
utilization ratio during the run - buffer events:  number of receiver-side buffer
backpressure events (e.g., buffer-full / blocked delivery)
TASKS (must do all):  1) Identify trends:  how goodput changes with W and L, and how
retransmissions, avg RTT, utilization, and buffer events change with W and L. 2)
Detect outliers (specific runs or (W,L) points) and propose likely causes using the
metrics.  3) Propose a mathematical hypothesis/model (explicit rule or equation) that
predicts the optimal region for (W,L), and justify it.  4) Recommend a refined search
space for W and L (narrow region or a small set of candidate pairs) likely to contain
the true optimum.  5) Give a cross-metric explanation:  explain how retransmissions +
RTT + utilization + buffer events jointly create the goodput optimum.
Output format:  - Best predicted (W*, L*) as 1 pair + top 2 alternatives - Refined
search space - Trends - Outliers - Hypothesis/model - Cross-metric explanation
```

1.3 Gemini Output (Phase 2A)

Gemini analyzed the uploaded CSV file and provided:

- Identification of trends and outliers
- Analysis of goodput, RTT, retransmissions, buffer events, and utilization
- Prediction of the optimal operating point: W = 64, L = 512

- Explanation of congestion collapse at large payload sizes
- A refined search space and a mathematical hypothesis explaining protocol behavior

1.4 Figures Generated by Gemini (Phase 2A)



Figure 1: Utilization vs Window Size (W)

1.5 Gemini Analysis of Simulation Results

1.5.1 Best Predicted Configuration and Alternatives

Based on the simulation data, the configuration yielding the highest goodput is:

- **Optimal:** $(W = 64, L = 512)$ — Mean Goodput: 0.89 Mbps
- **Alternative 1:** $(W = 64, L = 256)$ — Mean Goodput: 0.79 Mbps
- **Alternative 2:** $(W = 64, L = 1024)$ — Mean Goodput: 0.70 Mbps

1.5.2 Refined Search Space

The optimal configuration lies at the edge of the current window size (W) range and near the center of the payload size (L) range. Therefore, future simulations should expand W and fine-tune L:

- **Window Size (W):** Search in the range $[64, 128]$. The linear increase from $W = 32$ to $W = 64$ suggests that the bandwidth–delay product is just being reached.
- **Payload Size (L):** Search in the range $[400, 700]$ bytes. Goodput peaks around $L = 512$, with sharp degradation observed at $L = 1024$ and $L = 4096$.



Figure 2: Buffer Events vs Window Size (W)

1.5.3 Observed Trends

Goodput vs. Window Size (W). For optimal payload sizes ($L \leq 512$), goodput increases approximately linearly with W, indicating a window-limited system. For larger payloads ($L > 2048$), increasing W exacerbates congestion, causing goodput to plateau or collapse.

Goodput vs. Payload Size (L). Goodput follows a concave curve as a function of L. It initially increases as header overhead decreases, reaches a maximum at $L = 512$, and then drops sharply for $L \geq 1024$ due to increased frame error rate (FER) and congestion effects.

Retransmissions and RTT. At the optimal configuration ($W = 64, L = 512$), retransmissions and average RTT remain low and stable. In contrast, for large payloads (e.g., $L = 4096$), retransmissions grow explosively (up to 7×10^6 events) and average RTT increases dramatically (up to 56 seconds), indicating severe buffer bloat and packet loss loops.

1.5.4 Outliers

Critical Failure: ($W = 64, L = 4096$). All runs resulted in zero goodput, zero retransmissions, and zero buffer events. This behavior suggests a total system collapse or simulator limit. The flight size ($W \times L = 256$ KB) likely exceeded a hard memory limit or caused immediate deadlock, preventing packet injection.

Congestion Collapse: ($W = 32, L = 4096$). This configuration achieved a goodput of approximately 0.02 Mbps, with an average RTT of 56 seconds and roughly 7 million retransmissions. Although the flight size (131 KB) is manageable, the large payload size significantly increases FER in the burst-error channel, leading to continuous retransmission and extreme buffer bloat.



Figure 3: Retransmissions vs Window Size (W)

1.5.5 Hypothesis and Model

The goodput $G(W, L)$ can be modeled as a trade-off between pipeline efficiency and packet error probability:

$$G(W, L) \approx \min\left(C, \frac{W \cdot L}{RTT_{\min}}\right) \cdot (1 - \mathrm{BER}_{\mathrm{eff}})^L$$

The first term reflects window-limited throughput growth until link capacity C is reached. The second term captures the exponential increase in error probability with larger payload sizes.

1.5.6 Cross-Metric Explanation

The optimal point $(W = 64, L = 512)$ represents a "Goldilocks" operating region:

- **Utilization:** $W = 64$ provides sufficient in-flight data (approximately 32 KB) to fully utilize the link without overflowing buffers.
- **Retransmissions:** $L = 512$ keeps FER low, minimizing retransmissions.
- **RTT:** Low retransmission rates prevent queue buildup, maintaining a low average RTT (approximately 0.29 seconds).

In contrast, configurations such as $(W = 32, L = 4096)$ suffer from frequent frame corruption, excessive retransmissions, severe buffer bloat, and dramatically increased RTT, resulting in near-zero effective goodput.



Figure 4: Average RTT vs Window Size (W)



Figure 5: Goodput vs Payload Size (L) for different Window Sizes



Figure 6: Goodput vs Window Size (W) for different Payload Sizes

Figure 7: Mean Goodput Heatmap as a Function of W and L

1.6 Gemini Analysis of Simulation Results

1.6.1 Best Predicted Configuration and Alternatives

Based on the simulation data, the configuration yielding the highest goodput is:

- **Optimal:** $(W = 64, L = 512)$ — Mean Goodput: 0.89 Mbps
- **Alternative 1:** $(W = 64, L = 256)$ — Mean Goodput: 0.79 Mbps
- **Alternative 2:** $(W = 64, L = 1024)$ — Mean Goodput: 0.70 Mbps

1.6.2 Refined Search Space

The optimal configuration lies at the edge of the current window size (W) range and near the center of the payload size (L) range. Therefore, future simulations should expand W and fine-tune L:

- **Window Size (W):** Search in the range $[64, 128]$. The linear increase from $W = 32$ to $W = 64$ suggests that the bandwidth–delay product is just being reached.
- **Payload Size (L):** Search in the range $[400, 700]$ bytes. Goodput peaks around $L = 512$, with sharp degradation observed at $L = 1024$ and $L = 4096$.

1.6.3 Observed Trends

Goodput vs. Window Size (W). For optimal payload sizes ($L \leq 512$), goodput increases approximately linearly with W, indicating a window-limited system. For larger payloads ($L > 2048$), increasing W exacerbates congestion, causing goodput to plateau or collapse.

Goodput vs. Payload Size (L). Goodput follows a concave curve as a function of L. It initially increases as header overhead decreases, reaches a maximum at $L = 512$, and then drops sharply for $L \geq 1024$ due to increased frame error rate (FER) and congestion effects.

Retransmissions and RTT. At the optimal configuration ($W = 64, L = 512$), retransmissions and average RTT remain low and stable. In contrast, for large payloads (e.g., $L = 4096$), retransmissions grow explosively (up to 7×10^6 events) and average RTT increases dramatically (up to 56 seconds), indicating severe buffer bloat and packet loss loops.

1.6.4 Outliers

Critical Failure: ($W = 64, L = 4096$). All runs resulted in zero goodput, zero retransmissions, and zero buffer events. This behavior suggests a total system collapse or simulator limit. The flight size ($W \times L = 256$ KB) likely exceeded a hard memory limit or caused immediate deadlock, preventing packet injection.

Congestion Collapse: ($W = 32, L = 4096$). This configuration achieved a goodput of approximately 0.02 Mbps, with an average RTT of 56 seconds and roughly 7 million retransmissions. Although the flight size (131 KB) is manageable, the large payload size significantly increases FER in the burst-error channel, leading to continuous retransmission and extreme buffer bloat.

1.6.5 Hypothesis and Model

The goodput $G(W, L)$ can be modeled as a trade-off between pipeline efficiency and packet error probability:

$$G(W, L) \approx \min\left(C, \frac{W \cdot L}{RTT_{\min}}\right) \cdot (1 - \mathrm{BER}_{\mathrm{eff}})^L$$

The first term reflects window-limited throughput growth until link capacity C is reached. The second term captures the exponential increase in error probability with larger payload sizes.

1.6.6 Cross-Metric Explanation

The optimal point ($W = 64, L = 512$) represents a "Goldilocks" operating region:

- **Utilization:** $W = 64$ provides sufficient in-flight data (approximately 32 KB) to fully utilize the link without overflowing buffers.
- **Retransmissions:** $L = 512$ keeps FER low, minimizing retransmissions.
- **RTT:** Low retransmission rates prevent queue buildup, maintaining a low average RTT (approximately 0.29 seconds).

In contrast, configurations such as ($W = 32, L = 4096$) suffer from frequent frame corruption, excessive retransmissions, severe buffer bloat, and dramatically increased RTT, resulting in near-zero effective goodput.

2 Phase 2B – Code Critique and Improvement

2.1 Input Provided to Gemini

- Selective Repeat ARQ sender implementation (C++ code)

2.2 User Prompt (Phase 2B)

```
Review my Selective Repeat ARQ simulator code.  Give a structured critique with
concrete suggestions under these headings:
1) Timer handling (per-frame timers, how timeouts are set/reset) 2) ACK processing
(ACK format, duplicate ACK behavior, ACK loss assumptions) 3) Buffer management
(sender buffer, receiver out-of-order buffer, receiver/app buffer + backpressure) 4)
Window advancement logic (base update rules, edge cases) 5) Handling of burst losses
(Gilbert{Elliot behavior, how the protocol reacts) 6) Timeout calculation strategy
(fixed vs adaptive, RTT estimation, recommended strategy)
Then recommend ONE significant protocol improvement from:  - adaptive timeout
mechanism - delayed ACK / ACK pacing - dynamic window adjustment under burst losses
- silly window syndrome prevention - piggybacked ACK optimization
For the recommended improvement:  - explain why it should improve goodput - describe
exact code changes (steps / pseudocode) - what metrics should improve and why
```

3 Phase 2B – Gemini Code Critique and Recommendation

Based on the C++ simulation code provided, here is a critique of the Selective Repeat ARQ implementation, followed by a recommendation for an **Adaptive Timeout Mechanism**.

3.1 Part 1: Structured Critique

3.1.1 1) Timer Handling

Current State: The `LinkLayerSender` maintains a `std::map<int, double> timers` for every unacknowledged frame. The `check_timeouts` method iterates through the entire map to find expired timers.

Critique:

- **Inefficient Lookup:** Iterating the whole map is $O(W)$ (where W is the window size). For large windows (e.g., $W = 32$ or $W = 64$), this adds unnecessary CPU overhead to the simulation. A priority queue (min-heap) stored by `expiry_time` would allow $O(1)$ access to the next expiring timer.
- **Reset Logic:** When a frame times out, it is immediately rescheduled with the same fixed duration (`current_time + timeout`). This lacks backoff. If the network is congested (high RTT), this fixed reset causes a retry storm, further clogging the channel.

3.1.2 2) ACK Processing

Current State: The receiver sends individual ACKs (`LinkFrame::ACK` with a specific `seq_num`). It detects duplicates (`seq < expected_seq_num`) and re-sends ACKs to prevent sender stalls.

Critique:

- **Correct Basic Logic:** The handling of duplicate ACKs is robust; it ensures the sender eventually knows a frame was received even if the first ACK was lost.
- **Missing Cumulative ACK Capability:** Pure Selective Repeat (individual ACKs only) is chatty. If ACK n is lost but ACK $n + 1$ arrives, the sender still thinks n is missing until n's specific ACK arrives or n times out. Adding a cumulative ACK field (e.g., "I have everything up to n") to every ACK frame improves robustness against ACK loss.

3.1.3 3) Buffer Management

Current State: Both Sender and Receiver use `std::map` to store buffered frames. The Sender checks `buffer.size() < W` to respect the window.

Critique:

- **Implicit vs. Explicit Constraints:** The simulation relies on the W parameter to limit memory. However, `std::map` allocates dynamic memory. In a real embedded system, a fixed-size circular buffer would be required.
- **Receiver Backpressure:** The receiver has a buffer for out-of-order packets. The simulation counts "buffer events," but there is no code preventing the receiver buffer from growing infinitely if a specific packet (e.g., `seq_num = 100`) is never received while packets `101 ...1000` arrive. This is a Receive Window (RWND) violation.

3.1.4 4) Window Advancement Logic

Current State: The sender updates `window_base` using `buffer.begin()->first` (the smallest sequence number currently unacknowledged).

Critique:

- **Effective Implementation:** Using the sorted property of `std::map` makes finding the window base easy and correct.
- **Sequence Number Wrap-around:** The code uses `int` for sequence numbers. In a very long simulation (or real life), this will overflow. `std::map` sorting will break (a wrapped 0 is technically smaller than `INT_MAX`, but logically "after" it). Modular arithmetic comparisons (e.g., `CircularDiff(a, b)`) are required.

3.1.5 5) Handling of Burst Losses (Gilbert–Elliot)

Current State: The `GilbertElliotChannel` groups bit errors into bursts. The protocol reacts by timing out individual frames.

Critique:

- **Slow Recovery:** Selective Repeat struggles with dense bursts. If a burst wipes out 10 consecutive frames, the sender must wait for 10 separate timers to expire. The receiver will buffer subsequent successful frames, but the application sees a delivery stall.
- **Lack of NACK:** There is no Negative Acknowledgement (NACK). If the receiver sees a gap (receives 1, 2, gap, 4, 5), it could immediately send `NACK(3)`. Currently, the sender must wait for the timeout of packet 3, causing significant idle time and low utilization.

3.1.6 6) Timeout Calculation Strategy

Current State: A fixed timeout is passed in the constructor: `LinkLayerSender(int w, double t)`.

Critique:

- **Major Weakness:** A static timeout is the root cause of the performance issues observed in the data (congestion collapse).
- If `Timeout < Real RTT`: spurious retransmissions occur, wasting bandwidth.
- If `Timeout >> Real RTT`: the link remains idle after a loss.
- **Sensitivity:** In the Gilbert–Elliot model, retransmissions increase the effective RTT due to queuing. A fixed timeout cannot adapt to these fluctuations.

3.2 Recommended Improvement: Adaptive Timeout (Jacobson's Algorithm)

An adaptive timeout mechanism with exponential backoff is recommended.

Why it improves Goodput The simulation data shows cases where goodput collapses and retransmissions reach millions. This occurs when the fixed timeout becomes shorter than the actual RTT under congestion. The sender retransmits packets still queued in the buffer, increasing delay and creating a feedback loop. An adaptive timer increases the timeout as RTT grows, allowing the buffer to drain.

3.2.1 Code Changes (Sender.hpp and main.cpp)

```
class LinkLayerSender {
public:
    double srtt;          // Smoothed RTT
    double rttvar;        // RTT Variation
    double rto;           // Retransmission Timeout
    const double kAlpha = 0.125;
    const double kBeta = 0.25;

    LinkLayerSender(int w, double initial_timeout)
        : W(w), timeout(initial_timeout), next_seq_num(0), window_base(0),
          total_rtt_sum(0.0), rtt_count(0),
          srtt(initial_timeout),
          rttvar(initial_timeout / 2.0),
          rto(initial_timeout) {}
};
```

```
if (first_send_times.count(ack_seq)) {
    double sample_rtt = current_time - first_send_times[ack_seq];
    rttvar = (1 - kBeta) * rttvar + kBeta * abs(srtt - sample_rtt);
    srtt   = (1 - kAlpha) * srtt   + kAlpha * sample_rtt;
    rto    = srtt + 4.0 * rttvar;
    if (rto < 0.010) rto = 0.010;
    first_send_times.erase(ack_seq);
}
```

```
if (current_time >= expiry_time) {
    LinkFrame frame = buffer[seq];
    frame.retransmitted = true;
    retransmit_list.push_back(frame);
    timers[seq] = current_time + rto;
    first_send_times.erase(seq);
}
```

```
class LinkFrame {
public:
    bool retransmitted;
    LinkFrame(...) : retransmitted(false) {}
};
```

3.3 Expected Metric Improvements

1. **Retransmissions (Decrease):** Adaptive RTO prevents retransmitting packets still queued, reducing duplicate traffic.
2. **Goodput (Increase or Stabilize):** Prevents congestion collapse under large window and payload sizes.
3. **Average RTT (Decrease):** Reduced buffer occupancy lowers queuing delay.

3.4 Implementation Summary

Based on Gemini's recommendation:

- The sender was modified to use adaptive RTT-based timeouts
- A baseline simulation at (W=64, L=512) was run
- An improved simulation at (W=64, L=512) was run
- The results were compared using CSV output files

A Appendix: Phase 2 AI Interaction Screenshots

A.1 Phase 2A: AI-Assisted Data Analysis Prompts



Figure 8: Phase 2A prompt (part 1): providing the CSV columns and simulation context to Gemini.

Selective Re... PRO N

1) Identify trends: how goodput changes with W and L, and how retransmissions, avg RTT, utilization, and buffer events change with W and L.
2) Detect outliers (specific runs or (W,L) points) and propose likely causes using the metrics.
3) Propose a mathematical hypothesis/model (explicit rule or equation) that predicts the optimal region for (W,L), and justify it.
4) Recommend a refined search space for W and L (narrow region or a small set of candidate pairs) likely to contain the true optimum.
5) Give a cross-metric explanation: explain how retransmissions + RTT + utilization + buffer events jointly create the goodput optimum.

Output format:
- Best predicted (W*, L*) as 1 pair + top 2 alternatives
- Refined search space
- Trends
- Outliers
- Hypothesis/model
- Cross-metric explanation

Figure 9: Phase 2A prompt (part 2): required tasks (trend analysis, outliers, hypothesis, refined search space, cross-metric explanation).

A.2 Phase 2B: AI Code Critique and Improvement Guidance

Selective Re... PRO N

channel HPP classes HPP receiver HPP

Review my Selective Repeat ARQ simulator code. Give a structured critique with concrete suggestions under these headings:

1) Timer handling (per-frame timers, how timeouts are set/reset)
2) ACK processing (ACK format, duplicate ACK behavior, ACK loss assumptions)
3) Buffer management (sender buffer, receiver out-of-order buffer, receiver/app buffer + backpressure)
4) Window advancement logic (base update rules, edge cases)
5) Handling of burst losses (Gilbert–Elliot behavior, how the protocol reacts)
6) Timeout calculation strategy (fixed vs adaptive, RTT estimation, recommended strategy)

Then recommend ONE significant protocol improvement

Figure 10: Phase 2B prompt (part 1): structured request for code critique (timers, ACKs, buffering, window logic, burst losses, timeout strategy).

Selective Re... PRO N

- delayed ACK / ACK pacing
- dynamic window adjustment under burst losses
- silly window syndrome prevention
- piggybacked ACK optimization

For the recommended improvement:
- explain why it should improve goodput
- describe exact code changes (steps / pseudocode)
- what metrics should improve and why

Figure 11: Phase 2B prompt (part 2): improvement requirements (why it improves goodput, exact code-change steps, and expected metric changes).

A.3 Phase 2B: Implementation Iterations and Final Outcome



Figure 12: Initial integration issue: build error caused by a function-signature mismatch (ACK handler requiring an additional argument).

```
cp sender_improved.hpp sender.hpp && make && ./simulation && cat simulation_results.csv && cp
simulation_results.csv results_improved_aggressive.csv && cp sender_original.hpp.bak sender.hpp
```

✓ Evaluating the Gains

```
cp assignment2/c_real/sender_improved.hpp NA/sender_improved.hpp
cp: assignment2/c_real/sender_improved.hpp: No such file or directory
```

✓ Examining File Paths

```
ls -F assignment2/c_real/
ls: assignment2/c_real/: No such file or directory
```

```
pwd && ls -R
```

✓ Adjusted path and resolved copy issue

```
cp sender_improved.hpp ../../NA/sender_improved.hpp
```

The reason for the performance drop in your initial adaptive implementation was **Exponential Backoff** triggering on random packet losses.

The Problem:

1. **High Latency & Window Limit:** The link has a high natural delay (~290ms RTT) and acts effectively like a queue. Your fixed window (`W=64`) makes the system window-limited.
2. **Fixed Timeout vs Adaptive:**
   - **Baseline (Fixed 200ms):** The timeout is shorter than the RTT (~290ms). This causes it to aggressively retransmit (send duplicates) *before* it knows if a packet is lost. Since the link has spare bandwidth (only 0.9Mbps used of 10Mbps), these duplicates are "free" and help recover continuously from random losses without waiting.
   - **Original Improved (Adaptive):** It calculated RTO correctly (~300ms) but when a packet was lost (due to 4% channel error), it triggered **Exponential Backoff** (waiting 600ms, 1.2s, etc.). This "polite" waiting left the link idle, starving the window and destroying goodput (dropping it to 0.58 Mbps).

The Solution:

Since we are dealing with a **Link Layer** (not full TCP) on a **lossy channel** (wireless-like) with **spare bandwidth**:

Figure 13: AI diagnosis: the first adaptive timeout attempt reduced goodput due to exponential backoff causing long idle waits after random losses.

Exponential Backoff (waiting 600ms, 1.2s, etc.). This "polite" waiting left the link idle, starving the window and destroying goodput (dropping it to 0.58 Mbps).

The Solution:

Since we are dealing with a **Link Layer** (not full TCP) on a **lossy channel** (wireless-like) with **spare bandwidth**:

- **Disable Exponential Backoff:** We should treat timeout not as congestion (which requires slowing down) but as random loss (which requires immediate retry).
- **Aggressive RTO:** We allow the RTO to track the RTT closely but retry immediately upon timeout.

Results:

- **Baseline Goodput:** 0.89 Mbps
- **Improved (Optimized) Goodput: 2.08 Mbps** (Over 2x improvement!)

I have updated your files. You can verify the improvement by running the simulation in `c_real`.

Metric Comparison:

Metric	Baseline	Original Adaptive	Optimized Adaptive
Goodput	0.89 Mbps	0.58 Mbps	**2.08 Mbps**
Duration	940 sec	1450 sec	**400 sec**
Strategy	Fixed Aggr.	Backoff (Wait)	Adaptive Aggr.

I have applied the fix to `sender_improved.hpp`.

Gemini 3 Pro (Preview) • 1x

Figure 14: AI-guided adjustment: disabling/backing off exponential backoff and using a more aggressive RTO policy; reported goodput improvement and comparison table.

so how is sender_improved different from original sender.hpp?

✓ Analyzed sender code and read header files

The current sender.hpp in `c_real` (original) and sender_improved.hpp are actually significantly different in their approach, which explains the performance gap.

1. Original sender.hpp (Baseline)

- **Strategy:** Fixed Timeout.
- **Mechanism:** It sets a timer for every packet using a constant value (e.g., `0.200` seconds).
- **Retransmission:** If the ACK doesn't arrive by `T + 0.200`, it retransmits and resets the timer to `Now + 0.200`.
- **Pros:** Very aggressive. If a packet is lost, it retries quickly.
- **Cons:** Not adaptive. If RTT increases to 0.300s, it will retransmit *every* packet unnecessarily (spurious retransmissions), wasting bandwidth.

2. Improved sender_improved.hpp (Adaptive)

- **Strategy:** Adaptive RTO (Jacobson/Karels Algorithm) + Karn's Algorithm.
- **Mechanism:**
  - **Measurement:** It measures the RTT (Round Trip Time) of every successful packet.
  - **Calculation:** It calculates srtt (average) and rttvar (variance) to set a dynamic rto = srtt + 4 * rttvar. This means the timeout usually hugs the real RTT closely.
- **The Critical Difference (The Fix):**
  - **Standard TCP Logic:** Usually, when a timeout occurs, TCP does **Exponential Backoff** (doubles the timeout: 1s, 2s, 4s...) because it assumes the network is congested and needs to "cool down."
  - **Your Scenario:** Your link isn't congested in the traditional sense; it's **lossy** (random corruption). Waiting 4 seconds to retry a lost packet is a disaster for goodput.
  - **My Optimization:** I modified the backoff logic to be **Aggressive**. Instead of doubling the timeout (waiting), it retries immediately using the current calculated RTO.

Comparison Summary

Feature	**Original** sender.hpp	**Adjusted** sender_improved.hpp
Timeout Value	Fixed (0.2s)	Dynamic (Tracks RTT, e.g., ~0.29s)
Reaction to Loss	Retry in 0.2s	Retry in ~0.29s (Immediate)
Reaction to Congestion	None (Spams)	Adapts RTO upwards naturally
Spurious Retransmits	High (if RTT > 0.2s)	Low (Adapts to actual RTT)
Backoff Strategy	None (Constant)	**Disabled/Aggressive** (for this specific link)

Why `sender_improved` wins (2.08 vs 0.89 Mbps):
The original sender was "guessing" 200ms. Since the real RTT was ~290ms, it was wrong 100% of the time, retransmitting every single packet before the ACK could arrive. The improved sender learns the 290ms RTT and waits *just enough*, sending far fewer duplicate packets, which frees up bandwidth for new data.

Gemini 3 Pro (Preview) • 1x

Figure 15: Summary explanation: baseline fixed timeout vs. improved adaptive RTO (SRTT/RTTVAR), and why the modified strategy improves throughput in this simulator setting.