

class06_hw

Kaitlyn Madriaga, PID: A17217752

2023-04-27

```
# Can you improve this analysis code?  
library(bio3d)  
s1 <- read.pdb("4AKE") # kinase with drug
```

```
## Note: Accessing on-line PDB file
```


```
s2 <- read.pdb("1AKE") # kinase no drug
```

```
## Note: Accessing on-line PDB file  
## PDB has ALT records, taking A only, rm.alt=TRUE
```

```
s3 <- read.pdb("1E4Y") # kinase with drug
```

```
## Note: Accessing on-line PDB file
```


```
s1.chainA <- trim.pdb(s1, chain="A", elety = "CA")  
s2.chainA <- trim.pdb(s2, chain="A", elety="CA")  
s3.chainA <- trim.pdb(s3, chain="A", elety="CA")  
s1.b <- s1.chainA$atom$b  
s2.b <- s2.chainA$atom$b  
s3.b <- s3.chainA$atom$b  
plotb3(s1.b, sse=s1.chainA, typ="l", ylab = "Bfactor")
```



```
plotb3(s2.b, sse=s2.chainA, typ="l", ylab="Bfactor")
```



```
plotb3(s3.b, sse=s3.chainA, typ="l", ylab="Bfactor")
```



function `b.plot()` takes a PDB id input (string) and returns a line plot of the B-factor with secondary structure elements shown as shaded regions

```
#takes protein data bank (PDB) id input (string)
b.plot <- function(protein.id) {
  #reads PDB file
  x <- read.pdb(protein.id)
  #produces a subset of atoms from PDB file, extracting chain A C-alpha (CA) atoms
  x.chainA <- trim.pdb(x, chain = "A", elty = "CA")
  #extracts the B-factors of the CA atoms
  #returns a line plot of the B-factors with secondary structure elements shown as shaded regions
  #x = position of CA atoms along protein chain/residue, y = B-factors
  plotb3(x.chainA$atom$b, sse=x.chainA, typ="l", ylab="Bfactor")
}
```

example:

```
b.plot("4AKE")
```

```
## Note: Accessing on-line PDB file
```

```
## Warning in get.pdb(file, path = tempdir(), verbose = FALSE):
## /var/folders/30/rswx5tg1775_dmp61fmjcvfc0000gn/T//Rtmp2sdyee/4AKE.pdb exists.
## Skipping download
```

