STATIC/JS/APP.JS LINE-BY-LINE EXPLANATION

app.js is the browser-side controller. It loads storage/listing/property API data, renders cards/details, handles profile menu behavior, dismisses flash messages, and handles avatar fallbacks.

WRAPPER AND UTILITIES

Lines 1-2: wrap the script in an IIFE and enable strict mode.

Lines 4-8: configure INR currency formatting for Indian rent/deposit values.

Lines 10-15: text returns a fallback for null, undefined, or empty values and stringifies valid values.

Lines 17-23: formatMoney converts values to numbers and formats invalid values as INR zero.

Lines 25-34: createElement builds an element, assigns a class, and optionally sets text content.

Lines 36-45: setStatus replaces a status container with a heading and message.

Lines 47-58: apiUrlWithCurrentFilters copies current page query parameters into an API URL.

Lines 60-62: detailUrl replaces the trailing 0 in the detail URL template with the listing id.

Lines 64-71: addMeta appends one dt/dd pair inside a wrapper div.

LISTING CARDS AND LISTING API

Lines 73-117: listingCard creates one listing card with image, featured tag, location, title, price, metadata, and detail link.

Lines 119-137: loadStorageStatus fetches /api/storage and updates the data source pill, or shows API unavailable.

Lines 139-148: loadListings locates the listing grid/status/count elements and reads the detail URL template.

Lines 149-161: fetch listing JSON using current filters, parse listings, and update count.

Lines 163-172: show an empty-state message when no listings match.

Lines 174-180: render listing cards, hide status, and show the grid.

Lines 181-193: on failure, hide the grid, set count to zero, and show an API error message.

PROPERTY DETAIL RENDERING

Lines 195-200: setPropertyText writes text into a selected element when it exists.

Lines 202-220: renderAmenities splits the amenities string by commas and renders li items.

Lines 222-229: renderProperty updates document title and hero image.

Lines 231-249: fill property type/city, title, address, price, rent, deposit, bedrooms, bathrooms, area, furnishing, description, and owner fields.

Lines 250-258: show/hide the Featured tag and set the hidden listing id input.

Lines 260-266: render amenities and unhide the property content.

Lines 268-300: loadProperty fetches one listing, renders it, or shows the not-found state and title on errors.

UI BEHAVIORS

Lines 302-331: initProfileToggle opens/closes the profile popover, closes it on outside click, and closes it on Escape.

Lines 333-347: initFlashDismiss auto-fades success/info flash messages after two seconds.

Lines 349-361: initAvatarFallbacks hides broken avatar images and shows initials fallback text.

Lines 363-370: on DOMContentLoaded, initialize UI behaviors and start API loading for whichever page is present.

Line 371: closes the IIFE.