

Remove and Install The Forks - Stark VARG MX 1.2 / EX

Video link: https://www.youtube.com/watch?v=FoGSZh_VOdI

Source video: Remove and Install The Forks- Stark VARG MX 1.2 by Stark Future Official

Applicable models: MX 1.2 / EX

Scope

This guide follows the same step-by-step workshop structure as the MX tutorials, but it is derived as a visual sequence from the official Stark Future ASMR video. Because the source video does not provide usable captions or narration, the procedure is documented through curated screenshots and concise action guidance.

Preparation

- Place the bike on a stable stand or work area before starting the procedure.
- Prepare the correct tools for the fasteners, clips, brackets, and components shown in the video.
- Keep removed hardware organized in sequence so reassembly follows the same order as the video.
- Have a torque wrench ready for any tightening steps that specify a torque value.

Removal Procedure

1. Prepare access to the Forks

Remove the surrounding hardware needed to expose the Forks and its clamping or axle points.

Keep the removed fasteners organized in sequence so reassembly matches the video.



2. Remove the visible retaining hardware for the Forks

Remove the visible Forks fasteners in the order shown and support the part as it comes free.

Support the component as the last fastener is removed.



3. Release any bracket, clip, or coupling attached to the Forks

Free any bracket, clip, spacer, linkage, or connector that still ties the Forks to the bike.

Note the orientation of these supporting pieces before setting them aside.



4. Remove the Forks from the bike

Slide the Forks free from the bike once the clamping hardware and support pieces are released.

Inspect the removed part and the mounting points before reassembly.



Installation Procedure

5. Position the Forks for installation

Return the Forks to its mounting position and align the holes, tabs, or locating surfaces.

Hold the component in place until the first retaining hardware is started.



6. Reconnect or refit the support pieces for the Forks

Reinstall any bracket, clip, spacer, linkage, or coupling associated with the Forks.

Make sure each supporting piece is seated correctly before final tightening.



7. Install the retaining hardware for the Forks

Install the Forks retaining hardware by hand first and keep the part aligned as the hardware is tightened.

Check that the component remains aligned while the hardware is brought fully home.

Tighten the KYB upper triple clamp and middle/lower triple clamp pinch bolts to the etched torque values marked on each fork assembly.



8. Verify the completed installation of the Forks

Inspect the final position of the Forks and confirm that all hardware, clips, and surrounding parts are back in place.

Check the component for correct fit and movement before returning the bike to service.



Critical Checks Before Riding

- Confirm the serviced component is fully seated and all fasteners are tightened in the correct order.
- Recheck all torque-critical hardware before riding.
- Make sure all routed cables, clips, brackets, and surrounding parts are returned to their original positions.
- Inspect the bike visually for any missing hardware before returning it to service.