

# Generation of counterterms in MADNkLO

Simone Lionetti

April 3, 2019

This document describes the contents of the file `subtraction.py` (located in `madgraph/core`).

## 1 Classes

### 1.1 SubtractionLeg

For the purpose of the subtraction, it is impractical to carry around the whole information that is contained in an object of the type `base_objects.Leg`. A simpler object `SubtractionLeg` is therefore defined with the following three attributes:

- **n**: an integer that indicates the leg number in the process,
- **pdg**: the PDG identifier which specifies the type of particle,
- **state**: a flag to specify if the leg is in the initial or in the final state.

For convenience, a class `SubtractionLegSet` which represents a set of `SubtractionLeg`'s is also implemented. Internally, this is just a sorted `tuple` since it is assumed that order is irrelevant. However, this object also provides some additional useful methods.

### 1.2 SingularStructure

The `SingularStructure` class is designed to identify unresolved limits in phase space, and by extension counterterms. It is a recursive structure which represents a tree of `SubtractionLeg`'s in a process. At each level, the leaves are gathered into a `SubtractionLegSet` attribute called `'legs'` and the `SingularStructure` that specify sub-trees are grouped into a `list` called `'substructures'`. There are currently three classes that inherit from `SingularStructure` and represent different unresolved limits:

- **SoftStructure** indicates that all of its sub-legs are soft,
- **CollStructure** indicates that all of its sub-legs are collinear,
- **BeamStructure** specifies that a leg is taken from a hadron beam after some splitting.

The generic parent class `SingularStructure` can be instantiated to group together several structures and specify an additional set of legs; this feature is exploited in the implementation of momentum mappings to identify which particles to recoil against.

For the sake of concreteness, a non-trivial example of `SingularStructure` is illustrated in fig. 1. In the conversion to a string, `SingularStructure`'s are converted to a single character, and the PDG codes and the state labels of `SubtractionLeg`'s are suppressed,<sup>1</sup> such that the object of fig. 1 prints as

$$C(C(C(5,13),C(7,10,11,16)),S(4,6,8),1,9). \quad (1)$$

The conversion of objects to characters is carried out through the method `name()`, according to the rules

$$\begin{aligned} \text{SingularStructure} &\rightarrow '\text{'}, & \text{CollStructure} &\rightarrow '\text{C}', \\ \text{SoftStructure} &\rightarrow '\text{S}', & \text{BeamStructure} &\rightarrow '\text{F}'. \end{aligned} \quad (2)$$

---

<sup>1</sup> This is the default behaviour, the printout can be tuned by calling the function `__str__()` explicitly and passing the keyword arguments `print_n`, `print_pdg` and `print_state`.




Figure 1: Example scheme of a **SingularStructure** object. The nodes in bubbles belong to the list of **substructure** of the structure they are linked to on the left, while the ones in boxes belong to its **legs**. Within **SubtractionLeg** objects, initial and final states are here abbreviated with the letters **i** and **f** respectively.

Whenever the species of particles and their state are not relevant or clear from the context, we will identify **SingularStructure**'s using their printout for brevity.

In order to understand how limits are specified using these objects, let us consider some simpler examples. While the **SingularStructure**  $\mathcal{C}(3,5,7,8)$  indicates the limit where legs number 3, 5, 7 and 8 are simultaneously taken to be collinear,  $(\mathcal{C}(3,5), \mathcal{C}(7,8))$  denotes the limit where 3 goes collinear to 5, and 7 to 8.<sup>2</sup> These situations are still distinct from the nested limit  $\mathcal{C}(\mathcal{C}(3,5), 7, 8)$ , which approaches the configuration where all four particles are collinear by first letting legs 3 and 5 go to the same direction, and subsequently sending the angles among their common parent, leg 7 and 8 to zero. Similarly,  $\mathcal{S}(\mathcal{C}(4,7))$  indicates the limit of legs 4 and 7 going collinear to each other, and their parent leg subsequently going soft.

### 1.3 Current

### 1.4 Counterterm

### 1.5 IRSubtraction

## 2 Generation of elementary structures

Given a process, the first

## References

<sup>2</sup> Note that the outermost bracket around the latter printout denotes a **SingularStructure** of unspecified type, as indicated in eq. (2). Although the default behaviour does not distinguish among different orderings of the limits which appear at the same level, this can be tweaked using the keyword argument `orderless` of the comparison function `__eq__` for **SingularStructure**.