

Table 1: Milestone progress for the CAN-FD bus transceiver implementation.

#	Milestone	Status	Progress	Est. Remaining	Notes
1	CAN MAC TX (no error handling)	Done (review pending)	100%	-	TB: ~1M affirmations.
2	CAN MAC RX (no error handling)	Done (review pending)	100%	-	TB: 14.7k affirmations, coverage-driven.
3	TB CAN MAC RX-TX (no error handling)	Skipped	-	-	Separate paths, individual TBs suffice.
4	CAN FCE + MAC error handling	Done (review pending)	100%	-	3-state FSM, integrated into <code>can_mac</code> wrapper. TB: 227 affirmations.
5	Extend TB with MAC error cases	Partial	60%	2 days	TX done (8 injection types). RX error injection not yet implemented.
6	CAN PCS RX TX (no error handling)	Not started	0%	5 days	TX and RX PCS modules needed.
7	Extend TB with PCS timing	Not started	0%	3 days	Depends on milestone 6.
8	CAN FCE PCS error handling	Done (review pending)	100%	-	Bus-off entry/recovery tested in <code>can_fce_tb</code> .
9	Extend TB with PCS functionality	Not started	0%	3 days	Bit timing, TDC, SP/SSP verification. Depends on 6 and 7.
10	CAN LLC RX TX (no error handling)	Not started	0%	5 days	TX and RX LLC modules needed.
11	Extend TB with LLC	Not started	0%	3 days	Depends on milestone 10.
12	CAN FCE LLC error handling	Done (review pending)	100%	-	Bus-off indication and recovery tested in <code>can_fce_tb</code> .
13	Extend TB with LLC error cases	Not started	0%	5 days	Depends on milestones 11 and 12.
-	Documentation (report, verification plan)	Ongoing	-	Continuous	
Sum				16 days	

Table 2: Testbench execution status and affirmation counts.

Testbench	Affirmations	Coverage	Status
can_fce_tb	227	Reset, normal usage, random stress	Passing
can_mac_bs_tb	11,561	Dynamic/fixed stuff bits (Reset, normal usage, random bit streams)	Passing
can_mac_crc_tb	54,084	CRC-15, CRC-17, CRC-21 (Reset, normal usage, random frames)	Passing
can_mac_ser_tx_tb	793,708	IDE, FDF, DLC 0-15 (Reset, normal usage, random frames)	Passing
can_mac_tx_tb	268,903	All formats, 8 error injection types (Reset, normal usage, random frames and injections)	Passing
can_mac_rx_tb	14,704	IDE, FDF, DLC 0-15 (Reset, normal usage, random frames)	Passing