

IMT Nord Europe
École Mines-Télécom
IMT-Université de Lille

RÉPUBLIQUE FRANÇAISE
Liberté Égalité Fraternité

Spatio-Temporal Transformer for Human Motion tasks

Spatio-Temporal Attention and Temporal Convolution for Motion2Text and Text2Motion Generation

Antony Manuel

IMT Nord Europe
Department of Computer Science
Master of Data Science

Lille, April 2026

Abstract

Understanding and modeling the relationship between human motion and natural language is a key challenge at the intersection of computer vision and natural language processing. This project investigates motion-language representation learning with a bidirectional focus. In the first place, it focuses on motion-to-text generation, aiming to automatically produce natural language descriptions from 3D human motion sequences. The second part of the project explores text-to-motion generation, where the goal is to synthesize realistic human motion sequences conditioned on textual descriptions. Using the HumanML3D dataset, which contains thousands of motion samples paired with rich textual annotations, I explored architectures based on transformer to encode temporal skeletal motion and decode corresponding textual descriptions, but also the other way around, then I propose in this work a novel approach with Spatio-Temporal Transformers and spatial-temporal attention mechanisms. For the first task, two complementary approaches are implemented: (1) a spatio-temporal transformer encoder coupled with a pre-trained language model decoder to leverage large-scale linguistic knowledge, and (2) a spatio-temporal transformer encoder followed by a temporal transformer decoder trained end-to-end. For the second task, a Spatio-Temporal Diffusion Transformer (DiT) is implemented to generate realistic human motion sequences from textual descriptions. Experimental results demonstrate the feasibility of generating coherent and semantically meaningful descriptions of human motion from 3D pose data. This work establishes a foundation for bidirectional motion-language modeling, with future extensions targeting gesture-to-motion generation and unified motion-language understanding frameworks. The code is available here.

Keywords: Spatio-temporal attention, Temporal Convolution, Diffusion models

Notation

$\mathcal{X}$	Set.
$\mathbb{N}$	Set of integers.
$\mathbb{R}$	Set of real numbers.
$\subset$	Strict inclusion.
$\subseteq$	Inclusion with possible equality.
$\lvert \cdot \rvert$	Absolute value of a real number.
$\lVert \cdot \rVert$	Euclidean norm of a vector.
x	A real scalar belonging to $\mathbb{R}$.
$x \in \mathbb{R}^n$	A vector in $\mathbb{R}^n$.
$X \in \mathbb{R}^{n \times d}$	A matrix in $\mathbb{R}^{n \times d}$.
I_n	Identity matrix of size n.
$X^\top$	Transpose of X.
X^{-1}	Inverse of X.
x	A random scalar variable.
$x \in \mathbb{R}^n$	A random vector in $\mathbb{R}^n$.
$X \in \mathbb{R}^{n \times d}$	A random matrix in $\mathbb{R}^{n \times d}$.
$P(x)$, $P(\mathbf{x})$	Probability distribution of x (resp. joint probability distribution of $\mathbf{x}$).
$x \sim P_x$	Random variable x follows a probability distribution P_x.
$\mathbb{E}(x)$	Expectation of x with respect to $P(x)$.
$\mathrm{Var}(x)$	Variance of x under $P(x)$.
x_i	i-th element of the vector x.
$X_{i,j}$	Element at row i, column j of the matrix X.
$X_{i,:}$	i-th row of the matrix X.
$X_{:,i}$	i-th column of the matrix X.
$f \circ g$	Composition of functions f and g.
dy/dx	Derivative of y with respect to x.
$\partial y/\partial x$	Partial derivative of y with respect to x.
$\partial f/\partial x$	Jacobian matrix $J \in \mathbb{R}^{n \times p}$ of $f : \mathbb{R}^n \to \mathbb{R}^p$.

Sometimes we use a function f whose argument is a scalar but apply it to a vector $f(x)$ or a matrix $f(X)$. This denotes the element-wise application of f to the array.

$$* \ * \ *$$

Contents

Contents **3**

1 Introduction **5**

2 Background **7**
1 Task Definition . . . 7
1.1 Motion Data . . . 7
1.2 Motion Captioning . . . 8
1.3 Motion Generation . . . 8
2 Attention mechanism . . . 8
3 Diffusion models . . . 9

3 Motion2Text **11**
1 Proposed architecture . . . 11
1.1 Overview . . . 11
1.2 Spatio-temporal Transformer . . . 11
1.2.1 Spatial Attention . . . 12
1.2.2 Temporal Attention . . . 12
1.2.3 Temporal Convolution . . . 12
1.3 Temporal Transformer . . . 12
1.4 Decoder . . . 12
2 Experiments . . . 13
2.1 Training Strategy . . . 13
2.2 Evaluation metrics . . . 14

4 Text2Motion **15**
1 Proposed architecture . . . 15
1.1 Overview . . . 15
1.2 Spatio-temporal Transformer Decoder . . . 16
2 Experiments . . . 16
2.1 Training Strategy . . . 16

2.2 Evaluation metrics 16

5 Results **17**
1 Results Analysis 17
2 Discussion 17

6 Conclusion **18**

Bibliography **19**

A Appendix **22**

B Annexes **24**
1 Markov Chain 24

Introduction

Human motion understanding is a cornerstone of human perception and cognition, as individuals continuously execute movements dictated by internal intentions and environmental interactions. Just as interpreting images, videos [1, 2], and natural language is fundamental to artificial intelligence, understanding human motion is equally critical. Consequently, modeling human kinematics has become essential across a broad spectrum of application domains, including human-computer interaction, autonomous robotics, sports analytics, healthcare diagnostics, and immersive gaming. With the development of deep learning, diverse kind of data-driven methods emerged, such as RNN methods or graph-based methods [3, 4] for motion prediction [5, 6], but also, Variational Autoencoders (VAE) [7], Generative Adversarial Networks (GAN) [8], Diffusion models [9] for realistic human motion generation.

However, modeling human motion remains a challenging task due to the complexity of human kinematics. Their inherent non-linearity, short or long-term dependencies and their inter-joints correlations make the task difficult. More importantly, human motion is mostly an unverbal communication, between humans and their environment, depending on a variety of factors such as their habits, culture, social norms and their individual intentions. Moreover, in the context of motion generation, human motion often require conditional information, such as textual descriptions or audio signals, in order to generate realistic and coherent motion sequences.

In this work, we focus, in the first place, on the problem of human motion description, which aims to generate textual descriptions of motion sequences. Secondly, we focus on the problem of human motion generation, which aims to generate motion sequences from textual descriptions. For both of these problems, the main challenge is to take into account both temporal dynamics and spatial dependencies whitin human body joints. As a mean to address this challenge, in both task we propose to consider the human body as a graph, where the joints are represented as nodes and the bones as edges. Therefore, as defined in Chen et al. [10], we propose to leverage spatio-temporal attention mechanism with temporal graph convolutions [11] and spatio-temporal graph convolutions [12] to model temporal and spatial dependencies of body joints. For the first task, we studied the effectiveness of such mechanism to extract temporal and spatial features from motion data and propose to leverage pre-trained language models such as T5 model sentence generation, as it showed

promising results in generated text [13]. Then, for the second one, we propose to leverage diffusion processes coupled with transformer architecture to generate motion sequences from textual descriptions. The proposed method is evaluated on the HumanML3D dataset[1] [14], which is a large-scale dataset of human motion sequences with corresponding textual descriptions.

This report is organized as follows: In chapter 2, we provide a background on both tasks, but also on the architecture used in this work. Chapter 3, 4, cover the proposed architecture for both motion-to-text captioning and text-to-motion generation tasks, respectively, including mathematical formulations, training details and evalutation metrics chosen. Finally, we draw conclusion in chapter 5 and present results of the proposed methods and a discussion on the findings and future directions.

[1] *More information about the dataset and how to obtain it can be found here.*

Background

1 Task Definition

To begin with, we introduce the human motion data representations, then formally define the two tasks of interest in this work, namely motion-to-text captioning and text-to-motion generation.

1.1 Motion Data

Human motion data is typically represented through a simplified motion human skeletons structure, with a set of connected joints. That can be categorize into two main types: *keypoint-based* or *position-based* and *rotation-based* representations [15, 16]. We can transit from one representation to another using forward kinematics and inverse kinematics. Other representations exist, such as the *velocity-based* representation, using change of joints positions or rotations between consecutive frames.

Rotation-based With the *rotation-based* formalism, human pose is represented by joint rotations mostly in $SO(3)$[1], which can be expressed in various formats, such as Euler angles, axis-angle, or quaternions. A widely use rotation-based representation is the parametric model SMPL [17]. It employs a set of pose parameters $\theta \in \mathbb{R}^{3\times J}$ and shape parameters $\beta \in \mathbb{R}^{10}$ to define the human body mesh, where J is the number of joints. Pose parameters θ encode the relative rotations of each joint, while shape parameters β process body shape configurations. From the pose and shape parameters, the model generates a mesh representation of the human body. Other models derived from SMPL, such as SMPL-X [18] and SMPLH [19], extend the original model to include additional joints and body parts, such as the face, hands, and feet, providing a more detailed representation of human motion.

Position-based The *position-based* representation describes, for each of the T frames, human motion as a set of 3D coordinates for each of the J joints. In other words, for each frame $m_t \in \mathbb{R}^{J\times 3}$, $m_{t,j} = (x_{t,j}, y_{t,j}, z_{t,j})$ represents the spatial configuration of joint

[1] The special orthogonal group in three dimensions

j at time step t. Then a motion sequence $M \in \mathbb{R}^{T \times J \times 3}$ of length T is represented as a tensor $M = [m_1, m_2, \ldots, m_T]$. In this work, we focus on the position-based representation, which is the one used ont he HumanML3D dataset [14]. In this case, the representation use $J = 22$ joints, and the motion sequence length T varies from x to x frames with an average legnth of x frames.

1.2 Motion Captioning

The original task of motion-to-text captioning aims to model the conditional distribution of natural language descriptions given an input motion sequence, and to generate a caption that faithfully reflects the semantic content of the motion. This task is similar to image or video captioning, where the goal is to generate a textual description of visual content. These tasks could easily be separated into two sub-tasks: (1) extracting visual features from the input and (2) generating a textual description based on the extracted features. Several methods have been proposed to address these captioning tasks, based on the combination of an image encoder, usually a CNN for the first sub-task and a text decoder for the second sub-task. For the text decoder, RNNs were widely used in the early works [20, 21], then LSTMs were introduced [22, 23, 24] and [1, 25] proposed to use those combination video captioning seen as a sequence-to-sequence task, and showed the effectiveness of LSTMs in capturing temporal dependencies in video sequences. Afterwards, Transformers [26] have been introduced in the field of text generation, and have shown to outperform RNNs and LSTMs in various NLP tasks, such as machine translation, text summarization, and question answering. Therefore, transformer achitecture has been widely adopted in image and video captioning tasks [27, 28, 29]. Despite the similarities between motion captioning and image/video captioning, motion captioning presents unique challenges due to the inherent complexity of human motion.

1.3 Motion Generation

For the human motion generation task, methods are classified into two main categories: *regression-based* methods and *generative* methods.

2 Attention mechanism

The first definition of Transformer architecture and self-attention mechanism is presented in the following paper [26]. The following section provides a brief overview of the mechanism presented on the previous paper, which is used in this work for both motion captioning and motion generation tasks.

Self-attention Initially, for a sequene of embedding $(w_1, w_2, \ldots, w_l)$ where $w_i \in \mathbb{R}^{d_{\text{model}}}$, the first step of this mechanism is to linearly map the embedding w_i into query $q_i \in \mathbb{R}^{d_k}$,

key $k_i \in \mathbb{R}^{d_k}$, and value $v_i \in \mathbb{R}^{d_v}$ representations. Then the dot product is computed between each queries and all keys scaled by the square root of the key dimension $\sqrt{d_k}$, which measures the similarity of each key to the corresponding query. Then a softmax function is applied to the result to compute a weighted sum of the value. In practice, the attention mechanism is compute simultaneously for all queries, keys, and values packed together in matrices $Q, K, V \in \mathbb{R}^{l \times d_{\text{model}}}$, where l is the length of the input sequence, and d_{model} the dimension of the model. The scaled dot-product attention is then computed as follows:

$$\text{Attention}(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V. \tag{2.1}$$

Moreover, in Transformer architectures, this operation is performed in parallel over h heads:

$$\text{MultiHead}(Q, K, V) = \text{Concat}(\text{head}_1, \ldots, \text{head}_h)W_O, \tag{2.2}$$

where each head is defined as: $\text{head}_i = \text{Attention}(QW_Q^{(i)}, KW_K^{(i)}, VW_V^{(i)})$, and $W_O \in \mathbb{R}^{hd_k \times d_{\text{model}}}$ is a learnable linear output projection.

Cross-attention To condition text generation on motion information, the decoder attends to the output of the motion encoder through a cross-attention mechanism. Let $H \in \mathbb{R}^{T \times d_{\text{model}}}$ denote the final output of the motion encoder. In the cross-attention sublayer, the decoder hidden states serve as queries, while the encoder outputs are used as keys and values:

$$Q = YW_Q, \quad K = HW_K, \quad V = HW_V,$$

where $W_Q, W_K, W_V \in \mathbb{R}^{d_{\text{model}} \times d_k}$ are learnable projection matrices.

The attention operation is computed using scaled dot-product attention defined in (**??**). This mechanism enables the decoder to dynamically focus on relevant motion features when generating each output token.

3 Diffusion models

There are mainly three types of diffusion models: *Score Matching with Langevin Dynamics* (SMLD) [30], *Denoising Diffusion Probabilistic Model* (DDPM) [9], and *Score-based Generative Model* (SGM) [31]. However, in this work, we only focus on the DDPM paradigm. As introduced in the paper by Ho et al.[9], diffusion process corresponds to two Markov chains that deconstruc data with defined noise and reconstruct the desired samples from the noise.

The forward chain gradually adds Gaussian noise, to a data sample x_0 of distribution $q(x_0)$, over a series of time steps $(t = 1, \ldots, T)$, resulting in a sequence of latent variables $(x_1, \ldots, x_T)$. In order to end up with a clean standard normal distribution at the final time

step T, the forward process is governed by a variance schedule $(\beta_1, \ldots, \beta_T)$, and is defined as follows:

$$q(x_{1:T}|x_0) = \prod_{t=1}^{T} q(x_t|x_{t-1}), q(x_t|x_{t-1}) = \mathcal{N}(x_t; \sqrt{1-\beta_t}x_{t-1}, \beta_t\mathbf{I}) \tag{2.3}$$

Additionally, instead of sampling step-by-step iteratively, the paper leverages the property that $q(x_t|x_0)$ can be calculated directly in closed form at any arbitrary timestep t. Let $\alpha_t = 1 - \beta_t$ and $\bar{\alpha}_t = \prod_{s=1}^{t} \alpha_s$, the distribution becomes:

$$q(x_t|x_0) = \mathcal{N}(x_t; \sqrt{\bar{\alpha}_t}x_0, (1-\bar{\alpha}_t)\mathbf{I}) \tag{2.4}$$

and, any sample $x_t \sim q(x_t|x_0)$ can be expressed as:

$$x_t = \sqrt{\bar{\alpha}_t}x_0 + \sqrt{1-\bar{\alpha}_t}\epsilon \quad \text{where } \epsilon \sim \mathcal{N}(0, \mathbf{I})$$

On the other hands, the reverse process aims to reconstruct the original data sample x_0 from the noisy sample x_T by learning the parameterized Gaussian transition $p_\theta(x_{t-1}|x_t)$ at each time step t:

Motion2Text

1 Proposed architecture

1.1 Overview

The architecture proposed can be viewed as an encoder-decoder architecture, where the encoder is a concatenation of a spatio-temporal transformer encoder followed by a temporal transformer encoder. The first sublayer seize spatial interactions between joints in intra-frame through spatial attention. Subsequently, the temporal transformer encoder captures inter-frame temporal dependencies through temporal convolution. Moreover, in order to obtain additional temporal dependencies, the spatio-temporal encoder is followed by a temporal transformer encoder, which captures long-term temporal dependencies through temporal attention. Afterwards, a temporal Transformer decoder is used to generate a textual description of the motion sequence based on the spatio-temporal features previously provided by the encoder.

The following section provides a detailed description of this encoder-decoder architecture.

1.2 Spatio-temporal Transformer

Based on Chen et al. [10] proposed architecture, we simple transposed it to a motion task, where the human body of each frame in the motion is considered as a graph. The nodes correspond to the joints of the human body and the edges represent the connections between them. The spatial self-attention is still applied to the spatial dimension of the




Fig. 3.1: Spatio-temporal Transformer architecture

motion data, while the temporal convolution is applied to the temporal dimension in order to capture temporal dependecies.

1.2.1 Spatial Attention

For each joint i in t
Multihead attention attention definition

1.2.2 Temporal Attention

Multihead attention attention definition

1.2.3 Temporal Convolution

Temporal Convolution sub-layer After spatial information is obtained, we impose temporal convolution operation on the temporal-edge in the spatio-temporal graph to model temporal dynamics within trajectory sequence. Given the input graph of shape (T, N, C), where T is history frame, N is node number and C is the embeddings, we use a standard 2D convolution with the kernel size (K Œ 1) to force on processing along the temporal dimension, as expressed in the following: outputi = ConvKŒ1(M ultiHeadt i) (10) As a Transformer structure, we regularly imply layer normalization (Ba et al. (2016)) after skip connection in the end of TCN sub-layer. That is, the output of sub-layer is LayerN orm(x + Sublayer(x)). In this way, we have a well-defined operation on the constructed spatio-temporal graph.

1.3 Temporal Transformer

temporal convolution encoder decoder

1.4 Decoder

Transfer learning Employing a pre-trained language model decoder offers several advantages. First, it substantially reduces the amount of paired motion and text data required for effective training. Second, it improves training stability and generalization by leveraging robust linguistic representations learned during pre-training. Finally, transfer learning allows the model to concentrate on learning the alignment between motion representations and language, rather than learning language generation from scratch, resulting in more fluent and semantically accurate text outputs.

The text decoder used in this work is based on the T5 pre-trained Transformer language model, following the encoder-decoder architecture introduced by [13]. This model reformulates all NLP tasks into a unified text-to-text paradigm, making it particularly suitable for conditional text generation from motion representations.

Thereby, the decoder is initialized from a pre-trained T5 model and operates in an autoregressive manner, i.e. predicts the next value in the output sequence based on the previous values. In this context, at each time step, the decoder generates a text token conditioned on the output of the motion encoder and on the previously generated tokens. By leveraging large-scale pre-training, the decoder benefits from strong linguistic priors, such as syntactic structure and semantic consistency, which would be difficult to learn from limited specific data alone.

Moreover, as the motion encoder, the decoder consists of a stack of $N = 6$ layers, each composed of three sub-layers: a self-attention mechanism and a cross-attention mechanism, and a position-wise feed-forward network. Likewise, each sub-layer is followed by a residual connection and layer normalization.

2 Experiments

2.1 Training Strategy

cross entropy loss contrastive learning teacher forcing

The model parameters are optimized using the Adam optimizer. The learning rate is set to $\eta = 10^{-4}$, and training is performed using batches of 16 sequences of approximately same legnth, padded if needed. To improve training stability, gradient clipping is applied, and the learning rate may be decayed during training according to a predefined schedule. All components of the model, including the motion encoder and the text decoder, are trained end-to-end.

Loss function The model is trained to maximize the likelihood of the ground-truth text sequence conditioned on the input motion representation. Given a target sequence of tokens $\mathbf{y_{gt}} = (y_1, y_2, \ldots, y_j)$, the training objective is defined using the cross-entropy loss. At each decoding step t, the model predicts a probability distribution $p(y_t \mid y_{<t}, H)$ over the vocabulary, where H denotes the output of the motion encoder. The loss is computed as:

$$\mathcal{L}_{\text{CE}} = -\sum_{t=1}^{T_t} \log p(y_t \mid y_{<t}, H).$$

Minimizing this loss encourages the model to assign high probability to the correct target tokens at each time step.

Teacher forcing During training, teacher forcing is employed to improve convergence and stability. Specifically, the ground-truth token y_{t-1} is provided as input to the decoder when predicting the token y_t, rather than using the model's own previous prediction. This allows the decoder to learn the correct conditional distributions efficiently, while avoiding the accumulation of errors during training.

2.2 Evaluation metrics

BLEU, ROUGE, METEOR, CIDEr

Text2Motion

1 Proposed architecture

1.1 Overview

stFormer architecture with diffusion based decoder for human motion generation from textual descriptions

[32] [33] [9]




Fig. 4.1: The Diffusion Transformer (DiT) architecture, reproduced from Peebles & Xie (2023).

1.2 Spatio-temporal Transformer Decoder

Diffusion based decoder

2 Experiments

2.1 Training Strategy

L2 Loss contrastive learning

2.2 Evaluation metrics

Mean squared error (MSE) Fréchet Inception Distance (FID) Mean Per Joint Position Error (MPJPE)

Results

1 Results Analysis

Initially, the tokenizer exhibited several decoding issues, notably incorrect subword combinations such as *"sclimbing"* or *"salimbs"*. In other cases, the decoding process entered repetitive loops, producing sequences with repeated tokens (e.g., *"legs legs legs ..."*) or hallucinated a lot and generated words in russian or german.

To mitigate these instabilities, several corrective measures were explored. First, motion features were normalized in order to reduce scale-related inconsistencies in the encoder outputs. Subsequently, the projection layer responsible for mapping the motion encoder representations to the T5 model embedding space was redesigned. Specifically, the original single linear layer was replaced with a three-layer multilayer perceptron (MLP), where each layer is followed by a ReLU activation and a dropout layer. This architectural modification improved the stability of the generated sequences and reduced repetitive decoding behavior.

2 Discussion

You probably found all the files from.

Training Error	**Testing Error**
0	∞

Tab. 5.1: The Results

Conclusion

Bibliography

[1] S. Venugopalan, M. Rohrbach, J. Donahue, R. Mooney, T. Darrell, and K. Saenko, "Sequence to sequence – video to text," 2015.

[2] X. Zhou, A. Arnab, S. Buch, S. Yan, A. Myers, X. Xiong, A. Nagrani, and C. Schmid, "Streaming dense video captioning," 2024.

[3] W. Mao, M. Liu, M. Salzmann, and H. Li, "Learning trajectory dependencies for human motion prediction," 2020.

[4] T. N. Kipf and M. Welling, "Semi-supervised classification with graph convolutional networks," 2017.

[5] J. Martinez, M. J. Black, and J. Romero, "On human motion prediction using recurrent neural networks," 2017.

[6] K. Fragkiadaki, S. Levine, and J. Malik, "Recurrent network models for kinematic tracking," *CoRR*, vol. abs/1508.00271, 2015.

[7] D. P. Kingma and M. Welling, "Auto-encoding variational bayes," 2022.

[8] I. J. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio, "Generative adversarial networks," 2014.

[9] J. Ho, A. Jain, and P. Abbeel, "Denoising diffusion probabilistic models," 2020.

[10] W. Chen, F. Wang, and H. Sun, "S2tnet: Spatio-temporal transformer networks for trajectory prediction in autonomous driving," 2022.

[11] C. Yu, X. Ma, J. Ren, H. Zhao, and S. Yi, "Spatio-temporal graph transformer networks for pedestrian trajectory prediction," 2020.

[12] S. Yan, Y. Xiong, and D. Lin, "Spatial temporal graph convolutional networks for skeleton-based action recognition," 2018.

[13] C. Raffel, N. Shazeer, A. Roberts, K. Lee, S. Narang, M. Matena, Y. Zhou, W. Li, and P. J. Liu, "Exploring the limits of transfer learning with a unified text-to-text transformer," 2023.

[14] C. Guo, S. Zou, X. Zuo, S. Wang, W. Ji, X. Li, and L. Cheng, "Generating diverse and natural 3d human motions from text," in *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 5142–5151, 2022.

[15] W. Zhu, X. Ma, D. Ro, H. Ci, J. Zhang, J. Shi, F. Gao, Q. Tian, and Y. Wang, "Human motion generation: A survey," 2023.

[16] B. Cheng, Z. Zhou, Y. Deng, S. Du, Z. Wang, Y. Wen, Y. Zhang, S. Ni, Y. Kong, L. Xie, and X. Yang, "Context-aware human motion generation: A comprehensive survey," *Design and Artificial Intelligence*, vol. 1, no. 1, p. 100007, 2025.

[17] M. Loper, N. Mahmood, J. Romero, G. Pons-Moll, and M. J. Black, "SMPL: A skinned multi-person linear model," *ACM Transactions on Graphics, (Proc. SIGGRAPH Asia)*, vol. 34, pp. 248:1–248:16, Oct. 2015.

[18] G. Pavlakos, V. Choutas, N. Ghorbani, T. Bolkart, A. A. A. Osman, D. Tzionas, and M. J. Black, "Expressive body capture: 3d hands, face, and body from a single image," in *Proceedings IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2019.

[19] J. Romero, D. Tzionas, and M. J. Black, "Embodied hands: Modeling and capturing hands and bodies together," *ACM Transactions on Graphics, (Proc. SIGGRAPH Asia)*, vol. 36, Nov. 2017.

[20] X. Chen and C. L. Zitnick, "Learning a recurrent visual representation for image caption generation," 2014.

[21] J. Mao, W. Xu, Y. Yang, J. Wang, Z. Huang, and A. Yuille, "Deep captioning with multimodal recurrent neural networks (m-rnn)," 2015.

[22] O. Vinyals, A. Toshev, S. Bengio, and D. Erhan, "Show and tell: A neural image caption generator," 2015.

[23] K. Xu, J. Ba, R. Kiros, K. Cho, A. Courville, R. Salakhutdinov, R. Zemel, and Y. Bengio, "Show, attend and tell: Neural image caption generation with visual attention," 2016.

[24] S. J. Rennie, E. Marcheret, Y. Mroueh, J. Ross, and V. Goel, "Self-critical sequence training for image captioning," 2017.

[25] J. Donahue, L. A. Hendricks, M. Rohrbach, S. Venugopalan, S. Guadarrama, K. Saenko, and T. Darrell, "Long-term recurrent convolutional networks for visual recognition and description," 2016.

[26] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, and I. Polosukhin, "Attention is all you need," 2023.

[27] Y. Luo, J. Ji, X. Sun, L. Cao, Y. Wu, F. Huang, C.-W. Lin, and R. Ji, "Dual-level collaborative transformer for image captioning," 2021.

[28] Y. Wang, J. Xu, and Y. Sun, "End-to-end transformer based model for image captioning," 2022.

[29] S. Herdade, A. Kappeler, K. Boakye, and J. Soares, "Image captioning: Transforming objects into words," 2020.

[30] Y. Song and S. Ermon, "Generative modeling by estimating gradients of the data distribution," 2020.

[31] Y. Song, J. Sohl-Dickstein, D. P. Kingma, A. Kumar, S. Ermon, and B. Poole, "Score-based generative modeling through stochastic differential equations," 2021.

[32] W. Peebles and S. Xie, "Scalable diffusion models with transformers," 2023.

[33] D. Lian, D. Zhou, J. Feng, and X. Wang, "Scaling shifting your features: A new baseline for efficient model tuning," 2023.

Appendix

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet

nisl. Vivamus quis tortor vitae risus porta vehicula.

Annexes

1 Markov Chain