

# Control Aware Radio Resource Allocation in Low Latency Wireless Control Systems

Mark Eisen\*   Mohammad M. Rashid<sup>†</sup>   Konstantinos Gatsis\*  
Dave Cavalcanti<sup>†</sup>   Nageen Himayat<sup>†</sup>   Alejandro Ribeiro\*  
\*University of Pennsylvania   <sup>†</sup>Intel Corporation

February 4, 2019

## Authors' General Response to the Associate Editor and Reviewers' Comments

We thank the associate editor and the reviewers for the time and effort invested in providing constructive suggestions. The requests most common among the reviewers concerned numerous points of clarification that add to the understandability and readability of the manuscript. Two reviewers raised questions and comments regarding the derivation of the problem in Example 1. Reviewers also raised key questions regarding some assumptions made in the analysis. A more detailed account of the major changes implemented in the manuscript follows.

- [C1] Reviewers 1 and 3 expressed concerns about the derivation of Example 1 and the stability analysis in Section V-C. We have thus expanded upon Example 1 that makes the derivations more explicit. We have revised Section V-C to give further details on the stability claim. We have also identified an omission in the previous version that has been corrected. More specifically, assuming we have a statistically accurate dual variable solution, using Proposition 2 and Theorem 2 we argue that the actual packet success rate selected by the algorithm can be made sufficiently close to the optimal one. Since the latter leads to system stability then the packet success rate selected by our algorithm also leads to stability. We thank the reviewers for these comments.
- [C2] Reviewer 1 has suggested some additional numerical experiments to explore the effects of different parameters in the performance. Per the reviewer's suggestion, we have added Figure 4 to the paper, which compares both the suboptimality and constraint violation of the resource allocations generated by Newton's method over a non-stationary channel using two different accuracies  $\hat{V}$ . The results demonstrate an interesting effect that can occur if the choice of  $\hat{V}$  is too strict. We thank the reviewer for this suggestion.
- [C3] Reviewers raised numerous questions regarding some of the practical considerations in Section VI, such as backtracking parameter selection as well as satisfying the non-stationary assumption in Assumption 4. To address these concerns, we have added additional details to

Section VI to clarify many of these points, and an additional remark after Assumption 4. We thank the reviewers for raising these questions.

### Response to Reviewer 1

We thank the reviewer for the comments, feedback, and questions. The reviewer raised concerns about the placement of the work within the URLL control and communication framework and literature. The reviewer also brings up points of clarification regarding the problem formulation. Each concern is addressed individually below.

1. *“The authors need to recast the framework within ultra-reliable and low-latency control and communication.”*

To be written

2. *“It was unclear whether the focus is on communication for a given control or the other way around. Taht is currently it looks like the solution is based on sequential design.”*

We thank the reviewer for brining up this point of clarification. The focus of this work is designing a scheduling protocol for a given system and control. As such, the control is assumed to be given, or chosen agnostic to the communication, while the communication is designed relative to both the system dynamics and choice of control. [We have added a sentence to Section II to clarify this point.](#)

3. *“The article would improve a lot if specific use cases are defined.”*

To be written

4. *“Linear control was adopted (for tractability) but clearly the nonlinearity is needed”*

The reviewer brings up a reasonable point about the formulation of the wireless control problem. Indeed, many practical systems feature both nonlinear dynamics and potentially nonlinear controls. As stated, the proposed approach focuses on linear systems and controls so that we may derive analytic expressions for the control-aware adaptive packet delivery rates. In practice, nonlinear systems may be linearized for the purposes of obtaining such packet delivery rate targets in (23) and performing the proposed CALLS method as written. [To demonstrate how this may be done, in the revised manuscript we have included additional simulations in Section VI in which we control a non-linear system using the CALLS method to schedule plant communications. In these simulations, while the actual dynamics and control being applied are nonlinear in nature, a linearization of the dynamics is used solely to derive the necessary PDR targets as in expression \(23\). Here, we demonstrate that the proposed method is applicable even in nonlinear systems.](#)

5. *“Reliability as not addressed however it is intertwined with latency”*

To be written

6. *“Authors did not cite recent and fundamental articles within URLLC:”*

We thank the reviewer for pointing out these references. They have been added to the revised manuscript, as well as [included in an added discussion of URLLC in the introduction \(Section I\).](#)

## Response to Reviewer 2

We thank the reviewer for the comments, feedback, and questions. The reviewer raised concerns about the readability of the abstract and made some suggestions regarding the simulation results. Each concern is addressed individually below:

1. *“Currently, it is not easy to follow the abstract. It should be revised. The contributions of the this paper should be highlighted.”*

We thank the reviewer for raising this point. We have revised the abstract in the manuscript to be more clear and the highlight the specific contributions of the paper.

2. *“In simulation part, it would be great if the authors could compare the proposed CALLS method with other methods if possible, since there are also some papers discussing communication resource allocation for multiple control loops.”*

To be written

### Response to Reviewer 3

We thank the reviewer for the comments, feedback, and questions. The reviewer raised points of clarification regarding the system setup and proposed additional comparisons to be made in the simulation results. Each concern is addressed individually below:

1. *“ Why do you only consider the AWGN channels? How will your scheme performance when considering fading channels? Is the fading channel also a typical scenario for WiFi based in-door wireless control system? ”*

We thank the reviewer for raising this point, as this aspect of the model is poorly worded in the previous version of the manuscript. We do indeed consider a fading channel to model the wireless channel conditions (specifically, IEEE Channel Model E). In our simulations, we use AWGN curves to evaluate packet error probabilities, but the curves are evaluated at the complete SNR values, which take into account the instantaneous fast fading channel conditions. In addition, we point out that IEEE Channel Model E is the current standard for measuring channel conditions in an indoor environment. More sophisticated models may be developed, but are outside the scope of this work. [We have revised the manuscript to clarify these points regarding the wireless channel model.](#)

2. *“In your system, how do you obtain accurate channel state information? E.g. for AWGN channels, you need to test the noise variance. Is your scheme sensitive to channel estimation errors?”*

This is a good point raised by the reviewer. **To be written.**

3. *“The proposed system shall be compared to more existed typical scheduling scheme employed in control system.”*

**To be written**