

[Resources](#) > [Project / Exam](#) > [Xtext grammar](#) > Statemachonk - xtext

Statemachonk - xtext

Date

Sort by



Toke Odgaard-Jans

SystemRoot:

```
'statemachine' name=Name states+= State conditions+=Condition transitions+=Transition  
;
```

Name:

```
'Number' | 'String'
```

```
;
```

State:

```
'state' name=Name conditions+=Condition transitions+=Transition  
;
```

Condition:

```
'condition' name=Name  
;
```

Transition:

```
'transition' name=Name  
;
```

last updated 04-03-2026 13:31



Toke Odgaard-Jans

Apparently I can't edit this anymore. The above was slightly wrong. We have the right solution below:

grammar org.xtext.example.statedsl.StateDSL with org.eclipse.xtext.common.Terminals
generate stateDSL "http://www.xtext.org/example/statedsl/StateDSL"

Domainmodel:

```
(elements+=Type);
```

Type:

StateMachine;

StateMachine:

'StateMachine' name=ID (states+=State)+ (transitions+=Transition) start=State

;

Name:

'Number' | 'String';

State:

'State' name=ID

;

Condition:

'condition' name=ID

;

Transition:

'transition' name=ID from=State to=State condition=Condition

;

posted 04-03-2026 14:24



Yoganata Kristanto



posted 09-03-2026 21:21
