# Formatting text

Web development I: Front-end engineering

## Tips



Specifying fonts is more like merely suggesting them

We don't really have full control over which font users will see

We should use generic fonts as a *fallback* 

# Font Properties



<u>font-family</u>

<u>font-size</u>

<u>font-weight</u>

<u>font-style</u>

<u>font-variant</u>

<u>font</u>

Font name

Font size

Font weight (boldness)

Font style (italics)

Font variant (small caps)

Shorthand declaration

# Specifying the font name



- Font names must be capitalized: "Arial" instead of "arial"
  - Exception: generic font families: sans-serif, monospace, etc.
- Use commas to separate multiple font names as fallback cases:

```
o p { font-family: Arial, sans-serif; }
```

• Font names with spaces (e.g. Duru Sans) must appear within quotes:

```
o p { font-family: "Duru Sans", Arial, sans-serif; }
```

#### Generic font families



**Serif** (e.g. Times New Roman)

Sans-serif (e.g. Arial)

Monospace (e.g. Courier New)

Cursive (e.g. Comic Sans)

Fantasy (e.g. Impact)

Serif











Sans-serif











Monospace











Hello Andale Mono

Cursive







**Fantasy** 







#### Custom web fonts



```
@font-face {
  font-family: "myFont";
  src: url("myFont.woff2");
html {
  font-family: "myFont", serif;
```

Many fonts aren't free to use: check license!

All browsers understand the <u>WOFF</u> format

WOFF2 supports <u>TrueType</u> and <u>OpenType</u>

fonts

Font declaration order is important

## Specifying the font size



```
h1 { font-size: 1.5em; }

h1 { font-size: 150%; }

h1 { font-size: x-large; }

h1 { font-size: larger; }

Relative keywords
```

Default font size is 16px

#### CSS units

рх

pixels



computed font-size value

pt points ex x-height of the font

pc picas rem root em, set in html element

mm millimeters ch width of the zero (0) letter

cm centimeters vw viewport width, 1% default

in inches viewport height, 1% default

vmin viewport min(width,height) size

Relative:

em

(only good for **print** materials) vmax viewport max(width,height) size

## Specifying other font styles



**font-weight:** normal | bold | bolder | lighter | 100 | 200 | 300 | 400 | 500 | 600 | 700 | 800 | 900 | inherit

font-style: normal | italic | oblique | inherit

font-variant: normal | small-caps | inherit

Shorthand declaration: style + weight + variant + size/line-height + family
h3 { font: oblique bold small-caps 1.5em/1.8em Verdana, sans-serif; }

## Changing text color



```
p { color: gray; }

p { color: #665544; }

Hexadecimal notation (RRGGBB)

p { color: #654; }

Shorthand hex notation

p { color: rgb(10,12,56); }

RGB decimal notation

p { color: rgba(10,12,56, 0.5); }

RGBA decimal notation with transparency

p { color: hsl(265, 23%, 90%); }

HSL notation
```

## Text adjustments



**line-height:** number | length measurement | percentage | normal | inherit

text-indent: length measurement | percentage | inherit

text-align: left | right | center | justify | inherit

text-decoration: none | underline | overline | line-through | blink

text-transform: none | capitalize | lowercase | uppercase | inherit

**letter-spacing:** length measurement | normal | inherit

word-spacing: length measurement | normal | inherit

## Text adjustments



vertical-align: baseline | sub | super | top | text-top | middle |

textbottom | bottom | percentage | length | inherit

white-space: normal | pre | nowrap | pre-wrap | pre-line | inherit

text-direction: | tr | rtl | inherit

text-shadow: 'horizontal offset' 'vertical offset' 'blur radius' 'color' | none

#### List bullets and numbers



list-style-type: none | disc | circle | square | decimal | decimal-leading-zero | lower-alpha | upper-alpha | lower-latin | upper-latin | lower-roman | upper-roman | lower-greek | inherit

**list-style-position:** inside | outside | inherit

list-style-image: url | none | inherit