DOU YEE
ENTERPRISES (S) PTE LTD

2304 Bedok Reservoir Road, Bedok Industrial Park C, Singapore 479223
Tel: (65) 64442678 Fax: (65) 67437172
Email: marketing@douyee.com.sg Website: www.douyee.com

Product Data Sheet

PRODUCT CODE / PART NUMBER: DY6008-HS-1102E-1G-EVA/RUBBER-S3LSRFOHRO-SK-SIZE

PRODUCT: Static Dissipative Safety Shoes

BRAND NAME: **EUROSTAT®** *Safetykey*



FEATURES:

This safety shoe is made of Black Spilt Barton Leather Upper, Mesh Lining, EVA Midsole, Nitrile Rubber (NBR) Outsole, Steel Toe Cap and Composite Midplate.

- Water Resistant
- 200J Impact Resistance
- 15KN Compression Resistance
- 1100N Penetration Resistance
- Light Weight, Excellent Comfort
- Resistant to Oil and Most Chemicals
- Non-Marking and Slip Resistant Outsole (SRC)

Specifications

Item	Properties / Typical Values	Test Method
Materials	Upper : Black Spilt Barton Leather Toe Cap : Steel Midplate : Composite Insole : High Density Foam Midsole : Static Dissipative PU Outsole : Static Dissipative Nitrile Rubber (NBR)	
Footwear only Resistance	$< 1.0 \times 10^9$ ohms	ANSI/ESD STM9.1
Footwear System Resistance	$< 1.0 \times 10^9$ ohms	ANSI/ESD STM9.1
Electrical System Resistance of a person wearing footwear while standing on conductive flooring	$< 1.0 \times 10^9$ ohms	ANSI/ESD STM97.1
Color	Upper : Black Midsole : Black Outsole : Black	
Sizes (European)	36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46 & 47	
Conformity	The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article Annex V, including the application clauses of the Essential Health and Safety Requirements of the PPE Regulation EU 2016/425 for Category II products. This has been shown through satisfactory testing to EN ISO 20345:2022 and examination of the Technical File Documentation (Category: S3PLSRFOHRO)	

NITRILE RUBBER (NBR)	COMPOSITE MIDPLATE	STEEL TOE CAP (#604)
		

Date: 2025 / 2026