DOU YEE
ENTERPRISES (S) PTE LTD

2304 Bedok Reservoir Road, Bedok Industrial Park C, Singapore 479223
Tel: (65) 64442678 Fax: (65) 67437172
Email: marketing@douyee.com.sg Website: www.douyee.com

# Product Data Sheet

**PRODUCT CODE / PART NUMBER: DY6008-HS-354C-NAVY BLUE-35M-RUBBER-S1-SIZE**

**PRODUCT:** Static Dissipative Safety Sneaker, Navy Blue

**BRAND NAME: EUROSTAT®**



**FEATURES:**

This safety shoe is made of Navy Blue Microfiber PU, Mesh Lining, High Density Foam Insole, Nitrile Rubber (NBR) Outsole and Composite Toe Cap

- 200J Impact Resistance
- 15KN Compression Resistance
- Light Weight, Excellent Comfort
- Resistant to Oil and Most Chemicals
- Non-Marking and Slip Resistance Outsole

## Specifications

| Item | Properties / Typical Values | Test Method |
|---|---|---|
| Materials | Upper : Microfiber PU<br>Toe Cap : Composite<br>Outsole : Static Dissipative Nitrile Rubber (NBR) | |
| Footwear only Resistance | $< 1.0 \times 10^9$ ohms | ANSI/ESD STM9.1 |
| Footwear System Resistance | $< 3.5 \times 10^7$ ohms | ANSI/ESD STM9.1 |
| Electrical System Resistance of a person wearing footwear while standing on conductive flooring | $< 3.5 \times 10^7$ ohms | ANSI/ESD STM97.1 |
| Color | Upper : Navy Blue<br>Outsole : White | |
| Sizes (European) | 225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 285, 290 & 300mm | |
| Conformity | 1) The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article Annex V, including the application clauses of the Essential Health and Safety Requirements of the PPE Regulation EU 2016/425 for Category II products. This has been shown through satisfactory testing to EN ISO 20345:2011 and examination of the Technical File Documentation (Category: S1 SRC)<br>2) SIRIM MS ISO 20345: 2008 (License No.: PC004375)<br>3) CNS 20345: 2015 (R3B081) | |

| RUBBER OUTSOLE | COMPOSITE TOE CAP |
|---|---|
|  |  |

| Size (mm) | 225 | 230 | 235 | 240 | 245 | 250 | 255 | 260 | 265 | 270 | 275 | 280 | 285 | 290 | 300 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Average weight per pair (g) | 825 | 860 | 893 | 936 | 954 | 979 | 1016 | 1033 | 1047 | 1063 | 1128 | 1160 | 1234 | 1307 | 1353 |

Date: 2025 / 2026