DOU YEE
ENTERPRISES (S) PTE LTD

2304 Bedok Reservoir Road, Bedok Industrial Park C, Singapore 479223
Tel: (65) 64442678 Fax: (65) 67437172
Email: marketing@douyee.com.sg Website: www.douyee.com

Product Data Sheet

PRODUCT CODE / PART NUMBER: DY6008-HS-354C-WHITE-35M-RUBBER-S1-SIZE

PRODUCT: Static Dissipative Safety Sneaker, White

BRAND NAME: EUROSTAT®



FEATURES:

This safety shoe is made of White Microfiber PU, Mesh Lining, High Density Foam Insole, Nitrile Rubber (NBR) Outsole and Composite Toe Cap

- 200J Impact Resistance
- 15KN Compression Resistance
- Light Weight, Excellent Comfort
- Resistant to Oil and Most Chemicals
- Non-Marking and Slip Resistance Outsole

Specifications

Item	Properties / Typical Values	Test Method
Materials	Upper : Microfiber PU Toe Cap : Composite Outsole : Static Dissipative Nitrile Rubber (NBR)	
Footwear only Resistance	$< 1.0 \times 10^9$ ohms	ANSI/ESD STM9.1
Footwear System Resistance	$< 3.5 \times 10^7$ ohms	ANSI/ESD STM9.1
Electrical System Resistance of a person wearing footwear while standing on conductive flooring	$< 3.5 \times 10^7$ ohms	ANSI/ESD STM97.1
Color	Upper : White Outsole : White	
Sizes (European)	225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 285, 290 and 300mm	
Conformity	1) The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article Annex V, including the application clauses of the Essential Health and Safety Requirements of the PPE Regulation EU 2016/425 for Category II products. This has been shown through satisfactory testing to EN ISO 20345:2011 and examination of the Technical File Documentation (Category: S1 SRC) 2) SIRIM MS ISO 20345: 2008 (License No.: PC004375) 3) CNS 20345: 2015 (R3B081)	

RUBBER OUTSOLE	COMPOSITE TOE CAP
	

Size (mm)	225	230	235	240	245	250	255	260	265	270	275	280	285	290	300
Average weight per pair (g)	825	860	893	936	954	979	1016	1033	1047	1063	1128	1160	1234	1307	1353

Date: 2025 / 2026