DOU YEE
ENTERPRISES (S) PTE LTD

2304 Bedok Reservoir Road, Bedok Industrial Park C, Singapore 479223
Tel: (65) 64442678 Fax: (65) 67437172
Email: marketing@douyee.com.sg Website: www.douyee.com

Product Data Sheet

PRODUCT CODE / PART NUMBER: DY6008-HS618C-1G-PU/PU-S2SRFO-SK-SIZE e9

PRODUCT: Static Dissipative Safety Shoes, Black

BRAND NAME: **EUROSTAT®** *Safetykey*



CE

FEATURES:

This safety shoe is made of 3D-mesh Polyester + TPU Heat Seal Upper, 3D-mesh Lining, EUROSTAT® PU Insock, Composite Toe Cap and Double Density PU/PU Outsole.

- 200J Impact Resistant
- 15KN Compression Resistant
- Light Weight, Slip-On with Shoelaces
- Water Resistant and Comfortable Upper
- Non-Marking and Slip Resistant (SR) Outsole Resistant to Fuel Oil (FO) and Most Chemicals

Specifications

Item	Properties / Typical Values	Test Method
Materials	Upper : 3D-mesh Polyester + TPU Heat Seal Toe Cap : Composite Midsole : Static Dissipative PU Outsole : Static Dissipative PU	
Footwear only Resistance	$< 1.0 \times 10^9$ ohms	ANSI/ESD STM9.1
Footwear System Resistance	$< 1.0 \times 10^9$ ohms	ANSI/ESD STM9.1
Electrical System Resistance of a person wearing footwear while standing on conductive flooring	$< 1.0 \times 10^9$ ohms	ANSI/ESD STM97.1
Color	Upper : Black Midsole : Black Outsole : Blue	
Sizes (European)	36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46 & 47	
Conformity	1) The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article Annex V, including the application clauses of the Essential Health and Safety Requirements of the PPE Regulation EU 2016/425 for Category II products. This has been shown through satisfactory testing to EN ISO 20345: 2022 and examination of the Technical File Documentation (Category: S2SRFO)	

PU OUTSOLE	COMPOSITE TOE CAP
	

Size	36	37	38	39	40	41	42	43	44	45	46	47
Average weight per pair (g)	945	979	1012	1046	1079	1113	1147	1179	1214	1247	1280	1314

Date: 2025 / 2026